Inventec NX-H3003A Smart Edge Server System





Inventec NX-H3003A Smart Edge Server System User Manual

Home » Inventec » Inventec NX-H3003A Smart Edge Server System User Manual

Contents

- 1 Inventec NX-H3003A Smart Edge Server System
- 2 Disclaimer
- **3 Conventions**
- **4 Safety Symbols**
- **5 Safety Precautions**
- **6 Tools Required**
- 7 Introduction
- 8 Instructions for Use
- 9 Manual Organization
- 10 Packing Checklist
- 11 Product Specifications
- 12 Product Features and Summary
- 13 System Overview
- 14 FCC STATEMENT
- 15 Documents / Resources
 - 15.1 References
- **16 Related Posts**



Inventec NX-H3003A Smart Edge Server System



Copyright Notice

All rights, including copyright, in the content of this manual are owned or controlled by Inventec and protected by the Taiwan and International Copyright Act.

No one may transmit, adapt, assign, compile, rent, sell, change, copy, reproduce, distribute, publish, display, broadcast, or use in any way the content of this manual, in whole or in part, for any other purpose whatsoever without the prior written permission of Inventec.

Trademarks

All product names or brands mentioned herein are the trademarks of Inventec, its subsidiaries or other respective owners in Taiwan, the United States and other countries.

Disclaimer

This manual provides information about the set-up and installation of the product herein. Nothing herein may be construed as granting any right or license relating to any intellectual property rights of this manual or product. Unless otherwise provided in the Purchase and Sale Agreement for this product, the manufacturer and distributor of this product will not be liable whatsoever relating to the distribution and/or use of this product. In addition, the manufacturer and distributor of this product hereby specifically disclaim any express or implied warranties of merchantability, fitness for a particular purpose, or non-infringement of third-party rights in connection with this product.

Manufacturers of this product may have the right to change specifications and product descriptions at any time without notice.

Warning!

Before opening the chassis cover, remove all power cords to completely disconnect power from the system.

About This Manual

Conventions

• To make sure that you perform certain tasks properly, take note of the following symbols used throughout this

manual.

M	Warning:	Information to prevent injury to yourself when trying to complete a task.	
6	Caution:	Information to prevent damage to the components when trying to complete a task.	
Important: Information that you must follow to complete a tas		Information that you must follow to complete a task.	
(E)	Note:	Tips and information to aid in completing a task.	

Safety Symbols

- Before troubleshooting, you must be familiar with the safety information listed below. To avoid any potential hazards, the following symbols may be placed on some components of the product.
- The shape and colour of the symbols shown below are mainly for your reference. Please take the actual shipment as standard.

	Indicates the potential hazard of energy circuits or electric shock. To reduce the risk of injury from electric hazards, do not open this enclosure.
M	Warning: Any surface or area of the equipment marked with this symbol indicates the presence of electric shock hazards. The enclosed area
	contains no operator serviceable parts.
	Indicates the potential hazard of electric shock. The enclosed area contains no user or field serv iceable parts. Do not open for any reason.
\otimes	Warning: To reduce the risk of injury from electric shock hazards, do not
	open this enclosure.
	Indicates the presence of a hot surface or hot component.
	Warning: To reduce the risk of injury from a hot component, allow the surface to cool before tou ching it.
	Any RJ45 receptacle marked with this symbol indicates a network interface connection.
	Warning: To reduce the risk of electric shock, fire, or damage to the equipment, do not plug tele phone or telecommunications connectors into
	this receptacle.
	This symbol, on power supplies or systems, indicates that the equipment is supplied by multiple sources of power.
	Warning: To reduce the risk of injury from electric shock, remove all power
142	cords to completely disconnect power from the system.
	This symbol indicates that the component exceeds the recommended weight for one individual to handle safely.
	Warning: To reduce the risk of personal injury or damage to the equipment,
Weight in kg. Weight in lb.	observe local occupational health and safety requirements and guidelines for manual material h andling.

Safety Precautions

- Observe the following safety precautions when you are connecting or disconnecting any device.
- The product is a non-consumer product and for professional technical persons only.

Operation Safety

- Any operation on this product must be conducted by certified or experienced engineers.
- Before operating the product, carefully read all the manuals included in the product package.
- Before using the product, make sure that all cables are correctly connected and power cords are not damaged. If any damage is detected, contact your dealer as soon as possible.

- To avoid short circuits, keep paper clips, screws, and staples away from connectors, slots, sockets and circuitry.
- Avoid dust, humidity, and extreme temperatures; place the product on a stable surface.
- It is recommended that you wear gloves when assembling or disassembling the product to protect it from cuts and scrapes.
- When the product is powered on, heat sinks may be hot. Do not touch them.

Electrical Safety

- Before installing or removing signal cables, ensure that the power cords for the product and all attached devices are unplugged.
- To prevent electric shock hazards, disconnect the power cable from the electrical outlet before relocating the product.
- When adding or removing any additional device to or from the product, ensure that the power cords for those
 devices are unplugged before the signal cables are connected. If possible, disconnect all power cords from the
 existing product before you add a device.
- Use one hand, when possible, to connect or disconnect signal cables to prevent a possible shock from touching two surfaces with different electrical potentials.

Intended Application Uses

This product was evaluated as Information Technology Equipment (ITE), which may be installed in server rooms or computer rooms. The suitability of this product for other product categories and environments (such as medical, industrial, residential, alarm systems, and test equipment), other than an ITE application, may require further evaluation.

Site Selection

Restricted Access Location: The location for equipment is intended for installation only in a Server Room or Computer Room where both of the following apply:

- Access can only be gained by SERVICE PERSONS about the reasons for the restrictions applied to the location and about any precautions that shall be taken.
- Access is through the use of a TOOL lock and key, or other means of security, and is controlled by the authority responsible for the location.
- This equipment is not suitable for use in locations where children are likely to be present.

The system is designed to operate in a typical office environment. Choose a site that is:

- Clean, dry, and free of airborne particles (other than normal room dust).
- Well-ventilated and away from sources of heat including direct sunlight and radiators.
- Away from sources of vibration or physical shock.
- Isolated from strong electromagnetic fields produced by electrical devices.
- In regions that are susceptible to electrical storms, we recommend you plug your system into a surge suppressor and disconnect telecommunication lines to your modem during an electrical storm.
- Provided with a properly grounded wall outlet.
- Provided with sufficient space to access the power supply cord(s), because they serve as the product's main

Tools Required

A Phillips head screwdriver or a flat screwdriver is needed to install or remove the components in the server.

Introduction

Audience Assumptions

This document is for the person who installs, administers, and troubleshoots devices and systems. Inventec assumes you are qualified in the servicing of computer equipment and trained in recognizing hazards in products with hazardous energy levels.



Warning:

This product is a telecommunications terminal equipment that must be installed and set up by professional engineers before it can be set up and used, and may not be sold directly to general

consumers.

Instructions for Use



Warning:

This product is Class A equipment. To avoid electromagnetic interference, it should n ot be installed or used in residential environments. To reduce the impact of electromagnetic waves, please use this product properly.



Warning:

Radiation Exposure Statement: This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and your body.



Important:

This product is certified to the Technical Specification for Low Power Radio Frequen cy Equipment, version 3.8. Without approval, no company, firm or user may change the frequency, increase the power, or change the characteristics and functions of the original

design.



Important:

In addition to complying with the Technical Specification for Low Power Radio Frequency Equipment, version 3.8, this product should avoid affecting the operation of nearby radars.

1	Important:	This product is a low-power radio frequency device and should not be used in a manner that affects flight safety or interferes with legitimate communications. If inter ference is found, stop using it immediately and make improvements until there is no interference before continuing to use it. The legal communications referred to in the preceding paragraph refer to radio communications operated under the provisions of the Telecommunications Management Act. Low-power RF equipment must be able to withstand interference from electromagnetic devices that radiate electromagnetic waves for legitimate communications or industrial, scientific, and medical purposes.
---	------------	--

Manual Organization

This manual introduces the chassis along with the hardware information. This manual is generally organized as follows:


Introduction	General product introduction	
Connectors	Information about connectors on the front side	
Appendix	FCC Rules Notices	

Packing Checklist

Make sure you have all the components shipped with your system. If any item contained in the package is damaged or missing, please contact your local dealer for replacement. In addition, keep the box and packing materials for possible future use. The device is shipped with the following:

Chassis	NX-H3003A smart edge server			
Antenna	6x antenna, two types for LTE and Wifi			
	· LTE (Main) to 5G module (M) cable			
	· Wi-Fi to Wi-Fi module (ANT2) cable			
	LTE (M1) to 5G module (M1) cable			
	LTE (M2) to 5G module (M2) cable			
O-hi-	· Wi-Fi + BT to Wi-Fi module (ANT1) cable			
Cables	LTE (D/G) to 5G module (D/G) cable			
	· 1x Power adapter			
	· 1x power cord			
	· 4x Footpads			
Others	· 2x Wall hanging			

Product Specifications




	· Height: 42.1 mm		
	· Width		
	220 mm (without Ear Mount) and 256 mm (with Ear Mount)		
Dimensions	Length: 172 mm		
Weight	· Max-weight: 1.95 kg		
	· Switching power adapter		
Power Supply	Support AC input 100-240V / DC output 12V 8A		
	· Operating Temperature: -20°C ~ 60°C with 0.7m/s air		
	Storage Temperature: -40°C ~ 85°C		
	Operating Humidity: +8% ~ 90% RH		
	Storage Humidity: 5% ~ 95% RH		
Environmental and Certi fications	Vibration During Operation: IEC 60068-2-64		
	· Shock During Operation: IEC 60068-2-27		
	In a no-wind environment, 50°C is the highest currently supported, if the wind speed is 0.7m/sec, it can reach 60°C.		
Product Use Restriction Record	Support IEC61000-6-2 Level 2 pass		

Antenna Specifications

This product uses a detachable antenna, which is limited to the following antennas:

Brand	Model	Antenna Type	Frequency Range (MHz)	Gain (dBi)
	DAM-D7-B2-N0- 000 -58-13	Dipole	1710 – 1785	3.3
			2500 – 2570	2.8
			703 – 748	1.29
INPQ			2570 – 2620	2.84
			2500 – 2690	2.84
			3300 – 3570	3.09
			4700 – 4900	1.52

Product Features and Summary



Improved performance and higher efficiency

Paired with Intel® Core™ processor U series—Tiger Lake Up to achieve high-speed processing, computer vision and low-latency deterministic computing.

Flexible network configuration

• Supports IoT applications through 4GLTE or 5GNR (Sub 6G) and WiFi-6 modules, with high-bandwidth network communication capabilities to meet the needs of different applications.

Satisfactory stability and ease of maintenance

- Adopting a highly modular design structure and ultra-thin appearance, it is easy to repair and maintain.
- It is ideal for applications such as smart image monitoring, big data analysis, Industry 4.0, and smart medical industries.

High-performance 5G fixed wireless access

 Supports fixed wireless access (FWA) technology and provides 5G/LTE broadband services for rapid and efficient deployment.

New software driver platform


 Adopts Ubuntu Linux operating system and supports iGWS software platform to provide users with safe and reliable services

Chassis	NX-H3003A smart edge server		
Processor	· Intel® Core™ Processor U-Series Mobile – Tiger Lake Up3		
(CPU)	Up to 4 Processor Cores, TDP 15W		
System Memory	Support 2 DDR4 memory channels, one SODIMM per channel		
(DIMM)	Max. 3200MT/s, capacity up to 64GB		
Chipset	· Integrated SoC		
	2x M.2 Key M slot supports 2280 / 22110 form factors (CPU PCIe Gen 4 x2)		
	Al module		
	NVMe SSD module		
	1x M.2 Key B slot supports 2280 / 22110 form factors NVMe SSD module		
	LoRa module		
	. 1x M.2 Key E slot supports 2230 form factor (support Intel CNVio / CRF mo dules)		
	WiFi / BT module		
	1x M.2 Key B slot supports 3052 / 2280 form factors 5G module		
	NVMe SSD module		
Expansion Slot	1x SIM card slot (Nano SIM card form fact)		
Network	· 2x RJ-45 2.5G with TSN (Intel I225)		
Management	Microchip MEC1428 (Embedded Controller)		
Security	· TPM 2.0 (SPI interface)		
Display Interface	· 1x HDMI 2.0 port		
	· Front I / O		
	1x DB9 COM port		
	1x P12V input DC jack		
	1x Power Button / LED (Green / Amber) 1x Reset button		
	2x USB 3.2 Gen 2 port (10G) 2x USB 2.0 port		
	1x HDMI 2.0 port		
	2x RJ45 (2.5G TSN support) port		
I / O Interface	face · Internal I / O		

	1x COM port header (optional) 1x GPIO port (optional) 1x USB 3.2 Gen 2 port (10G)	
Thermal Design	· Fan-less with case fin design	
Antenna Design	Two types of antennas for LTE and WiFi support Gen 5 mobile phones and Gen 6 WiFi standards respectively	

System Overview

Front View



- 1. Link / Active LED of RJ45 Port 2
- 2. Speed LED of RJ45 Port 2
- 3. Link / Active LED of RJ45 Port 1
- 4. Speed LED of RJ45 Port 1
- 5. RJ45 Port 2
- 6. RJ45 Port 1
- 7. COM Port
- 8. HDMI Port
- 9. Dual USB 2.0 Port
- 10. Dual USB 3.0 Port
- 11. Reset Button
- 12. Power Button / LED

System LED and Button Information

LED	LED				
LED Type	Colour	LED Status	System Status		
	Green	On	DC power on		
		On	Stand by status		
	Amber	Blinking	The system is running on DC power.		
Power LED	_	Off	AC power off		
		On	Link-Up		
Onboard RJ-45 Link / Active LED	Green	Blinking	Traffic		
	_	Off	Link-Down		
	Green	On	2500 Mbps		
	Yellow	On	1000 Mbps		
Onboard RJ-45 Speed LED		Off	100/10 Mbps		
	_	Off	No Link		
Button					
Button Type	Behaviour	System Status			
		DC power on Shutdown OS normally			
	Short press	DC power off: Power on system			
Power Button	Long press ≥ 3s	DC power off			
Reset Button	Short press	Running normally			

FCC STATEMENT

Appendix A FCC Rules Notices

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference, and
- 2. This device must accept any interference received, including interference that may cause undesired operation.

Documents / Resources



Inventec NX-H3003A Smart Edge Server System [pdf] User Manual

NX-H3003A Smart Edge Server System, NX-H3003A, Smart Edge Server System, Edge Server System

References

• User Manual

Manuals+, Privacy Policy

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.