

ISOACOUSTICS 892ASUB Aperta Sub Subwoofer Isolation Instructions

Home » ISOACOUSTICS » ISOACOUSTICS 892ASUB Aperta Sub Subwoofer Isolation Instructions



Contents

- 1 ISOACOUSTICS 892ASUB Aperta Sub Subwoofer **Isolation**
- 2 Instructions
- 3 Discover. ...
- 4 Documents / Resources
- **5 Related Posts**



ISOACOUSTICS 892ASUB Aperta Sub Subwoofer Isolation



Instructions

- 1. Choose the location where the subwoofer will be positioned.
- 2. Place the Aperta Sub stand in position with the also acoustics logo facing forward. If the Aperta Sub stand will be positioned on a medium or thick carpet, attach the carpet disks underneath the isolators. The carpet disks

provide a strong connection in the carpet and a solid foundation for the Aperta Sub.

3. Gently lower the subwoofer on top of the Aperta Sub stand. The isolator should be positioned directly against the bottom of the subwoofer cabinet. The shape of the Aperta Sub stand allows positioning directly underneath the subwoofer cabinet without interference with the existing subwoofer feet. In some cases, the existing feet may need to be removed (if possible) to avoid interference.

Weight Capacity: 80 lbs (36.3 kg)

Discover. ...



IsoAcoustics warrants the Aperta Sub against evident defects in material and workmanship for a period of 2 years from the date of the original purchase. This warranty does not cover the mechanical damage resulting from misuse or abuse, lack of reasonable care, damage due to force majeure, or natural forces. IsoAcoustics shall not be liable for any special, indirect, direct, or consequential damages to other products or property.

Isoacoustics.com Developed by IsoAcoustics Inc. Markham, ON, Canada L3P 1X3 Assembled in China, Fabriqué en Chine U.S. Patent No.. 9,920,811 Brevet E-U. 9 920 811

Documents / Resources



<u>ISOACOUSTICS 892ASUB Aperta Sub Subwoofer Isolation</u> [pdf] Instructions 892ASUB Aperta Sub Subwoofer Isolation, 892ASUB, Aperta Sub Subwoofer Isolation, Sub Subwoofer, Subwoofer

Manuals+.