



ITC T-865CFB Broadcasting Wall Mounted Speaker Instructions

[Home](#) » [ITC](#) » ITC T-865CFB Broadcasting Wall Mounted Speaker Instructions 





Contents

[1 Feature:](#)

[2 Specifications:](#)

[3 Documents / Resources](#)

[3.1 References](#)

[4 Related Posts](#)

Feature:


- The housing is made of polystyrene material, which is lightweight. And it is easy to install in various application scenarios.
- The front panel adopts iron mesh decorative panel parts, which are beautiful and elegant.
- Multi-angle adjustment of the mounting bracket, easy to adapt to various application scenarios.
- Adopt a 5.25-inch mid-bass unit and a 25MM silk treble unit.
- 5 fixed constant voltage volume adjustment switch.
- Built-in high-quality linear audio power transformer.
- It is widely used in various small and medium-sized meeting rooms, banquet halls, hotels, commercial buildings, schools, entertainment, and leisure places.

Specifications:

Model	T-865CFB
Rated power (100V)	3W,6W,12.5W,25W,50W
Rated power (70V)	1.5W,3W,6W,12.5W,25W
Peak power	200W
Maximum SPL (rated/peak)	101dB/107dB
Frequency response	85Hz-20kHz
Sensitivity	84dB+-3dB
Speaker unit	5.25 inch mid-bass + 25MM silk treble
Dimensions (H x W x D)	376x202x184mmmm
Weight	4.1kg

www.itctech.com.cn
info@itc-pa.com.cn

Documents / Resources

	<p>ITC T-865CFB Broadcasting Wall Mounted Speaker [pdf] Instructions</p> <p>T-865CFB, Broadcasting Wall Mounted Speaker, Wall Mounted Speaker, Mounted Speaker, T-865CFB, Speaker</p>
--	---

References

- [ITC Guangzhou BaoLun Electronics Co., Ltd](#)