

Jandy
iQ-JNDY-RSPS8
iAquaLink
Conversion Kit



Jandy iQ-JNDY-RSPS8 iAquaLink Conversion Kit Installation Guide

[Home](#) » [Jandy](#) » Jandy iQ-JNDY-RSPS8 iAquaLink Conversion Kit Installation Guide 

Contents

- [1 Jandy iQ-JNDY-RSPS8 iAquaLink Conversion Kit](#)
- [2 Product Usage Instructions:](#)
- [3 FAQs](#)
- [4 Documents / Resources](#)
 - [4.1 References](#)



Jandy iQ-JNDY-RSPS8 iAquaLink Conversion Kit



Specifications

- Input Voltage: 115V or 230V
- Dual Voltage Capability: Configurable to 120 VAC or 240 VAC

- Compatibility: Works with various pool control systems and equipment
- Wireless Connectivity: WiFi and Zigbee support

Product Usage Instructions:

Installation:

To install the TCXTM Automation Conversion kit, follow these steps:

1. Remove the old timeclock from the enclosure.
2. Seamlessly fit the TCXTM into the enclosure for a quick and easy upgrade.
3. Connect the system to WiFi for wireless control.

Configuration:

To configure the TCXTM for operation, choose the pool pad system you want to swap with from the list of compatible systems provided in the manual.

Wireless Lighting Operation:

If you wish to add wireless lighting operation, ensure your installation location has a neutral wire at the existing light switch. Install the wireless light switch in your home for automated control.

Why TCX™ is the Best Option to Upgrade to Automation



Quick and Easy Install

Seamlessly fits into the most popular timeclock enclosures for a fast and easy upgrade.



Dual Voltage Capability

No need to call the electrician... As a qualified pool professional, it's easy to configure to 120 VAC or 240 VAC input because there's no main power rewiring.



Connects to iAquaLink®

Intuitive control using the same user interface you already know and pool owners love.



Control the Competition

TCX™ is capable of automating competitor equipment too!

#1 highest-rated pool control app in the industry with over 50K 5-star reviews

Swap the System. Keep the Can.

Conversion kits are designed to easily upgrade and replace existing automation systems with no main power rewiring.

Suggested Tools

- 1/4" Slotted Screwdriver
- Large Slotted Screwdriver
- #2 Phillips Screwdriver
- Wire Stripper and Pliers



- Simply remove the old timeclock.
- Snap in the new AquaLink® TCX™.
- You're all set!
- Sync your phone via Bluetooth® and easily connect to WiFi

Add Wireless Lighting Operation

No need to reroute the pool lights to the automation system; install the wireless light switch in the home for automated control.



NOTE: You must qualify installation location has a neutral wire at the existing light switch. The Zigbee switch requires a neutral wire to work.

FAQs

Why is TCXTM the best option for pool automation?

TCXTM offers quick installation, dual voltage capability, compatibility with various pool pads, and a highly-rated

control app for easy operation.


Can TCXTM automate competitor equipment?

Yes, TCXTM is capable of automating competitor equipment as well, providing flexibility in pool automation.

Does the TCXTM system require main power rewiring during installation?

No, there is no need for main power rewiring when installing the TCXTM system, making it easy for qualified pool professionals to configure.

Documents / Resources

	<p>Jandy iQ-JNDY-RSPS8 iAquaLink Conversion Kit [pdf] Installation Guide</p> <p>iQ30-RS, iQ-JNDY-RSPS8, iQ-JNDY-RS26, iQ-PENT-RSPS8, iQ-COMP-RSPS8, iQ-POL-RSPS8, TCX PCONV, iQ-JNDY-RSPS8 iAquaLink Conversion Kit, iQ-JNDY-RSPS8, iAquaLink Conversion Kit</p>
---	--

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.