



Kestrel Instruments K5 Series Wall Mount and AC Adapter User Guide

[Home](#) » [Kestrel Instruments](#) » Kestrel Instruments K5 Series Wall Mount and AC Adapter User Guide 

Contents

- [1 Kestrel Instruments K5 Series Wall Mount and AC Adapter](#)
- [2 Kestrel AC Adapter](#)
 - [2.1 Quick Start Guide](#)
 - [2.2 Drywall Mount Instructions](#)
- [3 Documents / Resources](#)
- [4 Related Posts](#)





Kestrel Instruments K5 Series Wall Mount and AC Adapter



Kestrel AC Adapter

Quick Start Guide

- Slide the battery door latch and open door. Replace with battery door attached to AC Adapter.
- Make sure the battery door “clicks” fully into place.
- Open or remove the impeller cover to allow air velocity measurements. If removed, keep in storage.
- Plug into outlet for setup.
- Long press the power button () to turn on the Kestrel.
- Press the gear button () to enter the “Options Menu”.
- Scroll to “Display” and press the Enter/Select button (—).
- Scroll to “Auto Shtdwn” and choose “Off”. Subsequently, the Kestrel 5400 will only shutdown by holding down the power button.
- Connect the included K5 series clip to the wall mount and mount to your desired location.
- Pick a spot you can easily access, as you may have to adjust settings on the unit.

Drywall Mount Instructions

- Use provided anchors for drywall.
- Measure and mark the location for the anchors.
- Drill a pilot hole.

- WARNING:** This is intended for indoor use only. Disconnecting or loss of AC power will render your device inoperable.

[illegible]