

LABCONCO

**3930221  
Protector  
Work  
Station  
with Built**



## LABCONCO 3930221 Protector Work Station with Built Owner's Manual

[Home](#) » [LABCONCO](#) » LABCONCO 3930221 Protector Work Station with Built Owner's Manual 

### Contents

- [1 LABCONCO 3930221 Protector Work Station with Built](#)
- [2 Overview](#)
- [3 Specifications](#)
- [4 Description](#)
- [5 For Product Assistance](#)
- [6 FAQs](#)
- [7 CONTACT INFORMATION](#)
- [8 Documents / Resources](#)
  - [8.1 References](#)



**LABCONCO 3930221 Protector Work Station with Built**



## Overview

- XPert Balance Enclosures provide user protection by keeping powders, particulates, and fumes contained during weighing procedures.
- They are well suited for pharmaceutical research and other laboratory applications involving the weighing of toxic substances. These vented balance safety enclosures may be ducted to the outside or connected to the FilterMate
- Portable Exhauster to be exhausted back into the laboratory through HEPA filters, carbon filters, or a combination of both HEPA and carbon filters.
- Their ample, 23" interior depth (30" depth for "Deep" models) easily accommodates large micro and analytical balances, and a true bag-in/bagout filter disposal system allows safe filter replacement.

## Specifications

- **Weight:** 110.0 lbs
- **Weight metric:** 50.0 kg
- **Dimensions:** 24"w x 29"d x 28.6"h
- **Electrical:** 230 volts, 50/60 Hz, no plug
- **Region:** International
- **Width:** 2'
- **Airflow Monitor:** Guardian Jr.
- **Air Usage/Static Pressure with Sash At Working Height:** At 60 fpm, exhausts 70 CFM at .02" H<sub>2</sub>O static pressure. At 80 fpm, exhausts 95 CFM at .03" H<sub>2</sub>O static pressure.
- **Blower Requirements:** Remote blower or
- **FilterMate Portable Exhauster(s) and filters required Conformance:** ANSI Z9.5, Modified ASHRAE 110, SEFA 1
- **Lighting:** None. Light Kit Accessory available.

- **Sash Opening Height:** 8.0" (20.3 cm)
- **Type:** Balance Enclosure
- **With Built-In HEPA Filtration:** No

## Description

### Features

- Low profile fits in tight spaces
- Deep 23" or 30" interior easily accommodates large micro and analytical balances
- Patented Clean-Sweep™ airfoil allows air to sweep the work surface for maximum containment
- Upper containment sash foil bleeds air into the enclosure to direct concentrations of contaminants away from the operator's breathing zone
- Upper dilution air supply introduces room air at the top of the sash to dilute concentrations in the upper chamber and bathes the back of the sash with clean air
- Patented\* rear baffle with zones of perforations promotes horizontal laminar airflow to maximize containment. Airflow openings pull inflow air from under the airfoil so that clean air continually flows over the airfoil creating a constant barrier of protection from contaminants
- Side-entry airfoils allow air to sweep across the interior glass surfaces to enhance containment
- Sturdy glacier white and gray, dry powder epoxy-coated aluminum frame and steel rear plenum and baffle dissipate the static charge and provide durability and better corrosion resistance compared to acrylic models.
- No unreliable plastic-to-plastic bonding is used
- Tempered safety glass front sash, sides, and top offer excellent visibility, ambient light, and protection. Glass provides improved fire, scratch, and corrosion resistance than acrylic and dissipates static charge. 8", 10" or 12" high sash opening limits exhaust demand, conserves costly tempered room air and requires a smaller remote blower than most fume hoods
- An ergonomic 20° angled sash allows a closer view, reduces glare, and provides a more comfortable operating position than vertical sashes. The hinged sash pivots upward and locks to a loading height of 20"
- Two utility ports with iris openings allow passage of tubing, electrical cords, and interface cables from inside to the back exterior for connection to services
- Flexible exhaust options. 2" x 10" rectangular exhaust collars on the top and bottom allow the XPert
- Balance Enclosure to be connected to ductwork for exhausting to the outside or a FilterMate™
- Portable Exhauster for filtered removal of powders, particulates, or fumes. Using the bottom exhaust collar keeps ductwork hidden, maximizing room visibility.
- Particulate containment independently verified by SafeBridge Consultants, Inc
- ASHRAE 110-1995 conformity as independently verified by ECT, Inc
- Free validation package available. Contains SafeBridge Consultants, Inc. and ECT, Inc. Test Reports; Installation Qualification/ Operation Qualification (IQ/OQ) Protocol; and Maintenance Log.

### Options

- 2', 3', 4', 5', 6' and 8' widths
- Built-in Guardian™ 1000 Digital or Guardian™ Jr. Airflow Monitor with low voltage electrical cord, power pack, and plug

- International electrical configuration
- XPert Balance Enclosure Systems. One catalog number includes the XPert Balance Enclosure with Guardian
- Jr. Airflow Monitor, FilterMate Portable Exhauster, and Black Solid Epoxy Dished Work Surface

### **Required Accessories**


- Connection to a remote blower or FilterMate Portable Exhauster.
- Work surface.
- Supporting base.
- Carbon Filters for Some Models (see brochure).

### **Optional Accessories**

- Fluorescent Light Kits for installation atop the Enclosure for enhanced illumination of the interior. Include auxiliary electrical receptacle with switch.
- Transition Adapters for connecting ductwork routed either up or down
- Exhaust Dampers to allow adjustment to the airflow
- Utility Shelf Kit for attaching to the rear baffle perforations to hold a printer, utensils and other miscellaneous weighing supplies
- Replacement HEPA Filter
- Replacement Bag for HEPA Filter Bag-In/Bag-Out to ensure contamination of particulate matter during filter changing.

### **For Product Assistance**

- [International Customer Service](#).



- [Eric Liu](#) Regional Sales Manager, Asia



## FAQs


- **Q: Can the XPert Balance Enclosure be used without connecting to a blower or FilterMate Portable Exhauster?**
  - **A:** No, connection to a blower or exhauster is required for proper ventilation and containment of substances.
- **Q: How often should the HEPA filters be replaced?**
  - **A:** HEPA filters should be checked regularly and replaced according to usage and manufacturer recommendations to maintain air quality.
- **Q: Is the Bag-In/Bag-Out system necessary for filter replacement?**
  - **A:** Yes, the Bag-In/Bag-Out system ensures safe handling and disposal of contaminated filters during replacement.

## CONTACT INFORMATION





- Labconco Corporation
- 8811 Prospect Avenue
- Kansas City, MO 64132-2696
- Phone: [816-333-8811](tel:816-333-8811)



## Documents / Resources

	<p><b><a href="#">LABCONCO 3930221 Protector Work Station with Built</a></b> [pdf] Owner's Manual 3930221 Protector Work Station with Built, 3930221, Protector Work Station with Built, Work Station with Built, Station with Built, Built</p>
--	---

References

-  [TCPDF](#)
-  [2' XPert Balance Enclosure with Guardian Jr. Airflow Monitor - Labconco](#)
-  [International Customer Service - Labconco](#)
-  [Eric Liu - Labconco](#)
- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.