

LAMP MonoFlat LIN-X Hinge Instruction Manual

Home » **LAMP** » **LAMP** MonoFlat LIN-X Hinge Instruction Manual




Contents

- 1 MonoFlat LIN-X Hinge
- **2 Product Specification**
- 3 Parts List
- 4 Overall (unit: mm)
- **5 Overlay Distance**
- **6 Position of LIN-X Body**
- **7 Mounting Plate Position**
- 8 Installation
- 9 Adjustments
- 10 Individual Parts for Tall / Heavy
- 11 Documents / Resources
 - 11.1 References
- **12 Related Posts**

MonoFlat LIN-X Hinge

Thank you for purchasing this MonoFlat LIN-X hinge by SUGATSUNE. Before proceeding with the installation, please read this instruction manual carefully for the best possible result and ensure your safety.




WARNING WARNING


- Failure to observe the following precautions may result in injury and/or lead to damage to surrounding cabinets or fittings.
- Choose suitable screws to ensure proper installation of the cabinet and door.
- Ensure that door size, weight and material correspond to the specifications in this manual.
- Do not disassemble or modify the system.

Product Specification

Door Width	400~500 mm
Door Height	600~900 mm
Door Thickness	15~24 mm
Door Weight	Max. 7 kg (per door)


Parts List






Overall (unit: mm)

• Picture shows the left hand door use. (Right hand door use is symmetrical.)




Overlay Distance


- Side overlay as shown in Fig.1 is:
 19mm for mounting plate 230-P4W-32T: 0mm (Standard)
 14mm for mounting plate 230-P4W-32T: 5mm
- An opening clearance of 2mm is required on both sides of the door.



Position of LIN-X Body


• Prepare the door as per Fig.2 and Fig.3






Mounting Plate Position

• Prepare the sideboard for mounting plate installation as per Fig.4




Installation

1 Mounting Plate Installation:





2 Cup Cover Installation:



Ensure that the two are pointing toward the edge of the door.


3 LIN-X Body Installation:






Ensure that the two LIN-X bodies are parallel by measuring both the base and mounting plate distances.

4 Connecting Plate Installation:





5 Door Installation:



Ensure that the two LIN-X body is securely attached to the mounting plates.


Adjustments






Individual Parts for Tall / Heavy Doors

Door Preparation




Cabinet Preparation



Product Specification

Door Width	400~500 mm	
Door Height	600~900 mm	
Door Thickness	15~24 mm	
Door Weight	Max. 7 kg (per door)	



Hinge Distance A

# of Hinges	Length of Connecting Bar (mm)						
	540	840	1140	1440	1740	2040	
2 pcs	490	790	1090	_	_	_	
3 pcs	245	395	545	695	845		
4 pcs	_	263.3	363.3	463.3	563.3	663.3	
5 pcs	_	_	273.5	348.5	423.5	498.5	

SUGATSUNE KOGYO CO.,LTD. Phone: +81 (0)3 3866 2260 Fax: +81 (0)3 3866 4447

E-mail: <u>export@sugatsune.co.jp</u> Website: <u>www.sugatsune-intl.com</u> SUGATSUNE KOGYO (UK) LTD. Phone: +44 (0)1491 680737 Fax: +44 (0)1491 60762

E-mail: sales@sugatsune.co.uk
Website: www.sugatsune.co.uk

SUGATSUNE AMERICA, | Phone: +1 310 3296373 Fax: +1 310 3290819 E-mail: sales@sugatsune

Website: www.sugatsune



Documents / Resources



LAMP MonoFlat LIN-X Hinge [pdf] Instruction Manual MonoFlat LIN-X Hinge, MonoFlat, MonoFlat Hinge, LIN-X Hinge, Hinge

References

- ** Company Top | Architectural and Industrial Component Hardware | Japanese Manufacturer | LAMP |
 Sugatsune Global
- ** Company Top | Architectural and Industrial Component Hardware | Japanese Manufacturer | LAMP |
 Sugatsune UK
- * Architectural & Industrial Component Hardware | Sugatsune
- ③

Manuals+,