

LEDOLUX ORBIT LED Lamp Instruction Manual

Home » LEDOLUX » LEDOLUX ORBIT LED Lamp Instruction Manual


Contents


- 1 LEDOLUX ORBIT LED
- Lamp
- **2 PRODUCT OVERVIEW**
- 3 NOTE
- **4 APPLICATION**
- **5 NOT INCLUDED**
- 6 Documents / Resources
- **7 Related Posts**



LEDOLUX ORBIT LED Lamp







	ø	Н	Waga
100W	340mm	200mm	4.5kg
150W	340mm	200mm	5.0kg
200W	340mm	200mm	5.0kg
240W	340mm	200mm	5.5kg

NOMINAL VOLTAGE

205 - 260V ~

FREQUENCY

50 / 60Hz

COLOUR TEMPERATURE

4000K / 5000K

LUMINOUS EFFICACY

200lm/W

BEAM ANGLE

120° / 90° / 60°

OPERATING TEMPERATURE


-25°C ÷ +65°C

MOUNTING HEIGHT

NOTE

- The terminal block is not supplied. Installation must be performed by a qualified person. In case of doubts as to the installation or use of the LED luminaire, consult the manufacturer.
- Replace the luminaire after a failure. Self-repair shall void the warranty.
- This product contains a light source with energy efficiency class A.
- · Keep the luminaire in a cool, dry, and clean environment. Keep away from water and fire
- Make sure you disconnect the power supply before installation. Turn on the power after connecting and securing all luminaires in the circuit.
- The light source used in this luminaire should only be replaced by the manufacturer or their service representative, or a similarly qualified person
- Protect your eyes, and avoid looking at the light for a long period of time.
- Dirtiness that settles down on the luminaire due to normal operation shall be cleaned with a damp cloth.
- Do not use invasive cleaners or cleaning methods.

APPLICATION



- · Industrial facilities
- Warehouses
- · Technical rooms
- · Sport facilities

Ledolux Poland Sp. z o.o. E-mail: info@ledolux.pl Tel: +48 696 966 622 Data: 12.12.2022

We reserve the right to make design changes to luminaires.

Make sure you disconnect the power supply before installation




1. Fix the mounting bracket to the luminaire (hook M10, 10Nm).




2. Drill a hole in the ceiling and install the hook.




3. Hang luminaire




4. Connect the luminaire according to the wire markings.




5. Keep it watertight while connecting it.



6. Drill a hole in the ceiling, install screws.



- 7. Fix the mounting bracket to the luminaire using a hex wrench (4mm, 3Nm). Adjust the angle of tilt of the luminaire and lock the holder with a hex key (6mm, 5Nm). Attach the luminaire to the wall/ construction.
- 8. Connect the luminaire according to the wire markings. Keep it watertight while connecting it




NOT INCLUDED

Connecting the power cable



Connecting the dimming cable



When no dimming, secure dimming cables – separate and isolate each one.

Documents / Resources



LEDOLUX ORBIT LED Lamp [pdf] Instruction Manual ORBIT, ORBIT LED Lamp, LED Lamp, Lamp

