

LiftMaster 84505R Secure View Smart Garage Opener **Instruction Manual**

Home » LiftMaster » LiftMaster 84505R Secure View Smart Garage Opener Instruction Manual



Contents

- 1 LiftMaster 84505R Secure View Smart Garage **Opener**
- 2 Popular features
- 3 Camera with 2-way communication
- 4 In the box
- **5 Specifications**
- 6 Documents / Resources
 - **6.1 References**
- 7 Related Posts



LiftMaster 84505R Secure View Smart Garage Opener



Popular features

Quiet and smooth operation

Best-in-class belt drive system and DC motor provides reliable operation and lasting service.

myQ® Connected

Control, secure and monitor the garage from the myQ app anytime, from anywhere.

Secure in-garage delivery

Enables Amazon Key In-Garage Delivery – free for Amazon Prime members.

Security+ 2.0®

Safeguards garage access by sending a new code with every click of the remote.

myQ Diagnostics compatible

Provides real-time insights for your garage door via its Health Report. You will be sent alerts if an issue arises and can connect to your Dealer for professional services if needed.

Invisible light beam system

Auto-reverses the garage door if there is an obstruction.

Posilock® protection


Electronically protects against forced openings of the door.

Camera with 2-way communication

A built-in 130° wide angle camera lets you see and hear what's happening in your garage through the myQ app.



Do more with myQ



Use the myQ app to control, secure and monitor your garage and conveniently share and manage access to your home without sharing passcodes or keys. Also, take the hassle out of service repair and easily connect to a trusted Dealer through the myQ app

Integrated dual LED lighting system



Increase the functionality of the garage and never change a garage light bulb again. Dual lighting system provides 1,500 lumens of long-lasting LED light that brightens high traffic areas of the garage.

In the box

3-Buttom Remote Control



Operates up to 3 openers or myQ light accessories. Safeguards your home with Security+ 2.0.

Multi-Function Control Panel®



Operates the garage door opener and lights from inside the garage.

Specifications

Motor

12V DC, 53 RPM, automatic thermal protection

Mechanics

- Steel chassis, T-rail and trolley, full reinforced belt drive mechanism (63:1 gear reduction and adjustable door arm)
- Auto-force adjustment for changing weather and environmental conditions
- · Electronic limits for easy setup
- DC Wi-Fi logic board with built-in surge suppressor (for replacement logic boards, order part 050DCTBFMC)

Power

120V AC, 60 Hz voltage, 6A current rating, UL Listed, 4' power cord (3-prong)

Speed

7.2" per second upward, 7.2" per second downward

Lighting

Dual light lens LED - 1,500 lumens

Dimensions

• Opener head: 10.5" L x 12.72" W x 8.185" H

Note: when both decorative doors are open, the width of the opener is 30".

Rail Options:	7' (2777BD)	8' (2778BD)	10' (2770BD)
Installed Length:	127"	139"	163"
Max Opening:	7' 6"	8' 6"	10' 6"

Mounting

Side-to-Side

Warranties

Lifetime: Motor and Belt

2. 1 Year: Parts, Camera, Accessories and LED

Security+ 2.0

Radio controls:

Operating range ~200'; Operating temperature: -40F to 150F; 3-Button Remote Control (893LM), Remote Control Code Format: Security+2.0, premium remote control; Garage Door Opener Code Format: Security+2.0; Antiburglary coding.

Encrypted controls:

Multi-Function Control Panel (882LMW); Program remote controls, maintenance alert system, easy Wi-Fi set up.

myQ Radio

902-928 MHz 50-Channel FHSS (frequently hopping spread spectrum); Provides 2-way communication from garage door opener and myQ accessories; Enables monitoring and control of garage door openers via smartphone or tablet.

HomeLink® compatible (version 4.0 or higher)

May require an external adapter depending on the model and year of vehicle. Visit HomeLink.com for additional information.

Carton 1 shipping details

• Dimensions: 14" x 12" x 11"

 Contents: Garage Door Opener Head (84505R), Multi-Function Control Panel (882LMW), 3-Button Remote Control (893LM), The Protector System® Safety Reversing Sensors

· Weight: 19.4 lbs.

Carton 2 shipping details

• **Dimensions:** 10'4" x 5" x 5" (for 7' rail)

• Contents: Assembled Solid-Steel Belt T-Rail

• Weight: 17 lbs.

Documents / Resources



<u>LiftMaster 84505R Secure View Smart Garage Opener</u> [pdf] Instruction Manual 84505R, Secure View Smart Garage Opener, 84505R Secure View Smart Garage Opener, View Smart Garage Opener, Smart Garage Opener, Opener

References

- ♠ HomeLink
- LiftMaster | Garage Door Openers, Remotes & Accessories