



# LINDY 38205 50m Cat.6 HDMI and IR Extender with Loop Out Owner's Manual

[Home](#) » [LINDY](#) » LINDY 38205 50m Cat.6 HDMI and IR Extender with Loop Out Owner's Manual 

## Contents

- [1 LINDY 38205 50m Cat.6 HDMI and IR Extender with Loop Out](#)
- [2 Product Information](#)
- [3 Features](#)
- [4 Packaging data](#)
- [5 Disclaimer.](#)
- [6 Documents / Resources](#)
- [7 Related Posts](#)



**LINDY 38205 50m Cat.6 HDMI and IR Extender with Loop Out**



## Product Information

- Extends 4K HDMI 18G signals over 50m distances with standard network cable
- Supports resolutions up to 3840×2160@60Hz 4:4:4 8bit, with support for HDR
- An HDMI loop-through output creates an additional viewing zone with a local display
- PoC (Power over Cat.6) functionality for power from a single power supply

50m Cat.6 HDMI 4K60 & IR Extender with PoC & Loop Out

Lindy 50m Cat.6 HDMI & IR Extender with Loop Out. Type: AV transmitter & receiver, Maximum resolution: 3840 x 2160 pixels, Cable types supported: Cat5e, Cat6. Connectivity technology: Wired, USB connector type: Micro-USB. Operating voltage: 24 V, Input current: 1 A. Receiver dimensions (WxDxH): 70 x 15 x 97 mm, Receiver weight: 151 g, Transmitter dimensions (WxDxH): 70 x 15 x 97 mm. Package width: 220 mm, Package depth: 70 mm, Package height: 130 mm

## Features


- Type \* AV transmitter & receiver
- Maximum resolution \* 3840 x 2160 pixels
- Cable types supported Cat5e, Cat6
- Maximum transfer distance 50 m
- Chipset SIL9396, SIL9630
- Maximum refresh rate 60 Hz
- Extended display identification data (EDID) ✓
- IR pass-through ✓
- HDCP pass-through ✓
- Bandwidth 18 Gbit/s
- HDCP ✓
- Material Metal

- Product colour Black
- Certification CE, FCC, REACH & California Proposition 65

### Ports & interfaces

- Connectivity technology \* Wired
- RJ-45 input ports 1
- RJ-45 output ports 1
- HDMI in 1
- Number of HDMI outputs 2
- HDMI version 2.0
- USB ports quantity 2
- USB connector type Micro-USB
- Remote (IR) input 1
- Remote (IR) output 1

### Ports & interfaces

- DC-in jack 

### Power

- Operating voltage 24 V
- Input current 1 A

### Operational conditions

- Operating temperature (T-T) 0 – 40 °C
- Storage temperature (T-T) -20 – 60 °C
- Operating relative humidity (H-H) 20 – 90%

### Weight & dimensions


- Receiver dimensions (WxDxH) 70 x 15 x 97 mm
- Receiver weight 151 g
- Transmitter dimensions (WxDxH) 70 x 15 x 97 mm
- Transmitter weight 156 g

### Packaging data

- Package width 220 mm
- Package depth 70 mm
- Package height 130 mm
- Package weight 605 g

- Package type Box

**Packaging content**

- Cables included IR
- Manual 

**Technical details**


- Sustainability certificates RoHS

**Disclaimer.**

The information published here (the “Information”) is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided “AS IS” and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information.

You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

**Documents / Resources**

	<p><a href="#">LINDY 38205 50m Cat.6 HDMI and IR Extender with Loop Out</a> [pdf] Owner's Manual 38205 50m Cat.6 HDMI and IR Extender with Loop Out, 38205, 50m Cat.6 HDMI and IR Extender with Loop Out, IR Extender with Loop Out, Loop Out</p>
---	---