

Linxura SCHA-1-SP Network Thermostat Smart Controller User Guide

Network Thermostat Setup Guide Video Link: <https://youtu.be/Nqg3Q67zoko>

Contents

- [1 Supported Features for the Network Thermostat](#)
- [2 How to link Linxura with Network Thermostat.](#)
- [3 How to use Linxura to control the Network Thermostat device.](#)
- [4 Documents / Resources](#)
 - [4.1 References](#)

Supported Features for the Network Thermostat

Network Thermostat button action description table

Actions	Supported Mode	Descriptions
Click/Double Click	Mode: Heat, Cool, Auto, Eco	Heat: Switch to Heat mode. Cool: Switch to Cool mode. Auto: Switch to Auto mode. Eco: Switch to Eco mode. Off: Turn off the thermostat.
	Temperature: Heat Setpoint, Cool Setpoint	Heat Setpoint: Activate heating when below set temperature. Cool Setpoint: Activate cooling when above set temperature.
Rotate Clockwise/ Rotate Counterclockwise	Temperature Up, Temperature Down	Temperature Up: Raise the temperature by a preset percentage per rotation. Temperature Down: Lower the temperature by a preset percentage per rotation.

How to link Linxura with Network Thermostat.

Step 1:

Make sure your Network Thermostat device is set up in the Network Thermostat app and functioning properly. Make sure Linxura, Linxura app, Hunter Douglas are connected to same Wi-Fi network.

Step 2:

Open your Linxura app and then select the Linxura you want to bind with Network Thermostat.

Step 3:

Choose a button.

Step 4:

Click 'Select platform'.

Step 5:

Select 'Network Thermostat' option.

Step 6:

Select Network Thermostat device.

Step 7:

Log in to your Network Thermostat account and click 'Save.'

How to use Linxura to control the Network Thermostat device.**Step 1:**

Click the '+' icon to add a Click Action.

Step 2:

Click 'Mode' and select one of the options.

Step 3:

Select one of the Options.

Step 4:

Click 'Temperature'.

Step 5:

Set the temperature of the NetworkThermostat.

Step 6:


Click the 'Save'.

Step 7:

You can follow the same steps to configure Double Click, Rotate Clockwise, and Rotate Counterclockwise.

You can now use Linxura to control your Network Thermostat!

Documents / Resources

	<p>Linxura SCHA-1-SP Network Thermostat Smart Controller [pdf] User Guide</p> <p>SCHA-1-SP Network Thermostat Smart Controller, SCHA-1-SP, Network Thermostat Smart Controller, Thermostat Smart Controller, Smart Controller, Controller</p>
--	---

References

- [User Manual](#)

[Manuals+](#), [Privacy Policy](#)

This website is an independent publication and is neither affiliated with nor endorsed by any of the trademark owners. The "Bluetooth®" word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. The "Wi-Fi®" word mark and logos are registered trademarks owned by the Wi-Fi Alliance. Any use of these marks on this website does not imply any affiliation with or endorsement.