



Lumie SAI2206 Alarm Clock and Dawn Simulator Instruction Manual

[Home](#) » [lumie](#) » Lumie SAI2206 Alarm Clock and Dawn Simulator Instruction Manual 

Lumie SAI2206 Alarm Clock and Dawn Simulator

Contents

- [1 Safety](#)
- [2 Getting started](#)
- [3 Documents / Resources](#)
- [4 Related Posts](#)

Safety



Read instructions for use.

If the unit is damaged, contact Lumie before use.



Keep away from water and damp.



For indoor use only.

The unit gets warm when the light is on, so make sure that it is not covered.

Use only the mains power adaptor supplied.

Keep the mains power adaptor and cable away from heated surfaces. If either are damaged, they should be replaced with an approved Lumie product.

To power down or reset, remove the mains power adaptor from the wall socket. You should therefore ensure the socket is easily accessible.



Caution – do not attempt to service or modify any part of the unit.

If the unit has been stored outside the recommended operating temperature range (5 °C to 35 °C), allow it to stand for at least 1 hour before applying power to avoid condensation or overheating.

The light source contained in this luminaire shall only be replaced by Lumie or an authorised Lumie distributor.

Electromagnetic compatibility

Electrostatic discharge may affect the working of this product. If this occurs, simply switch off for at least 10 seconds and the unit will reset.

Disposal



Do not throw out the mains power adaptor or the unit with normal domestic waste. Take them to an official recycling point to be disposed of responsibly.

Getting started

The ideal place for Sunrise Alarm is on a bedside table near a mains socket.

- Connect the mains power adaptor to the socket on the back of the unit.
- Plug into a mains power supply.

Set the current time when the display flashes. If it stops flashing, press

T on the back panel.

The hours will flash.

- Use – or + to set the hours.
- Press T on the back panel to confirm and continue.

The minutes will flash.


- Use – or + to set the minutes.
- Press T on the back panel to confirm and continue.
- Use – or + to choose 24H or 12H.
- Press T on the back panel to confirm and exit to the current time.

To change the current time

- Press T on the back panel and set the time as above.



Documents / Resources

	<p>Lumie SAI2206 Alarm Clock and Dawn Simulator [pdf] Instruction Manual</p> <p>SAi2206 Alarm Clock and Dawn Simulator, SAI2206, Alarm Clock and Dawn Simulator, Clock a nd Dawn Simulator, Dawn Simulator, Simulator</p>
---	---