



UT60S

Specification	Range	Accuracy
Certificates	CE, UKCA, cETLus	
DC voltage (V)	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	$\pm(0.5\%+3)$
AC voltage (V)	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	$\pm(0.8\%+3)$
DC current (A)	999.9 μ A/999.9mA/9.999A	$\pm(0.8\%+3)$
AC current (A)	999.9 μ A/999.9mA/9.999A	$\pm(1.0\%+3)$
Resistance (Ω)	99.99 Ω /999.9 Ω /9.999k Ω /99.99k Ω /999.9M Ω /99.99M Ω	$\pm(0.8\%+2)$
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999 μ F/99.99 μ F/999.9 μ F/9.999mF/99.9mF	$\pm(4\%+5)$
Frequency	9.999Hz~9.999MHz	$\pm(0.1\%+5)$
Duty cycle	0.1~99.9%	$\pm(3\%+5)$
Temperature	-40°C~1000°C/-40°F~1832°F	$\pm4^\circ\text{C}/\pm5^\circ\text{F}$

Features

Display count	9999
Auto range	✓
NCV	✓
Diode/REL	✓
Continuity test	✓
Acousto-optic indication(NCV/continuity/battery power)	✓
Low battery indication	$\leq 3.6\text{V}$
Data hold	✓
Auto power off	15Min
Operation temperature	0°C~40°C
Safety	CATII 1000V/CATIII 600V

General Characteristics

Battery	1.5VAAA x3
Product color	Red and Gray
Product net weight	290g
Product size	169 x 81 x 46mm
Standard individual packing	Gift Box, Manual, Thermocouple
Standard quantity per carton	20pcs
Standard carton size	420 x 320 x 300mm