

[illegible][illegible]

SPECIFICATIONS									
Type	Continuous power handling	Frequency response	Nominal impedance	Sensitivity (2.50V/m)	External diameter	Mounting cutout diameter	Total depth		
QX302	3-1/2" (89mm)	two-way speaker	25W	60Hz - 20kHz	90dB	3-9/16" (89mm)	3-1/8" (73mm)	2" (51mm)	Mounting depth
	5-1/4" (133mm)	two-way speaker	35W	75Hz - 21kHz	90dB	4-1/8" (104mm)	3-3/4" (89mm)	2-13/32" (65mm)	
	5-1/4" (133mm)	two-way speaker	45W	80Hz - 21kHz	91dB	5-1/8" (127mm)	4-3/4" (120mm)	2-7/8" (67mm)	
	6-1/2" (165mm)	two-way speaker	60W	85Hz - 21kHz	92dB	6-1/2" (165mm)	5-1/8" (127mm)	2-7/8" (72mm)	
	8-11/16" (220mm)	two-way speaker	120W	85Hz - 21kHz	92dB	7-1/8" (182mm)	6-1/2" (165mm)	2-7/8" (72mm)	
QX402	4" (100mm)	two-way speaker	25W	60Hz - 21kHz	90dB	3-9/16" (89mm)	3-3/8" (73mm)	2" (51mm)	Mounting depth
	5-1/4" (133mm)	two-way speaker	35W	75Hz - 21kHz	90dB	4-1/8" (104mm)	3-3/4" (89mm)	2-13/32" (65mm)	
	5-1/4" (133mm)	two-way speaker	45W	80Hz - 21kHz	91dB	5-1/8" (127mm)	4-3/4" (120mm)	2-7/8" (67mm)	
	6-1/2" (165mm)	two-way speaker	60W	85Hz - 21kHz	92dB	6-1/2" (165mm)	5-1/8" (127mm)	2-7/8" (72mm)	
	8-11/16" (220mm)	two-way speaker	120W	85Hz - 21kHz	92dB	7-1/8" (182mm)	6-1/2" (165mm)	2-7/8" (72mm)	
QX602	4" (100mm)	two-way speaker	25W	60Hz - 21kHz	90dB	3-9/16" (89mm)	3-3/8" (73mm)	2" (51mm)	Mounting depth
	5-1/4" (133mm)	two-way speaker	35W	75Hz - 21kHz	90dB	4-1/8" (104mm)	3-3/4" (89mm)	2-13/32" (65mm)	
	5-1/4" (133mm)	two-way speaker	45W	80Hz - 21kHz	91dB	5-1/8" (127mm)	4-3/4" (120mm)	2-7/8" (67mm)	
	6-1/2" (165mm)	two-way speaker	60W	85Hz - 21kHz	92dB	6-1/2" (165mm)	5-1/8" (127mm)	2-7/8" (72mm)	
	8-11/16" (220mm)	two-way speaker	120W	85Hz - 21kHz	92dB	7-1/8" (182mm)	6-1/2" (165mm)	2-7/8" (72mm)	
QX642	4" (100mm)	two-way speaker	25W	60Hz - 21kHz	90dB	3-9/16" (89mm)	3-3/8" (73mm)	2" (51mm)	Mounting depth
	5-1/4" (133mm)	two-way speaker	35W	75Hz - 21kHz	90dB	4-1/8" (104mm)	3-3/4" (89mm)	2-13/32" (65mm)	
	5-1/4" (133mm)	two-way speaker	45W	80Hz - 21kHz	91dB	5-1/8" (127mm)	4-3/4" (120mm)	2-7/8" (67mm)	
	6-1/2" (165mm)	two-way speaker	60W	85Hz - 21kHz	92dB	6-1/2" (165mm)	5-1/8" (127mm)	2-7/8" (72mm)	
	8-11/16" (220mm)	two-way speaker	120W	85Hz - 21kHz	92dB	7-1/8" (182mm)	6-1/2" (165mm)	2-7/8" (72mm)	
QX962	6" (152mm)	two-way speaker	25W	60Hz - 21kHz	90dB	5-1/16" (8.3mm)	5-1/16" (8.3mm)	2-7/8" (72mm)	Mounting depth
	8" (203mm)	two-way speaker	35W	75Hz - 21kHz	90dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
	8" (203mm)	two-way speaker	45W	80Hz - 21kHz	91dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
	10" (254mm)	two-way speaker	60W	85Hz - 21kHz	92dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
	12" (305mm)	two-way speaker	100W	85Hz - 21kHz	94dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
QX963	6" (152mm)	two-way speaker	25W	60Hz - 21kHz	90dB	5-1/16" (8.3mm)	5-1/16" (8.3mm)	2-7/8" (72mm)	Mounting depth
	8" (203mm)	two-way speaker	35W	75Hz - 21kHz	90dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
	8" (203mm)	two-way speaker	45W	80Hz - 21kHz	91dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
	10" (254mm)	two-way speaker	60W	85Hz - 21kHz	92dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
	12" (305mm)	two-way speaker	100W	85Hz - 21kHz	94dB	6-1/16" (9.5mm)	6-1/16" (9.5mm)	2-7/8" (72mm)	
QX600C	6-1/2" (165mm)	two-way component system	70W	60Hz - 21kHz	90dB	6-1/4" (158mm)	6-1/8" (158mm)	2-5/8" (65mm)	Mounting depth
	8-1/2" (215mm)	two-way component system	100W	60Hz - 21kHz	90dB	8-1/4" (210mm)	8-1/8" (210mm)	2-5/8" (65mm)	
	10-1/2" (267mm)	two-way component system	150W	60Hz - 21kHz	90dB	10-1/4" (262mm)	10-1/8" (262mm)	2-5/8" (65mm)	
	12-1/2" (318mm)	two-way component system	200W	60Hz - 21kHz	90dB	12-1/4" (313mm)	12-1/8" (313mm)	2-5/8" (65mm)	
	14-1/2" (368mm)	two-way component system	250W	60Hz - 21kHz	90dB	14-1/4" (363mm)	14-1/8" (363mm)	2-5/8" (65mm)	

8-11/16" (220mm)

5-1/16" (143mm)

9-5/16" (235mm)

6-1/2" (164mm)

6-1/2" (164mm)

9-5/16" (235mm)

GX962/GX963

- Side View:
 - Top Diameter: 8-3/4" (221 mm)
 - Mounting Hole Diameter: 3-3/8" (85 mm)
 - Mounting Hole Spacing: 7-7/8" (199 mm)
 - Bottom Diameter: 7-7/8" (199 mm)
- Top View:
 - Outer Diameter: 5-1/8" (130 mm)
- Bottom View:
 - Top Diameter: 4-3/4" (120 mm)
 - Mounting Hole Diameter: 2-1/4" (57 mm)
 - Mounting Hole Spacing: 2-7/8" (74 mm)

GX862

- Side View:
 - Top Diameter: 7-5/16" (185 mm)
 - Mounting Hole Diameter: 2-7/16" (67 mm)
 - Mounting Hole Spacing: 2-7/8" (72 mm)
 - Bottom Diameter: 2-7/8" (72 mm)
- Top View:
 - Outer Diameter: 3-9/16" (89 mm)
- Bottom View:
 - Top Diameter: 3-1/8" (79 mm)
 - Mounting Hole Diameter: 1-7/16" (36 mm)
 - Mounting Hole Spacing: 2" (51 mm)

GX502

- Side View:
 - Top Diameter: 4-3/4" (120 mm)
 - Mounting Hole Diameter: 2-1/4" (57 mm)
 - Mounting Hole Spacing: 2-7/8" (74 mm)
- Top View:
 - Outer Diameter: 4-1/8" (104 mm)
- Bottom View:
 - Top Diameter: 3-3/4" (95 mm)
 - Mounting Hole Diameter: 1-7/8" (47 mm)
 - Mounting Hole Spacing: 2-19/32" (60 mm)

GX402

- Side View:
 - Top Diameter: 3-3/4" (95 mm)
 - Mounting Hole Diameter: 1-7/8" (47 mm)
 - Mounting Hole Spacing: 2-19/32" (60 mm)
- Top View:
 - Outer Diameter: 4-1/8" (104 mm)
- Bottom View:
 - Top Diameter: 3-3/4" (95 mm)
 - Mounting Hole Diameter: 1-7/8" (47 mm)
 - Mounting Hole Spacing: 2-19/32" (60 mm)

GX302

- Side View:
 - Top Diameter: 3-9/16" (89 mm)
 - Mounting Hole Diameter: 2-7/16" (67 mm)
 - Mounting Hole Spacing: 2-7/8" (72 mm)
 - Bottom Diameter: 2-7/8" (72 mm)
- Top View:
 - Outer Diameter: 3-9/16" (89 mm)
- Bottom View:
 - Top Diameter: 3-1/8" (79 mm)
 - Mounting Hole Diameter: 1-7/16" (36 mm)
 - Mounting Hole Spacing: 2" (51 mm)

[illegible][illegible][illegible][illegible]