

MF5 Metal and Conductive Target Detector

Minelab's unique Simultaneous Multi-Frequency Digital technology results in the MF5 providing superior detection capabilities by combining the advantages of Pulse Induction and Continuous Wave technologies. The MF5 is a lightweight and compact detector designed for operator comfort and ease of use. The MF5 is suitable for Non-Government Organisations (NGO) and military clearance operations.



The **MF5** is supplied as a Detecting Set comprising:

Included Items:

- MF5 Detector
- Carry Bag
- Hard Transit Case
- C cell Batteries (NiMH or Alkaline x 4)
- Earset
- Test Piece
- Operations Manual
- Field Guide



MF5 Key Features



- Detects metal and conductive targets including fine wires and carbon rods
- Able to detect targets in all types of soil regardless of mineralised content
- Selectable Target Alert Responses (Audio, Visual (LED), Vibration)
- Selectable sensitivity
- Adjustable volume
- Three sensor modes:
 - / Detection Mode
 - / Interrogation Mode
 - / Pinpoint Mode
- Provides indications of ferrous and non-ferrous targets, carbon rods and fine wires
- Able to operate in environments of high electrical interference
- Provision of a Tactical Mode selectable at start-up or anytime during operations
- Fully adjustable for operator comfort
- Simple and intuitive controls
- Fast and simple three step setup procedure
- Open web coil
- Waterproof — IP 68

MF5 SPECIFICATIONS

MF5 GENERAL SPECIFICATIONS

Volume Control	1 to 9
Collapsed Size	400 x 99 x 194 mm (15.7" x 3.9" x 7.6")
Extended Size	1615 x 191 x 237 mm (63.6" x 7.5" x 9.3")
Weight, Operational	2.8 kg (6.2 lb) with rechargeable NiMH C cell batteries
Audio Output	Internal Speaker / MF5 Earset / Audio Adaptor Cable
Earset	MF5 Earset
Waterproof	Waterproof to 3 m / 10 ft (IP 68)
Operating Temperature Range	-30°C to +60°C (-22°F to 140°F)
Storage Temperature Range	-30°C to +80°C (-22°F to 176°F)
Environmental	MIL-STD-810G
EMC	MIL-STD-461G
Compliance	CE / RCM / FCC / IC
Software Upgradeable	Yes
Battery Compatibility	Rechargeable NiMH / Alkaline C cells
Battery Life	10 hours with NiMH batteries

MF5 DETECTION SPECIFICATIONS

Key Technologies	Simultaneous Multi-Frequency Digital Metal Detection
Coil	Transmit Coil: Monoloop 269 x 191 mm (10.6" x 7.5")
	Receive Coil: Figure 8
Operating Frequencies	Four frequencies in the range 5 kHz to 75 kHz
Output Power	<-30dBm
Sensitivity	1 to 5
Noise Cancel	Automatic, Operator initiated
Ground Balance	Automatic, Operator initiated, Settings retained after switch off
Target Identification	Ferrous / Non-Ferrous / Carbon Rods — Fine Wires

COUNTERMINE

+61 (8) 8238 0888
 countermin@minelab.com.au

www.minelab.com/countermine

As a world leader in metal sensing technology, Minelab strives to continually improve its product range. Minelab reserves the right to introduce changes to the design, technical features and accessories of this product. MF5® and MINELAB® are registered trademarks of Minelab Electronics Pty. Ltd.

