



Meraki Go GX50 Datasheet

Meraki Go Router Firewall Plus

GX50

Performance

- Firewall Throughput - 500+ Mbp/s
- Client VPN Throughput - 300 Mbps
- VPN Tunnels - 50
- Recommended for 50 clients

Interfaces

- WAN Interface: 1x 10/100/1000 BASE-T Ethernet (RJ45)
- LAN interfaces: 4x 10/100/1000 BASE-T Ethernet (RJ45)

Network and Security Services

- Stateful firewall
- Port Forwarding
- DHCP services
- DNS based security powered by Cisco Umbrella (additional subscription required)
- Client VPN
- Site-to-Site VPN (GX50 to GX50 only)

Environment

- Operating temperature: 32 °F to 113 °F (0 °C to 45 °C)
- Humidity: 5 to 95% non-condensing
- Kensington lock hard point

Power

- 18W DC Power Supply Included

Power Load

- 5 Watts idle
- 14 Watts max

Physical Dimensions

- 1.1 x 5.1 x 9.4 in / 27 x 130 x 239 mm, not including deskmount feet or

Warranty

- 1 year hardware warranty (US and Japan)

mount plate

- 2 year hardware warranty (UK and EU)

Weight

- 1.74 lb / 0.79 kg

LED Indicators

- 2 Ethernet status
- 1 power/booting/firmware upgrade status

In the Box

- GX50-HW: Meraki Go Security Gateway
- Wall mount and screw kit
- Quick start guide
- PSU and ethernet cable

Model List / Accessories

GX50-HW-XX Security Gateway - Desktop

GA-PWR-50WAC 50W Replacement Laptop Style Adapter for GX50

XX = US/UK/EU

Cisco Systems, Inc. | 500 Terry A. Francois Blvd, San Francisco, CA 94158 | (415) 432-1000 | help@meraki-go.com