

TEST REPORT

FCC Rules Part 15.247

Report Reference No.....: MTEB24120264-R

FCC ID.....: RGR-KMC4

Compiled by

(position+printed name+signature)..: File administrators Alisa Luo



Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng



Approved by

(position+printed name+signature)..: Manager Yvette Zhou



Date of issue.....: Dec.20,2024

Representative Laboratory Name.: Shenzhen Most Technology Service Co., Ltd.

Address.....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China.

Applicant's name.....: Stillwater Designs and Audio Inc.

Address.....: 3100 N Husband St. Stillwater OK 74075 USA

Test specification/ Standard.....: FCC Rules Part 15.247

TRF Originator.....: Shenzhen Most Technology Service Co., Ltd.

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Weather Resistant Gauge -Style Media Center with Bluetooth

Trade Mark.....: KICKER

Model/Type reference.....: KMC4

Listed Models: N/A

Modulation Type.....: GFSK, $\pi/4$ DQPSK, 8DPSK

Operation Frequency.....: From 2402MHz to 2480MHz

Hardware Version.....: 1120-KMC402-MB06

Software Version.....: KMC4-X3-KIC-V1.45

Rating.....: DC 12V by DC Source

Result.....: **PASS**

TEST REPORT

Equipment under Test : Weather Resistant Gauge -Style Media Center with Bluetooth

Model /Type : KMC4

Listed Models : N/A

Remark 1 : N/A

Applicant : **Stillwater Designs and Audio Inc.**

Address : 3100 N Husband St. Stillwater OK 74075 USA

Manufacturer : **Eastern Partner Limited**

Address : Room 1413, ICC Tower ,Fuhau San Road,Futian CBD,Shenzhen 518048,China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1 REVISION HISTORY	4
2 TEST STANDARDS	5
3 SUMMARY	6
3.1 General Remarks	6
3.2 Product Description	6
3.3 Equipment Under Test	6
3.4 Short description of the Equipment under Test (EUT)	6
3.5 EUT operation mode	7
3.6 Block Diagram of Test Setup	7
3.7 Test Item (Equipment Under Test) Description*	7
3.8 Auxiliary Equipment (AE) Description	7
3.9 Antenna Information*	7
3.10 Related Submittal(s) / Grant (s)	8
3.11 Modifications	8
3.12 EUT configuration	8
4 TEST ENVIRONMENT	9
4.1 Address of the test laboratory	9
4.2 Environmental conditions	9
4.3 Summary of measurement results	10
4.4 Statement of the measurement uncertainty	10
4.5 Equipments Used during the Test	11
5 TEST CONDITIONS AND RESULTS	12
5.1 AC Power Conducted Emission	12
5.2 Radiated Emission	13
5.3 Maximum Peak Output Power	30
5.4 20dB Bandwidth	31
5.5 Frequency Separation	32
5.6 Number of hopping frequency	33
5.7 Time of Occupancy (Dwell Time)	34
5.8 Spurious RF Conducted Emission	35
5.9 Pseudorandom Frequency Hopping Sequence	36
5.10 Antenna Requirement	37
6 TEST SETUP PHOTOS OF THE EUT	38
7 PHOTOS OF THE EUT	39
APPENDIX I. Duty Cycle	40
APPENDIX II. Dwell Time	45
APPENDIX III. Number Of Hopping Channel	48
APPENDIX IV. Conducted Peak Output Power	50
APPENDIX V. 99% Bandwidth	51
APPENDIX VI. 20dB Bandwidth	53
APPENDIX VII. Carrier Frequencies Separation	55
APPENDIX VIII. Conducted Out Of Band Emission	57

1 Revision History

Revision	Issue Date	Revisions	Revised By
00	2024.12.20	Initial Issue	Alisa Luo

2 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

3 SUMMARY

3.1 General Remarks

Date of receipt of test sample	:	2024.12.03
Testing commenced on	:	2024.12.04
Testing concluded on	:	2024.12.20

3.2 Product Description

Product Name:	Weather Resistant Gauge -Style Media Center with Bluetooth
Model/Type reference:	KMC4
Power Supply:	DC 12V by DC Source
Testing sample ID:	MTYP07678
Bluetooth :	
Supported Type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	PCB Antenna
Antenna gain:	0dBi

3.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 12V by DC Source

3.4 Short description of the Equipment under Test (EUT)

This is a Weather Resistant Gauge -Style Media Center with Bluetooth For more details, refer to the user's manual of the EUT.


3.5 EUT operation mode

The Applicant provides communication tools software(Engineer mode) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency:

Channel	Frequency (MHz)
00	2402
01	2403
⋮	⋮
38	2440
39	2441
40	2442
⋮	⋮
77	2479
78	2480

3.6 Block Diagram of Test Setup



3.7 Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A					
EUT B					

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.8 Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1				
AE 2				

3.9 Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	PCB Antenna	2.4 – 2.5 GHz	---	0dBi
Antenna 2					

*: declared by the applicant.

3.10 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for the device filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

3.11 Modifications

No modifications were implemented to meet testing criteria.

3.12 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - Supplied by the lab

●	ADAPTER	M/N:	/
		Manufacturer:	/

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.
The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Designation No.: CN1315

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

4.3 Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Test result
§15.247(a)(1)	Carrier Frequency separation	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Middle	Compliant
§15.247(a)(1)	Number of Hopping channels	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Full	GFSK 8DPSK	<input checked="" type="checkbox"/> Full	Compliant
§15.247(a)(1)	Time of Occupancy (dwell time)	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Middle	Compliant
§15.247(a)(1)	Spectrum bandwidth of aFHSS system 20dB bandwidth	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(b)(1)	Maximum output power	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d)	Band edge compliance conducted	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	Compliant
§15.205	Band edge compliance radiated	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d)	TX spurious emissions conducted	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.247(d)	TX spurious emissions radiated	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	Compliant
§15.209(a)	TX spurious Emissions radiated Below 1GHz	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Middle	Compliant
§15.107(a) §15.207	Conducted Emissions 9KHz-30 MHz	GFSK Π/4DQPSK 8DPSK	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	GFSK	<input checked="" type="checkbox"/> Middle	N/A

Remark:

1. The measurement uncertainty is not included in the test result.
2. We tested all test mode and recorded worst case in report

4.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)
20dB Bandwidth	/	5%	(1)
Maximum Conducted Output Power	/	0.80dB	(1)
Spurious RF Conducted Emission	/	1.6dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.5 Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware versions	Last Cal.
1.	L.I.S.N.	R&S	ENV216	100093	/	2024/03/15
2	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	/	2024/03/15
3.	Receiver	R&S	ESCI	100492	V3.0-10-2	2024/03/15
4	Receiver	R&S	ESPI	101202	V3.0-10-2	2024/03/15
5	Spectrum analyzer	Agilent	9020A	MT-E306	A14.16	2024/03/15
6	Bilong Antenna	Sunol Sciences	JB3	A121206	/	2024/08/14
7	Horn antenna	HF Antenna	HF Antenna	MT-E158	/	2024/03/15
8	Loop antenna	Beijing Daze	ZN30900B	/	/	2024/03/15
9	Horn antenna	R&S	OBH100400	26999002	/	2024/03/15
10	Wireless Communication Test Set	R&S	CMW500	/	CMW-BASE-3.7.21	2024/03/15
11	Spectrum analyzer	R&S	FSP	100019	V4.40 SP2	2024/03/15
12	High gain antenna	Schwarzbeck	LB-180400KF	MT-E389	/	2024/03/15
13	Preamplifier	Schwarzbeck	BBV 9743	MT-E390	/	2024/03/15
14	Pre-amplifier	EMCI	EMC051845S E	MT-E391	/	2024/03/15
15	Pre-amplifier	Agilent	83051A	MT-E392	/	2024/03/15
16	High pass filter unit	Tonscend	JS0806-F	MT-E393	/	2024/03/15
17	RF Cable(below1GHz)	Times	9kHz-1GHz	MT-E394	/	2024/03/15
18	RF Cable(above 1GHz)	Times	1-40G	MT-E395	/	2024/03/15
19	RF Cable (9KHz-40GHz)	Tonscend	170660	N/A	/	2024/03/15
20	Power meter	R&S	NRVS	100444	/	2024/03/15

Note: The Cal.Interval was one year.

5 TEST CONDITIONS AND RESULTS

5.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS

N/A


5.2 Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$\text{Transd} = AF + CL - AG$$

RADIATION LIMIT

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.


The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz})) + 40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz})) + 40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30) + 40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
3. For below 1GHz testing recorded worst at GFSK DH5 middle channel.
4. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
5. Remark: Result=Reading value+Factor

For 30MHz-1GHz



For 1GHz to 25GHz

Note: GFSK, $\pi/4$ DQPSK and 8DPSK all have been tested, only worse case GFSK is reported.

GFSK (above 1GHz)

Frequency(MHz):			2402		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	54.41	PK	74	19.59	52.51	31.42	6.98	36.5	1.9
4804	46.82	AV	54	7.18	44.92	31.42	6.98	36.5	1.9
7206	53.24	PK	74	20.76	42.64	37.03	8.87	35.3	10.6
7206	43.14	AV	54	10.86	32.54	37.03	8.87	35.3	10.6

Frequency(MHz):			2402		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804	53.76	PK	74	20.24	51.86	31.42	6.98	36.5	1.9
4804	43.4	AV	54	10.6	41.5	31.42	6.98	36.5	1.9
7206	52.5	PK	74	21.5	41.9	37.03	8.87	35.3	10.6
7206	41.57	AV	54	12.43	30.97	37.03	8.87	35.3	10.6

Frequency(MHz):			2441		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	53.54	PK	74	20.46	51.48	30.98	7.58	36.5	2.06
4882	42.28	AV	54	11.72	40.22	30.98	7.58	36.5	2.06
7323	54.24	PK	74	19.76	43.32	37.66	8.56	35.3	10.92
7323	41.2	AV	54	12.8	30.28	37.66	8.56	35.3	10.92

Frequency(MHz):			2441		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882	52.67	PK	74	21.33	50.61	30.98	7.58	36.5	2.06
4882	46.43	AV	54	7.57	44.37	30.98	7.58	36.5	2.06
7323	51.54	PK	74	22.46	40.62	37.66	8.56	35.3	10.92
7323	43.87	AV	54	10.13	32.95	37.66	8.56	35.3	10.92

Frequency(MHz):			2480		Polarity:		HORIZONTAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	58.77	PK	74	15.23	55.7	31.47	7.8	36.2	3.07
4960	45.55	AV	54	8.45	42.48	31.47	7.8	36.2	3.07
7440	56.09	PK	74	17.91	44.35	38.32	8.72	35.3	11.74
7440	42	AV	54	12	30.26	38.32	8.72	35.3	11.74


Frequency(MHz):			2480		Polarity:		VERTICAL		
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960	57.35	PK	74	16.65	54.28	31.47	7.8	36.2	3.07
4960	45.69	AV	54	8.31	42.62	31.47	7.8	36.2	3.07
7440	55.72	PK	74	18.28	43.98	38.32	8.72	35.3	11.74
7440	42.75	AV	54	11.25	31.01	38.32	8.72	35.3	11.74


REMARKS:


1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier


- 3. Margin value = Limit value- Emission level.
- 4. -- Mean the PK detector measured value is below average limit.
- 5. The other emission levels were very low against the limit.


Results of Band Edges Test (Radiated)















No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		2483.500	51.38	-8.29	43.09	74.00	-30.91	peak		
2	*	2483.500	37.94	-8.29	29.65	54.00	-24.35	AVG		


*:Maximum data x:Over limit !:over margin

















5.3 Maximum Peak Output Power

Limit

The Maximum Peak Output Power Measurement is 125mW (20.97).

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the powersensor.

Test Configuration



Test Results

See Appendix IV

5.4 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

See Appendix VI

5.5 Frequency Separation

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $\frac{2}{3} \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

See Appendix VII

5.6 Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.

Test Configuration



Test Results

See Appendix III

5.7 Time of Occupancy (Dwell Time)


Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration



Test Results

See Appendix II

5.8 Spurious RF Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300KHz to measure the peak field strength, and measure frequency range from 9KHz to 25GHz.

LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

Test Results

See Appendix VIII

5.9 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

5.10 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance



The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an PCB Antennaconnect to PCB board and no consideration of replacement. Please see EUT photo for details.

Results: Compliance.

6 Test Setup Photos of the EUT




7 Photos of the EUT


See related photo report.

APPENDIX I. Duty Cycle
Test Result


Modulation	Packets	Channel	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)
GFSK	DH5	0	2.880	3.748	76.84	0.7684	1.1441
		39	2.880	3.748	76.84	0.7684	1.1441
		78	2.880	3.748	76.84	0.7684	1.1441
π /4DQPSK	2-DH5	0	2.884	3.748	76.95	0.7695	1.1379
		39	2.886	3.748	77.00	0.7700	1.1351
		78	2.884	3.748	76.95	0.7695	1.1379
8DPSK	3-DH5	0	2.886	3.748	77.00	0.7700	1.1351
		39	2.888	3.748	77.05	0.7705	1.1323
		78	2.886	3.748	77.00	0.7700	1.1351

Test Graphs






GFSK(DH5)_Channel 39




GFSK(DH5)_Channel 78




π/4DQPSK(2-DH5)_Channel 0




π/4DQPSK(2-DH5)_Channel 39




π/4DQPSK(2-DH5)_Channel 78



8DPSK(3-DH5)_Channel 0



8DPSK(3-DH5)_Channel 39





8DPSK(3-DH5)_Channel 78

APPENDIX II. Dwell Time Test Result


Modulation	Packet	Channel	Pulse Width (ms)	Number of Pulses in 31.6 seconds	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	CH39 (2441MHz)	0.3744	314	117.56	< 400	PASS
	DH3		1.632	160	261.12		PASS
	DH5		2.880	108	311.04		PASS
π /4DQPSK	2-DH1		0.3840	316	121.34		PASS
	2-DH3		1.656	159	263.3		PASS
	2-DH5		2.888	96	277.25		PASS
8DPSK	3-DH1		0.3852	315	121.34		PASS
	3-DH3		1.632	164	267.65		PASS
	3-DH5		2.896	102	295.39		PASS

Test Graphs







Pulse Width
 $\pi/4$ DQPSK_2-DH1




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH1




Pulse Width
 $\pi/4$ DQPSK_2-DH3




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH3




Pulse Width
 $\pi/4$ DQPSK_2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
8DPSK_3-DH1




Number of Pulses in 31.6 seconds
8DPSK_3-DH1




Pulse Width
8DPSK_3-DH3



Number of Pulses in 31.6 seconds
8DPSK_3-DH3



Pulse Width
8DPSK_3-DH5




Number of Pulses in 31.6 seconds
8DPSK_3-DH5

APPENDIX III. Number Of Hopping Channel

Test Result

Modulation	Packet	Number of Hopping Channel	Limit	Result
GFSK	DH5	79	15	PASS
GFSK	DH5	79	15	PASS
GFSK	DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS


Test Graphs




Hopping Plot
GFSK



Hopping Plot
GFSK




Hopping Plot
GFSK




Hopping Plot
 $\pi/4$ DQPSK



Hopping Plot
 $\pi/4$ DQPSK




Hopping Plot
 $\pi/4$ DQPSK



Hopping Plot
8DPSK



Hopping Plot
8DPSK



Hopping Plot
8DPSK

APPENDIX IV. Conducted Peak Output Power**Test Result**


Modulation	Packet Type	Channel	Peak Output Power (dBm)	Peak Output Power (mW)	Max. Avg. Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	-3.927	0.405	None	≤30	PASS
		39	-3.591	0.437	None		PASS
		78	-3.531	0.444	None		PASS
π/4DQPSK	2-DH5	0	-3.036	0.497	None	≤20.97	PASS
		39	-2.723	0.534	None		PASS
		78	-2.666	0.541	None		PASS
8DPSK	3-DH5	0	-2.604	0.549	None		PASS
		39	-2.273	0.593	None		PASS
		78	-2.236	0.598	None		PASS


APPENDIX V. 99% Bandwidth

Test Result


Modulation	Channel	Center Frequency (MHz)	99% BW (MHz)
GFSK	0	2402	0.86129
	39	2441	0.84252
	78	2480	0.85506
$\pi/4$ DQPSK	0	2402	1.1816
	39	2441	1.1758
	78	2480	1.1874
8DPSK	0	2402	1.1810
	39	2441	1.1820
	78	2480	1.1910

Test Graphs





8DPSK 3-DH5 Channel 0



8DPSK 3-DH5 Channel 39




8DPSK 3-DH5 Channel 78


APPENDIX VI. 20dB Bandwidth

Test Result


Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9542
	39	2441 MHz	0.9513
	78	2480 MHz	0.9532
$\pi/4$ DQPSK	0	2402 MHz	1.280
	39	2441 MHz	1.306
	78	2480 MHz	1.279
8DPSK	0	2402 MHz	1.297
	39	2441 MHz	1.297
	78	2480 MHz	1.291

Test Graphs





8DPSK 3-DH5 Channel 0



8DPSK 3-DH5 Channel 39



8DPSK 3-DH5 Channel 78


APPENDIX VII. Carrier Frequencies Separation

Test Result

Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Limit (MHz)	Result
GFSK	DH5	2440.1422	2441.0459	0.9037	0.636	PASS
GFSK	DH5	2439.9757	2440.8284	0.8527	0.634	PASS
GFSK	DH5	2440.0264	2441.0387	1.0123	0.635	PASS
$\pi/4$ DQPSK	2-DH5	2439.8224	2441.1197	1.2973	0.853	PASS
$\pi/4$ DQPSK	2-DH5	2439.8245	2440.9682	1.1437	0.871	PASS
$\pi/4$ DQPSK	2-DH5	2439.8281	2440.8167	0.9886	0.853	PASS
8DPSK	3-DH5	2439.8152	2440.8485	1.0333	0.865	PASS
8DPSK	3-DH5	2440.0741	2440.97	0.8959	0.865	PASS
8DPSK	3-DH5	2439.976	2440.9964	1.0204	0.861	PASS

Test Graphs





APPENDIX VIII. Conducted Out Of Band Emission**Test Result****Non-Hopping**






Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2398.97	-47.531	-24.11	-23.421	PASS
			2400.00	-52.117	-24.11	-28.007	PASS
			4803.80	-59.491	-24.11	-35.381	PASS
			7206.60	-62.970	-24.11	-38.860	PASS
			9601.90	-45.479	-24.11	-21.369	PASS
			9607.50	-62.833	-24.11	-38.723	PASS
		39	4882.42	-54.863	-23.78	-31.083	PASS
			7322.67	-62.096	-23.78	-38.316	PASS
			9757.93	-44.910	-23.78	-21.130	PASS
			9764.80	-62.248	-23.78	-38.468	PASS
		78	2483.50	-49.032	-23.68	-25.352	PASS
			4959.83	-54.708	-23.68	-31.028	PASS
			7440.66	-63.023	-23.68	-39.343	PASS
			9914.00	-45.527	-23.68	-21.847	PASS
			9920.24	-62.024	-23.68	-38.344	PASS
$\pi/4$ DQPSK	2-DH5	0	2398.99	-48.829	-24.11	-24.719	PASS
			2400.00	-51.118	-24.11	-27.008	PASS
			4803.10	-60.597	-24.11	-36.487	PASS
			7205.90	-62.943	-24.11	-38.833	PASS
			9601.90	-45.439	-24.11	-21.329	PASS
			9607.50	-63.447	-24.11	-39.337	PASS
		39	4881.17	-57.135	-23.89	-33.245	PASS
			7323.30	-61.928	-23.89	-38.038	PASS
			9757.93	-45.279	-23.89	-21.389	PASS
			9764.80	-62.318	-23.89	-38.428	PASS
		78	2483.50	-49.041	-23.75	-25.291	PASS
			4960.45	-53.272	-23.75	-29.522	PASS
			7440.66	-62.134	-23.75	-38.384	PASS
			9914.00	-45.479	-23.75	-21.729	PASS
			9920.86	-64.809	-23.75	-41.059	PASS
8DPSK	3-DH5	0	2398.99	-48.039	-24.13	-23.909	PASS
			2400.00	-51.902	-24.13	-27.772	PASS
			4804.40	-60.435	-24.13	-36.305	PASS
			7205.90	-63.450	-24.13	-39.320	PASS
			9601.90	-45.648	-24.13	-21.518	PASS
			9608.10	-62.447	-24.13	-38.317	PASS
		39	4881.79	-56.321	-23.83	-32.491	PASS
			7322.67	-62.546	-23.83	-38.716	PASS
			9757.93	-45.161	-23.83	-21.331	PASS
			9764.80	-64.497	-23.83	-40.667	PASS
		78	2483.50	-50.316	-23.7	-26.616	PASS
			4959.83	-54.234	-23.7	-30.534	PASS
			7439.41	-62.418	-23.7	-38.718	PASS
			9920.24	-63.183	-23.7	-39.483	PASS
			24941.3	-45.697	-23.7	-21.997	PASS


Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2400.00	-50.486	-24.3	-26.186	PASS
			2483.50	-51.006	-23.97	-27.036	PASS
			2398.97	-48.531	-24.32	-24.211	PASS
			2400.00	-51.054	-24.32	-26.734	PASS
			2483.50	-50.722	-23.86	-26.862	PASS
			2395.26	-49.530	-24.24	-25.290	PASS
			2400.00	-49.625	-24.24	-25.385	PASS
			2483.50	-50.922	-23.98	-26.942	PASS
$\pi/4$ DQPSK	2-DH5		2400.00	-50.024	-25.05	-24.974	PASS


			2483.50	-50.315	-23.77	-26.545	PASS
			2397.97	-50.005	-24.14	-25.865	PASS
			2400.00	-50.068	-24.14	-25.928	PASS
			2483.50	-50.435	-23.75	-26.685	PASS
			2397.19	-49.252	-24.12	-25.132	PASS
			2400.00	-49.835	-24.12	-25.715	PASS
			2483.50	-50.428	-23.77	-26.658	PASS
			2398.22	-49.946	-25.1	-24.846	PASS
8DPSK	3-DH5		2400.00	-51.132	-25.1	-26.032	PASS
			2483.50	-51.819	-23.76	-28.059	PASS
			2398.31	-49.267	-24.29	-24.977	PASS
			2400.00	-50.557	-24.29	-26.267	PASS
			2483.50	-50.497	-23.74	-26.757	PASS
			2398.99	-50.461	-24.28	-26.181	PASS
			2400.00	-50.688	-24.28	-26.408	PASS
			2483.50	-51.224	-24.09	-27.134	PASS

Test Graphs

Out Of Band Emission
GFSK_DH5_Channel 0Out Of Band Emission
 $\pi/4$ DQPSK_2-DH5_Channel 030.0 MHz - 25000.0 MHz
GFSK_DH5_Channel 030.0 MHz - 25000.0 MHz
 $\pi/4$ DQPSK_2-DH5_Channel 0Out Of Band Emission
GFSK_DH5_Channel 39Out Of Band Emission
 $\pi/4$ DQPSK_2-DH5_Channel 39




30.0 MHz - 25000.0 MHz
GFSK_DH5_Channel 39




30.0 MHz - 25000.0 MHz
 $\pi/4$ DQPSK_2-DH5_Channel 39




Out Of Band Emission
GFSK_DH5_Channel 78




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH5_Channel 78




30.0 MHz - 25000.0 MHz
GFSK_DH5_Channel 78




30.0 MHz - 25000.0 MHz
 $\pi/4$ DQPSK_2-DH5_Channel 78




Out Of Band Emission
8DPSK_3-DH5_Channel 0




30.0 MHz - 25000.0 MHz
8DPSK_3-DH5_Channel 0




Out Of Band Emission
8DPSK 3-DH5 Channel 39



30.0 MHz - 25000.0 MHz
8DPSK 3-DH5 Channel 39



Out Of Band Emission
8DPSK 3-DH5 Channel 78



30.0 MHz - 25000.0 MHz
8DPSK 3-DH5 Channel 78



Out Of Band Emission(Left)
GFSK DH5 Channel Hopping



Out Of Band Emission(Left)
 $\pi/4$ DQPSK 2-DH5 Channel Hopping



Out Of Band Emission(Right)
GFSK DH5 Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK 2-DH5 Channel Hopping



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping




Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping



Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping

***** End of Report *****