


Loer Pendant Installation Instructions



Only qualified persons should assemble the luminaire. If in doubt, consult a suitably qualified electrician. Installation MUST be carried out in accordance and compliance with current building regulations.

Ensure the electrical supply is turned OFF at the fuse board.

The Loer Pendant has been designed to fit the E27/ES (Edison Screw) fitting ceiling kit provided. After adjusting the flex length to suit your space if needed, connect the ceiling rose (A) to the electricity supply (**220-240V AC 50-60Hz**). This must be installed by a qualified electrician before following the instructions below. The Loer pendant should be connected to the electricity supply and fixed to the ceiling before fitting the bulb and glass sphere diffuser due to the fragility of the glass.

Once the ceiling kit has been connected to the electricity supply and the pendant securely attached to the ceiling, screw in the light bulb supplied (A). The lampshade has been designed to work with an **LED** bulb, up to a maximum of **9.5 Watts**.

1. Carefully thread glass sphere over the light bulb (B) and locate onto the brass thread of the bulb holder. Gently tighten the sphere onto the bulb holder securely connecting the two parts. Due to the fragility of the glass sphere diffuser, this step should be carried out with great care to avoid breakage.
2. Turn the power supply on to complete installation.

*** If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard. For indoor use only. ***