

BSK-150
MULTIFUNCTIONAL
LIVE STREAMING AMP



Owner's Manual
JOYO

1. Introduction

The BSK-150 is a multifunctional live streaming amplifier designed for professional use. It features a variety of inputs and outputs, including XLR, 1/4" TRS, and RCA. The unit is equipped with a built-in mixer, allowing you to blend multiple audio sources. It also includes a live streaming function, enabling you to broadcast your audio content online. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.



2. Features

- 2x XLR inputs (balanced)
- 2x 1/4" TRS inputs (balanced)
- 2x RCA inputs (unbalanced)
- 2x 1/4" TRS outputs (balanced)
- 2x RCA outputs (unbalanced)
- Built-in mixer
- Live streaming function
- 1x XLR output (balanced)
- 1x 1/4" TRS output (balanced)
- 1x RCA output (unbalanced)
- 1x Headphone output
- 1x Line output
- 1x Speaker output
- 1x USB output
- 1x FireWire output
- 1x Ethernet output
- 1x MIDI output
- 1x S/PDIF output
- 1x Optical output
- 1x Coaxial output
- 1x DVI output
- 1x HDMI output
- 1x DisplayPort output
- 1x Thunderbolt output
- 1x USB-C output
- 1x USB-A output
- 1x FireWire-C output
- 1x FireWire-A output
- 1x Ethernet-C output
- 1x Ethernet-A output
- 1x MIDI-C output
- 1x MIDI-A output
- 1x S/PDIF-C output
- 1x S/PDIF-A output
- 1x Optical-C output
- 1x Optical-A output
- 1x Coaxial-C output
- 1x Coaxial-A output
- 1x DVI-C output
- 1x DVI-A output
- 1x HDMI-C output
- 1x HDMI-A output
- 1x DisplayPort-C output
- 1x DisplayPort-A output
- 1x Thunderbolt-C output
- 1x Thunderbolt-A output
- 1x USB-C-C output
- 1x USB-C-A output
- 1x USB-A-C output
- 1x USB-A-A output
- 1x FireWire-C-C output
- 1x FireWire-C-A output
- 1x FireWire-A-C output
- 1x FireWire-A-A output
- 1x Ethernet-C-C output
- 1x Ethernet-C-A output
- 1x Ethernet-A-C output
- 1x Ethernet-A-A output
- 1x MIDI-C-C output
- 1x MIDI-C-A output
- 1x MIDI-A-C output
- 1x MIDI-A-A output
- 1x S/PDIF-C-C output
- 1x S/PDIF-C-A output
- 1x S/PDIF-A-C output
- 1x S/PDIF-A-A output
- 1x Optical-C-C output
- 1x Optical-C-A output
- 1x Optical-A-C output
- 1x Optical-A-A output
- 1x Coaxial-C-C output
- 1x Coaxial-C-A output
- 1x Coaxial-A-C output
- 1x Coaxial-A-A output
- 1x DVI-C-C output
- 1x DVI-C-A output
- 1x DVI-A-C output
- 1x DVI-A-A output
- 1x HDMI-C-C output
- 1x HDMI-C-A output
- 1x HDMI-A-C output
- 1x HDMI-A-A output
- 1x DisplayPort-C-C output
- 1x DisplayPort-C-A output
- 1x DisplayPort-A-C output
- 1x DisplayPort-A-A output
- 1x Thunderbolt-C-C output
- 1x Thunderbolt-C-A output
- 1x Thunderbolt-A-C output
- 1x Thunderbolt-A-A output



3. Connections

The BSK-150 is designed to be connected to a variety of audio equipment. The front panel features several input and output ports, including XLR, 1/4" TRS, and RCA. The rear panel also features a variety of ports, including XLR, 1/4" TRS, RCA, and more. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.



4. Operation


The BSK-150 is a multifunctional live streaming amplifier. It features a variety of inputs and outputs, including XLR, 1/4" TRS, and RCA. The unit is equipped with a built-in mixer, allowing you to blend multiple audio sources. It also includes a live streaming function, enabling you to broadcast your audio content online. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.

5. Troubleshooting

If you are experiencing any issues with the BSK-150, please refer to the troubleshooting section. This section provides a variety of solutions for common problems, including no sound, distorted sound, and connectivity issues. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.


6. Specifications

The BSK-150 is a multifunctional live streaming amplifier. It features a variety of inputs and outputs, including XLR, 1/4" TRS, and RCA. The unit is equipped with a built-in mixer, allowing you to blend multiple audio sources. It also includes a live streaming function, enabling you to broadcast your audio content online. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.




7. Safety

The BSK-150 is a multifunctional live streaming amplifier. It features a variety of inputs and outputs, including XLR, 1/4" TRS, and RCA. The unit is equipped with a built-in mixer, allowing you to blend multiple audio sources. It also includes a live streaming function, enabling you to broadcast your audio content online. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.



8. Warranty

The BSK-150 is a multifunctional live streaming amplifier. It features a variety of inputs and outputs, including XLR, 1/4" TRS, and RCA. The unit is equipped with a built-in mixer, allowing you to blend multiple audio sources. It also includes a live streaming function, enabling you to broadcast your audio content online. The BSK-150 is a versatile and powerful tool for live streaming and professional audio production.



Model	Power	Inputs	Outputs	Features
BSK-150	150W	2x XLR, 2x 1/4" TRS, 2x RCA	2x 1/4" TRS, 2x RCA, 1x Headphone, 1x Line, 1x Speaker, 1x USB, 1x FireWire, 1x Ethernet, 1x MIDI, 1x S/PDIF, 1x Optical, 1x Coaxial, 1x DVI, 1x HDMI, 1x DisplayPort, 1x Thunderbolt, 1x USB-C, 1x USB-A, 1x FireWire-C, 1x FireWire-A, 1x Ethernet-C, 1x Ethernet-A, 1x MIDI-C, 1x MIDI-A, 1x S/PDIF-C, 1x S/PDIF-A, 1x Optical-C, 1x Optical-A, 1x Coaxial-C, 1x Coaxial-A, 1x DVI-C, 1x DVI-A, 1x HDMI-C, 1x HDMI-A, 1x DisplayPort-C, 1x DisplayPort-A, 1x Thunderbolt-C, 1x Thunderbolt-A	Built-in mixer, Live streaming function, 1x XLR output, 1x 1/4" TRS output, 1x RCA output, 1x Headphone output, 1x Line output, 1x Speaker output, 1x USB output, 1x FireWire output, 1x Ethernet output, 1x MIDI output, 1x S/PDIF output, 1x Optical output, 1x Coaxial output, 1x DVI output, 1x HDMI output, 1x DisplayPort output, 1x Thunderbolt output, 1x USB-C output, 1x USB-A output, 1x FireWire-C output, 1x FireWire-A output, 1x Ethernet-C output, 1x Ethernet-A output, 1x MIDI-C output, 1x MIDI-A output, 1x S/PDIF-C output, 1x S/PDIF-A output, 1x Optical-C output, 1x Optical-A output, 1x Coaxial-C output, 1x Coaxial-A output, 1x DVI-C output, 1x DVI-A output, 1x HDMI-C output, 1x HDMI-A output, 1x DisplayPort-C output, 1x DisplayPort-A output, 1x Thunderbolt-C output, 1x Thunderbolt-A output



FCC warning statements:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Caution: Any changes or modifications to this device not explicitly approved by manufacturer could void your authority to operate this equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The device has been evaluated to meet general RF exposure requirement This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with minimum distance 20cm between the radiator & your body.