X-SENSE


Your Trusted Home Safety Innovator



CONTENT

Company Overview	 Company Profile 	2 - 3
	Worldwide Market	4
	• Product Overview	5-6
Product Overview	Smoke Alarms	7 - 14
	Carbon Monoxide Alarms	15 - 18
	 Combination Smoke and Carbon Monoxide Alarms 	19 - 20
	Smart Home Security System	21 - 28
Knowledge Hub	• Installation Locations	29-31
	 Detection Principle: Photoelectric vs. Ionization 	32





Company Overview



Company Profile

X-Sense Innovations Co., Ltd.

Established in 2013, X-Sense is a renowned pioneer in home and commercial safety products, committed to ering exceptional quality through cutting-edge technologies and premium materials.

Having successfully sold over 15 million devices across 50+ countries, X-Sense continuously expands its expertise to cater to the evolving needs of its customers. Our company takes pride in offering professional and tailored solutions to meet diverse market demands.



60⁺
PATENTS GRANT-



15,000,000+

DEVICES



50⁺
COUNTRIES SHIPPED



500⁺
EMPLOYEES WORLD-



8 PRODUCTION



100% FULL INSPECTION



















Worldwide Market











X-SENSE







Product Overview

Smoke Alarms

Smoke& CO Detectors

Types

Smoke Alarm

Carbon Monoxide Alarm

Combo Smoke & CO Alarm

Heat Alarm

Standalone

Traditional alarms that work independently.





(XC01)







Link⁺

Interconnects with each other via RF technology so if one is triggered, they all go off.











Wi-Fi

They work with X-Sense app or TuyaSmart app so that you will be intantly notified from mobile phone.



X-SENSE



X-SENSE




XC04-WX

Link⁺ Pro

Can achieve both RF interlinked and Wi-Fi functions with base station.









XH02-M







Photoelectric Technology



Small yet Powerful



Hassle-Free Installation



Insect-Proof Design



Self-Check Function



Easily Silence or Test the Device



85 dB Alarm



XS01 Series

Standalone Smoke Alarm XS01

Wireless Interlinked Smoke Alarm XS01-WR

Wi-Fi Smoke Alarm XS01-WX (X-Sense App)

Wi-Fi Smoke Alarm XS01-WT (TuyaSmart App)

Technical Specifications:

Model	XS01	XS01-WR	XS01-WT	XS01-WX
Power Source	10-year 3 V CR2/ 3A lithium battery	Replaceable 3 V CR123A lithium battery	Replaceable 3 V CR123A lithium battery	Replaceable 3 V CR123A lithium battery
Sensor Type	Photoelectric	Photoelectric	Photoelectric	Photoelectric
Operating Life	10 years	10 years	10 years	10 years
Alarm Sound Level	≥ 85 dB at 3 m	≥ 85 dB at 3 m	≥ 85 dB at 3 m	≥ 85 dB at 3 m
Dimension	Ø 78 × 48 mm	Ø 78 × 48 mm	Ø 78 × 48 mm	Ø 78 × 48 mm

XS01 Standalone Smoke Alarm



- 10-Year Sealed-In Lithium Battery
- End-of-Life Warning

XS01-WR <a>®


Wireless Interlinked Smoke Alarm

0 0 0 0 24 0 0 0 Wirelessly Interlinks with 24 Link⁺ Devices

Full Home Coverage within 250 m Range

Quick Location of Source Alarm







X-Sense App Wi-Fi Smoke Alarm XS01-WX



Wi-Fi Connection



Real-Time Notifications



Silence at Your Fingertips

TuyaSmart App Wi-Fi Smoke Alarm XS01-WT



Standalone Smoke Alarm (SD01)



Escape Light





10-Year Sealed-In Lithium Battery



3-Color LED Indicator



Self-Check Function



Photoelectric Technology



End-of-Life Warning



85 dB Alarm





Link+ Series Photoelectric EN 14604 Mute Mode Ø 146 × 51 mm



SD06-W





Wireless Interconnected Smoke Alarm®



Photoelectric Technology



85 dB Alarm



Wirelessly Interlinks with 24 Link⁺ Devices



Self-Check Function



Full Home Coverage within 250m Range



Low Battery Warning



10-Year Sealed-In Lithium Battery



Quick Location of Source Alarm

SD11 Series Standalone Smoke Alarm



- 10-Year Battery Life
- Self-Check Function
- Low Battery Warning
- Sensitive and Accurate
- Insect-Proof Design
- Wire-Free Installation in Minutes

Technical Specifications:

Model

SD11/SD12/SD19

Power Source

10-year 3 V CR2/3A lithium battery

Sensor Type

Photoelectric

Operating Life

10 years

Alarm Sound Level

≥ 85 dB at 3 m

Dimension

122 × 122 × 45 mm







10-Year Life Figaro Electrochemical CO Sensor



Informative, Easy-to-Read LCD



3-Color LED Indicator



Free-Standing or Wall Mounted



Self-Check Function



Test/Silence Button







XC Series

Standalone Carbon Monoxide Alarm XC01

Standalone Carbon Monoxide Alarm XC01-R

Standalone Carbon Monoxide Alarm XC01-WR
Wi-Fi Carbon Monoxide Alarm XC04-WX

Technical Specifications:

Model	XC01	XC01-R	XC01-WR	XC04-WX
Power Source	10-year 3 V CR2/ 3A lithium battery	Replaceable CR123A or CR2/3A lithium battery	Replaceable 3 V CR123A lithium battery	Replaceable 3 V CR123A lithium battery
Sensor Type	Electrochemical	Electrochemical	Electrochemical	Electrochemical
Operating Life	10 years	10 years	10 years	10 years
Alarm Sound Level	≥ 85 dB at 3 m	≥ 85 dB at 3 m	≥ 85 dB at 3 m	≥ 85 dB at 3 m
Dimension	135 × 63 × 24 mm	135 × 63 × 24 mm	135 × 63 × 24 mm	135 × 63 × 24 mm

XC01 Standalone Carbon Monoxide Alarm







XC01-R Standalone Carbon Monoxide Alarm







XC01-WR [©] Wireless Interlinked Carbon Monoxide Alarm



Wirelessly Interlinks with 24 Link⁺ Devices



Full Home Coverage within 250 m Range



Quick Location of Source Alarm
























CO Series

Standalone CO Alarm CO03D

Wireless Interlinked CO Alarm CO03D-W [©]

Technical Specifications:


Model	CO03D	CO03D-W	
Power Source	Replaceable 1.5 V × 3 AA batteries	Replaceable 1.5 V × 3 AA batteries	
Sensor Type	Electrochemical	Electrochemical	
Operating Life	10 years	10 years	
Alarm Sound Level	≥ 85 dB at 3 m	≥ 85 dB at 3 m	
Dimension	110 × 110 × 37 mm	110 × 110 × 37 mm	

Combination Smoke and Carbon Monoxide Alarms

Standalone Combination Smoke and Carbon Monoxide Alarm







3-Color LED Indicator



2-In-1 Protection


- 10-Year Sealed-In Lithium Battery

 End-of-Life Warning
- Wirelessly Interlinks with 24 Link⁺ Devices
- Full Home Coverage within 250 m Range
- Quick Location of Source Alarm



SBS50 Base Station


Connects 50 devices to cover every corner





Smart Home Security System - Monitor remotely with your family

- Comprehensive Protection: Up to 50 devices can be connected to X-Sense SBS50 Base Station, including smoke detectors, CO detectors, water leak detectors, and more.
- User-Friendly App: Easy setup, assign specific locations and monitor the working status for each device.
- Impressive Transmission Range: Most devices offer an open-air transmission distance of 1,700 ft (500 m).
- **Instant Alerts**: If an alarm is triggered, our base station will loud at to 110 dB and instant notifications on the app telling you exactly where the problem is, even if you're not at home.



- Real-Time Notifications
- Test or Silence Your Devices via App
- Device Sharing Feature
- Self-Check Function via App
- App Shows the Location
- Easily to Locate the Source of Alarm
- Low Battery Warning and Malfunction Warning from App
- Data History

Link+ Pro Smoke Alarm



Small yet Powerful



Insect-Proof Design



Hassle-Free Installation



XS01-M

Link+ Pro CO Alarm



10-Year CO Sensor



Free-Standing



Peak CO Concentration Memory



XC01-M

Link+ Pro Heat Alarm



Class A1 Heat Alarm



7-Year Life Time



XH02-M

© Link+ Pro

- Link⁺ Pro is an upgraded technology by X-Sense, which offers 2 connectivity options to cater to your preferences.
- When linked to the base station, devices maintain wireless interconnection, and you'll receive real-time notifications through the X-Sense app.
- Alternatively, Link⁺ Pro units can independently connect with other Link⁺ or Link⁺ Pro series devices, even without the SBS50 base station. These devices form an interlinked network, where all will sound if one is triggered to provide maximum safety.

Water Leak Alarm



Thermo-Humidity Sensor





24/7 Real-Time Monitoring

Industrial-Grade Swiss Sensor



Place It Anywhere



Free Data Export



Compatible with Alexa



For Home Comfort, Agriculture, Food Storage and More

Smoke and CO Alarm Listener



Makes Non-Smart Alarms Intelligent



Works with X-Sense Alarms & UL Listed Detectors



Free Real-Time Alerts



Low Battery Warning



Replaceable Alkaline Battery




Wall Mounted



Wire-Free Installation in Minutes







SAL100





IMPORTER

BC Company
's-Hertogenbsoch
info@bccompany.nl
www.bccompany.nl
+31 (0)85-0043.901

X-SENSE PRO

Telephone: +31(0)85-0043903 Email: info@xsensepro.nl Web: www.xsensepro.nl