

VS20WRF/VS20BRF THERMOSTAT - FULL USER MANUAL





TABLE OF CONTENTS

1. Introduction	5
1.1 Product Compliance	
1.2 Safety Informations	
,	
2. Product Overview	6
2.1 Montage	6
2.2 Package content	6
2.3 Proper thermostat location	
2.4 Connection Description (VS20WRF/VS20BRF thermostat)	6
3. About ZigBee network	7
3.1 ZigBee network - creation and work	
3.2 Compatibility with SALUS devices (ONLINE AND OFFLINE)	8
4 Defense von stant (Fust namen un)	•
4. Before you start (first power up)	
4.1 LCD icon description	
· ·	
4.3 First power up sequence, language choice and preparing to the pair process	IV
5. Installation by SALUS Smart Home application (ONLINE MODE)	11
5.1 General informations about SALUS Smart Home application	
5.2 Configuration as a programmable thermostat	
5.2.1 Pairing with underfloor heating wiring centre (KLO8RF/Control Box)	
5.2.2 Pairing with wireless TRV radiator head	
5.2.3 Pairing with Smart Plug SPE600	17
5.2.4 Pairing with Smart Relay SR600	19
5.2.5 Pairing with RX10RF receiver	21
5.3 Configuration as a hot water timer	
5.3.1 Pairing with Room Extension Receiver (RX2)	
6. OPERATING in ONLINE MODE (by app)	25
6.1 General informations	25
6.2 App icons description	25
6.2.1 Programmable thermostat	
6.2.2 Hot Water Timer	
6.3 Change thermostat name (pencil icon)	
6.4 Work as a programmable thermostat	
6.4.1 Setpoint temperature change	28
6.4.2 Heat/Cool mode change (KLO8RF connection)	
6.4.3 Thermostat modes	30
6.4.3.1 Schedule mode	30
6.4.3.2 Temporary override mode	34
6.4.3.3 Manual mode	34
6.4.3.4 Frost protection	35
6.4.4 Key lock function	36
6.4.5 Compatibility with window/door sensor OS600 / SW600	
6.4.6 Compatibility with Smart Plug SPE600	
6.4.7 Compatibility with Smart Relay SR600	
6.5 Work as a hot water timer (work modes)	40
6.5.1 Turned ON mo <u>de</u> - II	
6.5.2 AUTO mode - 🔼	
6.5.3 Turned OFF mode - 💌	
6.5.4 Temporarily ON mode - 🔼	43

6.6 Identification mode	44
6.7 Pinning/unpinning thermostat to/from application dashboard	45
6.8 User settings (basic settings)	46
6.9 Admin settings (installer parameters)	
6.10 OneTouch rules (add/edit)	48
6.11 Error codes (exclamation mark in app)	
6.12 Wireless signal strength test	
6.13 Factory reset (removing thermostat from the app and ZigBee network)	54
7. Installation in OFFLINE MODE without SALUS SmartHome application	56
7.1 General informations	
7.1 General morniations	
7.2.1 Available operation modes	
7.2.2 Grouping - installation of the thermostat as a group controller - MASTER - or as a group thermostat	
(SLAVE)(SLAVE)	60
7.2.3 Installation as a programmable thermostat	60
7.2.4 Replace the zone assigned to another thermostat	
7.2.4 Replace the zone assigned to another thermostat	
7.4 Pairing with RX10RF receiver	
7.5 Configuration as a Hot Water timer	
8. OPERATING in OFFLINE MODE	
8.1 Work as a programmable thermostat	
8.1.1 Work modes	
8.1.2 Heat/cool mode change (KLO8RF connection)	
8.2 Work as a hot water timer with RX10RF receiver	
8.2.1 Work modes	
8.3 User settings (basic settings)	
8.3.1 Schedule mode - programming schedule	
8.3.2 CAL function	
8.3.3 Time/Date	
8.3.4 Thermostat calibration	
8.3.5 Key lock function	77
9. Installer parameters	78
10. Factory Reset	80
11. Error codes (error codes description with possible solutions)	
12. Cleaning and Maintenance	84
13. Technical Informations	84
14. Warranty	85



1. Introduction

1.1 Product Compliance

This product complies with the essential requirements and other relevant provisions of Directives 2014/53/EU and 2011/65/EU. The full text of the EU Declaration of Conformity is available at the following internet address: www.saluslegal.com.

1.2 Safety Informations

- Before starting installation work and before using the product, read the entire manual.
- The information contained in the instructions is essential for proper functioning.
- To avoid accidents resulting in personal injury and material damage, please follow all safety precautions, specified in this manual.
- The device should not be used by people with limited mental, sensory or mental abilities, without experience, of insufficient knowledge as well as children.
- Do not use an unassembled device (eg without a cover).
- The device may only be opened by a qualified person.
- Keep electrical devices out of the reach of children and ensure that they do not play with it. Children should not be left unattended. If necessary, disconnect the control system for the entire room.
- Do not leave the packaging, cabinet, or any loose parts of the device unattended, as they pose a risk to children.

WARNING!

- Installation must be carried out by a qualified person with appropriate electrical qualifications in accordance with standards and regulations in force in the given country and in the EU.
- Never try to connect the device other than as described in the manual.
- Before assembly, repair or maintenance as well as during any connection works it is absolutely necessary disconnect the mains supply and make sure that the terminals and electric wires are not live.
- The device may not be exposed to extreme temperatures, strong vibrations or subjected to mechanical shock.
- The device should not be used in unfavorable environmental conditions or in rooms where there is a concentration of flammable gases, fumes or dust.

WARNING!

• There may be additional protection requirements for the entire installation that the installer is responsible for maintaining.



Care for the natural environment is of paramount importance to us. The awareness that we manufacture electronic devices obliges us to dispose of used electronic components and devices safely. Therefore the company has received a registration number issued by the Chief Inspector for Environmental Protection. The crossed out symbol the trash can on the product means that the product must not be disposed of with ordinary waste containers. Sorting waste for recycling helps to protect the environment. It is the user's responsibility to surrender used equipment to a designated collection point for recycling waste from electrical and electronic equipment.

2. Product Overview

VS20WRF / VS20BRF is a room temperature thermostat that is used for wireless control of iT600 series devices such as: KL08RF wiring centre, TRV radiator valve and RX10RF boiler receiver. In combination with Universal Gateway UGE600 this regulator can be controlled over the Internet using SALUS SmartHome app (Online mode). Without Internet connection (Offline mode) thermostat works locally, but its communication with other devices must be done through the coordinating unit - C010RF.

2.1 Montage

2.2 Package content

- 1) VS20WRF/VS20BRF thermostat
- 2) Mounting plate
- 3) 4x AAA batteries
- 4) Short instructions
- 5) Mounting screws












2.3 Proper thermostat location





Please note:


The ideal position to thermostat mounting is about 1,5m under floor level far from heating or cooling sources. Thermostat can't be exposed to sunlight or any extreme conditions like for example draft.

Because of fire and explosion risk there is not allowed to use thermostat in atmosphere of explosive gases and flammable liquids (eg coal dust). In case if any of listed dangers occur you have to use additional protection measures — anti-dust and explosive gases (tight cover) or prevent their formation. Furthermore, thermostat can't be used in condensation of water vapor conditions and be exposed to water action.

Wall mounting

Mounting: to mount thermostat you can use accesories included with the set (mounting screws). Remove back cover to mount the plate to the wall. Now please insert the batteries inside the thermostat. After this just attach thermostat to the plate right into designed holes in the plate.

2.4 Connection Description (VS20WRF/VS20BRF thermostat)



Symbols explanation:

S – volt-free contact

T – temperature sensor eg. FS300

S1, S2 terminals:

- air or floor temperature sensor
- external volt-free contact to connect any ON/OFF switch or occupancy sensor (Hotel card)
- external hot water thermostat

3. About ZigBee network

3.1 ZigBee network - creation and work

ZigBee is a wireless network based on IEEE 802.15.4 standard and it's communication takes place in the 2.4 GHz band. The network is based on a mesh topology, which allows for a very large range and high reliability. The maximum range of direct communication between two network nodes (devices) is about 100m in open space.

The devices included in the ZigBee network are divided into three types:

- coordinator there can only be one such device in each network. It acts as a connection node for all devices;
- **router (repeater)** this device is powered by 230VAC, with functionality similar to classic network routers, and it's task is to forward data packets and increase the range of the network;
- **terminal device** battery powered, sends data to the coordinator (also through the router) to which it is connected. It is usually put to sleep temporarily, which helps reduce energy consumption.

Built-in security in the ZigBee protocol (ISO-27001 and SSAE16 / ISAE 3402 Type II - SOC 2 certification) ensure high transmission reliability, detection and removal of transmission errors, as well as connectivity between established priority devices.

Security measures include:

- devices authenticated using a unique key pair;
- encrypted communication between the mobile application and the device;
- data encryption HTTPS encrypted using TLS, UDP channel with AES-128 encryption;
- layered access control to prevent tampering with one device threatening the entire system.

The ability to work many devices at a short distance from each other was achieved through the use of radio transmission of the spread spectrum signal. The main advantages of devices working in the ZigBee system are two-way communication and minimization of energy consumption, which in many cases allows them to be powered from chemical cells (alkaline batteries).

Four Simple steps to create ZigBee network:

Coordinator Installation - Universal Gateway for ONLINE and OFFLINE systems with internet application or CO10RF for only OFFLINE systems without application.






Now - add any device you want **powered 230VAC**.


Note to locate it as near coordinator as possible.



Now you can increase range of ZigBee network by adding more devices **powered 230 VAC**.



To extend your network you can add more battery devices and accesories.



COMPATIBILTY WITH OTHER SALUS CONTROLS DEVICES

VS20 thermostat can work in ONLINE or OFFLINE mode. At first step you need to decide in which mode your thermostat will work.

ONLINE MODE

Universal Gateway is CONNECTED TO THE INTERNET

You can configure and use all your devices in the Smart Home App

Download the Smart Home App on your iOS or Android device for remote access to your SALUS equipment.





SALUS Smart Home

OFFLINE MODE



0R



Universal Gateway is NOT CONNECTED TO THE INTERNET

You can use your devices locally without the SmartHome App. Gateway works in this mode as standard ZigBee coordinator.

CO10RF Coordinator - You can use standard ZigBee network coordinator to install and use your devices.

Compatibile devices:







SPE600 Smart Plug



KL08RF wireless wiring centre for 8-zone underfloor heating.



KL04RF extension



TRV (Thermostatic Radiator Valve) with wireless communication.



RX10RF receiver

Only with Online Mode

Other SmartHome devices/accessories



Window/door Sensor SW600 or OS600



Smoke detector **SD600**



Double/single OneTouch button



SB600/CSB600



Water leak sensor **WLS600**



RS600 Roller shutter




RE600 ZigBee network signal repeater (only with UGE600)



RE10RF ZigBee network signal repeater

4. Before you start (first power up)

4.1 LCD icon description




- 1. Comfort temperature
- 2. Standard temperature
- 3. Economic temperature
- **4.** Automatic mode
- **5.** PARTY mode
- **6.** Holiday mode
- 7. Frost protection mode
- 8. Temperature unit
- **9.** Group controller
- **10.** Manual mode / override temp.
- **11.** Current / set temperature
- 12. Program number

- **13.** AM / PM
- 14. Lock function
- **15.** Clock
- **16.** Day indicator
- 17. Settings
- 18. Low battery indicator
- 19. External temperature sensor
- 20. Hot water heating
- 21. Modes for Hot Water
- 22. Cooling mode ON
- 23. Internet connection indicator
- **24.** Gateway wireless connection
- 25. Heating mode ON

4.2 Button description

Button Description	
Button	Function
^ OR ∨	1. Increase or decrease setpoint temperature. 2. Increase or decrease Day, Clock, Timer, Party, Holiday and Boost. 3. Select installer parameter value.
< or >	Mode selection. Moving between parameters.
✓₀	1. OK key: Short press to confirm selection. 2. Long press to save and exit. 3. Long press to enter the user settings.
^ + ~	Hold down these buttons to lock or unlock the keyboard.
\(\sqrt{\} \	Hold down these buttons to enter installer parameter settings.


4.3 First power up sequence, language choice and preparing to the pair process



Remove the protection foil and insert 4xAAA batteries by removing back cover.

After that, thermostat will automatically power up and start boot sequence...

...it will display all icons...



" or " buttons.

Then confirm by so button.

5. Installation by SALUS Smart Home application (ONLINE MODE)

5.1 General informations about SALUS Smart Home application

Thanks to UGE600 Universal Gateway and SALUS Smart Home app system allows you to remote control of your heating system in any place you are in the moment by smartphone, tablet or computer with Internet connection. Then you have also access to advanced functions of VS20WRF/VS20BRF thermostat. You can also create OneTouch rules to customize system to your needs.

First make sure that you have downloaded the Salus Smart Home App from the Google Play or App Store. You will need to follow a few easy steps to create an account and then link your thermostat to the Universal Gateway and to the App.

You can also access the web version on: http://eu.salusconnect.io/







SALUS Smart Home





To begin the pairing process the Gateway should be plugged into the power supply and connected to the Internet. Also, make sure that the UGE600 is added to your Salus Smart Home App. For the installation of the Universal Gateway, please refer to the UGE600 manual on salus-manuals.com





Make sure that your UGE600 Universal Gateway is added to the App. The LED of the Gateway should be steady blue. Then go to VS20WRF/ VS20BRF thermostat and begin paring process with the UGE600 and add it to the App.

5.2 Configuration as a programmable thermostat

5.2.1 Pairing with underfloor heating wiring centre (KLO8RF/Control Box)




Please note:

For easier installation, please make sure you have already added underfloor heating wiring centre (KL08RF/Control Box) to your ZigBee network (please refer to the underfloor heating wiring centre manual instruction).




12



Thermostat is connected. Go to the Smart Home app to configure it.

Select your thermostat and press "Connect equipment" button.


Name your thermostat and go "Next"...





Press gear icon.

Select option "Programmable Thermostat".

Now choose "UFH Wiring Centre" option.









Select the zone which you want attribute to your thermostat.


20




Choose "No" if you want to set your own schedule later or "Yes" if default now.



Press "Finish" button to end the set up process in the app.



Gateway stop flashing and turn to steady blue color which means pair process has been finished.





After that thermostat will display main screen.
You succesfully configured VS20WRF/VS20BRF thermostat with KL08RF Control Box.

5.2.2 Pairing with wireless TRV radiator head




Please note:






Press "Scan for equipment" button.




App has started scanning...




searching for the thermostat...




Thermostat is connected. Go to the Smart Home app to configure it. 15




Select your thermostat and press "Connect equipment" button.




Name your thermostat and go "Next"...




Press gear icon.



Select option "Programmable Thermostat".




Now choose Smart Radiator Control.




Select your TRV radiator head from the list.


18)




Choose "No" if you want to set your own schedule later or "Yes" if default now.



Press "Finish" button to end the set up process in the app.



Gateway stop flashing and turn to steady blue color which means pair process has been finished.




After that thermostat will display main screen. You succesfully configured VS20WRF/VS20BRF thermostat with Wireless TRV radiator head.

5.2.3 Pairing with Smart Plug SPE600



Please note:


For easier installation, please make sure you have already added Smart Plug SPE600 to your ZigBee network (please refer to the Smart Plug SPE600




Press "Scan for equipment" button.

App has started scanning...


Thermostat is connected. Go to the Smart Home app to configure it.




Select your thermostat and press "Connect equipment" button.




Name your thermostat and go "Next"...




Press gear icon.




Select option "Programmable Thermostat".




Now choose Smart Plug.



Select your Smart Plug from the list.




Choose "No" if you want to set your own schedule later or "Yes" if default now.



Press "Finish" button to end the set up process in the app.



Gateway stop flashing and turn to steady blue color which means pair process has been finished.



After that thermostat will display main screen. You succesfully configured VS20WRF/VS20BRF thermostat with Smart Plug SPE600.

5.2.4 Pairing with Smart Relay SR600




Please note:

For easier installation, please make sure you have already added Smart Relay SR600 to your ZigBee network (please refer to the Smart Relay SR600 manual instruction).



Set your thermostat for underfloor heating by "
or "
or "
buttons. Then confirm by
button.



Now thermostat is looking for the signal from the coordinator...




Go to SALUS Smart Home app.




Open main menu.




Select "Settings".



Now enter to the "Setup Equipment".



Press "Scan for equipment" button.




App has started scanning...




...Gateway has started flashing red and searching for the thermostat...




Thermostat is connected. Go to the Smart Home app to configure it.




Select your thermostat and press "Connect equipment" button.




Name your thermostat and go "Next"...




Press gear icon.




Select option "Programmable Thermostat".




Now choose Smart Relay.



Select your Smart Relay from the list.




Choose "No" if you want to set your own schedule later or "Yes" if default now.



Press "Finish" button to end the set up process in the app.



Gateway stop flashing and turn to steady blue color which means pair process has been finished.




After that thermostat will display main screen. You succesfully configured VS20WRF/VS20BRF thermostat with Smart Relay SR600.

5.2.5 Pairing with RX10RF receiver



Please note:

For easier installation, please make sure you have already added RX10RF receiver to your ZigBee network (please refer to the RX10RF receiver manual instruction).



Set your thermostat for underfloor heating by " or " or " buttons. Confirm by " button.

Now thermostat is looking for the signal from the coordinator...

Go to SALUS Smart Home app




Open main menu.




Select "Settings".



Now enter to the "Setup Equipment".



Press "Scan for equipment" button.




App has started scanning...




...Gateway has started flashing red and searching for the thermostat...




Thermostat is connected. Go to the Smart Home app to configure it.




Select your thermostat and press "Connect equipment" button.



Name your thermostat and go "Next"...




Press gear icon.




Select option "Programmable Thermostat".




Choose "More" to expand the menu.



Now choose Boiler Receiver. If RX10RF is set as "RX1" then choose option "Boiler Receiver". If as a "RX2" then select "Room Extension Receiver".




Choose "No" if you want to set your own schedule later or "Yes" if default now.



Press "Finish" button to end the set up process in the app.



Gateway stop flashing and turn to steady blue color which means pair process has been finished.




After that thermostat will display main screen. You succesfully configured VS20WRF/VS20BRF thermostat with RX10RF receiver.

5.3 Configuration as a hot water timer

5.3.1 Pairing with Room Extension Receiver (RX2)



For easier installation, please make sure you have already added other devices to your ZigBee network, such as Underfloor Heating Control Box (KLO8RF) or RX10RF.



Set your thermostat for underfloor heating by " or " or " buttons. Confirm by • button.

Now thermostat is looking for the signal from the coordinator...

Go to SALUS Smart Home app.



Environment

Settings


Healty

Mily Stratus

SMUS

Lagual


Lagual



Open main menu.

 ${\sf Select}_{\it w} {\sf Settings}".$

Now enter to the "Setup Equipment".



Let's connect your equipment.

Check the box next to each place of equipment you'd like to connect you. Clox "Connect equipment".


Scanning for devices...

Connect to seem to be a connect or equipment.

Scanning for devices...

Cannot be seemed.


...Gateway has started flashing red and searching for the thermostat...




Press "Scan for equipment" button.

App has started scanning...


Thermostat is connected. Go to the Smart Home app to configure it.




Select your thermostat and press "Connect equipment" button.




Name your thermostat and go "Next"...




Press gear icon.




Press "More" to expand the menu.




Select option "Hot Water Timer".



Choose "More" to expand the menu.




Choose Room Extension Receiver.



Press "Finish" button to end the set up process in the app.



Gateway stop flashing and turn to steady blue color which means pair process has been finished.



After that thermostat will display main screen. You succesfully configured VS20WRF/VS20BRF thermostat as a hot water timer with RX10RF receiver.

6. OPERATING in ONLINE MODE (by app)


6.1 General informations

This section will show how to use your **VS20WRF/VS20BRF** thermostat with the **UGE600 Universal Gateway** and the **Salus Smart Home App**. In order to do that, you will need a **Salus UG600/UGE600 Universal Gateway**, the **Salus Smart Home App** and **Internet connection**. Controlling your thermostat via the App gives you a lot of freedom and the possibilities to manage the temperature in your house/office remotely (Smart Home app is available for Android/iOS mobile devices or Internet browser).

6.2 App icons description


6.2.1 Programmable thermostat

Menu view of VS20WRF/VS20BRF thermostat set as a programmable thermostat in **SALUS SmartHome** application:




6.2.2 Hot Water Timer


Menu view of VS20WRF/VS20BRF thermostat set as a Hot Water Timer in **SALUS SmartHome** application:




6.3 Change thermostat name (pencil icon)




Select the thermostat in the main app menu.



Press the thermostat's name.



Click on the pencil icon.



Name your termostat and confirm it by "Save" button.


6.4 Work as a programmable thermostat

6.4.1 Setpoint temperature change


You can change the setpoint by sliding the cursor to left/right on your App. On your App screen, the setpoint temperature is the number displayed in a larger font.




Select the thermostat in the main app menu.



Old setpoint value.



New setpoint value.



Thermostat has started heating (flame icon changed colour from white to orange).

6.4.2 Heat/Cool mode change (KLO8RF connection)

VS20WRF/VS20BRF thermostat could be a heating device or cooling device. **Default thermostat is set for heating.** To set cool mode you have to insert the jumper into "CO" terminal on KL08RF side. Look at the instructions below:

HEATING MODE:



When there is no jumper at "CO" terminal KL08RF is automatically working in heating mode.

In the application you will see orange thermostat tile with "Flame" icon when heating mode is on.

When thermostat is calling for heating then flame icon is displayed.

COOLING MODE:



When there is jumper at "CO" terminal KLO8RF is automatically working in cooling mode.

In the application you will see blue thermostat tile with "snowflake" icon when cooling mode is on.

On the thermostat display you will see "snowflake" icon.

6.4.3 Thermostat modes

6.4.3.1 Schedule mode

The **VS20WRF/VS20BRF thermostat** gives you the possibility to programm schedule. You can add up to 6 programs during one day by selecting the program's start time and temperature. You can choose from 3 different schedule configurations:

- Separate schedule for working days (Mo-Fri) and weekend (Sat-Sun)
- Individual schedules for each day at the week
- One schedule for whole week

To activate schedule mode:




Additionally, you can choose to set the Default schedule that already exist in the App, or to modify it according to your preferences. The schedule is displayed at the bottom of screen of your App on the selected thermostat. You can activate the schedule by pressing the Follow Schedule icon on your App. Once activated, the calendar icon will appear on your screen.

letter.

TO SET THE SCHEDULE IN THE APP:






Please note:

Daily


You can add **as many intervals as you wish** by repeating the procedure described from **steps 3 to 6**. The procedure is the same for all 3 schedule configurations. You can customize the programs on the thermostat in any way you want.

schedule. You can delete all default intervals by


button.




After you've added all the intervals, tap "Save" to save it. Your schedule has been saved and set.



ADDITIONALLY: You can duplicate the same schedule for other thermostat's. Click on the "Duplicate schedule" option.



Select thermostat for which you want to duplicate the schedule.



Now app is saving your choice and after it you will have the same schedule for thermostat's you've selected.






Please note:


When thermostat has no schedule (or it has been deleted) then it maintains a constant temperature 21 °C (in "Follow Schedule" mode).

TO SET DEFAULT SCHEDULE:



Select thermostat in the main app menu.

Press thermostat's name.



Scroll down and press pencil icon.

To set default schedule use "Default schedule" button. It will remove all current intervals and it will set default schedule.

6.4.3.2 Temporary override mode

Temporary override mode means manual temperature change during active schedule mode:



When "Follow schedule" mode is active, use slider to set new setpoint temperature.

When you have overwritten the temperature then hand icon will appear next to calendar which means that temporary override mode is working until next schedule program.

When you overwrote schedule's setpoint temperature then on the thermostat's display you will see the hand icon.



NOTE: Temporary override mode will be maintained until next program will come, as it has been set in the schedule.

6.4.3.3 Manual mode

If the thermostat follows a schedule or is in frost protection mode, user can change the operating mode to the **manual mode**. In **manual mode** thermostat will maintain setpoint temperature until user will manually change it to a new value or select a new operating mode. When thermostat works in **manual mode**, the hand icon 🤚 will be displayed in the app screen.



Select "Permanent Hold" mode.

Hand icon confirms that thermostat is in manual mode.


6.4.3.4 Frost protection

In **Frost protection mode** the thermostat is displaying actual room temperature and maintain "frost protection" setpoint temperature specified in thermostat settings (please refer to chapter 8.3). When thermostat works in **Frost protection mode** then you have no possibilities to change temperature setpoint. To activate **Frost protection mode** online please followe steps below:





Also on the thermostat's display you can see that frost protection mode is activated by "Snow" icon.





confirm by "Save" button.

6.4.4 Key lock function

You can lock/unlock buttons in your thermostat by application.



Click on the "padlock" icon to lock/unlock thermostat buttons.


When buttons are locked then also you can see on the thermostat display "key" icon.

6.4.5 Compatibility with window/door sensor OS600 / SW600


VS20WRF/VS20BRF thermostat paired with window/door sensor **OS600/SW600** allows to create OneTouch rules when window/door is **opened** or **closed**. If thermostat will receive information from window/door sensor (that window has been opened for example) then OneTouch rule will turn off heating until window close. If you want to have acces to this function then first you have to add window/door sensor **OS600** or **SW600** (**please refer to the OS600 or SW600 manual instruction**).




To pair window/door sensor OS600/SW600 with VS20WRF/VS20BRF thermostat please follow steps below:



Select the thermostat in the main app menu.



Press thermostat's name.



Choose the window icon.




Mark sensors which you want to link together with the thermostat. You can additionaly lock buttons on thermostat when window is opened by marking option above.

Press "Save" button to finish pair process…

VS20WRF/VS20BRF thermostat paired with SPE600 Smart Plug allows to turn on/off any electric device eg. pump, radiator or valve with actuator. When thermostat starts heating then plug will turn on device (or turn off when there is no need to heat). If you want to have acces to this function then first you have to add SPE600 Smart Plug to the SALUS SmartHome system (please refer to the SPE600 manual instruction).




To pair SPE600 Smart Plug with VS20WRF/VS20BRF thermostat please follow steps below:



VS20WRF/VS20BRF thermostat paired with Smart Relay SR600 allows to wireless control of eg. radiator, pump, boiler. When thermostat start heating then SR600 Smart Relay will turn on device (or turn off when there is no need to heat). If you want to have access to this function then first you have to add SR600 Smart Relay to the SALUS SmartHome system (please refer to the SR600 manual instruction).



To pair SR600 Smart Relay with VS20WRF/VS20BRF thermostat please follow steps below:



6.5 Work as a hot water timer (work modes)


VS20WRF/VS20BRF thermostat has 4 work modes as a hot water timer:

- Turned ON (thermostat is manually turned on and work as long as you change this mode to another or switch it off),
- AUTO mode (thermostat is following schedule which you programmed look at chapter 6.4.3.1 Schedule mode, page 30),
- Turned OFF (thermostat is manually turned off as long as you select other mode),
- Temporarily ON mode (you can fast set the water heating time in this mode in limited hour period (from 1 to 4 hours)).

6.5.1 Turned ON mode -

Thermostat is manually turned on and work as long as you change this mode to another or switch it off. To set this mode on, please follow steps below:






Now you can see thermostat's tile in orange colour which means it has started call for heating.

Also on thermostat's display you can see the current mode.

6.5.2 AUTO mode - 🖪

Thermostat is following schedule which you programmed - look at chapter 6.4.3.1 Schedule mode, page 29. To set this mode on, please follow steps below:



6.5.3 Turned OFF mode -

Thermostat is manually turned off as long as you select other mode. To set this mode on, please follow steps below:



Thermostat is turned off.
Tile is in green colour.

Also on thermostat's display you can see the current mode.


6.5.4 Temporarily ON mode -


You can fast set the water heating time in this mode in limited hour period (from 1 to 4 hours). To set this mode on, please follow steps below:



6.6 Identification mode

Identification mode can be useful when we are pairing more than one device in one moment and we don't know which device is which. Beyond, if our system include more that one **UGE600 Universal Gateway** then we can easily identify which device is paired with which gateway.






the main app menu.

In the **Identification mode** thermostat's display will start flashing **"Id"** information for 10 minutes.


You can also identify your device during thermostat's pairing process:



Click on the magnifying glass icon.

6.7 Pinning/unpinning thermostat to/from application dashboard


To pin/unpin thermostat from dashboard in Smart Home application please follow steps below:



Open main menu in the app.

Select equipment.

Select All equipment option.




Select your VS20WRF/VS20BRF thermostat.

Press on the "Pin" icon to pin/unpin thermostat to/from the app dashboard.

6.8 User settings (basic settings)


User settings of VS20WRF/VS20BRF thermostat determine basic thermostat parameters. Please see below how to enter those settings:





Scroll down to the settings section.


BASIC SETTINGS:



6.9 Admin settings (installer parameters)




PLEASE NOTE: Admin settings are mainly for qualified installers or knowledgeable users.




Select the thermostat in the main app menu.

Press thermostat's name.



Select thermostat's settings.



Scroll down to enter "Admin settings".



All service parameters with detailed admin settings are described on page 74!


6.10 OneTouch rules (add/edit)

OneTouch - function that distinguish **SALUS Smart Home system** in terms of functionality. **OneTouch** rules are pre-configured set of actions defined in the interface easy in use. You can **switch** it **on** or **off** anytime. **OneTouch** informs thermostat or other device how it has to work according to pre-set settings. In application are **4 pre-defined OneTouch** rules:

- Party Mode set thermostat temperature to 21 °C for 2 hours
- Comfort Temperature set thermostat temperature to 21°C
- Frost Protection Mode set thermostat to the Frost Mode (temperature setpoint can be set in the user settings) 5°C by default
- Holiday Mode set thermostat to the Holiday Mode



To activate **OneTouch** rules please follow steps below **(example on Party Mode)**:





Press "Apply" to confirm.

pressing "Run now" button.

Click, Add One Touch" to add it.

You can also create your own **OneTouch** rule. As an example we will create OneTouch rule which activates **"send me a notification"** action under **"temperature is below 10 °C"** condition. Please look at the steps below how to set this **OneTouch** rule.






Enter OneTouch rule name.

Press "Add a AND OneTouch" button.


At this step choose condition which have to be fullfill in order to activate the rule.



Select which thermostat you want to link up with your OneTouch rule.

Choose the condition details for your thermostat. In this case select "Temperature Below" option.


Enter a temperature setpoint trigger for your OneTouch rule. Press "Set" button to confirm.




Select "DO THIS" option to create OneTouch rule action.

Choose e-mail or SMS notification and enter the message content. Confirm by pressing "Set" button.


To finish OneTouch rule creation press "Save" button.



As an option OneTouch rule tile can be pinned to the dashboard.




Newly created OneTouch rule tile can be found under OneTouch main menu...




... and on your dashboard.



To force OneTouch rule activation select it tile...



...and press it's button.




OneTouch rule is now activated. In this example SMS message will be send to the user.



Please note: SMS notifications will be send to the user **only** if they are activated in the OneTouch settings and UGE600 Universal Gateway is connected to the Internet.


6.11 Error codes (exclamation mark in app)

If there is any error in the Smart Home system which relates to the devices performance or functionality then the Smart Home app will inform user about it by a red exclamation mark in the upper menu. Please look at the example below:



All current errors are displayed.

Errors are visible also on the thermostat's LCD display.



ERR 01-03 (Floor Sensor Defect) means that there is a break in the circuit of the temperature sensor plugged into the S1 / S2 contacts of the thermostat or the sensor has been activated and not connected to the thermostat.


> When problem has been solved (sensor change or re-connection in this case) exclamation mark will disappear in application and thermostat will stop flashing error.



Full list of errors is in chapter 11.

6.12 Wireless signal strength test

Each wireless device has a limited range. Beyond distance there are many more elements which could affect on. For example - concrete walls, other wireless network interferences, wooden walls, reinforced concrete ceilings, metal construction elements, pillars, aluminium foil for underfloor heating etc. **Smart Home system has built-in function which allows to check wireless signal quality. If you want to check your system connectivity and signal's strength please follow steps below:**



Signal quality is expressed in **decibel units (db)**. Compare your value with scale below:

-50db to 0db - very good quality signal

-75db to -50db - good quality signal

-85db to -75db - low quality signal

-95db to -85db - bad quality signal, make wireless connection nearly impossible



PLEASE NOTE: Every Smart Home system device which is powered 230VAC is also working as a signal repeater of ZigBee network. If system is based on battery devices there could be a need to use repeaters like Salus RE600, Salus RE10RF or any other device of Salus Smart Home series which is powered by 230V AC.


6.13 Factory reset (removing thermostat from the app and ZigBee network)

To make thermostat factory reset and remove it from the ZigBee network please follow steps below:




Select the thermostat in the main app menu.

Press thermostat's name.



At the very bottom of thermostat's menu choose "Remove" option.




Press "Delete" button to remove your thermostat from the app and confirm factory reset.



NOTE: Factory reset function removes thermostat from the ZigBee network. This means that thermostat is not visible anymore in the "My equipment" list.

You can also do factory reset from the thermostat directly. It will also remove your thermostat from the Zigbee network but you still will be able to see thermostat's tile. After factory reset thermostat tile will change to dark grey colour.






Press thermostat's name.



At the very bottom of thermostat's menu choose "Remove" option.



Press "Delete" button to remove your thermostat from the app and confirm factory reset.

7. Installation in OFFLINE MODE without SALUS SmartHome application

7.1 General informations

In OFFLINE mode (without application), you can use the **UGE600 Universal Gateway** or **CO10RF coordinator** to configure the system. Please note that you cannot use both devices at the same time. Before installing the system you have to decide:

- to create a network using the **UGE600 Universal Gateway** (you can connect it to the Internet in the future)
- to create a network using the **CO10RF coordinator** (you can't connect it to the Internet)




REMEMBER! The **UGE600 Universal Gateway** and **CO10RF coordinator** are two different devices. Each device creates and operates it's own network.



Universal Gateway is NOT CONNECTED TO THE INTERNET

You can use your devices locally without the Smart Home App. Gateway works in this mode as standard ZigBee coordinator.



CO10RF Coordinator

You can use standard ZigBee network coordinator to install and use your devices.

NOTE: CO10RF Coordinator is included in the set with the KL08RF Control Box.



Please note! If your system has been installed in the OFFLINE mode using the **UGE600 Universal Gateway** and then connected to the Internet, all devices should be found in the SALUS Smart Home application (using "Scan for equipment" button). All devices found in the application don't need to be reconfigured, because all settings are automatically copied from the gateway.

Please note! If your system was created using the **CO10RF coordinator** and you would like to control the devices via the Internet, then all devices should be reinstalled using the UGE600 Universal Gateway.



KLOSRF - Wiring Centre for 8-zone underfloor heating (UFH).



+ extension KL04RF



TRV (Thermostatic Radiator Valve) - with wireless communication.




RX10RF receiver

7.2 Pairing with underfloor heating wiring centre (KL08RF/Control Box)

7.2.1 Available operation modes

CASE 1


GROUP 1 - consists of 4 thermostats (in addition, more thermostats can be assigned to a group in further zones located in the wiring centre). Managed by 1 weekly, programmable thermostat, configured as a MASTER (group 1), e.g. VS20WRF. The other 3 thermostats are daily, non-programmable, configured as a SLAVE (group 1), e.g. VS20WRF, VS10WRF or HTRS-RF(30). The MASTER thermostat can affect the SLAVE thermostats (VS20WRF, VS10WRF or HTRS-RF(30)), which will follow the schedule set on the VS20WRF thermostat. Remember - if you want MASTER thermostat to control the SLAVE thermostats, then all SLAVE thermostats have to be set to AUTO mode - A. The VS20WRF thermostat is configured as a MASTER thermostat during pairing with the KL08RF underfloor heating wiring centre (see section 7.2.2).



CASE 2


GROUP 2 - consists of 2 thermostats. The first thermostat is a daily, non-programmable thermostat, configured as a SLAVE (group 2), e.g. VS20WRF. The second thermostat is a weekly, programmable thermostat, configured as a MASTER (group 2), e.g. VS20WRF. The MASTER thermostat can affect the SLAVE thermostats (VS20WRF), which will follow the schedule set on the VS20WRF thermostat. Remember - if you want MASTER thermostat to control the SLAVE thermostats, then all SLAVE thermostats have to be set to AUTO mode - A. The VS20WRF thermostat is configured as a MASTER or SLAVE thermostat during pairing with the KL08RF underfloor heating wiring centre (see section 7.2.2).

NOTE - you can also create the second group on the same wiring centre. The groups will operate independently of each other.



CASE 3


Programmable temperature thermostat - this is a single, independent thermostat assigned to any zone on the wiring centre, configured as a regular weekly, programmable thermostat (not MASTER, not SLAVE). In Offline mode it is possible to set a weekly schedule and the set temperature can be changed automatically according to the time programs. The thermostat's menu allows you to set three predefined temperature setpoints (see chapter 8.1. "Work modes") that are used as part of the programmable schedule. It also has the ability to work separately in manual mode, not related to the schedule. Configuration of the VS20WRF thermostat as a programmable temperature thermostat occurs during pairing with the KL08RF underfloor heating wiring centre (see section 7.2.3).




7.2.2 Grouping - installation of the thermostat as a group controller - MASTER - or as a group thermostat (SLAVE)

In this chapter you will learn how to set VS20WRF/VS20BRF thermostat as a group controller (MASTER) or group thermostat (SLAVE). Please look at the instructions below:

VS20WRF/VS20BRF AS A GROUP CONTROLLER (MASTER):




Close the ZigBee network.



7.2.3 Installation as a programmable thermostat




For easier installation, please make sure you have already added Underfloor Heating Wiring Centre / Control Box KLO8RF to your ZigBee network (please refer to the wiring centre manual instruction).




signal from the coordinator. Press **v**o button to confirm.

number (press PAIR button on the KLO8RF to see its address number). Press \checkmark o button to confirm.


areas with 4 zones (8 zones in control box in total 2 areas, without KLO4RF extension) and press **√**∘ button to confirm.



Use \checkmark or \checkmark buttons to select the zone number and press \checkmark o button to confirm.




When thermostat is succesfully paired, main screen will be displayed.



Close the ZigBee network.

7.2.4 Replace the zone assigned to another thermostat

You can replace zone on the wiring centre, which is occupied by other thermostat (it will remove it from that zone). To do it follow steps below:



Press so button to confirm zone replacement. You can always change the zone using or buttons if you don't want to replace it.


Confirm by **√**∘ button.

When thermostat is succesfully paired, main screen will be displayed.

7.3 Pairing with wireless TRV radiator head



For easier installation, please make sure you have already added wireless TRV radiator heads to your ZigBee network (please refer to the wireless TRV radiator head manual instruction).




Hold the button ((?)) for 10 seconds, The LED on the head should start to blink red. You can pair up to 6 TRV's with 1 thermostat. All TRV's have to be within the same room with thermostat.

Set your thermostat for radiators by or buttons.

Confirm by button.

Now thermostat is looking for the signal from the coordinator...




Open the ZigBee network.

The thermostat has been added to the ZigBee network and paired with the gateway/coordinator.

Press

button to confirm.


Device is paired with coordinator, diode on the TRV will start to blink orange.



Press > button.
Thermostat is searching for TRVs radiator heads...

Diode on the TRV will light up once green and stop blinking.

On the LCD you will see the number of paired TRV's. Once all TRV's are paired press so button to finish the pairing process.



TRV has been added.


When thermostat is succesfully paired main screen will be displayed.

Close the ZigBee network.

7.4 Pairing with RX10RF receiver



For easier installation, please make sure you have already added RX10RF receiver to your ZigBee network (please refer to the RX10RF receiver manual instruction).




Hold \checkmark_{\circ} + \checkmark + \gt buttons for 5 seconds to expand menu.

Use \checkmark or \checkmark buttons to:


- choose pairing with the RX10RF receiver in the "RX1" configuration, if the receiver is set as RX1 (receiver responds to the heating signal from any thermostat),
- choose pairing with the RX10RF receiver in the "RX2" configuration, if the receiver is set as RX2 (receiver responds to the heating signal only from one thermostat).

 Confirm by
 obutton


Now thermostat is looking for the signal from the coordinator...



Open the ZigBee network.




Thermostat has caught the signal from the coordinator. Press \checkmark 0 button to confirm.



Confirm choice by **√**∘ button.



When thermostat is succesfully paired main screen will be displayed.




Close the ZigBee network.

7.5 Configuration as a Hot Water timer


7.5.1 Pairing with Room Extension Receiver (RX2)




For easier installation, please make sure you have already added other devices to your ZigBee network, such as Underfloor Heating Control Box (KLO8RF) or RX10RF.



button to confirm.



When thermostat is succesfully paired main screen will be displayed.



Close the ZigBee network.

8. OPERATING in OFFLINE MODE


8.1 Work as a programmable thermostat

8.1.1 Work modes

VS20WRF/VS20BRF offers few work modes. Frame on a given icon indicates which mode is currently active. In manual mode (4) , (4) or (5) only one temperature level is maintained. Thermostat follows programmed schedule when AUTO mode is active ("A" icon). Detailed description of work modes is located below:

- **Comfort temperature mode** pre-defined setpoint temperature. Usually set when we are indoors. The highest maintained temperature in heating mode or the lowest if thermostat works in the cooling system. Acting alone works as a manual mode.
- Standard temperature mode pre-defined setpoint temperature. Usually set during the day when we are around the house. Acting alone works as a manual mode.
- **Economic temperature mode -** pre-defined setpoint temperature. Usually set at night or when we are out of the house. Acting alone works as a manual mode.
- A **Automatic mode temperature (schedule)** follows programmed schedule. Schedule can be temporarily override with new setpoint temperature (temporary override mode will be active to the next change forced by schedule, hand icon will be displayed).
- T Party mode this mode sets the comfort temperature 🔄 for a user-defined time (maximum 9 hours 50 minutes).
- Holiday mode this mode sets the frost protection mode 🕸 for a user-defined time (maximum 99 days).
- Frost protection mode usually used during extended periods of absence or during the holidays (only available in heating mode).


Example - comfort temperature mode setpoint editing:



8.1.2 Heat/cool mode change (KLO8RF connection)

VS20WRF/VS20BRF thermostat is designed to work in heating and cooling systems. By default thermostat is set to heating mode. To change from heating to cooling mode it's necessary to insert jumper into "CO" terminal (KL08RF wiring centre). Look at the instructions below:


HEATING MODE:



"CO" terminal of the KLO8RF wiring centre - if contacts are opened, then all thermostats paired with KLO8RF are in heating mode.

When thermostat is calling for heating, then flame icon is displayed.

COOLING MODE:



"CO" terminal of the KLO8RF wiring centre - if contacts are closed, then all thermostats paired with KLO8RF are in cooling mode.

When thermostat is calling for cooling, then snowflake icon is displayed.


8.2 Work as a hot water timer with RX10RF receiver

8.2.1 Work modes

VS20WRF/VS20BRF thermostat as a Hot Water timer has 4 modes available:

- ON Turned ON thermostat is manually turned on and work as long as you change this mode to another or switch it off,
- A AUTO mode thermostat is following schedule which you programmed look at chapter 8.4.1 Schedule mode, page 65,
- OFF Turned OFF thermostat is manually turned off as long as you select other mode,
- **B Temporarily ON mode** you can fast set the water heating time in this mode in limited hour period (from 1 to 4 hours 1).

Example - setting the "Turned ON" mode:




8.3 User settings (basic settings)


8.3.1 Schedule mode - programming schedule

To program schedule in offline mode please follow steps below:


enter the menu.



There are 4 possible schedule variants. Use \langle and \rangle buttons to select schedule variant and confirm by \checkmark 0 button:




Schedule programming example for the WORKING DAYS variant:




Select schedule variant by ✓o button.

Use ✓ or ✓ buttons to set hour.
Confirm by ✓ o button.


Use ✓ or ✓ buttons to set minutes. Confirm by ✓∘ button.



Use \langle and \rangle buttons to choose comfort, standard or economic setpoint temperature.



Confirm by \checkmark o button.



Schedule editing will jump to the next program's time setting.

Set time for selected mode using


or buttons again.

Confirm by obutton.




Repeat steps 5 and 9 for the next time periods in the schedule to set whole program for selected variant. No time --:-- on the display means given program is skipped. There are 6 programs/time periods in the schedule. Hold \checkmark 6 button for 3 seconds to save and exit schedule editing.

To run the schedule (activate thermostat's automatic mode), use \langle and \rangle buttons to move the frame to the "A" icon.



8.3.2 CAL function

It is available only when the thermostat is paired with the TRV radiator head. The function activates an advanced self-learning algorithm for systems not equipped with the RX10RF receiver. The system performs a very precise calibration of devices in order to auto-adapt to room conditions.



0 - ON / OFF

The algorithm should be used in a system equipped with an RX10RF (RX1) module to control a gas boiler. The advantage of the algorithm is that the heating process begins with the opening of the TRV radiator heads and ensures the flow of the medium in the system before the boiler is started. The system also ensures that the boiler is shut down earlier via the RX10RF (RX1) module, before all radiators are completely throttled on the valves by the TRV radiator heads.

1 - AUTO

The default setting means that the system itself decides about the choice of the control algorithm:


- if the thermostat works in the system together with RX10RF (RX1), i.e. we have boiler control, the heads will be controlled according to the ON / OFF algorithm,
- if there is no RX10RF (RX1) the thermostat selects the self-learning algorithm (Advanced Self Learning Control).
- 2 Advanced Self Learning Control advanced self-learning algorithm. The algorithm is provided for systems that are not equipped with the RX10RF (RX1) module. The fluid flow in the hydraulic system must be ensured (by-pass installed), if all heads are closed and the boiler can work. The correct operation of the algorithm consists in double calibration of the TRV head:
- standard when installing the head on the valve
- precise in order to auto-adapt to room conditions and maintain a stable set temperature.


Precise calibration may take several hours (or even more if one thermostat controls several heads simultaneously). While the thermostat is calibrating, the display shows "CAL" in place of the hour.

Calibration is performed automatically. There is no need to force it manually.

8.3.3 Time/Date


Time/date change or edit can be done **only in Offline mode**. In **Online Mode** thermostat will synchronise **current** time and date based on information taken from the Internet. To set time/date follow steps below:






8.3.4 Thermostat calibration

Thermostat calibration is a function which allows user to recalibrate internal thermostat's temperature sensor by a given number of degrees (in the range from -3,0 °C to 3,0 °C in 0,5 °C steps). To calibrate thermostat's temperature sensor please follow steps below:




8.3.5 Key lock function

To LOCK/UNLOCK **VS20WRF/VS20BRF thermostat** keys in **OFFLINE MODE** you have to press and hold $\checkmark + \land$ buttons for **3 SECONDS.** When thermostat is **locked**, you will see padlock icon on the display. When thermostat is **unlocked** padlock icon is not visible.



9. Installer parameters

To enter installer parameters please follow steps below. Please refer to parameters table description before any changes. Use \checkmark or \land buttons to move up or down between all parameters. Every change/selection confirm by \checkmark 0 button:




dXX	Function	Parameter Values	Description	Default Values
100	T	0	Celsius [°C]	0
d00	Temperature unit	1	Fahrenheit [°F]	
d01	The method of controlling the temperature of the heating system	0	by TPI algorithm	0
		1	SPAN ±0.25°C	
		2	SPAN ± 0.5°C	
d02	Correction of the displayed temperature	from -3.0°C to +3.0°C	If the thermostat indicates an incorrect temperature, it can be corrected by $\pm3.0^{\circ}\text{C}$	0°C
		0	No sensor	
d03	Floor temperature sensor use (S1,S2)	1	Temperature sensor connected	0
		2	Dew point sensor connected (only in UFH)	
		3	Occupancy sensor connected	

dXX	Function	Parameter Values	Description	Default Values	
10.4	Internal relay	0	The controller measures the temperature only at the external sensor		
d04	(active when d03=1)	1	The sensor is used as a protection against overheating of the floor	0	
d05 (only	Control of the coaling made	1	SPAN ±0.5°C	2	
in UFH)	Control of the cooling mode	2	SPAN ±1.0°C	2	
		0	Standard ON/OFF algorithm		
d06 (only with TRV)	TRV control algorithm	1	Automatic selection	1	
,		2	Advanced self-learning algorithm		
-107	07 Valve protection		Disable		
d07	Valve protection	1	Enable	1	
d08	Frost protection temperature	5-17°C	Frost protection temperature (and for holiday mode)	5℃	
400	T: (0	12 hours	1	
009	d09 Time format		24 hours	1	
d11	Cummar tima changa	0	Disabled	1	
ull	Summer time change	1	Enabled		
d12	Heating temperature limit	5-35°C	Maximum heating/cooling temperature that can be set by the user	35°C	
d13	Cooling temperature limit	5-40°C	Minimum heating/cooling temperature that can be set by the user	5℃	
d14	Max floor temperature (active in heating mode when d04=1)	6-45°C	To protect the floor against overheating, the heating will be switched off when the maximum temperature of the floor sensor is reached.	27°C	
d15	Min floor temperature (active in heating mode when d04=1)	6-45°C	To protect the floor, heating will be activated when the minimum floor sensor temperature has been reached.	10°C	
d16	Lower floor temperature limit for cooling (Function active when d04 = 1).	6-45°C	To protect the floor, cooling will be switched off when the set minimum temperature is reached.	6°C	
FEATURES AVAILABLE ONLY FROM THE APPLICATION LEVEL:					
d17	Allow buttons to be unlocked	0	OFF	1	
417	from the thermostat	1	ON	'	
140	Deactivate the need to confirm the change of the	0	OFF		
d18	temperature setpoint by pressing the 🗸 button.	1	ON	0	


10. Factory Reset

To **RESET** VS20WRF/VS20BRF thermostat to it's factory default settings please follow steps below:



11. Error codes (error codes description with possible solutions)

Thermostat constantly monitors the network status, wireless connection status and the operation of connected sensors or paired devices. If it detects any failure then following error codes can be displayed alternately with the current room temperature value.





In Online mode error is also shown in the Smart Home application (with detailed description). Exclamation mark informs user about existing errors.



Error codes description with possible solutions:

ERROR CODE	DISPLAY DESCRIPTION	ERROR DESCRIPTION	TROUBLESHOOTING
1.	Err XX-01	TRV paired with thermostat - TRV hardware error.	Reinstall the TRV head or replace it. If necessary, contact with the SALUS Technical Department.
2.	Err XX-02	Floor is overheated (heating mode). / Floor is overcooled (in cooling mode).	 Set the heating medium temperature or change D14 parameter. Set the cooling medium temperature or change D16 parameter.
3.	Err XX-03	Floor sensor is broken.	 If floor sensor is connected to S1/S2 input, check the wiring. If floor sensor is not connected, check the D03/D04 parameters settings.
4.	Err XX-04	Floor sensor is shorted.	• Check floor sensor wire insulation for any damages. Sensor resistance for $25^{\circ}C{=}10k\Omega.$
5.	Err XX-05	Thermostat lost contact with the CO10RF network coordinator or the UGE600 internet gateway.	Check the coordinator/gateway power supply connection. Force identification process from the coordinator/gateway or thermostat.
6.	Err XX-06	Thermostat lost connection with the wiring centre.	Is the wiring centre turned ON and Status Network LED diode solid? • If yes, send the heating signal from thermostat to the wiring centre

ERROR CODE	DISPLAY DESCRIPTION	ERROR DESCRIPTION	TROUBLESHOOTING
			 (change setpoint temperature). If LED diode of the Network Status is flashing, pair the wiring centre with the system in accordance to the manual instruction and pair thermostat with wiring centre.
7.	Err XX-07	Thermostat lost contact with the TRV head.	 Check TRV head batteries. Send the heating signal from thermostat and check if the TRV head is working. If the LED diode on the TRV head is flashing, repeat the pairing procedure with thermostat according to the manual instructions.
8.	Err XX-08	Thermostat has lost connection with the RX10RF receiver (RX1 mode).	 Is the RX10RF receiver plugged to the power supply and the top LED diode is red? The Auto/Manual switch has to be set to AUTO position. Force identification process from the coordinator/gateway side and check if the devices are within the network. Send the heating signal from thermostat If the top LED diode is flashing, perform the pairing procedure according to the RX10RF manual instruction.
9.	Err XX-09	Thermostat has lost connection with the RX10RF receiver (RX2 mode).	 Is the RX10RF receiver plugged to the power supply and the top LED diode is red? The Auto/Manual switch has to be set to AUTO position. Force identification process from the coordinator/gateway side and check if the devices are within the network. Send the heating signal from thermostat If the top LED diode is flashing, perform the pairing procedure according to the RX10RF manual instruction.
10.	Err XX-10	KL10RF wiring centre has lost connection with the DHW time programmer. Error is displayed on all thermostats and on the DHW programmer.	Is the wiring centre turned ON and Status Network LED diode solid? • If yes, send the heating signal from DHW programmer to the wiring centre. • If LED diode of the Network Status is flashing, pair the wiring centre with the system in accordance to the manual instruction and pair DHW timer with wiring centre.
11-18.	Err XX-11 XX-18	Wiring centre has lost connection with thermostat of the given zone: e.g. 11 = with zone 1; 12 = with the zone 2 etc. Error is displayed on all thermostats.	 Check the thermostat power supply. Send the heating signal from thermostat. If necessary, reinstall the thermostat.
19.	Err XX-19	Wiring centre has lost connection with the CO10RF coordinator/UGE600 internet gateway. Error is displayed on all thermostats.	 Is the wiring centre turned ON and Status Network LED diode solid? Force identification process from the coordinator/gateway side and check if wiring centre is within the network. If LED diode of the Network Status is flashing, pair the wiring centre with the system in accordance to the manual instruction and pair all thermostats with wiring centre.


ERROR CODE	DISPLAY DESCRIPTION	ERROR DESCRIPTION	TROUBLESHOOTING
20.	Err XX-20	Wiring centre has lost connection with the RX10RF receiver operating in RX1 mode. Error is displayed on all thermostats.	 Is the wiring centre turned on? Status Network LED diode should be solid. Force identification process from the coordinator/gateway side and check if devices are within the network. If the LED diode of the AUTO/MANUAL receiver switch is flashing, follow the RX10RF manual instruction for pairing.
21.	Err XX-21	TRV head has lost connection with CO10RF coordinator/UGE600 internet gateway.	 Check TRV head batteries (replace if necessary). Check if the coordinator/ internet gateway is connected to the power supply. Force identification process from the coordinator/gateway side and check if devices are within the network. Send the heating signal from thermostat.
22.	Err XX-22	Low battery level in the TRV head.	Replace TRV head batteries.
23.	Err XX-23	TRV head's pairing error or head is incompatible with the system.	Remove TRV head from the system and repeat pairing procedure with thermostat.
24.	Err XX-24	Thermostat was rejected by the wiring centre.	Perform the thermostat's pairing procedure again.
25.	Err XX-25	Thermostat has lost connection with the nearest 230V powered device.	• Check the power supply of the nearest 230V device. If there is problem with RF signal range, install the ZigBee Network Repeater and pair thermostat with the receiver again (wiring centre, TRV head etc.)
26-29.	Err XX-26 XX-29	Wiring centre has lost connection with thermostat of the given zone: e.g. 26 = with zone 9; 27 = with zone 10; 28 = with zone 11, 29 = with zone 12. Error is displayed on all thermostats.	 Check the thermostat's power supply. Send the heating signal from thermostat. If necessary, reinstall the thermostat.
30.	Err XX-30	TRV head has a problem with the internal gear mechanism.	Reinstall the TRV head or replace it. If necessary, contact with the SALUS Technical Department.
31.	Err XX-31	Adaptation error of the TRV head assembled on the radiator valve insert.	 Check assembly of the TRV head on radiator valve insert and reinstall the TRV head. Check the compatibility of the TRV head and radiator valve insert; replace the valve insert if necessary.
32.	Err XX-32	Thermostat's battery level is low.	Replace thermostat batteries.
33.	Err XX-33	The RX10RF receiver has lost connection with thermostat.	 Force identification process from the coordinator/gateway side and check if devices are within the network. Send the heating signal from thermostat side and check if RX10RF receiver is turning ON. If the top LED diode is flashing, perform the pairing procedure according to the RX10RF manual instruction. Pair thermostat with the RX10RF receiver again according to the thermostat's manual instruction.


12. Cleaning and Maintenance

The **VS20WRF/VS20BRF thermostat** requires no special maintenance. Periodically, the outer casing can be wiped clean using a dry cloth (please DO NOT use solvents, polishes, detergents or abrasive cleaners, as these can damage the thermostat). There are no user serviceable parts within the unit; any servicing or repairs could only be carried out by **Salus Controls** or their appointed agents.

13. Technical Informations

Power supply	4 x AAA batteries
Temperature range	5 - 35℃
Temperature measurement accuracy	0.5℃
SPAN	±0.25°C or ±0.5°C
RF	ZigBee 2,4 GHz
Dimensions [mm]	86 x 86 x 29





14. Warranty

SALUS Controls warrants that this product will be free from any defect in materials or workmanship, and shall perform in accordance with its specification, for a period of five years from the date of installation. SALUS Controls sole liability for breach of this warranty will be (at its option) to repair or replace the defective product.

Customer Name:	
Customer Address:	

Tel No: Email:	
Company Name:	
Tel No: Email:	
Installation Date:	
Installer Name:	
Installer Signature:	
	3



DISTRIBUTOR OF SALUS CONTROLS:

QL CONTROLS Sp. z o.o., Sp. k. Rolna 4, 43-262 Kobielice, Poland

IMPORTER:

SALUS Controls Plc
Units 8-10 Northfield Business Park
Forge Way, Parkgate
Rotherham
S60 1SD
United Kingdom





www.salus-controls.com

SALUS Controls is a member of the Computime Group.

Maintaining a policy of continuous product development SALUS Controls plc reserve the right to change specification, design and materials of products listed in this brochure without prior notice.

Issued: 16 VII 2020

Version: 12

