

T3+

Productively clean both open and tight spaces using advanced technologies in one cost-effective, ultra-maneuverable auto-scrubber

- Equipped standard with either ec-H2O™ or FaST® technologies extending scrubbing three times longer between empty/fills
- Wider cleaning path, combined with advanced technologies, increases productivity by over 30%
- Able to clean in virtually all the same spaces as a traditional 20 in/500 mm scrubber
- Perfectly sized for small and mid-sized retail facilities and route cleaners



ecH2O™
ELECTRICALLY CONVERTED WATER

FaST®
Foam Scrubbing Technology

The Safe Scrubbing Alternative®



T3+ WALK-BEHIND AUTOMATIC SCRUBBER—SPECIFICATIONS

FEATURES

Scrubbing System

Cleaning path	24 in	600 mm
Solution tank capacity	10.5 gal	40 L

Productivity (per hour)

Theoretical Max	28,560 ft ²	2,650 m ²
Estimated Coverage*	18,150 ft ²	1,690 m ²

Drive System

Brush motor horsepower	0.875 hp	0.65 kW
Brush RPM	285 rpm	285 rpm
Brush/pad pressure	50 & 90 lbs	23 & 41 kg

Solution Delivery System

Solution tank description	Full access & cleanable	
Solution capacity	10.5 gal	40 L

Recovery System

Recovery tank description	Full access & cleanable	
Recovery tank capacity (includes demisting chamber)	15 gal	57 L
Vacuum motor	0.5 hp – two stage	0.37 kW – two stage
Vac motor CFM	65 cfm	1.84 cmm
Vac motor sealed waterlift	40 in	1,020 mm

Battery System

Battery run time (continuous cleaning rating)	24V, 155 AH / Up to 3 hours	
--	-----------------------------	--

Dimensions/Weights

Product height	43 in	1,090 mm
Product length	48.25 in	1,225 mm
Product width (with squeegee)	30 in	760 mm
Product weight (with batteries)	391 lbs	177 kg

Decibel Rating

Operator's position**	68.5 dBA
-----------------------	----------

Warranty

A minimum of ten (10) years on rotationally molded polyethylene housing and parts free from defects and workmanship under normal use and service. The non-polyethylene parts a three (3) year-or 2,500 hours of operation-warranty under use and service. Labor coverage of warranty items for three (3) years.

*Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.
** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers and OSHA.

SEEING IS BELIEVING

For a demonstration or additional information, send an e-mail to info@tennantco.com.

Tennant

701 North Lilac Drive
Minneapolis, MN 55422
800.553.8033 | 763.540.1200
In Quebec: 800.361.9050
www.tennantco.com
info@tennantco.com