



# FSP600-60MRB(S)

## FEATURES

- Certified CB 62368-1 & CB 60950-1
- Meet 80 Plus Gold
- PMBus V1.2
- Design for 5,000 Meter above sea level
- High Reliability
- Low Ripple & Noise
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection

## SAFETY STANDARD APPROVAL



## DESCRIPTION

FSP600-60MRB(S) is an unique Mini-redundant power supply. It comes to offer the same form factor from 350W to 600W, and the total power capacity up to 600 Watts, plus hot swap features, which makes it to be perfectly fit in a standard 2U server chassis, and used in an industrial or home office environment. In addition, the power supply is ideally the best choice for server, workstation, communication or any other automation applications. This product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.

## GENERAL SPECIFICATIONS

Dimension (L x W x H): 190 x 150 x 84 (mm)  
7.49 x 5.91 x 3.3 (inch)

Efficiency: 80 Plus Gold

Hold-up time: 115V / 60Hz: ≥ 16ms  
230V / 50Hz: ≥ 16ms

Operating altitude: 5,000 meters above sea level

### Environment

Working temperature: 0°C to 50°C  
Storage temperature: -20°C to + 80°C  
Working humidity: 90% RH non-condensing  
Storage humidity: 90% RH non-condensing

MTBF: 100,000 hours of continuous operation at 25°C, Max,-output load

Applications: Workstation ,Storage System ,IPC Controller

## INPUT SPECIFICATIONS

Input voltage: 90-264Vac  
Input frequency: 47-63Hz  
Input current: 115Vac @ 6A, 230Vac @ 3A

## OUTPUT RATING

| Outputs      | +3.3V | +5V   | +12V   | -12V   | +5Vsb | -5V    |
|--------------|-------|-------|--------|--------|-------|--------|
| Max.         | 20.0A | 20.0A | 49.0A  | 0.5A   | 3.0A  | 0.3A   |
| Min.         | 0.0A  | 0.0A  | 1.0A   | 0.0A   | 0.0A  | 0.0A   |
| Regulation   | ±5%   | ±5%   | ±5%    | ±10%   | ±5%   | ±5%    |
| Ripple/Noise | 50 mV | 50 mV | 120 mV | 200 mV | 50 mV | 200 mV |

The +3.3V and +5V total output shall not exceed 130W  
-5V (Optional)

## MECHANICAL SPECIFICATIONS

UNIT: mm

