



UniFlood M G2

BVP355 180LED RGBWW 220V L50 15 DMX

18890 lm – 360 W – –

The Philips UniFlood M gen2 is a cost-effective, exterior-rated architectural LED floodlight that's designed for façade, landscape and outdoor floodlighting applications. The robust, modular, rectangular design features highly-efficient optics, making it ideal for illuminating everything from multi-storey façades and bridges to landmarks and monuments. This LED floodlight is available in white, monochromatic colours, RGB, RGBW and tunable white. It comes with six different spread lenses ranging from narrow spot to wide flood and has DMX512/RDM control option. A truly modular floodlight that gives architects and designers the freedom to explore a wide range of concepts and designs with no limitations.

Warnings and Safety

- For outdoor use only.

Product data

General information	
Light source colour	RGBW
Driver included	Yes
Optical cover/lens type	GC [Clear glass]
Control interface	Dynamic DMX/RDM
Connection	Flying leads/wires and 2 push-in connectors 4-pole
Cable	Cable 0.5 m without plug 3-pole and 2 cables 0.5 m with connector 4-pole
Protection class IEC	Safety class I
Flammability mark	F [For mounting on normally flammable surfaces]
CE mark	CE mark

Operating and electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Inrush current	60 A
Power factor (min.)	0.9
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Housing material	Extruded aluminium
Optical cover/lens material	Acrylate
Overall length	486 mm

UniFlood M G2

Overall width	478 mm
Overall height	231 mm
Effective projected area	0.234 m²
Colour	Dark Grey
Dimensions (height x width x depth)	231 x 478 x 486 mm

Approval and application

Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]

Initial performance (IEC compliant)

Initial luminous flux (system flux)	18890 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	52 lm/W
Init. Corr. Colour Temperature	-
Init. Colour rendering index	>80
Initial input power	360 W

Power consumption tolerance	+/-10%
-----------------------------	--------

Application conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product data

Full product code	871951492947000
Order product name	BVP355 180LED RGBWW 220V L50 15 DMX
EAN/UPC – product	8719514929470
Order code	92947000
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401750263
Net Weight (Piece)	18.750 kg



Dimensional drawing



BVP355 180LED RGBWW 220V L50 15 DMX

