

HY15LM Flow Kit



Properly mixed grout is a key to ensuring proper performance of the nVent LENTON Interlok Splicing System. The HY15LM Flow Kit is used to perform a modified slump test exclusively with nVent LENTON Interlok HY15LM Grout.

FEATURES

Includes all components needed to perform the slump test

Durable and reusable

SPECIFICATIONS

Table 1/1

Catalog Number	Unit Weight
LK430	6.5 lb

ADDITIONAL PRODUCT DETAILS

Prior to installation, please read and understand the detailed instructions and safety notices provided in the nVent LENTON Interlok Instruction Manual.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical
Support

Europe

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE