

Input

- COAX/AES/OPT :PCM 16-24bit/44.1-192kHz; DSD DOP64

- USB :

PCM 16-32bit/44.1-768kHz;

DSD DOP64-DOP256;

NATIVE DSD: DSD64-DSD512

OS support: Windows 7~11 32/64bit; macOS; Linux

- IIS: PCM 16-32bit/44.1-768kHz; DSD DOP64-DOP256;

NATIVE DSD: DSD64-DSD1024

- LAN: more in the future

- 10M Clock in: 50 Ohm BNC, 0dBm-20dBm,

square wave 0.2V-3.3V, sinewave 0.5-3.3V。

Output

Frequency Response: 20-20kHz /+ -0.2dB (Oversampling)

Dynamic range: >115dB

Signal-to-noise ratio: >122dB

Crosstalk: -134dB @ 1kHz

THD+N: <=0.003% @1kHz

IMD: ≈0.008% @ 0dbfs

RCA: 2.5Vrms (VOLUME FIXED) 100Ω

XLR: 5.0Vrms (VOLUME FIXED) 100Ω

XLR pinout: 1-Ground 2-Hot 3-Cold

Other

Power Supply: AC 115V/230V 50/60Hz

Power Consumption<30W

Size: 330mm (Width) * 260mm (Length) * 65mm (Height) (protrusion not included)

Packing size: 420mm (Width) * 360mm (Length) * 175mm (Height);

Weight: 7Kg (with package)

Sandblasted aluminum alloy case: Silver or Black version