

# XL-TRACE CONTRACTOR PACK, LOW SMOKE ZERO HALOGEN SELF-REGULATING CABLE KIT



nVent RAYCHEM contractor packs comprise a fixed length of heating cable supplied in an easy-to-use and carry spool box. The spool allows the installer to feed out the required length easily, reducing installation time and effort.

## FEATURES

Unparalleled safety, low smoke zero halogen construction: up to 90% less smoke emissions and improved self-extinguishing properties

Zero halogen: IEC60754-1 tested and compliant

Improved self-extinguishing properties under the IEC62395 flammability test

Energy efficient: self-regulating cable, major savings when used with proportional ambient sensing controller (PASC), no cable overheating possible

Self-regulating technology: cut-to-length on site to mitigate any design variations

Quick and easy installation with the RayClic fast connection system

## SPECIFICATIONS

|                                      |                        |
|--------------------------------------|------------------------|
| <b>Nominal Height:</b>               | 6.8 mm                 |
| <b>Nominal Width:</b>                | 13.8 mm                |
| <b>Supply Voltage:</b>               | 220 – 240 V            |
| <b>Min Installation Temperature:</b> | -40 °C                 |
| <b>Ground Path Type:</b>             | Braid                  |
| <b>Outer Jacket Material:</b>        | Low Smoke Zero Halogen |
| <b>Heating Cable Technology:</b>     | Self-Regulating        |

| Catalog Number | Item Name                       | Length | Nominal Power Output @ 5°C, 230V | Max Continuous Exposure Temperature, Power On | Color |
|----------------|---------------------------------|--------|----------------------------------|---|-------|
| 1244-021262    | XL-Trace-InstallerPack-10XL-30m | 30 m   | 10 W/m                           | 65 °C   | Plum  |
| 1244-021263    | XL-Trace-InstallerPack-10XL-50m | 50 m   | 10 W/m                           | 65 °C   | Plum  |
| 1244-021264    | XL-Trace-InstallerPack-10XL-80m | 80 m   | 10 W/m                           | 65 °C   | Plum  |
| 1244-021265    | XL-Trace-InstallerPack-15XL-50m | 50 m   | 15 W/m                           | 65 °C   | Green |
| 1244-021266    | XL-Trace-InstallerPack-15XL-80m | 80 m   | 15 W/m                           | 65 °C   | Green |
| 1244-021267    | XL-Trace-InstallerPack-26XL-50m | 50 m   | 26 W/m                           | 65 °C   | Blue  |

| Catalog Number | Item Name                       | Length | Nominal Power Output @ 5°C, 230V | Max Continuous Exposure Temperature, Power On | Color  |
|----------------|---------------------------------|--------|----------------------------------|---|--------|
| 1244-021268    | XL-Trace-InstallerPack-26XL-80m | 80 m   | 26 W/m                           | 65 °C   | Blue   |
| 1244-021269    | XL-Trace-InstallerPack-31XL-50m | 50 m   | 31 W/m                           | 85 °C   | Purple |
| 1244-021270    | XL-Trace-InstallerPack-31XL-80m | 80 m   | 31 W/m                           | 85 °C   | Purple |

## WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.nvent.com](http://www.nvent.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

### North America

Tel +1.800.545.6258  
Fax +1.800.527.5703  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Europe, Middle East, Africa

Tel +32.16.213.511  
Fax +32.16.213.604  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)

### Asia Pacific

Tel +86.21.2412.1688  
Fax +86.21.5426.3167  
[cn.thermal.info@nvent.com](mailto:cn.thermal.info@nvent.com)

### Latin America

Tel +1.713.868.4800  
Fax +1.713.868.2333  
[thermal.info@nvent.com](mailto:thermal.info@nvent.com)



Our powerful portfolio of brands:  
**nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF**  
**TRACER**