

! To be discontinued

IEC contactor, TeSys Deca, nonreversing, 150A, 100HP at 480VAC, 3 phase, 3 pole, 3 NO, 208VAC 50/60Hz coil, open style

LC1D1506LE7

! To be discontinued on: Dec 31, 2026

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| Range | TeSys | |
|--------------------------------|---|--|
| Range of Product | TeSys Deca | |
| Product or Component Type | Contactor | |
| Device short name | LC1D | |
| Contactor application | Resistive load Motor control | |
| Utilisation category | AC-3 AC-1 AC-3e AC-4 | |
| Poles description | 3P | |
| [Ue] rated operational voltage | Power circuit <= 1000 V AC 25400 Hz Power circuit <= 300 V DC | |
| [le] rated operational current | 200 A (at <140 °F (60 °C)) at <= 440 V AC AC-1 for power circuit 150 A (at <140 °F (60 °C)) at <= 440 V AC AC-3 for power circuit 150 A (at <140 °F (60 °C)) at <= 440 V AC AC-3e for power circuit | |
| [Uc] control circuit voltage | 208 V AC 50/60 Hz | |

Complementary

| Motor power kW | 40 kW at 220230 V AC 50/60 Hz (AC-3) |
|----------------------------|--|
| | 75 kW at 380400 V AC 50/60 Hz (AC-3) |
| | 80 kW at 415440 V AC 50/60 Hz (AC-3) |
| | 90 kW at 500 V AC 50/60 Hz (AC-3) |
| | 100 kW at 660690 V AC 50/60 Hz (AC-3) |
| | 75 kW at 1000 V AC 50/60 Hz (AC-3) |
| | 22 kW at 400 V AC 50/60 Hz (AC-4) |
| | 40 kW at 220230 V AC 50/60 Hz (AC-3e) |
| | 75 kW at 380400 V AC 50/60 Hz (AC-3e) |
| | 80 kW at 415440 V AC 50/60 Hz (AC-3e) |
| | 90 kW at 500 V AC 50/60 Hz (AC-3e) |
| | 100 kW at 660690 V AC 50/60 Hz (AC-3e) |
| | 75 kW at 1000 V AC 50/60 Hz (AC-3e) |
| Maximum Horse Power Rating | 40 hp at 200/208 V AC 50/60 Hz for 3 phase motors |
| | 50 hp at 230/240 V AC 50/60 Hz for 3 phase motors |
| | 100 hp at 460/480 V AC 50/60 Hz for 3 phase motors |
| | 125 hp at 575/600 V AC 50/60 Hz for 3 phase motors |
| Compatibility code | LC1D |
| Pole contact composition | 3 NO |
| Protective cover | With |
| | |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| [Ith] conventional free air thermal current | 200 A (at 140 °F (60 °C)) for power circuit | |
|---|--|--|
| Irms rated making capacity | 140 A AC for signalling circuit conforming to IEC 60947-5-1 250 A DC for signalling circuit conforming to IEC 60947-5-1 1660 A at 440 V for power circuit conforming to IEC 60947 | |
| Rated breaking capacity | 1400 A at 440 V for power circuit conforming to IEC 60947 | |
| [lcw] rated short-time withstand current | 250 A 104 °F (40 °C) - 10 min for power circuit 580 A 104 °F (40 °C) - 1 min for power circuit 1200 A 104 °F (40 °C) - 10 s for power circuit 1400 A 104 °F (40 °C) - 1 s for power circuit 1400 A - 1 s for signalling circuit 120 A - 500 ms for signalling circuit 140 A - 100 ms for signalling circuit | |
| Associated fuse rating | 10 A gG for signalling circuit conforming to IEC 60947-5-1 315 A gG at <= 690 V coordination type 1 for power circuit 250 A gG at <= 690 V coordination type 2 for power circuit | |
| Average impedance | 0.6 mOhm - Ith 200 A 50 Hz for power circuit | |
| Power dissipation per pole | 24 W AC-1 13.5 W AC-3 13.5 W AC-3e | |
| [Ui] rated insulation voltage | Power circuit 600 V CSA Power circuit 600 V UL Power circuit 1000 V IEC 60947-4-1 Signalling circuit 690 V IEC 60947-1 Signalling circuit 600 V CSA Signalling circuit 600 V UL | |
| Overvoltage category | III | |
| pollution degree | 3 | |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947 | |
| Safety reliability level | B10d = 684932 cycles contactor with nominal load EN/ISO 13849-1 B10d = 10000000 cycles contactor with mechanical load EN/ISO 13849-1 | |
| Mechanical durability | 8 Mcycles | |
| Electrical durability | 0.85 Mcycles 150 A AC-3 <= 440 V 1 Mcycles 200 A AC-1 <= 440 V 0.85 Mcycles 150 A AC-3e <= 440 V | |
| Control circuit type | AC 50/60 Hz | |
| Coil technology | Built-in bidirectional peak limiting diode suppressor | |
| Control circuit voltage limits | 0.30.5 Uc (-40158 °F (-4070 °C)):drop-out AC 50/60 Hz 0.81.15 Uc (-40131 °F (-4055 °C)):operational AC 50/60 Hz 11.15 Uc (131158 °F (5570 °C)):operational AC 50/60 Hz | |
| Inrush power in VA | 280350 VA 60 Hz cos phi 0.9 (at 68 °F (20 °C)) 280350 VA 50 Hz cos phi 0.9 (at 68 °F (20 °C)) | |
| Hold-in power consumption in VA | 218 VA 60 Hz cos phi 0.9 (at 68 °F (20 °C)) 218 VA 50 Hz cos phi 0.9 (at 68 °F (20 °C)) | |
| Heat dissipation | 34.5 W at 50/60 Hz | |
| Operating time | 2035 ms closing 4075 ms opening | |
| Maximum operating rate | 1200 cyc/h at 60 °C | |
| Connections - terminals | Control circuit: lugs-ring terminals - external diameter: 0.3 in (8 mm) Power circuit: lugs-ring terminals - external diameter: 1.0 in (25 mm) Power circuit: bars 1 - busbar cross section: 5 x 25 mm | |
| Tightening torque | Control circuit 10.6 lbf.in (1.2 N.m) lugs-ring terminals flat Ø 6 mm M3.5 Control circuit 10.6 lbf.in (1.2 N.m) lugs-ring terminals Philips No 2 M3.5 Power circuit 106.2 lbf.in (12 N.m) lugs-ring terminals hexagonal 0.5 in (13 mm) M8 Power circuit 106.2 lbf.in (12 N.m) bars hexagonal 0.5 in (13 mm) M8 Control circuit 10.6 lbf.in (1.2 N.m) lugs-ring terminals pozidriv No 2 M3.5 | |

| - | | |
|-------------------------------|--|--|
| Auxiliary contact composition | 1 NO + 1 NC | |
| Auxiliary contacts type | Mechanically linked 1 NO + 1 NC IEC 60947-5-1 Mirror contact 1 NC IEC 60947-4-1 | |
| Signalling circuit frequency | 25400 Hz | |
| Minimum switching voltage | 17 V for signalling circuit | |
| Minimum switching current | 5 mA for signalling circuit | |
| Insulation resistance | > 10 MOhm for signalling circuit | |
| Non-overlap time | 1.5 ms on de-energisation between NC and NO contact 1.5 ms on energisation between NC and NO contact | |
| Mounting Support | Rail Plate | |

Environment

| Standards | CSA C22.2 No 14 EN 60947-4-1 IEC 60947-4-1 IEC 60335-1:Clause 30.2 IEC 60335-2-40:Annex JJ UL 60335-2-40:Annex JJ UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 | |
|---|---|--|
| Product Certifications | UL CCC CSA CE UKCA Marine EAC | |
| IP degree of protection | IP20 front face IEC 60529 | |
| Protective treatment | THIEC 60068-2-30 | |
| Climatic withstand | IACS E10 exposure to damp heat | |
| Permissible ambient air temperature around the device | -40140 °F (-4060 °C) 140158 °F (6070 °C) with derating | |
| Operating altitude | 09842.52 ft (03000 m) | |
| Fire resistance | 1562 °F (850 °C) IEC 60695-2-1 | |
| Flame retardance | V1 conforming to UL 94 | |
| Mechanical robustness | Vibrations contactor open 2 Gn, 5300 Hz) Vibrations contactor closed 4 Gn, 5300 Hz) Shocks contactor closed 15 Gn for 11 ms) Shocks contactor open 6 Gn for 11 ms) | |
| Height | 6.2 in (158 mm) | |
| Width | 4.7 in (120 mm) | |
| Depth | 5.4 in (136 mm) | |
| Product Weight | 5.5 lb(US) (2.5 kg) | |

Ordering and shipping details

| Category | US10I1222359 | |
|-------------------|---------------|--|
| Discount Schedule | 0112 | |
| GTIN | 3389110726756 | |
| Returnability | No | |

Country of origin CZ

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|-----------------------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.61 in (16.8 cm) |
| Package 1 Width | 8.19 in (20.8 cm) |
| Package 1 Length | 7.28 in (18.5 cm) |
| Package 1 Weight | 4.70 lb(US) (2.13 kg) |

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

| ∇ Environmental footprint | |
|--|-------------------------------|
| Carbon footprint (kg CO2 eq, Total Life cycle) | 115 |
| Environmental Disclosure | Product Environmental Profile |

Use Better

| Materials and Substances | |
|--|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant with Exemptions |
| SCIP Number | A530c666-91dd-4119-8d61-f1c22a361ecb |
| REACh Regulation | REACh Declaration |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| PVC free | Yes |

Use Again

| ○ Repack and remanufacture | |
|----------------------------|--|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Product data sheet

LC1D1506LE7

Technical Illustration

Assembly's dimensions

