













UFC Ultra-Fine Cartridges for work in tight spaces are compatible with CV-5200, CV-500 Systems and Ultra-Fine Solder Hand piece CV-H2-UF.









Temperature	CV-Serie	Application
675 °F/357 °C	UFC-6	Temperature Sensitive
775 °F/413 °C	UFC-7	Most Standard

Please note the above temperatures are the maximum temperatures of the heater. The idle temperature is dependent on the geometry of the cartridge (up to 15°C lower.)

Ultra-Fine Chisel Cartridge			
	 0.02" 0.6mm	UFC-6CH5106S UFC-7CH5106S	(W x L) 0.6 x 5.1 mm
	 0.024" 0.6mm	UFC-6CH9006S UFC-7CH9006S	Long reach, (W x L) 0.6 x 9 mm
	 0.03" 0.8mm	UFC-6CH5108S UFC-7CH5108S	(W x L) 0.8 x 5.1 mm
	 0.031" 0.8mm	UFC-6CH9008S UFC-7CH9008S	Long reach, (W x L) 0.8 x 9 mm
	 0.05" 1.2mm	UFC-6CH5112S UFC-7CH5112S	(W x L) 1.2 x 5.1 mm

Ultra-Fine Conical Cartridge			
	 0.005" 0.13mm	UFC-6CN5101S UFC-7CN5101S	(ø x L) 0.13 x 5.1 mm
	 0.01" 0.2mm	UFC-6CN5102S UFC-7CN5102S	(ø x L) 0.2 x 5.1 mm

Ultra-Fine Conical Cartridge			
	UFC-6CN5502R UFC-7CN5502R	Bent 30°, for work under a microscope, ($\varnothing$ x L) 0.2 x 5.6 mm	
	UFC-6CN5504S UFC-7CN5504S	For work in tight spaces, ($\varnothing$ x L) 0.4 x 5.1 mm	
	UFC-6CN5504R UFC-7CN5504R	Bent 30°, for work under a microscope, ($\varnothing$ x L) 0.4 x 5.6 mm	
	UFC-6CN8004S UFC-7CN8004S	Long reach, ($\varnothing$ x L) 0.4 x 8.0 mm	

Ultra-Fine Rework Hoof-Cartridges – For Drag Soldering SOIC/QFP's			
	UFC-6HF5108S UFC-7HF5108S	Micro Hoof, (Bevel/L) 45° x 1.13 mm, ($\varnothing$ x L) 0.8 x 5.1 mm	
	UFC-6HF5112S UFC-7HF5112S	Micro Hoof, (Bevel/L) 45° x 1.71 mm, ($\varnothing$ x L) 1.21 x 5.1 mm	