



UPC Code: 078477471135 Country Of Origin: China

GSCM1-3C

Self-Test Cord Set GFCI, 15 Amp, 120 Volt, 3 Foot, Manual Reset

15 Amp, 120 VAC, Self-Test Manual Reset GFCI Cord Set, 3 Foot, 12-3 SJTW Cord, Molded on NEMA Plug 5266-CY (5-15P) and Connector 5269-CY (5-15R), Yellow

- Satisfies latest UL 943 self-test requirement
- Improve safety protect critical personnel from electrical shocks
- Withstand outdoor conditions rainproof and outdoor rated devices are OSHA compliant and feature weather-resistant SJTW cables
- Ideal for vending machines, construction sites, RV parks, marinas, and spas/hot

label

Silver-Neutral

Color: Yellow

ANSI: C-73

NEMA: WD-6

NOM: 057

Product Features

Cord Length: 3 FT.

Cord Type: 12-3 SJTW Yellow

Standards and Certifications

CSA: C22.2 No.42 & No. 144

CSA C22.2: File LR-57811

UL 498: File E-48380

UL 943: Class A (GFCI)

Warranty: 2-Year Limited

Product ID: Ratings marked on device

Terminal ID: Brass-Hot, Green-Ground,

- Automatic reset – automatically restore power to connected equipment when plugged in or after power interruption, ideal for hard to access locations

Technical Information

AC Horsepower Ratings Color : Yellow

At Rated Voltage: 3/4 Horsepower Mechanical Specifications

Electrical Specifications

Amperage : 15 A

Current Interrupting : 2 kA

Grounding : GFCI Ground Fault

Pole: 2

Short Circuit Current Rating: 2kA
Temperature Rise: Max 30C after 50
cycles OL at 150 percent rated current

Trip Level: 5mA plus or minus 1mA

Voltage: 120 VAC

Wire: 3

Environmental Specifications

Operating Temperature : -35C to +66C

Material Specifications
Blades/Contacts: Brass
Body Material: Polycarbonate

Flammability: Rated V-2 per UL94

Patents*

MX265718 US7436639 MX344697 US9276393

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 \cdot FAX: +1-800-832-9538 \cdot Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

