

TX3 Series



Features

USB Connection

USB port (USB 2.0 or above)

Microsoft Windows™

Compatible with Windows™ 7, 10, and 11

Outputs card ID via keyboard emulation

Eliminates manual data entry

Frequency: 125 kHz

Read Range: Up to 1 inch (25 mm)

Description

The TX3-P125 Enrollment Reader is meant to be paired with 125-kHz supported 26Bit Wiegand cards. These enrollment units are pre-configured with 26Bit Wiegand programming and will output the card ID as a decimal number via USB keyboard emulation, eliminating the need to enter the data manually. The enrollment reader is meant to be a simple tool for installers, their main purpose is to read a supported card (data capture) and output the value in clear text for registration. This reader serves as a convenient tool for installers, providing a simple and efficient way to capture card data and display it in clear text for easy registration.

The TX3-P125 Enrollment Reader integrates seamlessly with both TX3-Configurator and MiVISION (Mircom's cloud-based configurator). Simply place the cursor in the appropriate field, then present a credential (card or fob) to the reader—the card ID will be automatically entered.

Specifications

Technology	Proximity
Frequency	125 kHz
Dimensions	3.109" W × 4.615" H × 0.728" D (79 mm × 117 mm × 18 mm)
Weight	0.4 oz (11.34 g)
Read Range	Up to 1 inch (25 mm)
Certifications	FCC, CE
Voltage	5 volts, powered by USB
Current Draw	75 mA typical
Cable	USB A 2.0
Operating Temperature	−31° F to 150° F (−35° C to +66° C)
Operating Humidity	0% to 90% relative humidity
Color Options	Black
Warranty	Limited lifetime warranty
Technologies Supported	Pyramid + certain HID® 125-kHz Proximity protocols + certain AWID® 125-kHz Proximity protocols

Ordering Information

Model	Description
TX3-P123	125 KHz USB Proximity Enrollment Reader



Canada

25 Interchange Way Vaughan, ON L4K 5W3
Telephone: (905) 660-4655 | Fax: (905) 660-4113

U.S.A.

4575 Witmer Industrial Estates Niagara Falls, NY 14305
Toll Free: (888) 660-4655 | Fax Toll Free: (888) 660-4113

www.mircom.com

This document is provided by Mircom Technologies Ltd., MGC Systems Corp., or their affiliates, subsidiaries and brands, for convenience or marketing only and does not describe products or services technically. For technical information refer to technical manuals. We do not make representations or warranties regarding this information, including as to completeness or accuracy. We may change these contents at any time and reserve all rights in the contents, including copyrights, trademarks and other intellectual property. All other trademarks and registered trademarks are properties of their respective owners.

CATALOG NUMBER **6854**

Rev. 0