Method 1: Use the Type-c interface for screen casting

Step 1: Insert the peer into the Type-C interface of the meeting tablet and wait until the pairing succeeds.

Step 2: Insert the matching device into the type-C interface of the computer. After the indicator light is steady on, it indicates that the connection is successful. Then press the button to start screen casting.

Method 2: Use the USB interface for screen casting

Step 1: Insert the simultaneous screen into USB interface of tablet PC for conference and wait for successful pairing.



Step 2: Insert the simultaneous screen successfully paired into PC computer. If the computer is connected with the simultaneous screen for the first time, it is required to double-lick the "Client-exe or Client-app" application in the USB flash drive, the system will pop up the following interface automatically (if the simultaneous screen is not used for the first time, after waiting for 15 seconds, the system will automatically pop up the following interface):



Step 3: after the simultaneous screen is paired with PC, the following interface shall appear. Please click the middle button in the simultaneous screen to achieve display on the same screen.



Note: While the simultaneous screen is used for display on the same screen, it is required to guarantee that the hot spot of the conference tablet PC is on.

This devic

complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

Any changes or modifications not expressly approved by the party responsible for

reasonable protection against harmful interference in a residential installation. This

- To maintain compliance with FCC's RF Exposure guidelines, This equipment should be

Use only the supplied antenna