


Signal Repeater

The signal repeater extends the range of communication between devices, supporting multiple transmitters.



Features:

- **Power Supply:** AC 100V to 240V
- **Working Range:** Up to 450 feet in open air.
- **Supported Transmitters:** Up to 20 devices.

LED Indicator Definitions:

- **Fast Blinking:** Pairing mode.
- **Blink 3 Times:** Resetting the device.
- **Solid Blue:** Signal forwarding.

Pairing Operation:

1. Short press the "Pairing button" to enter pairing mode (blue LED blinks).
2. Activate transmitters within 10 seconds to complete pairing. The device exits pairing mode automatically.

Reset Operation:

- Hold the "Clearing" button for 3 seconds to reset. The blue LED will blink 3 times.

Important Notes:

- Do not use two repeaters within the same range.
- Do not pair the same transmitter with two repeaters simultaneously.

FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation.
Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum 20cm distance between the radiator and your body: Use only the supplied antenna.