



Prelude XS MagSafe

Power Adapter

User Guide


MagSafe Wireless
Charging Area



USB-C Port




Fold-Out AC Plug



Welcome to Prelude XS

Unfold the AC Plug and plug it directly into the AC socket. Prelude XS is ready to work.



Charging Your Device with Prelude XS


After the Prelude XS is plugged into the AC socket, you can use it to charge your wireless or non-wireless devices.

Wireless Charging

1.

Gently attach Prelude X/XR (not included) or iPhone MagSafe wireless charging area onto the powered Prelude XS.

* MagSafe compatible wireless charging for iPhone MagSafe series.



3.


Wireless charging in progress!



Wired Charging

1.

Connect the powered Prelude XS to your device with a USB-C cable (not included).



Safety & Handling

1. Keep wireless charging unit dry and away from liquids. Do not use on wet surfaces.
2. Do not attempt to disassemble or modify charger.
3. Always disconnect power supply before cleaning charger.
4. Keep away from high heat. Use in the temperature range between -5 and 40 degrees Celsius (23 and 104 degrees Fahrenheit).
5. Prelude XS is designed for faster and more efficient charging with iPhone MagSafe series and Apple MagSafe accessories.
6. Don't place credit cards, security badges, passports or key fobs between your iPhone and Prelude XS. This may damage magnetic strips or RFID chips in those items.
7. If you have a case that holds any of these sensitive items, remove them before charging or make sure that they aren't between the back of your device and Prelude XS.
8. Your iPhone or Prelude XS might get slightly warmer while your iPhone charges. To extend the lifespan of your battery, if the battery gets too warm, software might limit charging for only up to 80 percent.



9. If you keep your iPhone in a leather case while charging with your Prelude XS, the case might show imprints from compression of the leather. This is normal, but if you're concerned about this, we suggest using a non-leather case.

Specifications

Input	AC 110-240V 0.8A 60Hz
Wireless Output	5W / 7.5W / 10W
USB-C Output	5V = 3A, 9V = 3A

Package Contents

Prelude XS MagSafe Power Adapter	X1
User Manual	X1



THANK YOU FOR YOUR ORDER!

Learn more about BEZALEL and our full line of wireless charging products at bezalel.co.

Contact us at support@bezalel.co.