



Class 1

Sound Calibrator Nor1256

Class 1

Sound calibrator Nor1256

Nor1256 is a small battery-operated precision class 1 microphone calibrator conforming to IEC 60942 and ANSI S1.40. The combination of two different levels and two different frequencies allow both level linearity and frequency linearity to be verified. In addition, the sound calibrator measures the environmental conditions: air pressure, temperature and humidity. The all-digital design with a quartz controlled signal generator ensuring a frequency stability not yet seen on any calibrator on the market today. The reference microphone and control circuit together maintain a constant sound pressure level inside the calibration coupler and automatically adjust for changes in load volume, temperature, humidity, and barometric pressure. The selected level and frequency is clearly indicated on the OLED display.

Each calibrator is supplied with an individual accredited calibration certificate.



Key Features

Conforms to IEC 60942 : 2017 Class 1, and ANSI/ASA S1.40-2006 (R2024) Class 1.

Ultra-stable silicone reference microphone.

All-digital quartz-controlled signal generator.

Fully compensated for static pressure, humidity and temperature.

Sound pressure independent of microphone equivalent volume.

Robust, compact and battery operated.

114 and 94 dB @ 1000 and 250 Hz

Built-in display.

Supplied with accredited calibration certificate.

The Nor1256 offers two levels and frequencies in combination with measurement of ambient temperature, relative humidity and static pressure.

The generated sound pressure levels are 94 dB and 114 dB (re. 20 μ Pa) at 250 Hz and 1000 Hz. The twin frequencies and levels enables linearity and frequency response check of the microphone and allows a wide range of calibration applications to be covered by one unit.

The calibration level, frequency and environmental parameters are displayed on a high contrast OLED display. The calibrator can be used directly on 1" microphones and smaller microphone sizes via adapters. At power on the calibrator generate 114 dB@1000 Hz. A push on the dB button toggles between 94 and 114 dB. Likewise a push on the Hz button toggles between 1000 and 250 Hz. The °C/°F button displays the ambient pressure, temperature and humidity.

Specifications

Microphone size	1/1" and below. Adapter for 1/2" microphone Nor4583 (included)
Calibrator frequency (@ Reference conditions)	251.19 $\pm$ 0.30 Hz and 1000 $\pm$ 1.00 Hz
Generated Sound Pressure Level relative to 20μPa (@ Reference conditions)	114.0 $\pm$ 0.2 dB and 94.0 $\pm$ 0.2 dB
Distortion	Max 2.0%
Stabilizing time	20 seconds
Sensitivity to environmental conditions	As specified for IEC 60942 class 1 / ANSI S1.40
Environmental range for specified operation:	
Temperature:	-10°C to +50°C / 14°F to 122°F
Relative humidity:	25 % to 90 %
Air pressure:	65 kPa to 108 kPa
Additional specifications for the built in ambient measurement sensors:	
Temperature range:	-10°C to +50°C or 14°F to 122°F
Resolution / Accuracy:	0.1°C / $\pm$ 2°C or 0.1°F / $\pm$ 2°F
Atmospheric pressure:	65 kPa to 108 kPa; Resolution 0.1kPa; Accuracy $\pm$ 0.4 kPa, (for temperature above 0°C)
Relative humidity:	0% to 100%; Resolution 1%; Accuracy $\pm$ 4%, (for temperature above 0°C and humidity in the range 25% to 85%)
Power off	By power switch or when microphone is removed (may be deactivated)
Battery type	2 x LR03 alkaline batteries (AAA-size)
Battery life	< 10 hours
Battery low	Automatically switching off if battery voltage too low
Display type and resolution	Mono-colour OLED graphical display - 128x64 (WxH)
Weight / Size (LxWxH)	125 g / 0.28 lb / 97 x 51.5 x 41 mm / 3.8 x 2.0 x 1.6"
Accessories included	May vary if supplied as part of a Sound level meter kit: 1/2" microphone adapter Nor4583, Accredited calibration, 2 x AAA batteries, instruction manual and leather pouch Nor1345
Accessories available	1/4" microphone adapter Nor4589



 +47 32 85 89 00

 info@norsonic.com

 Gunnersbråtan 2, N-3409 Tranby, Norway

 norsonic.com