


Power Protection Solutions

for Data Centers and Facilities, Networks and Servers, Industrial, PCs and Workstations, and Mobile Computing Applications







"In a world that demands zero downtime, system availability is essential. As technologies and environments change via server consolidation, migration and centralization, businesses must be ready to adapt, quickly and constantly. The foundation of highly available networks, network-critical physical infrastructure (NCPI), is crucial to system availability and a company's agility. From surge protection to backup power, APC's end-to-end offering has a product for each price and performance criteria."

"From the challenge of operating an on-demand data center, to the implementation of high density applications or a VoIP network, to increasing mobile computing productivity, APC has the technology, systems and support to empower customers to meet their objectives."

Rodger B. Dowdell Jr.,
President and Chief Executive Officer

Frost and Sullivan Names APC 2005 Data Center Solutions Company of the Year

APC has received the 2005 Data Center Solutions Company of the Year Award from growth consulting firm Frost & Sullivan. This honor is based on a number of criteria, including market share growth, new market penetration, evidence of success derived from innovative strategies, and technological innovation and leadership.

The award honors APC's progress in the data center and large systems area, which the company estimates to be a \$7 billion market for network-critical physical infrastructure (NCPI). Demand for APC's InfraStruXure™

architecture for data centers, which integrates power, cooling, management and services within a rack-optimized design, nearly doubled in 2004 from 2003. APC was not only able to expand its customer base, but also showed foresight by recognizing the conditions that would create a market for a new class of product: an on-demand solution that addresses the challenges related to the data center life cycle including planning, installation, operations and end of life.

"For many years, APC's core competency has been in the low power range mar-



ket," said Farah Saeed, program manager for Backup Power Solutions with Frost & Sullivan. "But they were the first to recognize that the growth of network-critical physical infrastructure in data centers was creating an unmet need. APC responded with InfraStruXure, an innovative solution that fulfills the NCPI requirements of data centers while providing the flexibility needed to respond to business changes. InfraStruXure's standardized, modular component approach helps speed deployment, improve adaptability, and increase system availability, while reducing total cost of ownership."

Power is vital to the Information Age. Without electricity, the machines that create, transmit, or store our data, help us communicate, entertain us, or assist us in a multitude of ways cease to operate. In less critical circumstances, this is merely an inconvenience. When a company depends on its electronics to do business, the effects of power-related downtime are much more costly.

As the thought leader in power protection, APC offers a multitude of availability solutions using a fresh, innovative approach to meeting the real-world needs of customers. Recognizing that downtime is not an option, and that the status quo was meant to be challenged, APC strives to find new ways in which to ensure availability wherever data is created, transmitted, or stored.

TABLE OF CONTENTS

Data Center and Facility Power Protection6	
Server, Voice, and Data Network Power Protection 10	
ndustrial Power Protection	
Power Distribution and Customer Premise Power 20	
PC and Workstation Power Protection22	
Surge, Data line, and Mobile Power Protection 24	
nfraStruXure Systems for Applications	



System-level Solutions for Data Centers On Demand






Modular Systems

are complete, prepackaged systems that users can quickly and easily select for specific IT environments without spending the time needed for

customization. They are an ideal solution to rapidly respond to market trends such as increased density and converged voice/data applications.



Mobile Systems, such as InfraStruXure™ Express are true on-demand mobile data centers, which

can be provided

capable of supporting up to 250 servers. These solutions are designed for businesses working on transitional IT projects or developing robust business continuity and disaster recovery programs.



For users that prefer to customize their NCPI. Conventional Systems offer a complete range of individual components and services required to build a data center

or server room. These systems have standard lead times and installation requirements that are typical in unique or large IT environments.

APC's InfraStruXure™ is on-demand architecture for network-critical physical infrastructure (NCPI). The InfraStruXure design, which integrates power, cooling, rack, management and services, allows the selection of standardized components to create a solution through modular and mobile configurations. This standardization enables an easily scalable architecture designed to meet changing needs and future expansion. This award-winning, patent-pending approach provides increased availability, improved adaptability and speed of deployment as well as lower total cost of ownership for IT environments - from wiring closets to server rooms to data centers.

With integrated management becoming a critical component in the NCPI, APC offers comprehensive management solutions including InfraStruXure Manager. A browser accessible, user-friendly tool, InfraStruXure Manager provides monitoring of power, cooling, and environmental management at the rack or room level. APC also provides professional services that optimize the NCPI over the complete data center life cycle, including planning, installation, operation and end-of-life services.

For more information on InfraStruXure[™], see page 26



APC Power Protection Solutions

APC Power Solutions cover a wide range of requirements. The more mission-critical the application, the higher the necessity for as little downtime as possible, mandating continued operation through outages of any length. Some organizations might not require such

high availability, but require automatic, safe shutdown of important software and operating systems, keeping important data secure. Any power solution should, at the very least, prevent physical damage to hardware from transients (surges, spikes, sags, etc.).

IT Environment	Range	Best Price ("Good")	Best Value ("Better")	Best Performance ("Best")
Data Center/Facilities				·
Small Data Center (from 5 -20 Racks)	10-40kW	Smart-UPS® VT*	Smart-UPS® VT* + Battery Packs	Symmetra® PX
Medium Data Center (from 20 - 100 Racks)	40-80kW	Silcon®	Silcon® + Battery Packs	Symmetra® PX
Medium Data Center (from 20 - 100 Racks)	80-200kW	Silcon®	Silcon® + Battery Packs	Symmetra® MW
Large Data Center (>100 Racks)	200kW+	Silcon®	Silcon® + Battery Packs	Symmetra® MW
Server, Voice/Data Network				
Server Rooms (from 1 - 5 Racks)	3-9.9kW	Smart-UPS® RT	Smart-UPS® RT + Battery Packs	Symmetra® LX
Wiring Closet (from 1 - 3 Racks)	500-3,000W	Smart-UPS®	Smart-UPS® XL	Symmetra®
Server/Networking (<1 - 3 Servers)	1-865W	Smart-UPS® SC	Smart-UPS®	Smart-UPS® XL
Industrial		l .		
General Industrial Market	10-100kVA	AIS 3000	AIS 5000	AIS 5000 + Battery Packs
PC/Workstation				
UPS	350-1500VA	Back-UPS® ES	Back-UPS® CS	Back-UPS® RS
Surge Protection	1-11 outlets	SurgeArrest® Essential	SurgeArrest® Home/Office	SurgeArrest® Performance

^{*} Up to 32kW



One of APC's core competencies is UPS protection for the wide-ranging IT applications of today's businesses. Whether you need power protection for a few servers or for a large data center installation, APC has the optimal UPS for your specific IT environment. Offering scalable, redundant power protection for both single- and three-phase applications, APC's modular UPS solutions provide the foundation of building and scaling near-continuous power systems with a flexible range of power capacities.

A STATE OF THE STA			Company of the Compan	A Company of the Comp	
IT Environment	Range	Best Price ("Good") Best Value `("Better")		Best Performance ("Best")	
Data Center/Facilities					
Small Data Center (from 5 -20 Racks)	10-40kW	Smart-UPS® VT*	Smart-UPS® VT+ Battery Packs*	Symmetra® PX	
Medium Data Center (from 20 - 100 Racks)	40-80kW	Silcon®	Silcon® + Battery Packs	Symmetra® PX	
Medium Data Center (from 20 - 100 Racks)	80-200kW	Silcon®	Silcon® + Battery Packs	Symmetra® MW	
Large Data Center (>100 Racks)	200kW+	Silcon®	Silcon® + Battery Packs	Symmetra® MW	

^{*} Up to 32kW

Smart-UPS® VT

Performance power protection with scalable runtime for small data centers

Range: 10 to 40kVA in 400V, 10 to 30kVA in 208V and 20 to 30kVA in 480V

Smart-UPS*VT offers centralized three-phase power protection with the reliability of the award winning Smart-UPS family. Ideal for small data centers, large retail stores, regional offices, and dense power requirements, the Smart-UPS VT includes dual-mains input, automatic and maintenance bypasses, and scalable runtime with hot-swappable batteries for increased availability. Low cost of ownership is achieved through best-in-class efficiency and a reduction in rating of electrical infrastructure (wires, transformers, and generators) due to Smart-UPS VT's Soft Start feature.

APC's Network Management Card with temperature monitoring provides remote monitoring and management through a simple Web/SNMP interface and provides integration with InfraStruXure™ Manager. Serviceability is greatly enhanced by user-replaceable batteries, manageable extended run frames and included startup and standard onsite warranty services. All of these features make Smart-UPS VT the easiest UPS in its class to deploy, manage and maintain.

Input Power Factor Correction

Minimizes installation costs by enabling the use of smaller generators and cabling.

Hot-swappable Batteries

Ensures clean, uninterrupted power to protected equipment while batteries are being replaced.

Scalable Runtime

Allows additional run time to be quickly added as needed.

Dual Mains Input

Increases availability by allowing the UPS to be connected to two separate power sources.

Manual Maintenance Bypass

Reduces installation costs by eliminating the need for an external mechanical bypass.

Network Manageable

Provides remote management of the UPS over the network.



Symmetra® PX

High-performance, redundant power protection with scalable power and runtime for data centers

Range: 10-80kW N+1

Symmetra® PX, three-phase input/three-phase output (3:3), is a single unit, composed of modular components. This modular architecture provides the foundation of building and scaling near-continuous availability power systems with a flexible range of power capacity. The Symmetra PX packages the high availability requirements of easy power and runtime scalability into a very small footprint.

Configurable for N+1 Internal Redundancy

Provides high availability through redundancy by allowing configuration with one more Power Module than is necessary to support the connected load.

Power Modules Connected in Parallel

Enhances availability by allowing immediate, seamless recovery from isolated module failures.

Battery Modules Connected in Parallel

Delivers higher availability through redundant batteries.

Scalable Power Capacity

Reduces UPS over-sizing costs today by allowing quick upgrades later.

Modular Design

Provides fast serviceability and reduced maintenance requirements via self-diagnosing, field-replaceable modules.

User-replaceable Power Modules

Enables simple upgrades and replacements of the Power Modules.

User-replaceable Batteries

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR).

Network Manageable

Provides remote management of the UPS over the network.


Fully-rated Power kVA Equals kW

Reduces cost by eliminating the need for an oversized UPS for Power Factor Corrected (PFC) loads.

Generator Compatible

Ensures clean, uninterrupted power to protected equipment when generator power is used.





DATA CENTERS AND FACILITIES

Silcon®

Performance power protection with scalable runtime for data centers and facilities

Range: 40 to 80kW in 208V, 10 to 500kW in 480V and 60 to 480 kW in 400V

The APC Silcon® Series has the load capacity to serve a broad range of electrical equipment, from mainframe computers to large corporation-wide installations, production lines, electronic control systems and telecommunication equipment. Up to nine Silcon units can be paralleled to serve special demands for power upgrading or redundancy.

Input Power Factor Correction

Eliminates the need for an external phase-compensation unit and minimizes installation costs by enabling the use of smaller generators and cabling.

Fully-rated Power kVA Equals kW

Reduces cost by eliminating the need for an oversized UPS for Power Factor Corrected (PFC) loads.

Network Manageable

Provides remote management of the UPS over the network.

Generator Compatible

Ensures clean, uninterrupted power to protected

equipment when generator power is used.

Manageable External Batteries

Reduces preventative maintenance service needs by monitoring the health and status of the external batteries and their expected runtime.

Parallel-capacity Capable

Increases total power capacity by using multiple UPSs simultaneously.

Parallel-redundant Capable

Power the connected equipment with multiple UPSs to increase system redundancy.



Symmetra® MW

High performance, redundant power protection with scalable power and runtime for data centers and facilities

Range: 400kW to 1.6MW

Symmetra[®] MW redefines high-power UPS technology as a modular, fault-tolerant UPS in the 400-1600 kilowatt range. Ideal for large data centers, complete buildings, healthcare and other critical facility protection requirements, the Symmetra MW can be scaled for rigorous and changing electrical demands. Symmetra MW provides increased availability through internal N+1 configurability, predictive failure notification and multi-module paralleling features. Setting a new standard for low cost of ownership Symmetra MW delivers best-in-class efficiency and a reduction in rating of electrical infrastructure- wires, transformers and generators. Slide-in/out power modules, manageable external batteries and self-diagnosing features greatly reduce mean time to repair. Combined with a wide range of line-up and match options Symmetra MW provides a customizable system in a standardized design for any large on-demand network-critical physical infrastructure.

Modular Design

Provides fast serviceability and reduced maintenance requirements via self-diagnosing, field-replaceable modules.

Scalable Power Capacity

Reduces UPS over-sizing costs today by allowing quick upgrades later.

Fully-rated Power kVA Equals kW

Reduces cost by eliminating the need for an oversized UPS for Power Factor Corrected (PFC) loads.

Input Power Factor Correction

Eliminates the need for an external phase-compensation unit and minimizes installation costs by enabling the use of smaller generators and cabling.

Configurable for N+1 Internal Redundancy

Provides high availability through redundancy by allowing configuration with one more Power Module than is necessary to support the connected load.

Generator Compatible

Ensures clean, uninterrupted power to protected equipment when generator power is used.

Power Modules Connected in Parallel

Enhances availability by allowing immediate, seamless recovery from isolated module failures.

Battery Modules Connected in Parallel

Delivers higher availability through redundant batteries.

LCD Display

Provides schematic overview of critical data for guided operation and troubleshooting on color LCD touchscreen.



InfraStruXure[™] Power Distribution Units

The InfraStruXure™ PDU is configured to order and pre-engineered for Information Technology (IT) equipment in small to large data centers

Range: 3-Phase 40, 60, 80, and 150 kW

Enable increased availability of your data center by real time branch current monitoring and threshold setting with local and advanced remote notification. The Configure-to-Order (CTO) process allows for the factory installation and testing of breakers, branch circuit monitoring boards, load-test ports, and cut-to-size whips. The InfraStruXure[™] PDU can be deployed in non-raised floor environments for reduced installation costs and increase agility. Build an InfraStruXure PDU to your exact specifications to increase speed of deployment, reliability, and lower your total cost of ownership.

Alarm Thresholds

Current Transformers on each circuit that can provide amp ratings on each circuit position to prevent circuit breaker overloads.

Local and Web-based Monitoring

Status available to customers both in the data center and remotely.

Remote Management Capabilities

Full-featured network management interfaces that provide standards-based management via Web, SNMP, and Telnet. Allows users to access, configure, and manage units from remote locations to save valuable time. Associated with this feature is the ability to quickly and easily upgrade the firmware via network download to installed units for future product enhancements.

Wide Range of Applications

Configure-to-order process allows APC to configure, install, and test complete system before shipping.

Circuit Breaker Panel

Provides breaker positions for distribution to racks and power zones.

System Mobility

PDU equipment can easily be relocated to accommodate a changing data center environment.



InfraStruXure[™] Systems for High Density

Deploying new technology such as blade servers and server consolidation can easily create environments with greater than 3kW per rack power density. When deploying these high density applications, IT or Facilities Managers may find they have hot spots and cooling problems, unknown data center capabilities, the possibility for requiring oversized NCPI, special environments to deploy properly or the need to slow technology adoption based on high density deployment challenges. APC InfraStruXure™ Systems are designed to address these NCPI challenges with integrated systems designed specifically for high density.



For more information on InfraStruXure™ Systems for High Density, see page 26.

NETWORK AND SERVER



InfraStruXure™ Systems for First Time Data Center and Server Room Users

The challenges of improving, and even maintaining, IT productivity, have put pressures on today's IT and Facility Managers. As some are tasked with developing data centers for the first time, they may find they have limited IT resources, budget, experience or skill set for designing, operating or building data centers. They may face challenges in planning for unpredictable growth or limited space for a data center. APC InfraStruXure™ Systems are ideal for these "first-time" data center and server rooms users.

For more information on InfraStruXure™ Systems for First Time Data Center and Server Room Users, see page 26.



Smart-UPS® SC

Power protection for entry-level servers, voice and data networks

Range: 420-620VA Tower, 250-1500VA Rack/Tower Convertible 1U-2U





APC Smart-UPS® SC is ideal for small and medium businesses looking to protect entry-level servers and networking equipment from power disturbances and outages. The Smart-UPS® SC features network grade runtime, hot swap batteries, and built-in data line protection for worry free uninterruptible power protection for increased availability. The included PowerChute® Business Edition software, which has an installed base in the millions, gives entry-level network and server users a proven UPS management solution.

PowerChute® Business Edition also manages other Smart-UPS® models, allowing easy upgrades as applications change, without having to replace software or retrain administrators. Most Smart-UPS® SC models can be installed in either a tower or rack configuration, allowing standardization across multiple applications. Built on the same standards as the award-winning Smart-UPS®, with over 10 million installed, Smart-UPS® SC provides the basic features and manageability needed to protect entry-level applications.

Network Manageable

Monitor and control the UPS remotely via included PowerChute software.

Boost and Trim Automatic Voltage Regulation (AVR)

Gives higher application availability by correcting low and high voltage conditions without using the battery.

Dataline Surge Protection

Provides protection of connected equipment from power surges on the data lines.

User-replaceable Batteries

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR).

Audible Alarms

Provides notification of changing utility power and UPS conditions.

LED Status Indicators

Enables quick understanding and response to visual indicators showing UPS status.

Smart-UPS®

Performance power protection for servers, and voice and data networks

Range: 750-5000VA Tower, 750-5000VA Rack Mount 1U-5U





APC Smart-UPS® protects critical data by supplying reliable, network-grade power in either traditional tower or rack-optimized form factors. Award-winning Smart-UPS® is the perfect UPS for protecting business critical servers, voice and data networks, point of sale, retail/bank back office and ATM's. High real power output (watts), generous runtime, sine wave output, 16-segment LED visual display, and intelligent battery management make Smart-UPS® the leading server class UPS. Included PowerChute® management software provides IT administrators the comfort

Additional manageability is available through the SmartSlot, an internal accessory slot that allows installation of optional accessories to enhance the performance of your UPS. Designed and manufactured by APC and fully backed with free 24x7 technical support, Smart-UPS® remains the industry standard for all network UPSs. With over 10 million units installed worldwide and over 15 years of proven performance, Smart-UPS® is a UPS businesses trust for their critical applications.

of safe system shutdown and advanced UPS management.

Network Manageable

Monitor and control the UPS remotely via included PowerChute software or APC's Network Management Card (included in all models above 3kVA).

Intelligent Battery Management

Maximizes battery performance, life, and reliability through intelligent, precision charging.

Boost and Trim Automatic Voltage Regulation (AVR)

Gives higher application availability by correcting low and high voltage conditions without using the battery.

User-replaceable Batteries

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR).

LED Status Indicators

Enables quick understanding and response to visual indicators showing UPS status.

Audible Alarms

Provides notification of changing utility power and UPS conditions.

Smart-UPS® XL

Performance power protection with scalable runtime for servers, and voice and data networks

Range: 750-2200VA Tower, 1400-3000VA Rack Mount 2U-5U



APC Smart-UPS® XL protects your data by supplying reliable, network-grade power and scalable runtime in tower or rackmount form factors. Customers can configure up to 10 matching battery packs for runtimes exceeding 24 hours, if needed. Typical applications requiring longer runtime include critical application servers and storage, IP and PBX based voice networks, and enterprise network switches and hubs. Included PowerChute® management software provides IT administra-

Network Manageable

Monitor and control the UPS remotely via included PowerChute® software or APC's Network Management Card (included in all models above 3kVA).

Scalable Runtime

Allows additional run time to be quickly added as needed.

Intelligent Battery Management

Maximizes battery performance, life, and reliability through intelligent, precision charging.

Boost and Trim Automatic Voltage Regulation (AVR)

Gives higher application availability by correcting low and high voltage conditions without using the battery.

User-replaceable Batteries

tors the comfort of safe system shutdown and advanced UPS

management. Additional manageability is available through the

SmartSlot, an internal accessory slot that allows installation of

optional accessories to enhance performance. Engineered with the same standards as the award-winning Smart-UPS[®], with

over 10 million installed, the Smart-UPS® XL adds the advan-

tage of unsurpassed runtime capability for those business

applications that demand continual uptime.

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR).

LED Status Indicators

Enables quick understanding and response to visual indicators showing UPS status.

Audible Alarms

Provides notification of changing utility power and UPS conditions.

Smart-UPS® RT

Performance power protection with scalable runtime for space-constrained server rooms, and voice and data networks

Range: 1-10kVA Rack/Tower Convertible 2U-6U



APC Smart-UPS® RT is a family of high-density, performance UPSs for voice and data networks, medical labs, and light industrial applications. Capable of supporting 10kVA in a 6U rack/tower convertible form, users can support power hungry blade servers or heavily loaded equipment racks. This flexible form factor allows standardization across multiple applications. High power internal chargers

Network Manageable

Monitor and control the UPS and access environmental information remotely via included PowerChute® software or APC's Network Management Card with temperature monitoring (included in all models above 3kVA).

Automatic Internal Bypass

Supplies utility power to the connected loads in the event of a UPS overload condition or fault.

Scalable Runtime

Allows additional run time to be quickly added as needed.

Intelligent Battery Management

Maximizes battery performance, life, and reliability through intelligent, precision charging.

Frequency and Voltage Regulation

Gives higher application availability by correcting poor frequency and voltage conditions without using the battery.

ply with aggressive runtime demands of business-critical systems. Customers with harsh power environments looking for extremely tight voltage and frequency regulation, internal bypass, and input power factor correction typical of double conversion online topology will get them in the Smart-UPS® RT.


allow virtually unlimited additional matching battery packs to com-


User-replaceable Batteries

Increases availability by allowing a trained user to perform upgrades and replacements of the batteries reducing Mean Time to Repair (MTTR).

LED Status Indicators

Enables quick understanding and response to visual indicators showing UPS status.





Symmetra®

High performance, redundant power protection with scalable power and runtime for servers, and voice and data networks

Range: 2-6kVA N+1 Redundant Rack Mount 8U-10U

Engineered to deliver the highest level of business continuity possible, Symmetra® uses a modular, redundant architecture that can scale power and runtime as demand increases or when higher levels of availability are required. Symmetra's integrated manageability, and hot-swappable, user replaceable power, battery, and intelligence modules enable easy, fast maintenance and serviceability. Its 2-6kVA N+1 redundant rack-optimized form factor makes Symmetra ideal for protecting critical server racks and network rooms. Typical applications include Web and other key application servers, IP based and traditional PBX voice solutions, and enterprise type network switches.



Monitor and control the UPS and access environmental information remotely via the embedded APC Network Management Card with temperature monitoring.

Modular Design

Provides fast serviceability and reduced maintenance requirements via self-diagnosing, hot-swappable, and field-replaceable modules.

Configurable for N+1 Internal Redundancy

Provides high availability through redundancy by allowing configuration with one more Power Module than is necessary to support the connected load.

Scalable Power Capacity

Reduces UPS over-sizing costs today by allowing quick upgrades later.

Manageable External Batteries

Reduces preventative maintenance service needs by monitoring the health and status of the external batteries and their expected runtime.



LCD Display


Manage the UPS locally through a text-based display that allows quick diagnosis via stored alarm conditions and events.

Automatic Internal Bypass

Supplies utility power to the connected loads in the event of a UPS overload condition or fault.

Frequency and Voltage Regulation

Gives higher application availability by correcting poor frequency and voltage conditions without using the battery.



Symmetra® LX

High performance, redundant power protection with scalable power and runtime for space-constrained server rooms and voice and data networks

Range: 4-16 kVA N+1 Redundant Rack/Tower Convertible 13U-19U, 4-16kVA N+1 Redundant Extended Run Tower



Engineered to deliver the highest level of business continuity possible, the Symmetra® LX uses a modular, redundant architecture that can scale power and runtime as demand increases or when higher levels of availability are required. With built-in network manageability, and rack-optimized and tower models available from 4-16 kVA N+1 redundant, the online Symmetra LX is the choice to protect high-performance IT and Telecom equipment in business-critical server and network rooms. A flexible rack/stack design offers unmatched runtime and power capacity in space constrained

environments. Symmetra LX allows incredibly fast upgrades and maintenance with virtually all of its parts contained in field-swap-pable components. These include hot-swappable, user-replaceable power, battery, and intelligence modules, management cards, LCD display, fans, and external battery frames. Additionally the wiring tray, frame electronics, receptacles, and casters can be swapped in minutes if necessary. Symmetra LX achieves industry-leading footprint or U-space needed in an equipment rack, increased speed and ease of deployment, and reduced repair time.

Network Manageable

Monitor and control the UPS and access environmental information remotely via included PowerChute[®] software or APC's Network Management Card with temporature monitoring (included in all models above 3kVA).

dular Design

ides fast serviceability and reduced maintenance irements via self-diagnosing, hot-swappable, and -replaceable modules.

figurable for N+1 Internal Redundancy

ides high availability through redundancy by

Scalable Power Capacity

Reduces UPS over-sizing costs today by allowing quick upgrades later.

Manageable External Batteries

Reduces preventative maintenance service needs by monitoring the health and status of the external batteries and their expected runtime.

Shippable with Modules Installed

Enables pre-installation UPS staging and testing and faster installation.

LCD Display


Manage the UPS locally through a text-based display that allows quick diagnosis via stored alarm conditions and events.

Automatic Internal Bypass

Supplies utility power to the connected loads in the event of a UPS overload condition or fault.

Frequency and Voltage Regulation

Gives higher application availability by correcting poor frequency and voltage conditions without using the battery.



AIS® 3000

Performance power protection with scalable runtime for industrial applications, automation control, and critical manufacturing processes

Range: 10 to 40kVA (30kVA in 208V)

The AIS® 3000 offers a new way for plant and facility managers to achieve reliable and cost-effective protection for applications within industrial and manufacturing facilities. Legacy industrial solutions require on-site customization to fit these harsh environments. A modular design with factory installed hot-swappable batteries and electronics reduce configuration time and make the AIS 3000 easy to deploy and maintain. Standard reliability features include NEMA 12/IP51 protection, a standard 2 millimeter thick steel plate enclosure, and user-replaceable air filters. The AIS 3000 ships with dual mains input and a built-in maintenance bypass switch increasing system availability.

Dual Mains Input

Increases availability by allowing the UPS to be connected to two separate power sources.

Input Power Factor Correction

Minimizes installation costs by enabling the use of smaller generators and cabling.

Manual Maintenance Bypass

Reduces installation costs by eliminating the need for an external mechanical bypass.

User-replaceable Air Filters


Enables quick and simple replacement of air filters.

Network-manageable

Provides remote management of the UPS over the network

Scalable Runtime

Allows additional runtime to be quickly added as needed.



AIS® 5000

Reliable industrial power protection for three-phase industrial shop floor applications, automation control rooms and critical processes

Range: 10 - 100kVA

A reliable and cost efficient UPS designed for industrial shop floors, automation control rooms and other critical processes that require high availability, first class quality and performance in an industrial environment, the AIS® 5000 is simple to install and deploy for any three-phase (3:3) application. The built-in maintenance bypass switch and modular design approach assure low MeanTime to Repair and reduced service costs compared to legacy UPSs. The matching battery panels provide a wide variety of runtime needs.

Heavy Duty Design

The ruggedized industrial design of the UPS ensures that it can be installed even in harsh environments.

Parallel-redundant Capable

Increases the overall system availability, 2 units running in parallel with active load sharing.

Galvanic Isolation

Build-in isolation transformers for the rectifier and the inverter ensures galvanic isolation between input / output and the DC bus.


Built-in Manual Bypass

The build-in manual bypass switch eases maintenance and servicing of the unit and safeguards the customers load while performing important annual tests of the unit.

User-replaceable Air Filters

Enables quick and simple replacement of air filters.





GUTOR Industrial UPS and DC Systems

GUTOR provides custom-built industrial UPS systems, rectifiers and battery chargers which are engineered, manufactured and serviced (AC & DC) solutions used for industrial applications.

Today's modern business and industrial world is rapidly progressing, yet at the same time it is growing more vulnerable and dependent on the availability of quality power supply. **GUTOR** is specialized in the field of power protection. We aim to provide reliable products of a technologically high standard and top quality customer service. GUTOR primarily designs and develops its own high quality power protection technology. Our UPS systems are applied to meet requirements for applications in the Oil & Gas, Petrochemical, Chemical, and Power Generation industries. All products are of top quality, designed and assembled according to recognized worldwide technical and safety standards.

For more information, go to www.gutor.com

Basic Rack PDU

Power distribution for rack-mount equipment

Range: 1.4 kW - 12.5 kW, 15A - 50A, Horizontal or Vertical Mount

Rack-mountable

Includes horizontal, vertical, and toolless-mount varieties. Puts power where it is needed most - in the racks near the equipment.

Single Input Power Source

Supply power from one branch whip to multiple pieces of equipment, conveniently powering rackmount equipment. Saves time and money during installation by using one branch whip and standard connections.

Wide Range of Input and Output Connections

Includes a variety of input and output connections to distribute 120V, 208V, or 230V power to multiple outlets. Allow users to adapt to varying power requirements. Units can bring up to 14.4kW using a single branch whip.

Low Cost Power Distribution

Provides a number of outlets to bring power to rack equipment at an affordable price.

Metered Rack PDU

Power distribution units that monitor the aggregate power consumption of connected equipment

Range: 1.4 kW - 14.4 kW, 15A - 50A, Horizontal or Vertical Mount

Local and Web-based Monitoring

Status available to customers both in the data center and remotely.

Local Current Monitoring Display

Helps installers avoid overloaded circuits by providing a visible warning when the current draw is close to the maximum amperage draw of the strip.

Load Indicator LED

Indicates overload and warning conditions based on the user-defined alarm thresholds. Alerts users of potential overloaded circuits.

Alarm Thresholds

Define alarm thresholds in order to avoid overloaded circuits. Network and visual alarms inform the user of possible problems.

Wide Range of Input and Output Connections

Includes a variety of input and output connections to distribute 120V, 208V, or 230V power to multiple outlets. Allows users to adapt to varying power requirements. APC offers units that bring up to 14.4kW using a single branch whip.

Switched Rack PDU

Power distribution that remotely controls power to individual outlets and monitors the aggregate power consumption

Range: 1.4 kW - 12.5 kW, 15A - 50A, Horizontal or Vertical Mount

Remote Management Capabilities

Full-featured network management interfaces that provide standards-based management via Web, SNMP, and Telnet. Access, configure, and manage units from remote locations. Upgrade the firmware via network download to installed units for future product enhancements.

Remote Individual Outlet Control

Users can turn outlets off that are not in use (prevent overloads) or recycle power to locked-up equipment (minimize costly downtime and avoid travel time to equipment).

Power Delays

Users can configure the sequence in which power is turned on or off for each outlet to avoid in-rushes at

start-up. Sequencing also allows users to predetermine which piece of equipment is turned on first so other equipment dependant on that unit will function properly.

Alarm Thresholds

Define alarm thresholds in order to avoid overloaded circuits. Network and visual alarms inform the user of possible problems.

Local Current Monitoring Display

The aggregate current draw per power distribution unit is displayed on the unit via a digital display. The local digital display helps installers avoid overloaded circuits by providing a visible warning when the current draw is close to the maximum amperage draw of the strip.



Smart Distribution Panel with Automatic Transfer Switch (ATS)

Manages and delivers redundant power paths to the InfraStruXure™ system

Range: 250A, 400A, & 800A

The Smart Distribution Panel with Automatic Transfer Switch (ATS) integrates an ATS and electrical distribution panel to lower total cost-of-ownership while improving overall availability. The compact, pre-engineered design decreases installation time, minimizes one-time engineering costs and reduces the overall footprint. In addition, the device is rich with availability features such as open and closed transfer capabilities, superior device manageability (via the web, InfraStruXure Manager, or locally), and the ability to view numerous system alarms. When coupled with APC's Standby Power Generator, the solution monitors critical fluid levels, provides real-time calculations to alert users of available runtime given the current load and remaining fuel and automatically schedules generator and system load tests. Also, because the Smart Distribution Panel with ATS is designed to integrate with the InfraStruXure architecture, it is pre-engineered and sized to work with InfraStruXure solutions and contains many common features, such as pre-installed and pre-tested breakers.



The power distribution panel is integrated into the ATS, eliminating the need to install a separate distribution panel.

Fuel Level Converted to Actual Runtime

Runtime calculation is based on the remaining fuel and generator load.

ATS and UPS Coordination

The ATS and UPS are designed to work together seamlessly in the event of power loss.

InfraStruXure™ Manager Compatible

Enables centralized management via APC's InfraStruXure Manager.

Predictive Failure Alarms

Provide information about possible failures before they happen.



PowerShield

Complete line of reliable and flexible customer premise powering solutions for broadband telecommunication applications

Output: (Up To) 150W @ 48VDC; (Up To) 75W @ 12VDC

APC's PowerShield™ solution offers service providers that are deploying broadband fiber to the home/premises (FTTH/P), Hybrid Fiber-Coax (HFC), and/or wireless local loop networks a simple, reliable, and cost effective uninterruptible power source for customer premises equipment. In the case of FTTH/P networks, for instance, PowerShield offers a customer premises powering solution that, not only ensures that primary-line telephone service remains available in the event of a utility power failure, but also requires lower initial capital investment and has lower operational costs than competing powering technologies.

Cold-start Capable

PowerShield[™] can be turned on with a new charged battery, even if utility power is not available.

Automatic Self-test

Periodic battery self-test ensures early detection of a battery that needs to be replaced.

Hot-swappable Batteries

Ensures clean, uninterrupted power to protected equipment while batteries are being replaced.

User-replaceable Batteries

Battery replacement is simple and safe, and can be performed by the end-user. A technician is not required to replace the PowerShield battery.



Intelligent Battery Management

Maximizes battery performance, life, and reliability through intelligent, precision charging.

Global Safety Approvals

UL60950, CSA60950, IEC60950, EN60950 safety approvals. Meets IEC 61000-4-5 Immunity to Surge, and GR-1089-CORE, Section 4, Lightning and AC Power Faults standards.

IT Environment	Range	ge Best Price ("Good") Best Value `("Better")		Best Performance ("Best")	
PC/Workstation					
UPS	350-1500VA	Back-UPS® ES	Back-UPS® CS	Back-UPS® RS	
Surge Protection	1-11 outlets	SurgeArrest® Essential	SurgeArrest® Home/Office	SurgeArrest® Performance	

Back-UPS® RS

High performance battery backup and protection for business computers

Range: 500VA - 1500VA

The fully featured, high performance Back-UPS[®] RS series offers maximum protection in a versatile design. Up to six battery backup outlets with automatic voltage regulation (AVR) enable you to work through even the most frequent brownouts and power sags, conserving your battery power for when you need it most. The RS series provides both Ethernet and telephone data line surge protection, safeguarding against surges entering via network connections. Models include PowerChute Personal Edition software and can be placed either on the floor, desktop or shelf.

Battery-protected and Surge-only Outlets

Reserves power capacity and run time for connected equipment that require battery back-up while providing surge only protection for less critical equipment.

Power Conditioning

Protects connected loads from surges, spikes, lightning, and other power disturbances.

Boost and Trim Automatic Voltage Regulation (AVR)

Automatically corrects low and high voltage conditions, allowing you to work through brownouts and overvoltages without discharging the battery. This saves battery life, increases uptime, and improves your productivity.

LED Status Indicators

Enables quick understanding and response to visual indicators showing UPS status.

Equipment Protection Policy

Lifetime: \$150,000 (not available in all regions).

Safety-agency Approved

Ensures the product has been tested and approved to work safely with the connected service provider equipment and within the specified environment. UL, FCC, CE, C-Tick approvals.

USB Connectivity

Provides management of the UPS via keyed RJ45-USB Cables.



Serial Connectivity

Provides management of the UPS via keyed RJ45-Serial Codes.

Back-UPS® CS

Best value battery backup and protection for business computers

Range: 350VA - 650VA

The Back-UPS® CS offers professional-grade power protection for office systems with three battery backup outlets and three "surge only" outlets. Along with data line surge protection and safe system shutdown software, sophisticated power management features and pro-active audio-visual status indicators ensure that your office systems and their valuable data are protected from dangerous power surges, spikes and blackouts. Serial or USB connectivity gives users more flexibility making installation quicker and easier.

Battery-protected and Surge-only Outlets

Reserves power capacity and run time for connected equipment that require battery back-up while providing surge only protection for less critical equipment.

Power Conditioning

Protects connected loads from surges, spikes, lightning, and other power disturbances.

USB Connectivity

Provides management of the UPS via a USB port via keyed RJ45-USB cables (not available on all models).

Serial Connectivity

Provides management of the UPS via keyed RJ45-Serial Cables (not available on all models).

Equipment Protection Policy

Lifetime: \$100,000 (not available in all regions).

LED Status Indicators

Enables quick understanding and response to visual indicators showing UPS status.



Back-UPS® ES

Best Value battery backup and protection for home computers

Range: 325VA - 750VA

Designed for the home and home office, Back-UPS[®] ES series offers affordable battery backup and surge protection with up to ten outlets. Models provide phone, fax, and modem protection and include easy-to-install safe system shutdown software with USB connectivity.

Battery-protected and Surge-only Outlets

Reserves power capacity and run time for connected equipment that require battery back-up while providing surge only protection for less critical equipment.

Power Conditioning

Protects connected loads from surges, spikes, lightning, and other power disturbances.

Data Line Surge Protection

Provides protection of connected equipment from power surges on the data lines.

Equipment Protection Policy

Lifetime: \$75,000 (not available in all regions).

Transformer-block Spaced Outlets

Protect equipment with input transformer blocks without blocking access to other receptacles.

USB Connectivity

Provides management of the UPS via a USB port via keyed RJ45-USB cables (not available on all models).



Back-UPS® HS

Superior power management and protection for dataline panel box and home networking equipment

Range: 500VA

The Back-UPS[®] HS 500 is a complete management and power protection solution for your structured wiring and home networking applications. Remotely manage your UPS and control the four battery backup outlets via Web browser. Stay informed with five status LED indicators and remain protected with telephone, network, and co-axial/cable data line surge protection.

Data Line Surge Protection

Provides protection of connected equipment from power surges on the data lines.

Network Manageable

Provides remote management of the UPS over the network.

LED Status Indicators

Quickly understand UPS status with indicators.

Battery Replacement Without Tools

Allows quick, easy battery replacement.

Battery-protected and Surge-only Outlets

Reserves power capacity and run time for connected equipment that require battery back-up while providing surge only protection for less critical equipment.

Equipment Protection Policy

Lifetime: \$100,000 (not available in all regions).




Back-UPS for Office and Business Computers:Why Is Protection Important?

Availability of the desktop is important. For many businesses, keeping each or at least some of their desktops up and running is essential in preventing lost sales or business. The cost of one instance of downtime will almost always exceed the cost of a battery backup unit.

Data created and stored on a desktop is often too valuable to risk losing. The value of the data

stored and used on business workstations and desktops will often times exceed the cost of the hardware itself. In any distributed network, work in progress may not be covered, stored or backed up by the server when power is lost.

The cost of repairing or replacing hardware can be expensive and time consuming. At the very least, companies should make the minimal investment in surge protection products.



SurgeArrest® Essential*

Basic surge protection for computers and home electronics

1, 4 or 7 outlets, with or without phone surge protection, direct plug in, 4ft or 6ft cord length.



Power surges and spikes can destroy your electronic equipment. SurgeArrest® Essential will provide basic protection against these dangerous power fluctuations

- Basic protection against surges and spikes.
- Protection working indicator provides proactive notification of protection readiness.
- Building wiring fault indicator provides proactive notification of wiring problems.
- 1, 4, 5, 6 and 7 outlet models available.
- EMI/RFI filters attenuates line noise filters surge protector attenuates EMI/RFI line noise that can cause data errors and keyboard lockups, ensuring better performance of protected equipment.
- Some models offer telephone line surge protection jacks. It is very important to protect your equipment from "back door" surges traveling through data lines, as they can be as damaging to your equipment as surges traveling over power lines.

SurgeArrest® Home/Office*

Reliable surge protection for home or office computers and electronic equipment

6 or 8 outlets, with and without Coaxial protection.



APC's new SurgeArrest® Home/Office was designed in response to customer requests for additional safety and convenience features. Plug-activated safety shutters and cord management features were added to provide increased security and ease of use. Advanced power line and data line surge protection prevents damaging surges and spikes from reaching your sensitive equipment.

- Advanced protection against surges and spikes.
- Dataline surge protection jacks (phone, Ethernet and Coax available; varies by model) protects against surges traveling over data lines.
- Protection working' indicator provides proactive notification of protection readiness.
- Building wiring indicator provides proactive notification of wiring problems.
- 180 degree rotating cord allows for flexibility in placement.
- Cord management guide helps reduce cord clutter.
- 6 and 8 outlet models available.

SurgeArrest® Performance*

High performance surge protection for computers & electronics

8 and 11 outlets, with and without Ethernet protection.



The SurgeArrest® Performance provides maximum protection against surges, spikes and even lightning. Multi-stage surge protection and noise filter circuitry reduces these dangerous disturbances to harmless levels. With the same safety and convenience features of the SurgeArrest® Home/Office family, the SurgeArrest® Performance is ideal for high end computer electronic systems.

- Superior protection against surges and spikes.
- Data line surge protection jacks (phone, Ethernet and Coax available; varies by model) protects against surges traveling over data lines.
- Protection working indicator provides proactive notification of protection readiness.
- Building wiring indicator provides proactive notification of wiring problems.
- Overload indicator proactively warns of circuit overload.
- 180 degree rotating cord allows for flexibility in placement.
- Cord management guide helps reduce cord clutter.

^{*} Outlet type and product style varies by country.

ProtectNet®

Stand-alone data line surge suppression for network, telecommunication, PC and AV systems



- Protects equipment from surges traveling over data lines.
- Models available for Ethernet, Coax, digital telephone, analog telephone, Thinnet and Serial RS232 lines.

Power Ready Notebook Cases

Helping mobile professionals stay organized, protected, and connected

- Add APC's Universal Power Adapter (see below) to charge your notebook, phone and PDA simultaneously within the case from any single air, auto or ac power outlet.
- Universal notebook compartment.
- Convenient carrying case designed for easy access to all your mobile devices.
- Organizer panel easy access organizer panel helps keep important belongings at quick reach.
- Shock absorbing shoulder strap removable and adjustable strap is contoured and padded to provide maximum comfort with extreme loads.
- Removable, spill-proof pouch designed to keep your personal belongings secure and hidden.
- Security strap securely attaches the case directly on top of a roller case (backpack excluded).



Rack-mount ProtectNet®

Modular data line surge supression for network, telecommunication, PC and AV systems



- Protects equipment from surges traveling over data lines.
- Individual modules can be rack-mounted into any 19" rack using the PRM24 1U chassis.
- Modules can be mixed and matched to suit a particular environment.
- Modules can be replaced individually without interrupting other lines.
- Models available for Ethernet, Coax, digital telephone, analog telephone and Serial RS232 lines.

Universal Notebook Batteries

Portable computer batteries for the leading brands of notebook computers



- Notebook adapter tips included Allows compatibility with leading brands of notebook computers.
- Slim, lightweight design Saves space and weight.
- Four LED status indicators Visually indicates the battery's current state of charge.
- Adjustable output voltage setting Allows compatibility with leading brands of notebook computers.

Universal Power Adapters

Portable power for notebook computers and mobile devices



- Accepts power from auto, plane or wall sockets
 so you can access power anywhere you go.
- Notebook adapter tips included allows compatibility with leading brands of notebook computers.
- Replaces multiple power adapters saves space and weight.
- USB power port charges two mobile devices simultaneously, in addition to notebook computer.
- Adjustable output voltage setting allows compatibility with leading brands of notebook computers.
- LED Status Indicator visually indicates the unit's current status.

APC Tailors InfraStruXure™ for Specific Applications



In today's information technology environment, organizations deal with many changes, from increasing IT productivity while integrating existing systems, to providing increased business value and real-time enterprises, to supporting regulatory compliance. In many cases, this can result in new technology deployments such as blade servers, changes to the IT environment, converged networks and new enterprise capabilities. These business and technology trends are forging new types of IT environments with a need to quickly and effectively deploy key applications such as:

- High Density Deployment
- First-time Data Center Users
- VoIP Deployment
- Data Center Restructuring

APC's InfraStruXure™ availability architecture can now address NCPI issues for these key applications with integrated systems designed specifically for these applications.The systems, which integrate

power, cooling, management and services in a rack-optimized architecture are designed to increase availability and agility while reducing total cost of ownership.

To help your speed of deployment as well as future adaptability, these applications systems include a range of unique features such as preengineered integrated systems to minimize design time, fully-assembled delivery, quick connect components and many mobile and turnkey features. These agile systems help to address ever-changing business needs, making it ideal for technology rollouts/refreshes or changes to your IT environment.

Availability is certainly a critical factor in any IT environment. Availability can be improved with systems that are designed and tested for each particular application. Innovative solutions including new in-row cooling systems dramatically improve cooling predictability (on a rack- and row-level) up to 30kW per rack. New environmental and security access devices improve security, and new management

tools, standardized components and services are designed to reduce human error with logic tools and plug-able design approach.

Finally, with the need for increased IT productivity, your total cost of ownership will be improved as well, up to 35%. With energy costs a major percentage of data center operation, InfraStruXure's energy-efficient cooling systems can significantly reduce operating expenses. In addition, the initial capital costs are reduced with compact rack-based design, system-level pricing and "right-sized" power components that minimize the need for oversizing your data center.

As with any of the standardized, modular InfraStruXureTM designs, these systems can be provided as turnkey solutions or with any range of customization. These new InfraStruXureTM Systems for Applications are designed to ensure your key applications are successfully deployed.



InfraStruXure™ Systems for High Density

The deployment of new technology such as blade servers and server consolidation can easily create high-density environments. APC has a range of resources and solutions targeted specifically for high-density applications such as blade servers. All are designed to improve system availability and agility, allowing quick and effective deployment in data centers of all sizes while offering the lowest total cost of ownership (TCO).



InfraStruXure™ Systems for Data Center Restructuring

Mergers and acquisitions, outsourcing and business process innovation all make the world of business an unpredictable place. In response, data centers today have to be more agile, or capable of changing in a short period of time. Whether you are moving from a traditional data center, adding a disaster recovery center, or even in the process of server consolidation or business expansion, APC's pre-engineered solutions take the guesswork out of data center NCPI design.



InfraStruXure™ Systems for 1st Time Data Center and Server Room Users

The challenges of improving, and even maintaining IT productivity, have put un-experienced pressures on today's IT and Facility Managers. Converging networks (with major upgrades and modifications) while ensuring strong business continuity and disaster recovery strategy, is an overwhelming task. APC InfraStruXure™ Systems are ideal for departments with limited experience or resources in designing, operating and building data centers and server rooms.



InfraStruXure™ Systems for VoIP

If you're planning to deploy (or have deployed) Voice over Internet Protocol (VoIP) or IPTelephony, your converged network carrying data and voice becomes very critical. Your tolerance for downtime becomes zero. APC InfraStruXureTM Systems can support your entire Voice over IP network, including protection for IP phones, access points, wiring closets, Intermediate Distribution Frames (IDFs), Main Distribution Frames (MDFs) and the entire data center.

APC is Continually Expanding InfraStruXure™ System's Integrated Solution Set



The revolutionary
InfraStruXure™
with Integrated
Power Generation
combines a generator
with an integrated
automatic transfer
switch (ATS) and

distribution panel to provide extended on-site backup power for data centers.



APC now offers
InfraStruXure
with Integrated
Fuel Cells providing hours of
extended runtime
for IT applications
with high avail-

ability requirements. The integrated solution offers IT professionals the ability to provide power generation for their IT systems using fuel cell technology, an alternative to traditional extended-run options.



The Smart-UPS VT family now includes Smart-UPS VT InfraStruXure models which feature integrated Smart-UPS VT

power modules, hot swappable batteries, and integrated power distribution in one space saving rack. Since 1981, APC has been a global leader in power availability solutions, setting the industry standard for quality, innovation, and support. From its corporate headquarters in West Kingston, Rhode Island, APC operates sales offices throughout the world and manufacturing facilities on four continents and distribution facilities on five continents. APC ships products to over 150 countries.

Over 15 million satisfied customers worldwide depend on APC's Legendary Reliability*. Propelled by real-world experience and a drive towards technological innovation, APC has the experience, scale, global presence, and stability to respond to emerging IT availability needs.

As the recipient of hundreds of awards worldwide, APC is recognized for excellence in both its business and product performance. Every year since 1999, APC has been named to the Forbes Platinum 400 list of the Best Big Companies in America. For 11 years in a row, APC has received the Channel Champion award in the UPS category.





Learn how multiple power problems can wreak havoc with your electronic equipment. Download the FREE APC White Paper "The Seven Types of Power Problems". Visit us online at http://promo.apc.com and enter key code g309x.



For more information call: Tel: 800 800 4APC - US & Canada Tel: 401 789 0204 - World wide APC Corporate APC North America 132 Fairgrounds Road West Kingston, RI 02892 USA Call: 800 800 4APC Fax: 401 789 3710 **APC Latin America** 5301 Blue Lagoon Drive Suite #610 Miami, FL 33126 USA Call: 305 266 5005 Fax: 305 266 9695

APC Europe APC Ireland Ballybrit Business Park Galway, Ireland Call: +353 91 702000 Fax: +353 91 756909 APC Asia Pacific APC Australia Level 13 The Denison 65 Berry Street North Sydney, NSW 2060 Call: +61 2 9955 9366 Fax: +61 2 9955 2844 Visit: www.apc.com E-mail:apcinfo@apc.com Web Support:support.apc.com



Network and Server

UPS Runtime Estimates at a Glance

Smart-UPS SC / Smart-UPS Runtime @ Full Load Capacity (minutes) **Plug and Receptacle Types Capacity (Volt** Standard **APC Part Number** Form Input Output Amps/Watts) Runtime NFMA 5-15 NFMA 5-20 SC450RM1U* 450 / 280 6 (4) NEMA 5-15R SUA750RM2U 750 / 480 5 5-15P (6) NEMA 5-15R Rack SUA1500RM2U 1500 / 980 7 **NEMA L6-20** mount SUA2200RM2U 2200 / 1980 5 5-20P (6) NEMA 5-15R, (2) NEMA 5-20R SUA3000RM2U 3000 / 2700 3 L5-30P SC450RM1U* 450 / 280 6 (4) NEMA 5-15R NEMA 16-30 NEMA L14-30 SUA750 750 / 500 5-15P (6) NEMA 5-15R SUA1500 1500 / 980 (8) NEMA 5-15R Tower 5 SUA2200 2200 / 1980 5-20P (8) NEMA 5-15R, (2) NEMA 5-20R SUA3000 3000 / 2700 15-30P Smart-UPS XL Runtime @ Full Load Capacity (minutes) **Capacity (Volt** Standard Standard + (1) External Standard + (2) External **APC Battery Pack APC Part Number** Form Input Output Amps/Watts) Runtime **Battery Pack Battery Pack Part Number** SU1400RMXLB3U SU24R2XLBP 1400 / 1050 7 32 70 5-15P (6) NEMA 5-15R Rack SUA2200RMXL2U 2200 / 1580 6 21 50 5-20P (9) NEMA 5-15R. mount SUA48RMXLBP3U (2) NEMA 5-20R SUA3000RMXL3U 7 3000 / 2700 35 75 L5-30P SUA1000XL 1000 / 800 10 65 88 SUA24XLBP 5-15P (8)NEMA 5-15R SUM1500RMXL2U* 1500 / 1425 38 69 Tower SUM48RMXLBP2U (6) NEMA 5-15R, SUM3000RMXI2U* 3000 / 2850 3 16 32 L5-30P (2) NEMA 5-20R Smart-UPS RT* Runtime @ Full Load Capacity (minutes) **Capacity (Volt** Standard Standard + (1) External Standard + (2) External **APC Battery Pack** Form **APC Part Number** Input Output Amps/Watts) Runtime **Battery Pack Battery Pack Part Number** SURTA48RMXLBP SURTA1500RMXL 1500 / 1050 9 39 71 5-15P (6) NEMA 5-15R (6) NEMA 5-15R, SURTA3000RMXL 3000 / 2100 102 L5-30P 15 57 (2) NEMA 5-20R Rack SURT5000RMXLT-(12) 5-20R, (2) L6-20R, 5000 / 3500 5 27 50 L6-30P mount SURT192RMXLRP 1TF5 (1) L6-30R (1) Hard Wire 3-wire, SURT10000RMXLT-Hard Wire (24)NEMA 5-20R, 10000 / 8000 11 20 2TF5 3-wire (2) NEMA L6-20R SURTA1500XL 1500 / 1050 9 71 SURTA48XLBP 5-15P (6) 5-15R 39 (6) NEMA 5-15R, 3000 / 2100 SURTA3000XI 15 57 102 15-30P (2) NEMA 5-20R (8) 5-20R, (1) NEMA SURT5000XLT-1TF3 5000 / 3500 5 27 50 16-30P L14-30R, (4) NEMA L6-Tower 20R, (2) NEMA L6-30R SURT192XLBP (1) Hard Wire 3-wire, (16) NEMA 5-20R, (2) Hard Wire SURT10000XLT-2TF3 10000 / 8000 20 NEMA L14-30R, (6) 11 3-wire NEMA L6-20R, (2) NEMA L6-30R Symmetra / Symmetra LX* Runtime @ Full Load Capacity (minutes) **Capacity (Volt** Standard + (1) External Standard + (2) External **APC Battery Frame** Standard Form **APC Part Number** Input Output Amps/Watts) Runtime **Battery Frame Battery Frames Part Number** SYH4K6RMT-P1 4000 / 2800 13 51 92 (2) NEMA L6-20R, SYRMXR4B4 L6-30P (12) NEMA 5-20R SYH6K6RMT-P1 6000 /4200 12 38 65 Rack SYA8K16RMP 8000 / 6400 (4) NEMA L14-30R, 62 123 mount 208/240\/ (8) NEMA L5-20R, SYARMXR9B9 SYA12K16RMP 12000 / 9600 6 43 82 Hardwire 208/240 & 120V 4-Wire SYA16K16RMP 16000 / 12800 6 33 62 Hardwire 4-Wire 6 SYA8K16P 8000 / 6400 62 123 208/240V 208/240 & 120V

Tower

SYA12K16P

SYA16K16P

12000 / 9600

16000 / 12800

43

33

22

62

6

SYAXR9R9

Hardwire

4-Wire

Hardwire 4-Wire

^{*} Models are rack/tower convertible

Network and Server

UPS Runtime Estimates at a Glance

Smart-UPS SC / Smart-UPS Runtime @ Full Load Capacity (minutes)											
Form	APC Part Number	Capacity (Volt Amps/Watts)	Standard Runtime	Input	Output						
	SUA750RM1UJB	750 / 480	6	5-15P	(4) NEMA 5-15R						
Rack	SUA1500RM2UJB	1500 / 980	7	5-15P	(6) NEMA 5-15R						
mount	SUA3000RMJ2UB	3000 / 2700	3	L5-30P	(6)NEMA 5-15R, (2)NEMA 5-20R						
	SUA500JB	500 / 360	9		(6) NEMA 5-15R						
	SUA750JB	750 / 500	5	5-15P							
Tower	SUA1500JB	1500 / 980	7		(8) NEMA 5-15R						
	SUA2200JB	2200 / 1980	5	L5-30P	(8)NEMA 5-15R,						
	SUA3000JB	3000 / 2700	5	L3-30P	(2)NEMA 5-20R						

Plug and Receptacle Types

NEMA 5-15





NEMA L6-20









	SUA2200JB	2200 / 1980	5	L5-30P	(8)NEMA 5-15R,		'		
	SUA3000JB	3000 / 2700	5	L5-30P	(2)NEMA 5-20R				
Smart	-UPS RT* Runtime @	Full Load Capacity (minut	es)						
Form	APC Part Number	Capacity (Volt Amps/Watts)	Standard Runtime	Standard + (1) External Battery Pack	Standard + (2) External Battery Pack	APC Battery Pack Part Number	Input	Output	
	SURTA1500XLJ w/SURTRK	1500 / 1050	8	39	71	SURTA48XLBPJ W/SURTRK	5-15P	(6) NEMA 5-15R	
Rack	SURT5000XLJ-1TF4 w/SURTRK2	4600 / 3500	5	27	50		L6-30	(8)NEMA 5-20R, (2)NEMA L5- 20R, (3)NEMA L6-20R	
mount	SURT7500XLJ-2TF4 w/SURTRK2	7500 / 6000	7	16	28	SURT192XLBPJ	Hard Wire	(16)NEMA 5-20R, (4)NEMA	
	SURT10000XLJ-2TF4 w/SURTRK2	10000 / 8000	4	11	20		3-wire	L5-20R, (4)NEMA L6-20R, (2)NEMA L6-30R	
	SURTA1500XLJ	1050 / 1500	8	39	71	SURTA48XLBPJ	5-15P	(6) NEMA 5-15R	
Tower	SURT5000XLJ-1TF4	5000 / 3500	5	28	52		L6-30	(8)NEMA 5-20R, (2)NEMA L5-20R, (3)NEMA L6-20R, (2)NEMA L6-30R	
100001	SURT7500XLJ-2TF4	7500 / 6000	7	16	28	SURT192XLBPJ		Hard Wire 3-wire, (16)NEMA	
	SURT10000XLJ-2TF4	10000 / 8000	4	11	20		Hard Wire 3-wire	5-20R, (4)NEMA L5-20R, (4)NEMA L6-20R, (2)NEMA L6-30R	
Symm	etra / Symmetra LX	* Runtime @ Full Load (Capacity (minute	es)					
Form	APC Part Number	Capacity (Volt Amps/Watts)	Standard Runtime	Standard + (1) External Battery Frame	Standard + (2) External Battery Frame	APC Battery Frame Part Number	Input	Output	
	SYH4K6RMJ-P1	4000 / 2800	12	51	92	SYRMXR4B4J	L6-30P	(2) NEMA L6-20R,	
	SYH6K6RMJ-P1	6000 /4200	12	38	65	STNIVIAN4D4J	L0-30P	(12) NEMA 5-20R	
Rack mount	SYA8K8RMJ	8000 / 5600	8	28	50		Hard Wire	(4)NEMA L5-20R, (2)NEMA L14-30R, (1)Hard Wire 4-wire	
	SYA12K16RMJ	12000 / 8400	8	21	35	SYARMXR3B3J	4-wire	(8)NEMA L5-20R, (4)NEMA	
	SYA16K16RMJ	16000 / 11200	8	18	28			L14-30R, (1)Hard Wire 4-wire	
	SYA8K16JXR	8000 / 5600	8	72	143				
Tower	SYA12K16JXR	12000 / 8400	8	58	110	SYAXR9B9J	Hard Wire 4-wire	(1)Hard Wire 4-wire	
	SYA16K16JXR	16000 / 11200	8	40	74				

^{*} Models are rack/tower convertible

For the most recent sizing information and additional runtime options consult www.apc.com

Network and Server UPS Runtime Estimates at a Glance

Smart-UPS SC / Smart-UPS Runtime @ Full Load Capacity (minutes)									
Form APC Part Number		Capacity Standa (Volt Amps/Watts) Runtin		Input	Output				
Rack mount	SC450RMI1U*	450 / 280	6		(4) IEC 320 C13				
	SUA750RMI2U	750 / 480	5	IEC-320 C14					
	SUA1500RMI2U	1500 / 980	7						
	SUA2200RMI2U	2200 / 1980	5	IEC 220 C20	(8) IEC 320 C13, (1) IEC 320 C19				
	SUA3000RMI2U	3000 / 2700	3	IEC-320 C20					
	SC450RMI1U*	450 / 280	6		(4) IEC 320 C13				
	SUA750I	750 / 500		IEC-320 C14	(6) IEC 320 C13				
Tower	SUA1500I	1500 / 980	_		(8) IEC 320 C13				
	SUA22001	2200 / 1980	5	150,000,010	(8) IEC 320 C13,				
	SUA3000I	3000 / 2700		IEC-320 C19	(1) IEC 320 C19				

Plug and Receptacle Types

IEC Connector



	20A30001	3000 / 2700			(17.120.020.010							
Smart	Smart-UPS XL Runtime @ Full Load Capacity (minutes)											
Form	APC Part Number	Capacity (Volt Amps/Watts)	Standard Runtime	Standard + (1) External Battery Pack	Standard + (2) External Battery Pack	APC Battery Pack Part Number	Input	Output				
	SU1400RMXLIB3U	1400 / 1050	7	35	75	SU24R2XLBP	IEC 220 C14	(8) IEC 320 C13				
Rack	SUA2200RMXLI2U	2200 / 1580	7	36	76		IEC-320 C14	(9) IEC 320 C13				
mount	SUA3000RMXLI3U	3000 / 2700	6	21	50	SUA48RMXLBP3U	IEC-320 C20 British BS1363A Schuko CEE 7/EU1-16P	(8) IEC 320 C13, (1) IEC 320 C19				
	SUA1000XLI	1000 / 800	10	65	88	SUA24XLBP	JEO 000 044	(8) IEC 320 C13				
Tower	SUM1500RMXLI2U	1500 / 1425	12	38	69		IEC-320 C14	(9) IEC 320 C13				
101101	SUM3000RMXLI2U	3000 / 2850	3	16	32	SUM48RMXLBP2U	IEC-320 C20	(7) IEC 320 C13, (1) IEC 320 C19				
Smart	Smart-UPS RT* Runtime @ Full Load Capacity (minutes)											
Form	APC Part Number	Capacity	Standard	Standard + (1) External	Standard + (2) External	APC Battery Pack	Input	Output				

APC Part Number	(Volt Amps/Watts)	Runtime	Battery Pack	Battery Pack	Part Number	Input	Output
SURT1000RMXLI	1000 / 700	10	53	99	SURT48RMXLBP	IEC-320 C14	(6) IEC 320 C13
SURT3000RMXLI	3000 / 2100	14	57	102		IEC-320 C20, British BS1363A, Schuko CEE 7/EU1-16P	(8) IEC 320 C13, (2) IEC 320 C19
SURT5000RMXLI	5000 / 3500	5	27	50	SURT192RMXLBP	Hard Wire 3-wire	(8) IEC 320 C13, (2) IEC 320 C19
SURT10000RMXLI	10000 / 8000	4	11	20		Hard Wire 3-wire, Hard Wire 5-wire	(1) Hard Wire 3-wire, (4) IEC 320 C13, (4) IEC 320 C19
SURT1000XLI	1000 / 700	10	53	99	SURT48XLBP	IEC-320 C14	(6) IEC 320 C13
SURT3000XLI	3000 / 2100	14	57	102		IEC-320 C20 British BS1363A Schuko CEE 7/EU1-16P	(8) IEC 320 C13, (2) IEC 320 C19
SURT5000XLI	5000 / 3500	5	27	50	SURT192XLBP	Hard Wire 3-wire	(8) IEC 320 C13, (2) IEC 320 C19
SURT10000XLI	10000 / 8000	4	11	20		Hard Wire 3-wire, Hard Wire 5-wire	(1) Hard Wire 3-wire, (4) IEC 320 C13, (4) IEC 320 C19
	SURT3000RMXLI SURT5000RMXLI SURT10000RMXLI SURT1000XLI SURT3000XLI SURT5000XLI	SURT1000RMXLI 1000 / 700 SURT3000RMXLI 3000 / 2100 SURT5000RMXLI 5000 / 3500 SURT10000RMXLI 10000 / 8000 SURT1000XLI 1000 / 700 SURT3000XLI 3000 / 2100 SURT5000XLI 5000 / 3500	SURT1000RMXLI 1000 / 700 10	SURT1000RMXLI 1000 / 700 10 53	SURT1000RMXLI 1000 / 700 10 53 99	SURT1000RMXLI 1000 / 700 10 53 99 SURT48RMXLBP	SURT1000RMXLI 1000 / 700 10 53 99 SURT48RMXLBP IEC-320 C14

Symm	Symmetra / Symmetra LX* Runtime @ Full Load Capacity (minutes)											
Form	APC Part Number	Capacity (Volt Amps/Watts)	Standard Runtime	Standard + (1) External Battery Frame	Standard + (2) External Battery Frame	APC Battery Frame Part Number	Input	Output				
	SYH4K6RMI	4000 / 2800	13	51	92	SYRMXR4B4I		(8) IEC 320 C13,				
	SYH6K6RMI	6000 /4200	13	38	65	STNIVIAN4D4I		(2) IEC 320 C19				
Rack mount	SYA8K8RMI	8000 / 5600	7	72	143	SYARMXR9B9I	Hard Wire 3-wire	(1) Hard Wire 3-wire, (8) IEC 320 C13, (6) IEC 320 C19				
	SYA12K16RMI	12000 / 8400	8	50	95	STANIVIANDSI		Hard Wire 3-wire,	(1) Hard Wire 3-wire,			
	SYA16K16RMI	16000 / 11200	8	39	72		Hard Wire 5-wire	(8) IEC 320 C13, (10) IEC 320 C19				
	SYA8K8I	8000 / 5600	7	72	143		Hard Wire 3-wire					
Tower	SYA12K16I	12000 / 8400	7	50	95	SYAXR9B9I	Hard Wire 3-wire,	(1) Hard Wire 3-wire				
	SYA16K16I	16000 / 11200	8	39	72		Hard Wire 5-wire					

^{*} Models are rack/tower convertible