

RACKS BRAX.[®]

COMPATIBILITY POCKET GUIDE

FOR



4X4 ACCESSORIES

*FAST ON!
FAST OFF!*

AWNING AND ACCESSORY MODELS

CLICK OR TAP ON AN AWNING/ACCESSORY BELOW
TO TAKE YOU TO THE PAGE TO FIND OUT WHAT YOU NEED

ARB[®] AWNING 1.25 x 2.1m, 2.0 x 2.5m, 2.5 x 2.5m..... 3

ARB[®] ALUMINIUM ENCASED AWNING 2.5 x 2.5m* 4



ARB[®] AWNING 1.25 x 2.1m, 2.0 x 2.5m, 2.5 x 2.5m**HITCHES** REQUIRED MINIMUM FOR **FAST ON, FAST OFF!**

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	RACKSBRAX BRACKETS DO NOT FIT TO ARB[®] BASE RACK. WE RECOMMEND KAON'S UNIVERSAL AWNING BRACKET TO SUIT ARB BASE RACK (KS0375, KS0454) INSTEAD WITH THE HD HITCH + ARB BASE RACK.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE **PACKERS** TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION ✓ LOCKED GARAGES ✓ WORKSHOP WALLS	8160 – HD Wall Mounts*
UNSECURED LOCATION ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	8161 – HD Lockable Wall Mounts*

*NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.

ARB® ALUMINIUM ENCASED AWNING 2.5 x 2.5m*

*ALUMINIUM CASES HAVE 3 CHANNELS ON THE REVERSE OF AWNING, CHOOSE 2 ADJACENT CHANNELS FOR MOUNTING.

HITCHES REQUIRED MINIMUM FOR FAST ON, FAST OFF!

MOUNTING POINTS	2
HITCHES NEEDED	8159 – HD Hitch Standard*

*WILL ALSO WORK WITH THE TRIPLE VERSION.

BRACKETS OPTIONAL

MOUNTING POINTS	2
BRACKETS NEEDED	RACKSBRAX BRACKETS DO NOT FIT TO ARB® BASE RACK. WE RECOMMEND KAON'S UNIVERSAL AWNING BRACKET TO SUIT ARB BASE RACK (KS0375, KS0454) INSTEAD WITH THE HD HITCH + ARB BASE RACK.
✓ FOR BARS OR PLATFORM STYLES WITH TRANSVERSE SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8304 – HD Adjustable Brackets Short (DOUBLE)*; OR
✓ FOR PLATFORM STYLES WITH LONGITUDINAL SLATS (WITH NO PERIMETER LIP)	8300 – HD L50 L Brackets (DOUBLE)*; OR 8306 – HD Adjustable Brackets Long (DOUBLE)*.

*ROOF RACKS WITH PERIMETER LIPS REQUIRE [PACKERS](#) TO FIT RACKSBRAX BRACKETS (SOLD SEPARATELY). REFER TO [ROOF RACK GUIDE](#) FOR MORE INFORMATION ON RACKS WITH PERIMETER LIPS.

WALL MOUNTS OPTIONAL

BENEFITS	ALLOWS YOU TO REMOVE YOUR ROOF RACK ACCESSORY FROM YOUR VEHICLE SO THAT IT CAN BE FIXED TO A WALL WHEN NOT IN USE.
SECURED LOCATION ✓ LOCKED GARAGES ✓ WORKSHOP WALLS	8160 – HD Wall Mounts ⁺
UNSECURED LOCATION ✓ OPEN CARPORTS ✓ PUBLIC/SHARED GARAGE AREA	8161 – HD Lockable Wall Mounts ⁺

⁺NOTE: You cannot use Wall Mounts to mount anything to the vehicle – these are for static wall use ONLY.