PND-Q5S

Portable car smart screen

Main interface

1.CarPlay 2.Android Auto
3.HiCar 4.Settings
5.Time

Settings

Click Enter

You can set the adjustment in this interface

- 1.Support multi-language settings

  You can set the relevant language according to your own habits

- 2.Date and time settings

- 3.Time zone setting

Settings

Click Enter

Connection settings

- BT connection settings

- 1.Screen display brightness

- 2.Background replacement

Settings

Click Enter

Connection settings



- 3.A variety of different models boot LOGO selection



- 4.CarPlay Settings

  1.You can set the display on the right side of carplay

  2.Versions below IOS14.0 need to enable this function



- 1.Here you can adjust the volume of media, phone, and navigation respectively

Settings

Click Enter

Connection settings

- 1.Dual bluetooth connection

  1.After turning on this function, the mobile phone needs to be connected to the product to connect to the earphone or the car to make a sound

- 1.FM emission

  When this function is turned on, the machine will restart. It is a normal phenomenon. Please do not worry

- 1.Swipe down on the status bar in the middle of the screen

Two-wire connection

Phone



PND-Q5S

EarPhone

You can use your mobile phone to connect PND-Q5S and earphones.
The sound is played through the earphones.
Makes you safer during driving

CarPlay

Bluetooth boot connection to wifi is unsuccessful, you need to manually connect to wifi
The wifi name is the same as the bluetooth name, and the password is: 12345678

Select on machine Turn on the wifi of the mobile phone, turn on the Bluetooth of the mobile phone, find the Bluetooth name of the machine, click pairing, and automatically jump to CarPlay if the pairing is successful.



You can make calls after connecting to carplay

Android Auto

Bluetooth boot connection to wifi is unsuccessful, you need to manually connect to wifi
The wifi name is the same as the bluetooth name, and the password is: 12345678

Select on machine Turn on the wifi of the mobile phone, turn on the Bluetooth of the mobile phone, find the Bluetooth name of the machine, click pairing, and automatically jump to AndroidAuto if the pairing is successful.

You can make calls after connecting to Android Auto

Hicar

Bluetooth boot connection to wifi is unsuccessful, you need to manually connect to wifi
The wifi name is the same as the bluetooth name, and the password is: 12345678

Select on machine Turn on the wifi of the mobile phone, turn on the Bluetooth of the mobile phone, find the Bluetooth name of the machine, click pairing, and automatically jump to Hicar if the pairing is successful.



You can make calls after connecting to Hicar

Machine display

Size:136*91.5*28mm

Machine display



(Anti-theft screw)

1.AUX
2.TF Card
3.Type-C

Parameter

CPU: LINUX processor
Screen size: 5 inches HD
Resolution: 800*480IPS viewing angle Full lamination process
Screen Color: 65k
Screen brightness: 1000 nits
Touch: high precision capacitive touch
Interface: TF card/3.5cAUX audio
Working power supply: 5V waterproof power adapter
Working power range: 5v
Working current: maximum 2A
Frequency transmission: 87.5-108MHz
Speaker: Built-in 3W speaker
CarPlay: Support wireless/wired CarPlay (Note: iPhone 6 and above, iOS10 and above should be supported.)
Android Auto: Support wireless/wired Android Auto /hicar
(Note: The wireless Android automatic function requires an Android phone with Android 11 and above, and Android 11 and below can only use wired Android Auto. Contains Huawei phones.)
Information/Navigation/Music Control
Built-in high-sensitivity antenna, more sensitive response.
Mechanical properties:
Operating temperature: -20℃ to 70℃
IPX7 Waterproof: Yes

Thanks