# Glacier POU Water Cooler



The Glacier Point-of-Use water dispenser is available in Hot and Cold or Cook and Cold models. The rounded cabinet and fluted front give the Glacier a classic Greek column design suitable for any environment. While being aesthetically pleasing, the polyethylene cabinet's smooth finish is easily cleaned and refurbished. This commercial grade cooler will deliver years of trouble free optimum performance.

## **Features**

- · Double mechanical float system for reliable operation
- Secondary float acts as a safety precaution by shutting off water supply
- Manual reset switch located at top of system for easy access
  - \* Green indicates normal function







# Cook & Cold Grainger White Model # 60JH78 Grainger Black Model # 60JH79





Tomlinson<sup>™</sup> Touch Guard<sup>®</sup> hot water faucet

# Glacier



# **Point of Use system**

The Point Of Use Kit uses a primary float with a secondary backup in conjunction with a 1/4" quick connect fitting with cover to protect the fitting and tubing. Easily adaptable, the double mechanical float system installs easily onto the coolers.



# PERFORMANCE AND SPECIFICATIONS

## General

Air cooled, POU type water cooler

## **Cooler Cabinet**

Blow molded, high density polyethylene(HDPE) resistant to cracking

# **Faucet Type**

Tomlinson<sup>™</sup> self -closing with hot side Tomlinson<sup>™</sup> Touch Guard<sup>®</sup>

| ITEM                     |             | SPECIFICATIONS                 |
|--------------------------|-------------|--------------------------------|
| Power rating             |             | 100-115VAC 60Hz                |
| Standard current         |             | Hot & Cold: 6.2A               |
| Power<br>Consumption     | Cold        | 74W                            |
|                          | Hot         | 450W                           |
| Cold                     | Refrigerant | R134a                          |
|                          | Temp range  | 39.2 -50° F                    |
|                          | Capacity    | 0.7 us gal                     |
| Hot                      | Temp range  | 165.2-197.6° F                 |
|                          | Capacity    | 0.5 us gal                     |
| Refrigerant charge       |             | 0.9 oz                         |
| Product weight           |             | Hot & Cold: 30.1 lb            |
| Product boxed weight     |             | Hot & Cold: 34.2 lb            |
| Product dimensions       |             | 12.2"(W) X 12.4"(D) X 38.6"(H) |
| Product boxed dimensions |             | 12.6"(W) X 13.4"(D) X 44.1"(H) |



Point Of Use System



Hot water ON and OFF switch