

Airpanel Select

Synthetic pleated filter

Product Range



Select

Applications



Filter Class

Coarse



KEY FACTS

- Compact design
- Specially-finished support grid prevents oxidization
- Chemically-bonded media ensures pleat stability
- Simple installation and handling

DESIGN

Pleated, synthetic filter media laminated onto an expanded diamond grid, which features a special finish to prevent oxidization.

APPLICATIONS

Prefiltration for air conditioning and ventilation equipment and/or systems highly effective with coarse dust.

Airpanel Select

Synthetic pleated filter

PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	ISO 16890	mm	m³/h	Pa
800220014387	Coarse 80%	287 x 596 x 47	965	30
800220014356	Coarse 80%	296 x 296 x 47	494	30
800220014366	Coarse 80%	395 x 624 x 47	1390	30
800220014459	Coarse 80%	448 x 448 x 47	1130	30
800220014367	Coarse 80%	496 x 624 x 47	1744	30
800220014389	Coarse 80%	596 x 596 x 47	2000	30
			3400	80
800220014005	Coarse 80%	287 x 596 x 98	964	25
800220015247	Coarse 80%	296 x 296 x 98	494	25
800220014031	Coarse 80%	395 x 624 x 98	1390	25
800220014065	Coarse 80%	496 x 624 x 98	1744	25
800220015251	Coarse 80%	596 x 596 x 98	2000	25
			3400	65

SPECIFICATION

Recommended air flow	Flow rate ± 25 %	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity / 90 % cardboard frame
Regenerable	No	Incinerable	Yes, except for metal frames

OPTIONS

Frame	Moisture-resistant cardboard or metal
--------------	---------------------------------------

Airpanel Select XL

Synthetic pleated filter

Product Range



Select

Features

XL

Applications



Filter Class

Coarse



KEY FACTS

- Compact design
- Increased surface area for high dust holding capacity and low pressure drop
- Specially finished support grid prevents oxidization
- Simple installation and handling

DESIGN

Pleated, synthetic filter media laminated onto an expanded diamond grid, which features a special finish to prevent oxidization.

APPLICATIONS

Prefiltration for air conditioning and ventilation equipment and/or systems. Highly effective with coarse dust.

Airpanel Select XL

Synthetic pleated filter

PERFORMANCE DATA

Article No.	Filter Class	Dimensions	Flow Rate	Pressure Drop
	ISO 16890	mm	m ³ /h	Pa
800229014910	Coarse 80%	287 x 596 x 47	965	28
800229014916	Coarse 80%	296 x 296 x 47	494	28
800229014924	Coarse 80%	395 x 624 x 47	1390	28
800229014901	Coarse 80%	448 x 448 x 47	1130	28
800229014914	Coarse 80%	496 x 624 x 47	1744	28
800229014952	Coarse 80%	596 x 596 x 47	2000	28
			3400	75
800229014828	Coarse 80%	287 x 596 x 98	964	22
800229014837	Coarse 80%	296 x 296 x 98	494	22
800229014859	Coarse 80%	395 x 624 x 98	1390	22
800229014862	Coarse 80%	496 x 624 x 98	1744	22
800229061083	Coarse 80%	596 x 596 x 98	2000	22
			3400	62

SPECIFICATION

Recommended air flow	Flow rate ± 25 %	Rec. final pressure for efficient energy use acc. to EN 13053	Lowest value of initial pressure drop + 50 Pa, or initial pressure drop x 3
Heat resistance	Max. 70 °C	Moisture resistance	100 % rel. humidity / 90 % cardboard frame
Regenerable	No	Incinerable	Yes, except for metal frames

OPTIONS

Frame	Moisture-resistant cardboard or metal
--------------	---------------------------------------