

VSP1500L VSP1500R	Vehicle Specific Punch Full Size GM Truck 1500 Extended Cab '88+*	Specification Reference Sheet
----------------------	--	-------------------------------------



FEATURES

VSP ENCLOSURE

- **Vehicle Specific** – The VSP1500L (left) and VSP1500R (right) are custom molded to fit under the rear bench seat. The VSP1500R fits without alteration, whereas the VSP1500L replaces the toolbox.
- **Acoustic Suspension Enclosure** – The VSP enclosure uses an acoustic suspension design (sealed) for optimum performance. The enclosure is matched to the woofer for deep bass output while requiring minimal operating space.
- **Roto-Molded Urethane Construction** – The use of Roto-Mold manufacturing produces a composite enclosure with seamless construction. This greatly increases rigidity to prevent the enclosure from flexing and allows custom designs to be fabricated. The result is a radical, stronger, more reliable enclosure.

NOTE: Use the VSP1500R for systems requiring only one subwoofer. Use the VSP1500R and VSP1500L for systems requiring two subwoofers.

PUNCH WOOFER

- **PVA Cone** – The cone material used is spruce pulp paper and provides the necessary combination of weight and strength to allow high levels of output without cone break up. The cone is also treated with a water resistant PolyVinyl Acetate (PVA) Emulsion which increases cone rigidity and lowers distortion.
- **Aluminum Voice Coil Former** – The voice coil is made of multiple layers of copper wound on a black, anodized aluminum former. This improves the speaker's power handling by efficiently dissipating heat from the voice coil.
- **Hyper-Extended Pole Piece** – The pole piece has been extended to provide a more linear magnetic field for the operation of the woofer. This lowers distortion and provides the woofer with better low frequency response.
- **Vented Bumped Back Plate** – The back plate has been stepped deeper to allow the woofer more excursion for harder hitting bass. Additionally, the back plate is vented with a radiused aerodynamic vent that efficiently and quietly keeps the voice coil cool.

SPECIFICATIONS

VSP Enclosure

Frequency Response 24Hz-400Hz
Overall Dimensions ea. 8"H x 30½"W x 15"D
(20.32cm x 77.47cm x 38.10cm)
Weight ea. (woofer supplied) 22.6 lbs. (10.25kg)

Punch Woofer

Speaker Model RFP-1410
Nominal Impedance 4Ω
Fs 24Hz
RE 3.6Ω



LE 2.5mH
QMS 4.08
QES 0.27
QTS 0.25
VAS (ft³/liter) 2.72 (77L)
XMAX (in/mm) 0.31" (8mm)
SPL (dB @ 1w/1m) 87dB
Power Handling (RMS/Peak) 200W/400W
Speaker Displacement (ft³/liter) 0.06 (1.699L)

ACCESSORY PACK

(1) Input Terminal Cup	(1) 3/8" – 16 x 1¼" Bolt	(1) 3/8" Lock Washer	(8) #10-32 x 3/4" Allen Screws
(4) Phillips Screws	(1) 3/8" ID x 1½" OD Washer	(4) Foam Woofer Gaskets	(24") Black/Red 16 gauge Speaker Wire
(1) 4" x 4" Wax Square (VSP1500R)			



Specifications subject to change without notice

VSP1500L VSP1500R	Vehicle Specific Punch Full Size GM Truck 1500 Extended Cab '88+*	Installation Reference Sheet
<p>The Vehicle Specific Punch (VSP) enclosure is supplied in kit form to allow custom finishing techniques. The unfinished surface enables matching paint or carpet to be applied to the enclosure for seamless integration into the vehicle's interior. In addition, the input terminal cup can be positioned in the desired location where speaker wires can be conveniently routed from the amplifier to the enclosure.</p>		
<p style="text-align: center;">IMPORTANT – Please follow these instructions carefully!!</p> <p><i>The VSP enclosure is specially molded to fit particular vehicles. Be sure to attach the enclosure to the vehicle as specified in this installation sheet for optimized bass output. Failure to install the enclosure as specified in this document may allow the enclosure to become detached from the vehicle and possibly cause personal injury.</i></p> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="width: 15%;">   </div> <div style="width: 85%;"> <p>Always use eye protection when drilling.</p> <p>Never run wires underneath the vehicle. Run wires inside the vehicle and use rubber or plastic grommets to protect wires routed through metal.</p> </div> </div>		
<p>VSP ENCLOSURE PREPARATION</p> <ol style="list-style-type: none"> Select the desired location for the speaker terminal cup, and with a hole saw, cut a 2" diameter hole. Using the speaker terminal cup as a template, mark the holes used to secure the cup to the enclosure. Remove the cup and drill pilot holes using a 3/32" drill bit. Carpet or paint the enclosure(s) to your desired color theme. Connect the supplied speaker wire to the appropriate (+) and (–) terminals of the speaker cup. Connect the RED wire to the (+) terminal and the BLACK wire to the (–) terminal. Secure the speaker terminal cup to the enclosure using the (4) supplied Phillips screws. 		



VEHICLE PREPARATION

6. The VSP enclosure(s) will be located under the rear bench seat. Be sure to remove any obstructions for proper installation.
7. Fold up the rear bench seat.
8. If installing the VSP1500L in addition to the VSP1500R, permanently remove the factory toolbox located under the seat. Be sure to cover the extra hole using a rubber plug or silicone sealant.




VSP 1500R ENCLOSURE INSTALLATION

9. Thread the supplied bolt fully into the VSP enclosure and test fit the enclosure in the vehicle.
10. Remove the backing from the wax square and place it under the bolt location. Press down firmly on the enclosure to make an impression of the bolt head into the wax square. Making sure not to move the wax square, carefully remove the enclosure from the vehicle.
11. Check under the vehicle for brake or hydraulic lines before proceeding. Using a 1/2" diameter drill bit, drill a hole through the floor board using the wax square as your template.



VSP 1500L ENCLOSURE INSTALLATION

12. If installing the VSP1500L in addition to the VSP1500R, test fit the enclosure in the vehicle. Note that you will use the factory drilled tool box hole to secure the VSP1500L to the vehicle.
13. Run the speaker wire from the amplifier to the desired location(s) and connect the proper (+) and (-) speaker terminals to the enclosure(s).
14. The next procedure will require 2 people. While one person is positioning the VSP enclosure(s), the second person should insert the long bolt(s) from the underside of the vehicle. Put a bead of silicone sealant between the car sheet metal and the washer. Screw the bolt into this threaded insert and tighten it. **DO NOT OVERTIGHTEN.**
15. After the bolt(s) are tightened, spray rubberized undercoating over the bolt(s) and over any bare metal. This will prevent the metal from rusting and will prevent the bolt(s) from loosening due to vibrations.
16. If necessary, fine tune the system to find the proper bass level for your new VSP woofer enclosure.



VSP1500R



VSP1500L & VSP1500R

LIMITED WARRANTY INFORMATION

Rockford Corporation offers a limited warranty on Rockford Fosgate products on the following terms:

- **Length of Warranty**

1 year on VSP speakers (not the entire enclosure)

- **What is Covered**

This warranty applies only to Rockford Fosgate products sold to consumers by Authorized Rockford Fosgate Dealers in the United States of America or its possessions. Product purchased by consumers from an Authorized Rockford Fosgate Dealer in another country are covered only by that country's Distributor and not by Rockford Corporation.

- **Who is Covered**

This warranty covers only the original purchaser of Rockford product purchased from an Authorized Rockford Fosgate Dealer in the United States. In order to receive service, the purchaser must provide Rockford with a copy of the receipt stating the customer name, dealer name, product purchased and date of purchase.

- **Products found to be defective during the warranty period will be repaired or replaced (with a product deemed to be equivalent) at Rockford's discretion.**

- **What is Not Covered**

1. Damage caused by accident, abuse, improper operations, water, theft
2. Any cost or expense related to the removal or reinstallation of product
3. Service performed by anyone other than Rockford or an Authorized Rockford Fosgate Service Center
4. Any product which has had the serial number defaced, altered, or removed
5. Subsequent damage to other components
6. Any product purchased outside the U.S.
7. Any product not purchased from an Authorized Rockford Fosgate Dealer

- **Limit on Implied Warranties**

Any implied warranties including warranties of fitness for use and merchantability are limited in duration to the period of the express warranty set forth above. Some states do not allow limitations on the length of an implied warranty, so this limitation may not apply. No person is authorized to assume for Rockford Fosgate any other liability in connection with the sale of the product.

- **How to Obtain Service**

Please call 1-800-669-9899 for Rockford Customer Service. You must obtain an RA# (Return Authorization number) to return any product to Rockford Fosgate. You are responsible for shipment of product to Rockford.

Ship to: **Electronics**
Rockford Corporation
Warranty Repair Department
2055 E. 5th Street
Tempe, AZ 85281
RA#: _____

Ship to: **Speakers**
Rockford Acoustic Design
(Receiving-speakers)
609 Myrtle N.W.
Grand Rapids, MI 49504
RA#: _____

MADE IN THE USA

This product is designed, developed and assembled in the USA by a dedicated group of American workers. The majority of the components used in the construction of this product are produced by American companies. However, due to the global nature of their manufacturing facilities and the electronics parts industry in general, some parts may be manufactured in other countries.

Rockford Fosgate
Rockford Corporation
546 South Rockford Drive
Tempe, Arizona 85281 U.S.A.
In U.S.A., (602) 967-3565
In Europe, Fax (49) 850-3934-014
In Japan, Fax (81) 559-79-1265
www.rockfordfosgate.com