

WT-500

INTERNATIONAL TRAVEL TOUR SYSTEM

WT-500 series is powered by 1 AA battery which is enough for 15 hours of runtime and this provides tour guides a more economical solution to reduce the cost of batteries. WT-500 weighs only 70 g which brings comfort for the users without adding extra weight to their vacation. The long range of transmission range - 100 meters is suitable for not only indoor activities, such as museum tour or factory tour, but also outdoor touring.

-  Compact size and light weight
-  LCD display for battery, channel number reading
-  Channel lock and power saving functions
-  Up to 100 m wireless coverage
-  Suitable for indoor and outdoor use
-  Powered by 1 AA battery (Alkaline or NiMH) to allow 15 hours of battery life
-  Rechargeable design



group tour



museum tour



interpretation



exhibition



WT-500R



WT-500T

Chargers and Carry Bag/Case



HDC-505
5-slot charger



HDC-515
15-slot charger



HDC-525
25-slot charger



HDC-550
50-slot charger



CCW-30
30-unit carry case



TB-500
42-slot carry bag

Specifications	WT-500 
Carrier frequency range	584 ~ 870 MHz (region dependent)
Channels	40 or 80 (region dependent)
Power requirements	1 x AA (1.2 V 2100 mAh, NiMH) or 1 x AA (1.5 V Alkaline)
Charging time	8 hours
Operating range	100 m (line of sight)
Battery life (NiMH/Alkaline)	13 / 15 hours, typical
Dimensions (D x W x H)	24 x 40 x 97 (mm)
Weight	70 g (with battery)

* Specifications are subject to change