2 Arm Cam Kit 7"

4 Channel 7" HD Monitor, 2 Arm Cameras with Clamp Kit

JB-2A7D

Monitor

The 7" Analog HD LCD Monitor features a sharp display with adjustable distance grid lines, mirror image support, and an integrated speaker.

Backlit buttons ensure visibility in low light, and the monitor can be operated via remote control.



- Quad View, connect and view up to 4 Analog FHD cameras
- Built-in speakers for audio
- Adjustable distance grid lines for backing up reference
- Switch between mirror/normal image for any camera attached

Monitors Specs	
Monitor Type	7" TFT LCD Digital Display
Dot Resolution	1280 x 720
Screen Aspect Ratio	16:09
Contrast Ratio	500:01
Display Brightness	400cd/ ²
Field of View	U:50° D:60° L/R:70°
Camera Input	4 channel
Video Source	1Vp-p, 75Ω
Power Supply	DC 9V-32V
Power Consumption	5W
Operating Temperature	-20°C ∼ +70° C
Storage Temperature	-30°C ∼ +85° C
Video System	Auto NTSC/PAL
Overall Dimensions	7" (L) x 5" (H) x 1" (D)
Weight	400G
Impact Rating	5G
Dot Pitch	0.1926 (H) X 0.1710 (V)
Sync System	Internal





Arm Camera with Clamp

Keep it simple with the truck Arm Camera. The CA-ARMG1H is designed to fit this onto the arm bracket of your truck, no drilling to attach the camera is necessary! This camera is equipped with a wide 120° viewing angle, a 2.8mm lens and 10 infra-red lights for excellent night vision. Completely waterproof with a IP68 rating, this camera also has a 10G vibration rating. This camera comes with two different clamp sizes. The larger clamp set has a maximum diameter of 4" and minimum diameter of 3". The smaller clamp set has a maximum diameter of 1.25" and a minimum diameter of 1".



CONVENIENT INSTALLATION

Easily fits onto the arm bracket of various trucks

SIMPLE INSTALL

No drilling necessary to mount the camera.

120° VIEWING ANGLE

With an ultra-wide viewing angle, and 2.8mm lens the side camera will provide a complete view from sides of your vehicle to ensure complete safety with no blind spots

NIGHT VISION

10 infra-red lights support excellent night vision

COMMERCIAL GRADE

Completely waterproof camera with IP68 rating

Camera Specs	
Model	CA-ARMG1H
Sensor	2MP pixel , 1/2.8" CMOS sensor
Maximum frame rate	PAL:25fps/s NTSC:30fps/s
Min Illumination	1920 (H) × 1080 (V)
Electronic Shutter	Auto:PAL 1/50s(NTSC 1/60s)~1/100,000s
Backlight Compensation	Auto
Signal to Noise ratio	Better than 39dB
Audio output	Optional
IR Distance	5M
Focus	2.8MM M12,fix aperture F2.0, HFOV 120°
Waterproof grade	IP69
Material	Metal & Plastic
Installation Placement	Side of the Vehicle - Side Mirror Bracket
Operating Temperature	-30°C ~ +70°C
Working Relative Humidity	20% - 80%
Powered by	DC 12V ±10%
Weight	400g





