



Australian Canstar Blue Award Winner



Australians have voted Hisense as the LCD TV model they are most satisfied with, in the Canstar Blue Most Satisfied Customer Awards.

Hisense LCD TV owners awarded their LCD television sets the maximum five-stars score in the categories of "overall satisfaction" and "value" – higher than its competitors, and awarded four stars for "performance".

1 to 1 Pixel Mapping



1:1 pixel mapping means your TV is capable of displaying the image sent to it pixel for pixel, without scaling or processing the video in any way. This product feature means the product can be used as a computer monitor replicating the output resolution.

Full HD Resolution



True High Definition is sometimes referred to in marketing materials as "1080p" or "Full High-Definition". The number 1080 represents 1,080 lines of vertical display resolution, while the letter p stands for progressive scan or non-interlaced.

HDMI Inputs



High-definition audio and video inputs are applied to make sure the high-definition video and audio can have synchronized output. In addition, the unique HDCP technology is equivalent to the terminal display device, which is embedded HDCP. The digital and audio signals are reverted one-on-one, which ensures that the digital and video signals are not lost, and the original picture effect can be achieved.

SPECIFICATIONS

Model Number	HL40V78P
Series	V78 Series
Model Description	102cm (40in) LCD TV

DISPLAY

Display Area(mm)	885.6(H) x 498.15(V)
Resolution	1920 X 1080 (FULL HD Resolution)
Brightness(nit)	430cd/m2
Contrast Ratio	4000:1
Viewing Angle H/V	178H/178V
Response Time	8ms
Refresh rate	50HZ
Backlight system	CCFL

MULTIMEDIA PLAYER

Music formats	MP3
Video formats	mpg (encoding: Mpeg)
Photographs, graphics	JPEG,BMP

COMMERCIAL FEATURES

Hotel lock	YES
Teletext	YES
Clone settings	YES
Hotel Mode (Max Preset, volume limit)	YES
Serial port control	YES (for service use only)

RECEPTION

TV Tuner System	HD Digital Tuner & Analogue System
AV Color System	PAL/ NTSC
Audio System	B/B
NICAM/A2	YES
Maximum Audio Output	2 x 8 watts
Speaker Type	Embedded

TERMINAL INPUTS

RF Input	1
AV Input	1
Y Pb(Cb)/Pr(Cr) Input	2
HDMI Input (HDCP)	3
VGA Input	1
Audio Input for VGA	1
AV Output	1
Digital Audio Output(SPDIF)	1
Earphone Jack	1
USB	1 (Digital Media Port via USB)
RS232	1

OTHER FEATURES

FULL HD (1080p) resolution	YES
1 to 1 Pixel Mapping	YES
Progressive Scan	YES
Channel Coverage	Full Band
User def. Picture Formats	4:3, 16:9, Zoom 1, Zoom 2,Auto
Backlight control	YES
Noise Reduction	Digital Noise Reduction
Parental Control	YES
Clock	YES
Sleep Timer	YES
EQUALIZER	YES
Wall Mount Support	400(mm) x 200(mm) VESA Standard
Menu OSD	English only
Software updating	YES
Channel labelling	YES
Logical channel name	YES
Child lock	YES
HD Ready	YES
Still image	YES
Motion Compensation / MEMC	NO
AC-3	YES
EPG	YES
Sub-title	YES
Swivel stand	NO

POWER

Power Supply	AC 220-240V 50/60Hz
Power Consumption	TBC
Stand By Consumption	≤1W

DIMENSIONS

Dimension with stand (mm)	980 x 678 x 285
Dimension without stand(mm)	980 x 620 x 106

WEIGHT

Net Weight(without stand/with stand)	16kg
--------------------------------------	------

ACCESSORIES

Remote	1
Battery	2
Power cord	1
User manual	English
Warranty card	1