

VEHICLE Mazda BT50 & Ford Ranger Gen 2 11/11 - onwards
PRODUCT Transmission Spacer Kit
PART NUMBER TSS001

TOOLS REQUIRED

- 19mm socket
- Ratchet

FITTED TO PX RANGER 2012 - ONWARDS

A maximum of a 24mm spacer is available in 4mm increments.

1. This product can be fitted with the vehicle on the ground. If raising vehicle, ensure the vehicle is correctly supported. Support the driveshaft in the case it may fall and cause injury. Follow the instructions below for both sides of the bearing.
2. Ensuring the mount is supported, remove both retaining nuts from the centre bearing carrier.
3. Place the desired amount of spacers over the stud, with the balance of spacers not being used placed under the head of the new bolt supplied.
4. Install bolt with split washer placed under the bolt head, tighten with 19mm socket—Do not over tighten.
5. Test drive vehicle and assess vibration. If all spacers are fitted and vibration is still evident, you may require a Pinion angle adjustment using our WEDGE plates and SB022—long head leaf spring centre bolt.

HARDWARE SUPPLIED

- 2 x female bolts
- 12 x 4mm spacer washers
- 2 x split washers

BOLT TORQUE SPECS

	8.8	10.9	12.9
M10	41-60Nm	59-85Nm	65-94Nm
M12	71-105Nm	102-150Nm	114-164Nm
M14	112-168Nm	161-240Nm	182-265Nm
M16	175-260Nm	250-371Nm	282-406Nm

