

POWER RELAYS: 20–30 AMPS



Convenient Prepackaging is a Great Time Saver

- LED indicator
- Multiple contact ratings
- Override / HOA switch options available
- High/low voltage separation available
- 20-30 Amp models
- Pre-wired
- Enclosed or track mount
- Time delay models



ENCLOSED POWER RELAYS

Product Selection Guide. For full product information, see our website.

MODEL #	UL	COIL VOLTAGE		RELAY CONTACTS	CONTACT RATINGS			HIGH/LOW SEPARATION	OVERRIDE SWITCH	HOUSING STYLE *	SHIPPING WEIGHT
		AC/DC	AC		RESISTIVE	MOTOR	PILOT DUTY				
RIB2401B	•	24	120	1 SPDT	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac			B	0.500 lb.
RIB2402B	•	24	208-277	1 SPDT	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac			B	0.501 lb.
RIB2401SB	•	24	120	1 SPST	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac		1	B	0.497 lb.
RIB2402SB	•	24	208-277	1 SPST	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac		1	B	0.510 lb.
RIB2421B	•	24	120/208-277	1 SPDT	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac			B	0.525 lb.
RIB2421SB	•	24	120/208-277	1 SPST	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac		1	B	0.540 lb.
RIB2401SBC	•	24	120	1 SPDT	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac		2 +	B	0.565 lb.
RIB2402SBC	•	24	208-277	1 SPDT	20 A @ 277 Vac	2 HP @ 277 Vac	1,110 VA @ 277 Vac		2 +	B	0.598 lb.
RIB01P	•		120	1 DPDT	20 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•		C	0.956 lb.
RIB02P	•		208-277	1 DPDT	20 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•		C	0.965 lb.
RIB347P	•		347	1 DPDT	20 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•		C	0.952 lb.
RIB04P	•		480	1 DPDT	20 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•		C	0.952 lb.
RIB013P	•		120	1 3PST	20 A @ 300 Vac	7.5 HP @ 480 Vac, 3 Phase	Heavy Pilot Duty @ 600 Vac	•		C	1.008 lb.
RIB023P	•		208-277	1 3PST	20 A @ 300 Vac	7.5 HP @ 480 Vac, 3 Phase	Heavy Pilot Duty @ 600 Vac	•		C	1.020 lb.
RIB043P	•		480	1 3PST	20 A @ 300 Vac	7.5 HP @ 480 Vac, 3 Phase	Heavy Pilot Duty @ 600 Vac	•		C	0.993 lb.
RIB243P	•	24		1 3PST	20 A @ 300 Vac	7.5 HP @ 480 Vac, 3 Phase	Heavy Pilot Duty @ 600 Vac	•		C	0.974 lb.
RIB24Z	•	24		1 SPST N/O, 1 SPST N/C	30 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac			B	0.748 lb.
RIB12P	•	12		1 DPDT	20 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac			B	0.725 lb.
RIB12P30	•	12		1 DPDT	30 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac			B	0.888 lb.
RIB24P	•	24		1 DPDT	20 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac			B	0.724 lb.
RIB24P30	•	24		1 DPDT	30 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac			B	0.874 lb.
RIB01P30	•		120	1 DPST	30 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•		C	0.982 lb.
RIB01P30-S	•		120	1 DPST	30 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•	1 #	C	1.013 lb.
RIB02P30	•		208-277	1 DPST	30 A @ 300 Vac	3 HP @ 480-600 Vac	Heavy Pilot Duty @ 600 Vac	•		C	0.980 lb.

UL = UL Listed : UL916 Energy Management, UL864 Fire ; USA & Canada

* = See Housing Guide on pages 86-87

+ = SPDT with override requires 2 switches

= Coil side relay override (requires unit to be powered)

For full product information, see data sheets on website. Shipping weights are approximate and may change due to packaging options.