

IBM Half-high LTO Generation 4 SAS Tape Drive

Product Guide (withdrawn product)

The IBM Half High LTO Generation 4 SAS Tape Drive is the fourth-generation Linear Tape-Open (LTO) offering introducing larger storage capacities, increased performance, and advanced security features to effectively meet the demanding backup, archival and regulatory compliance requirements of your System x environments.

The IBM Half High LTO Generation 4 SAS Tape Drive is an excellent tape storage solution for businesses requiring backup or low-cost, real-time archiving of their data within a small window of time. This fourth generation drive provides up to twice the storage capacity, up to 1.6 TB with 2:1 compression, and provides up to a 50% performance increase, up to 240 MBps (864 GB/hr) with 2:1 compression, over the preceding LTO 3 half height technology. This enterprise data protection offering is available in a 5.25-inch half-height internal form factor for integration into IBM System x tower servers and external IBM 1U rack-mount enclosures or a half-height external unit for stand-alone table top or rack shelf applications.

Figure 1 shows the IBM Internal Half-high LTO Generation 4 SAS Tape Drive.



Figure 1. IBM Internal Half-high LTO Generation 4 SAS Tape Drive

Did you know?

Data security is a growing requirement for businesses of all sizes today. The IBM Half-high LTO Generation 4 SAS Tape Drive delivers advanced security features to help ensure compliancy with data security, information disclosure, and privacy regulations for data at rest. Beyond WORM (Write-Once, Read-Many) cartridge support to preserve data in a non-erasable and non-rewritable format, LTO 4 technology also offers data encryption capabilities. LTO 4 hardware-based data encryption can assist in safeguarding against costly security breaches and exposure of proprietary data if a data cartridge is stolen or lost.

Part number information

Table 1 lists the ordering part numbers and feature codes.

Table 1. Ordering part numbers and feature codes

Description	Part number	Feature code
IBM Internal Half-high LTO Generation 4 SAS Tape Drive	44E8895	5397
IBM External Half High LTO Gen 4 SAS Drive, with US line cord	3628L4X	None
IBM External Half High LTO Gen 4 SAS Drive, with no line cord	3628N4X	None
IBM LTO Generation 4 Media 5 Pack	46C5359	5701 (1 cartridge)
IBM LTO Ultrium 4 800GB WORM Data Cartridge without labels - 20 pack	95P4461*	Not available
IBM LTO Universal Cleaning Cartridge	49Y9893	5347

* To order WORM cartridges, in United States and Canada, please call 1-888-IBM-MEDIA. For all other geographic locations, please select your country and distributor from <http://ibm.com/systems/storage/media/distributors/>.

The part number for the IBM Internal Half-high LTO Generation 4 SAS tape drive includes:

- LTO Generation 4 SAS tape drive assembly
- Mounting screws
- CD-ROM containing the User's Guide
- Cleaning cartridge
- Drive rails
- SAS cable for internal tape connectivity

The part numbers for the IBM External Half-high LTO Generation 4 SAS Tape Drive includes the following items:

- LTO Generation 4 SAS tape drive in an external enclosure
- CD-ROM containing the User's Guide
- Cleaning cartridge
- 3 meter external SAS cable
- 3628L4X also includes a 2.8 meter (9 ft) 10A / 125V US line cord

Features

The features of the IBM Half-high LTO Generation 4 SAS Tape Drive has the features and benefits listed in Table 2:

Table 2. Features and benefits

Feature	Benefits
6 Gbps SAS host interface	• Fast connection to the server
Up to 240 MBps data transfer rate	• Helps reduce the time required for backup • 50% transfer rate increase from current Half-high LTO Generation 3 drives
Up to 1.6 TB cartridge capacity	• Helps store greater amounts of data as your business grows

Digital Speed Matching (DSM)	• Supported on Ultrium 4 media in increments of 30 MBps to 120 MBps • Along with a larger buffer, helps to maximize drive performance when data rates are less than optimal
256 MB buffer	• Together with Digital Speed Matching, helps the drive mitigate fluctuations in data rates
Adaptive Data Compression	• With the 256 MB buffer, helps you achieve optimal performance and storage capacity • Helps improve data throughput and tape repositions • Helps support data integrity through synchronous, dynamic swapping of data compression scheme
256 AES encryption	• Helps keep the data on your tape media secure with encryption • Helps meet compliance requirements • Helps improve performance of your backup processes with dedicated encryption/decryption core
16 channel head	• Increases data throughput to support higher drive speeds
Timing-based servo positioning	• Patented technology that provides greater precision when writing data to tape • Enables the drive to support the use of narrower tracks • With the 16 channel head, linear density of the data is increased by 31% when compared to LTO Generation 3 drives
Advanced tape loader and threader mechanism	• Improves error recovery and provides greater reliability when loading threading and unloading tape cartridges • Independent loader and threader motors, coupled with positive pin retention helps retain the pin during a miss-pick and helps improve load & thread reliability • Designed to improve drive and media reliability
"On-the-fly" adaptive channel calibration	• Allows the drive to adjust to variations in the media and head while calibrating the channel. • Helps improve data throughput rates and data integrity
Copper based chips	• Based on IBM copper chip technology, provides improved performance while providing lower overall power consumption over previous generations of LTO drives
Superior power management	• Enables the drive to operate in write mode and idle mode for when the drive is not in use • Improves heat dissipation and provides greater operational efficiency than previous-generation LTO drives

WORM support	• WORM capable cartridges give you the option of storing vital data in a non-erasable, non-rewritable format, to meet strict regulatory requirements for data retention • Helps address evolving regulatory initiatives
Flexible mounting alternatives	• Half height external SAS tape drive for a low cost and space efficient table top or shelf unit alternative to mounting a drive internally in your server. • 5.25 in. half high internal SAS tape drive designed for internal installation in IBM System x tower servers or external IBM 1U rackmount enclosures

Specifications

The specifications for the Half-high LTO Generation 4 SAS tape drive are (when using Ultrium 4 cartridges):

- 6 Gbps SAS host interface
- Up to 800 GB native capacity and up to 1600 GB in compressed mode (2:1 compression ratio)
- 120 MBps native back-up rate and up to 240 MBps in compressed mode (2:1 compression ratio)
- Support for WORM (write once read many) on WORM cartridge types
- Burst data-transfer rate of 300 MBps for the SAS interface
- 256 MB read-and-write cache
- Read/Write compatibility with LTO Generation 3 cartridges. Read compatibility with LTO 2 and 3 cartridges
- Support for encryption of data on Ultrium 4 cartridges

Key prerequisites

The IBM Half-high LTO Generation 4 SAS Tape Drive prerequisites are:

- SAS controller
- One or more LTO Generation 3 or LTO Generation 4 data cartridge (not supplied with drive option)
- For the internal drive, an available half-height drive bay or supported external tape enclosure.

Physical specifications

The physical specifications of the IBM Internal Half-high LTO Generation 4 SAS Tape Drive are:

- Height: 43 mm (1.75 in.)
- Width: 149 mm (5.85 in.)
- Depth: 210 mm (8.40 in.)
- Weight: 1.5 kg (3 lb. 5 oz.)

The IBM External Half-high LTO Generation 4 SAS Tape Drive has the following physical specifications:

- Height: 58 mm (2.3 in)
- Width: 213 mm (8.4 in)
- Depth: 332 mm (13.1 in)
- Weight: 4.3 kg (9.5 lb)

Figure 2 shows the IBM External Half High LTO Generation 4 SAS Drive.



Figure 2. IBM External Half High LTO Generation 4 SAS Drive

Operating environment

The IBM Half-high LTO Generation 4 SAS Tape Drive is supported in the following environment:

- Temperature:
 - Operating: 10° to 40° degrees C (50° to 104° degrees F)
 - Non-operating: -40° to 60°C (-40° to 140°F)
- Relative humidity:
 - Operating: 20% to 80% (non-condensing)
 - Non-operating: 10% to 90% (non-condensing)
- Maximum altitude:
 - Operating: 3048 m (10000 ft.)
 - Non-operating: 3048 m (10000 ft.)

Warranty

The IBM Internal Half-high LTO Generation 4 SAS tape drive has a one-year limited warranty. When installed in a System x server, this tape drive assumes your system's base warranty and any IBM ServicePack upgrade. The IBM External Half-high LTO Generation 4 SAS Tape Drive has a three-year warranty.

Supported servers

The IBM Half-high LTO Generation 4 SAS Tape Drive is supported in the IBM System x servers that we listed in Table 3.

Table 3. Supported System x servers (Part 1)

	x3100 M3	x3200 M2	x3200 M3	x3250 M2	x3250 M3	x3350	x3400	x3400 M2	x3400 M3	x3455	x3500	x3500 M2	x3500 M3
Internal LTO 4 SAS Tape Drive (installed internally to the server)	N	Y*	Y	N	N	N	Y	Y	Y	N	Y	Y	Y
Internal LTO 4 SAS Tape Drive (installed externally in an enclosure)	N	Y*	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
External LTO 4 SAS Tape Drive	N	N	Y	Y	Y	Y	N	Y	Y	Y	N	Y	Y

* The tape drive is supported in x3200 M2 machine types 4367 and 4368 only.

Table 3. Supported System x servers (Part 2)

	x3550 M2	x3550 M3	x3620 M3	x3630 M3	x3650	x3650 M2	x3650 M3	x3655	x3690 X5	x3755	x3755 M3	x3850 M2	x3950 M2	x3850 X5
Internal LTO 4 SAS Tape Drive (installed internally to the server)	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Internal LTO 4 SAS Tape Drive (installed externally in an enclosure)	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y
External LTO 4 SAS Tape Drive	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	N	Y	Y	Y

Internal use

The following components are needed:

- A supported SAS host bus adapter installed in the server (see Table 3)
- An available 5.25-inch, half-height bay

External use

If the internal tape drive is to be installed in an external enclosure, the following components are needed. We describe these enclosures and the enclosure adapter kit in the "Supported enclosures and enclosure kit" section.

- A supported SAS host bus adapter installed in the server (see Table 3)
- A supported external enclosure:
 - IBM 1U Rackmount Tape Enclosure
 - IBM 4U Rackmount Tape Enclosure (now withdrawn)
 - IBM Half High Tabletop Tape Enclosure
- An IBM SAS Enclosure Adapter Kit (40K2599)

If the external tape drive is to be used, the a supported SAS host bus adapter installed in the server is needed. The host bus adapters supported with the tape drive are listed in Table 4.

Table 4. Host Bus Adapters for use with the IBM Half-high LTO Generation 4 SAS Tape Drive

Description	Part number	Feature code
IBM SAS HBA Controller	25R8060	1681
IBM 3 Gb SAS HBA Controller v2	44E8700	3583
IBM 6Gb SAS HBA Controller	46M0907	3875

For the latest and most accurate compatibility information, visit our ServerProven Web site at: <http://ibm.com/servers/eserver/serverproven/compat/us/> or the IBM System x Configuration and Options Guide at: <http://www.ibm.com/systems/xbc/cog/>.

Supported enclosures and enclosure kit

You can use the enclosures and enclosure kit shown in Table 5 with the internal tape drive when it is to be installed externally.

Table 5. Enclosures for use with the IBM Internal Half-high LTO Generation 4 SAS Tape Drive

Description	Part number	Feature code
IBM 1U Rack-mount Tape Enclosure	87651UX (AG)* 87651NX (AP and EMEA)†	8765HC1 fc 2290
IBM 4U Rack-mount Tape Enclosure (withdrawn)	87664UX (AG)* 8766NX (AP and EMEA)†	Not applicable
IBM Half High Tabletop Tape Enclosure	8767HHX (AG)* 8767HNX (AP and EMEA)†	8767HC1 fc 2287
IBM SAS Enclosure Adapter Kit‡	40K2599	5382

* These models are for customers in the Americas Group (AG - Canada, U.S., and countries in South America). These models ship with a NEMA 5-15P line cord

† These models are for customers in the countries known collectively as Asia Pacific (AP) and Europe, Middle East, Africa (EMEA). These models do not ship with a line cord.

‡ One adapter kit is needed per drive

The following figure shows the IBM Half-high LTO Generation 4 SAS Tape Drive installed in the left most bay of the IBM 1U Rack-mount Tape Enclosure (87651UX).



Figure 3. The tape drive installed in the 1U Rack-mount Tape Enclosure

The IBM SAS Enclosure Adapter Kit, 40K2599, includes the following items:

- SAS adapter/connector
- 3M external SAS cable

Popular configurations

In this section, we illustrate how you can use the IBM Half-high LTO Generation 4 SAS Tape Drive in configurations.

Internal installation

The following figure shows the IBM Half-high LTO Generation 4 SAS Tape Drive installed internally in a tower server.




Figure 4. The IBM Half-high LTO Generation 4 SAS Tape Drive installed internally in a tower server

Table 6 lists the parts that are used.

Table 6. Components used when installing the IBM Half-high LTO Generation 4 SAS Tape Drive into an x3500 M2 server

Diagram reference	Part number/ machine type	Description	Quantity
1	Varies	Supported server	1
2	44E8895	IBM Half High LTO Generation 4 SAS Tape Drive (includes internal cable)	1
3	46M0907	IBM 6 Gb SAS HBA Controller	1

Installation in a 1U external enclosure

The following figure shows the IBM Internal Half-high LTO Generation 4 SAS Tape Drive installed in an IBM 1U Tape Drive External Enclosure and connected to a System x server.




Figure 5. The tape drive installed in an IBM 1U Tape Drive External Enclosure and connected to a System x server

Table 7 lists the parts that are used.

Table 7. Components used when connecting the IBM Half-high LTO Generation 4 SAS Tape Drive installed in external tape drive enclosure to a supported System x server

Diagram reference	Part number/ machine type	Description	Quantity
1	Varies	Supported System x server	1
2	46M0907	IBM 6 Gb SAS HBA Controller	1
3	44E8895	IBM Half-high LTO Generation 4 SAS Tape Drive	1
4	87651UX	IBM 1U Tape Drive External Enclosure	1
Inside the enclosure	40K2599	IBM SAS Enclosure Adapter Kit (includes the internal cable, 3m external SAS cable)	1

The following figure shows an IBM 1U Tape Drive External Enclosure without the SAS Adapter Kit and after installing the SAS Adapter Kit.




Figure 6. The 1U Tape Drive Enclosure with and without the SAS Enclosure Adapter Kit

Supported software products

The IBM Half-high LTO Generation 3 SAS Tape Drive supports the following software products:

- CA Brighstor
- Tivoli Storage Manager
- Symantec Backup Exec
- Symantec Net Backup

Supported operating systems

The IBM Half-high LTO Generation 3 SAS Tape Drive supports the following operating systems:

- SUSE Linux
- Red Hat Linux
- Microsoft Windows 2003
- Microsoft Windows 2008

For the latest information about the specific versions and service packs that are supported, see IBM ServerProven at:

<http://ibm.com/servers/eserver/serverproven/compat/us/>

When you arrive at the IBM ServerProven site, select the blade server and then select the expansion card to see the supported operating systems.

Related publications

For more information, refer to the following resources:

- IBM HH LTO Generation 4 SAS Tape Drive Installation and User Guide
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-5074991>
- Installation Guide for IBM 1U Rackmount Tape Enclosure
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-64787>
- Installation Guide for IBM 4U Rackmount Tape Enclosure
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-64794>
- Installation Guide for IBM Half High Tabletop Tape Enclosure
<http://www.ibm.com/support/docview.wss?uid=psg1MIGR-64792>
- IBM System x Configuration and Options Guide
<http://www.ibm.com/systems/xbc/cog/>
- IBM US Announcement Letter for the IBM HH LTO Generation 4 SAS Tape Drive
<http://ibm.com/common/ssi/cgi-bin/ssialias?infotype=dd&subtype=ca&&htmlfid=897/ENUS108-272>

Related product families

Product families related to this document are the following:

- [Backup Units](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2022. All rights reserved.

This document, TIPS0746, was created or updated on June 7, 2011.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/TIPS0746>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/TIPS0746>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

System x®

The following terms are trademarks of other companies:

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft® and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.