

Panasonic®

**Building Passion,
Building Solutions.**
Panasonic Air Conditioning Systems

We face a time in which “quality air” differentiates business. It’s a time for Panasonic to fully display its strengths. Our ability to assemble and build superior systems isn’t just due to the rich resources we have as a comprehensive electronics manufacturer, but also to Panasonic’s 100 years of tradition, where each person thinks and acts on their own initiative while working in a team to reach further heights. We do not compromise. Each of our independent selves is a one stop solution. We face our customers’ challenges together with our customers and do all that we can to build effective systems. As a true partner for our customers, we strive to always be at the forefront of business.

- Please read the Installation Instructions carefully before installing the unit, and the Operating Instructions before using it.
- Specifications are subject to change without prior notice.
- The contents of this catalogue are accurate as of March 2021.
- Due to printing considerations, actual colours may vary slightly from those shown.
- All graphics are provided solely for the purpose of illustrating a point.



Do not add or replace refrigerant other than the specified type. Manufacturer is not responsible for damage or deterioration in safety due to usage of other refrigerant.

Authorised Dealer


OCAU_R32 PAC_CAT_2020_V3

Panasonic Australia Pty. Limited.

Address: 1 Innovation Road, Macquarie Park, NSW 2113
ACN 001 592 187 ABN 83 001 592 187

aircon.panasonic.com.au

R32 RESIDENTIAL & LIGHT COMMERCIAL AIR CONDITIONING 2020 / 2021



nanoe™X

R32
REFRIGERANT

A Better Life, A Better World

QUALITY AIR FOR LIFE

The new Panasonic NX series

The next generation is now

The new CONEX remote controller (CZ-RTC6BLW) multiplies the benefits of a standard nanoe™ X installation, letting you create clean, healthy air in your living spaces 24 hours a day, anytime, anywhere. Choose your quality of air - a new era in air conditioning solutions is here.

CONTENTS

Product Line-up	4 - 5	Indoor Unit	
Better Air Quality	6 - 11	High Static Pressure Ducted	30 - 33
CONEX	12 - 15	High Static Pressure Splittable Ducted	34 - 35
Ducted	16 - 19	High Static Pressure Adaptive Ducted	36 - 39
Outdoor Unit	20 - 29	Ultra Slim Ducted	40 - 41
		4-WAY Cassette	42 - 45
		4-WAY Mini Cassette	46 - 47
		Under Ceiling	48 - 51
		Wall Mounted	52 - 53
		Floor Console	54 - 55
		Dimensions	56 - 61
		Smart Control Management Solutions	62 - 63
		Panasonic Comfort Cloud	64 - 65
		Home Automation	66 - 67
		PAC Smart Connectivity+	68 - 75
		Panasonic AC Smart Cloud	76 - 77
		Controllers	78 - 87

24-hour^{*1}
nanoe™ X Air purification

nanoe™ X

24-hour nanoe™ X Air purification

Unlike the general filters found in an air purifier, nanoe™ X achieves a powerful inhibiting effect on not only airborne, but also adhered bacteria and viruses.

P. 6 - 11



P. 12 - 15

Make comfort more accessible with CONEX

CONEX goes beyond simple remote control to combine sophistication with simplicity, offering IoT integration that connects directly to a variety of apps for next-generation solutions.



P. 16 - 17

Maximum versatility adaptive ducted unit

Designed to deliver flexibility, performance, and comfort, Panasonic introduces an industry-leading horizontal/vertical design featuring powerful 150Pa static pressure in a compact unit.

Note: PF3 range only.

Product Line-up

Cooling Capacity		2.5 kW	3.6 kW	5.0 kW	6.0 kW	7.1 kW	10.0 kW	12.5 kW	14.0 kW	16.0 kW	18.0 kW	20.0 kW	22.4 kW					
Indoor Unit	Ducted	NX Series High Static Ducted High Static Pressure Model Page 30-33 for 6.0kW to 16.0kW	nanoeX nanoe X Generator Mark 2 ECONAVI ECONAVI ready						S-60PE3R	S-71PE3R	S-100PE3R	S-125PE3R	S-140PE3R	S-160PE3R				
														S-180PE3R5B	S-200PE3R5B	S-224PE3R5B		
Cassette	NX Series 4-WAY Cassette * Panel is provided as an option (CZ-KPU3H/CZ-KPU3A) Page 42-45	nanoeX nanoe X Generator Mark 1 ECONAVI ECONAVI ready						S-6071PU3E	S-6071PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E						
Under Ceiling	NX Series Page 48-51	nanoeX nanoe X Generator Mark 2 ECONAVI ECONAVI ready						S-6071PT3E	S-6071PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E						
Wall Mounted	NX Series Page 52-53	nanoeX nanoe X Generator Mark 2 ECONAVI ECONAVI ready								S-100PK3R								
Floor Console	Page 54-55	nanoeX nanoe X Generator Mark 1		CS-Z25UFRAW	CS-Z35UFRAW	CS-Z50UFRAW												
Outdoor Unit	NX Series* ¹ ¹ Except 16kW onwards	R32 Deluxe Model Page 20-29	R32 DRED ready								U-71PZH3R5	U-100PZH3R5 U-100PZH3R8* ²	U-125PZH3R5 U-125PZH3R8* ²	U-140PZH3R5 U-140PZH3R8* ²	U-160PZH2R5 U-160PZH2R8* ²	U-180PZH2R8* ²	U-200PZH2R8* ²	U-224PZH2R8* ²
	R32 Compact Model Page 20-29	R32 DRED ready				U-36PZ3R5	U-50PZ3R5	U-60PZ3R5	U-71PZ3R5	U-100PZ3R5 U-100PZ3R8* ²	U-125PZ3R5 U-125PZ3R8* ²	U-140PZ3R5 U-140PZ3R8* ²					* ² 3 phase	
	R32 Model	R32 DRED ready	CU-Z25UBRA	CU-Z35UBRA	CU-Z50UBRA	CU-Z60UBRA												

24-hour nanoe™ X Air purification*1

While the general filters in air purifiers are effective against airborne bacteria and viruses, nanoe™ X also works to inhibit longer-living, adhered bacteria and viruses. As well as this, the CONEX remote control (CZ-RTC6BLW) gives you access to your air conditioner anywhere, anytime, so you can turn nanoe™ X on even while you're out and enjoy 24-hour quality air in your home.

Airborne Viruses

Last up to 3 hours*2

Glass surface

Virus lifespan up to 4 days*2

Adhered Viruses

Last up to 2-7 days*2

Wood


Virus lifespan up to 2 days*2

Fabrics

Virus lifespan up to 2 days*2


*1 The nanoe™ X mode can be run independently from cooling or heating mode, and needs to be on for the 24 hour air purification to function.
*2 <https://www.businessinsider.com/coronavirus-lifespan-on-surfaces-graphic-2020-3>

How does nanoe™ X technology work against viruses?



1 Huge Quantity

9.6 trillion hydroxyl radicals are generated per second, inhibiting bacteria and adhered viruses. (nanoe X Generator Mark 1 generates 4.8 trillion hydroxyl radicals/ sec)



2 Longer lifespan

By creating hydroxyl radicals contained in water, nanoe™ X technology, increasing hydroxyl radicals lifetime so that nanoe™ X can spread over long distances.

<https://www.panasonic.com/global/consumer/clean/hydroxyl/technology.html>





3 Actively fill the room

Going beyond standard filter technology, hydroxyl radicals circulate throughout rooms inhibiting both airborne and adhered bacteria and viruses.

Effective on Adhered Pollutants

nanoe™ X penetrates deep into fabrics and deodorises, inhibits bacteria, viruses, mould, allergens, pollen and hazardous substances.

nanoe™ X extensively spread out through the room to inhibit adhered pollutants adhering to surfaces, while air filters only collect airborne dust but adhered substances.



nanoe™ X

nanoe™ X works even in larger space*3




nanoe™ X technology is used in a wide range of product lines, with proven effects*4 in both large and small spaces.

*3 Depends upon the actual system installed and varies depending upon room configuration.


*4 Please refer to P.10 for more information

Standard ducted air conditioning system without nanoe™ X



Viruses or bacteria carried by a room's occupants, as well as external pollutants from open windows, may actually be circulated around a home by conventional air conditioning.

Panasonic ducted air conditioning system with nanoe™ X



With a nanoe™ X-equipped ducted unit, it's not only viruses and bacteria that are circulated, the ducted unit itself produces a massive 9.6 trillion hydroxyl radicals per second which are delivered to rooms throughout the house, inhibiting viruses and bacteria.


24hr nanoe™ X comfort, wherever you are, anywhere, anytime

Get 24 hr Quality Air for you and your loved ones by turning nanoe™ X on using Panasonic Comfort Cloud*5 even when you're out, and enjoying clean air when you're at home. nanoe™ X functions in both cooling and heating modes and is maintenance-free, helping you keep your costs down with cleaner air.

Clean air independently when you are away (Fan Mode + nanoe™ X ON)



Comfort and Clean air when you are at home (Cooling or Heating Mode + nanoe™ X ON)



Only at 70W/Hour*6
Low energy consumption with fan mode 70W per hour for a single unit.

Maintenance-Free
No maintenance required for nanoe™ X generator device.

24-hour
nanoe™ X
Air Purification


*5 Wireless LAN Remote Control for Internet Connection required optional network adaptor. Indoor temperature display and some special function are not available through the App for some models.
*6 Energy consumption may vary depending on models and the external static pressure.

Bringing nature's balance indoors

nanoe™ X technology with the benefits of hydroxyl radicals

The well-being benefits of nature are well known - but do you know the power of hydroxyl radicals?


Abundant in nature, hydroxyl radicals (also known as OH radicals) inhibit pollutants, viruses and bacteria to clean and deodorise. nanoe™ X technology can bring these incredible benefits indoors so that hard surfaces, soft furnishings, and the indoor environment can be a clean and pleasant place to be, whether at home, at work, visiting hotels, shops or restaurants.



Hydroxyl radicals contained in water

A naturally occurring process

Hydroxyl radicals are unstable molecules looking to react with other elements like hydrogen molecules of pollutants. Thanks to this reaction, hydroxyl radicals inhibit the growth of pollutants such as viruses, bacteria, moulds, and odours, breaking them down and neutralising the unpleasant effects. This naturally occurring process has major benefits to improve indoor air quality.



Bringing nature's balance indoors
nanoe™ X technology with the
benefits of hydroxyl radicals

nanoe™ X technology with the benefits of hydroxyl radicals

Panasonic's nanoe™ X technology takes a step further and brings nature's detergent - hydroxyl radicals - indoors to help create an ideal environment.

By creating hydroxyl radicals contained in water, nanoe™ X technology significantly boosts their effectiveness, increasing hydroxyl radicals lifetime from less than a second in nature, to more than 600 seconds – 10 minutes.

<https://www.panasonic.com/global/consumer/clean/hydroxyl/technology.html>



Hydroxyl radicals in nature




Hydroxyl radicals contained in water
- nanoe™ X



Effectiveness of nanoe™ X


nanoe™ X deodorises, inhibits bacteria & viruses, mould, allergens, pollen and hazardous substances, as well as moisturising the whole room for smoother skin and hair.



For further details and validation data, please refer to the following website:
https://aircon.panasonic.com/introducing/whats_nanoex.html



Thanks to the nanoe™ X properties, several types of pollutants can be inhibited.



nanoe™ X reliably reaches pollutants.




Hydroxyl radicals transform
pollutants' proteins.



Pollutants activity is inhibited.

The evolution of nanoe™ X technology

Through continuous research and development, nanoe™ X is the latest generation of Panasonic nanoe technology.



Sensitive Choice (National Asthma Council Australia) Approved

Sensitive Choice is a community service program that aims to educate people on the importance of managing asthma and allergies. Developed by the National Asthma Council Australia in 2006, the program also encourages companies to produce products and services that are more asthma and allergy aware. Panasonic and Sensitive Choice have partnered to introduce nanoe™ X to the Australian market.





Verification tests for nanoe™ X effects in large spaces




Hazardous substances

The nanoe™ X inhibited hexadecane, a chemical contained in PM2.5 (267m²)

3rd party

A third-party certification organization SIRIM Berhad (SIRIM)^{*1}, conducted the performance experiment using a 4-Way Cassette equipped with a nanoe™ X device to inhibit hexadecane^{*2}, a chemical contained in PM2.5.



^{*1} SIRIM is a premier industrial research and technology organisation in Malaysia, a wholly-owned company of the Malaysian Government under the Ministry of International Trade and Industry (MITI).

^{*2} Hexadecane is a hazardous substance contained in gasoline and diesel exhaust gas.

Testing method: Measured the amount of attached organic substances in an approximately 802 m² sized test room
Inhibition method: nanoe X Generator Mark 1 released
Test substance: Hexadecane
Test result: Broken down 92% in 8 hours (ETRC257/16/1402 (R479/19))



odours

The nanoe™ X reduced the odours adhering to fibers such as curtains and carpets (139m²)

3rd party


Cigarette smoke odour

Results

Compared to natural reduction, the nanoe™ X blast reduced the odour intensity by more than approximately 0.7 after two hours.

Testing organization

KAKEN TEST CENTER General Incorporated Foundation in Japan, international testing institute.




Testing method: Verified using the six-level odour intensity scale method in an approximately 378m² sized test room
Inhibition method: nanoe X Generator Mark 2 released
Test substance: Surface-attached cigarette smoke odour
Test result: Odour intensity reduced by 0.7 levels in 2 hours (KT-19-015089-1)

The effects of nanoe™ X are recognised by experts in each field



Professor
Masafumi Mukamoto

Osaka Prefecture University
Veterinary Infectious Disease Studies




Various types of moulds enter houses along with people and air. Even if preventive action is taken in our everyday lives, it is often very difficult to inhibit the growth of mould, especially in humid environments. With nanoe™ X, we have experimental results^{*3*4} that show we can inhibit the growth of the types of mould and bacteria commonly found in various places in the house.

Hope for the creation of more comfortable spaces for those who have problems with asthma or atopic dermatitis



Professor
Masahiro Sakaguchi

Azabu University
School of Veterinary Medicine
Laboratory of Veterinary Microbiology I




We have experimental results that show nanoe™ X is capable of inhibiting allergens, such as pollen and dust mites. It is important to take precautions against the allergens that we inadvertently inhale in our daily lives. As nanoe™ X is effective in inhibiting invisible allergens, we can expect it will create a cleaner environment. As the safety of nanoe™ X has also been verified, nanoe™ X gives peace of mind to families with small children.

^{*3} Experimental results show that nanoe™ X is effective in inhibiting the growth of the following types of mould and bacteria commonly found in homes:
Mould: Trichophyton, Cladosporium, Malassezia furfur, Sporothrix schenckii, Exophiala jeikei, Absidia corymbifera, Rhodotorula rubra, Neurospora sitophila, Schizophyllum commune
Bacteria: Methicillin-resistant Staphylococcus aureus (MRSA), Listeria monocytogenes, Bacillus subtilis, Mycobacterium smegmatis, Nocardia asteroides, Neisseria gonorrhoeae, Salmonella enterica subsp. Enterica, Haemophilus influenza, Campylobacter jejuni.
^{*4} This verification was designed to generate basic research data on the effects of nanoe™ X on the mould and bacteria in laboratory conditions different from those found in living spaces. It was not designed to evaluate product performance.

Smart comfort with CONEX

CONEX goes beyond simple remote control to combine sophistication with simplicity, offering IoT integration that connects directly to a variety of apps for next-generation solutions.



CONEX


(CZ-RTC6BL / CZ-RTC6BLW)

Simple and sophisticated design in-and-out


User friendly interface with stylish design measuring just 86 x 86 mm, CONEX is an extremely compact remote controller which looks great in any room.

Easy control and access for end users, installers, and service partners with just one remote

User-friendly day-to-day operation for end users, simplified set up for installers, and convenient after-sales service access for service partners - all with one remote control.




A next-generation remote control solution optimised for usability, whatever your needs



True-comfort for end user— Comfort Cloud App

With Comfort Cloud, even when you are out, at anytime, you can maintain air quality as you please.



For restaurant owners

Remote control makes 24-hr nanoe™ X air purification*1 in restaurants a reality, even when they're closed.



For shop owners

Air conditioning before opening and give visitors a more comfortable experience.


For boutique hotel owners

Air conditioning before your guests arrive and give them the welcome they deserve.

*1 The nanoe™ X mode can be run independently from cooling or heating mode, and needs to be on for the 24 hour air purification to function.

True-comfort for end user and installer – H&C Control App

H&C Control App makes complex initial set-up easy and allows you to respond swiftly to clients' requests via Bluetooth using a smartphone or tablet.



Advantages

Comfort day-to day operations

It's now simpler than ever for end users to further customise settings to meet their needs and perform operations including basic settings.

Intuitive operation for easy configuration

Simplified initial controller configuration together with easy access to comprehensive settings including weekly timer and maintenance.

Straightforward suggestions to clients

Share a single screen with your customer and together tailor everything to meet their needs, from basic setup to weekly timers, all in real time.

Quicker configuration for multiple controllers

Save time with templates - Copy weekly timers and settings to multiple controllers.



True-comfort for service partners – H&C Diagnosis App

The H&C Diagnosis app allows users to intuitively browse current stats and information about an air conditioner via Bluetooth® using a smartphone or tablet and without the need to use a PC.



Advantages

Acquire diagnostic information from both outside and inside

Outdoor diagnosis is now possible via a new service checker interface*1. With CONEX, operation status can be checked and failure can be diagnosed from indoors too. The information you need is now available via both indoor and outdoor units even when site access may be difficult for either indoor or outdoor unit.

*1 Available as a spare part, compatible with new NX series only.


Acquire the information you need intuitively and quickly

Easy access to real-time service parameters and service checker data allows for more accurate repairs. Actual real-time operation data can be toggled between system and refrigerant circuit views, and previously recorded data can be viewed in the history.

A comprehensive error code table and guide gives details of error codes and how to handle them.



Refrigerant circuit view



Real time data



History data



New service checker interface
(Details are written in P.81)

Maximum versatility adaptive ducted unit


Designed to deliver flexibility, performance, and comfort, Panasonic introduces an industry-leading horizontal/vertical design featuring powerful 150Pa static pressure in a compact unit. Leading-class noise level performance and nanoe™ X technology provide comfort that's carried right the way through the ductwork.



Powerful 150Pa ESP in an industry-leading vertical installation

Our groundbreaking drain pan design delivers a ducted unit that can be mounted horizontally or vertically without the need for alterations^{*1}. Even when ceiling space for ductwork is limited, the slim design and powerful 150Pa static pressure allow for discrete placement away from rooms for total installation flexibility.



^{*1} Please refer to Installation Manual for full details.



Top-class noise level performance

A proprietary improved casing design realises an even smoother airflow and low noise (22dB - 29dB) operation while effortlessly maintaining enough pressure^{*2} to deliver quiet comfort ideal for hotel and guest rooms.

^{*2} Operating at 50Pa static pressure in Low fan mode.




Superior Air Quality



The new ducted models are equipped with nanoe™ X as standard, a unique air quality improvement technology producing twice the amount of hydroxyl radicals compared to previous generations. Combined with the strong static pressure this ensures pristine nanoe™ X air travels unaffected even through multiple duct shapes at lengths of 10m, as well as making them ideal for use in larger spaces.

Note: PF3 and PE3 (16.0kW and below) ranges only.




Based on in-house test result, even with a total ductwork length up to 10m, effectiveness of nanoe™ X is maintained.

Power-packed lower profile body


The indoor units have also been completely renewed, offering a 40mm height reduction to only 250mm^{*3} and a weight reduction of up to 10%, all while maintaining the same powerful 150 Pa.

^{*3} Compared to previous PF range.



Selectable air inlet position

The air inlet position is adjustable via a removable panel to allow both rear or bottom entry, depending on the duct installation.



Note: PF3 range only.

Easy to install splittable ducted

Create comfort faster. The newly designed high static pressure ducted model is improved for a more flexible installation. By dividing the unit into 3 components, the burden of installation is reduced.


Note: In the case of the S-180PE3R5B, S-200PE3R5B, and S-224PE3R5B



Easy Installation Design

3 Components For Easy In-Ceiling Assembly

The newly designed high static pressure ducted consists of 3 components, the heat exchanger, the fan and the fan casing. For easy installation, the unit has been designed to be lifted into the roof via return air grille, separated, and easily reassembled when in position.



New Ducted Model Key Factors


Bell Shaped Keyhole for Weight Support

Part of the keyhole is newly designed with a bell shape to reduce the burden of installation. It also enables temporary attachment.



2 Wire Connectors for Easy Installation

With only 2 wire connectors, installation has become much easier and faster.



12 Bolts & Screws for Easy Assembly

Only 12 screws and bolts need to be attached, allowing for a shorter installation time.

Even cooling for all rooms

Top Grade of Airflow Volume

Providing powerful air, Panasonic's splittable ducted has increased the rate of airflow by 16%^{*1}, reaching up to 1,400 L/s^{*2}. Its powerful airflow enables faster room temperature control.




3-step Static Pressure Set Up

You can select between the three Static Pressure modes of 200 Pa / 130 Pa / 75 Pa for extra installation flexibility.



Max.200 Pa Static Pressure Setting

A maximum static pressure setting of a powerful 200Pa enables the use of long ducts for installation in a wide range of spaces. Ideal for large-scale houses, offices and restaurants.



Easy Assembly Steps

Assembly takes three easy steps, even in limited spaces.



- 1 Install the fan to the heat exchanger and tighten the screws and bolts.
- 2 Assemble the connectors.
- 3 Install the chassis and tighten the screws and bolts.



^{*1} Comparison between S-224PE3R5B and S-224PE2R5B ^{*2} In case of S-224PE3R5B

All side discharge R32 outdoor units

Panasonic’s new range of outdoor units feature intuitive technology and thoughtful engineering. The two innovative ranges of R32 units, both Deluxe and Compact, feature energy and space saving technologies, permitting installation in even the tightest and most demanding conditions.



R32
REFRIGERANT

DRED
ready

INVERTER

MEPS
COMPLIANT

Blue Fin
Condenser

More Efficient, Less Space

Whilst maintaining its strong power, new R32 outdoor units get smaller. This enables them to fit into tighter spaces. Thus you can install these units in a vast variety of areas.

All side discharge from 6.0kw to 22.4kW

U-71PZH3R5

U-100PZH3R5
U-100PZH3R8*

U-125PZH3R5
U-125PZH3R8*

U-140PZH3R5
U-140PZH3R8*

U-160PZH2R5
U-160PZH2R8*

U-180PZH2R8*

U-200PZH2R8*

U-224PZH2R8*

Industry-leading Small Body with All 1-fan Models

U-36PZ3R5

U-50PZ3R5

U-60PZ3R5

U-71PZ3R5

U-100PZ3R5
U-100PZ3R8*

U-125PZ3R5
U-125PZ3R8*


U-140PZ3R5
U-140PZ3R8*

*1 3 phase

Precise Temperature Control

Constant Comfort Air Conditioning


Another advantage of Panasonic Premium Inverter technology includes its ability to ensure precise temperature control and offer a wider power output range to perform in even the most extreme conditions in Australia, ensuring constant comfort.



Graph shows each models' 10.0 kW Inverter High Static Pressure Ducted systems performance range during cooling.


NX Series - Refurbishing Made Easy

The new NX series has been developed to use 3-wired communication, making it simple to replace the three wire systems often used in older installations.



R22 Renewal. Fast, easy to install and cost-effective

Panasonic refrigerant oil is engineered to avoid the damage to units that can happen when oil types commonly found in air-conditioning systems react with each other. As well as preventing damage, this makes replacing R22 systems with the latest R32 model as simple as reusing the existing piping and replacing the indoor and outdoor unit. Switching to the latest R32 system also improves energy efficiency by approximately 30% compared to the R22 system.



Note: Only use existing piping after checking "IN CASE OF REUSING EXISTING REFRIGERANT PIPING" in the installation manual.

Outdoor Unit

Next Generation Refrigerant: R32

R32, an innovative refrigerant in all ways imaginable: it is easy to install, and compared to most other refrigerants it has a much lower environmental impact and saves energy.

- Low Global Warming Potential (GWP): 75% less impact on global warming vs R410A
- Energy Efficient: Higher energy efficiency than R410A
- Easy Installation: This refrigerant is 100% pure which makes it easier to recycle and reuse.

R32 Deluxe R32 Compact

Energy Saving Technology

The use of energy saving design for the structure of fans, fan motors, compressors and heat exchangers results in high TCSPF and HSPF value, which ranks as one of the top in the industry.




* The graph shows 4-WAY Cassette R32 Deluxe models values.
* TCSPF/HSPF is based on Commercial (Average)

Other Advanced Technology

Increased Piping Length for Greater Design Flexibility

Adaptable to various building types and sizes
Max. piping length :
50m (7.1kW),
85m (10.0kW-14.0kW),
75m (16.0kW, 18.0kW)
60m (20.0kW, 22.4kW)



*15m if the outdoor unit is below the indoor unit (7.1kW - 14.0kW)

Product Quality and Safety

All Panasonic air conditioners undergo strict quality and safety tests before sale. This rigorous process includes obtaining all necessary Safety Approvals, to ensure that all air conditioners we sell are not only built to the highest market standards, but are also completely safe.




Quiet Mode

Quiet mode reduces outdoor operating sound by 2dB. External input signal is also available.

Demand Response Compliant

Panasonic air conditioners are equipped with a Demand Response Enabling Device (DRED) which complies to both AS 4755 and AS 3823. Panasonic continues to design and develop products that are tailored to local needs and requirements.

The Equipment Energy Efficiency (E3) program has been supporting the development of DRED standards for air-conditioners which should comply with AS 4755. The functionality will be required for all installations in the very near future




Demand control terminal is available to control 0-50-75-100% of capacities.

Outdoor Unit Dimensions

Deluxe Model

R32 Deluxe Model Dimensions (7.1kW)

U-71PZH3R5




Outdoor Unit Dimensions

Deluxe Model


R32 Deluxe Model Dimensions (10.0kW – 14.0kW)

U-100PZH3R5 / U-100PZH3R8 / U-125PZH3R5 / U-125PZH3R8 / U-140PZH3R5 / U-140PZH3R8



R32 Deluxe Model Dimensions (16.0kW – 22.4kW)

U-160PZH2R5 / U-160PZH2R8 / U-180PZH2R8 / U-200PZH2R8 / U-224PZH2R8




Compact Model

U-36PZ3R5 / U-50PZ3R5




U-100PZ3R5 / U-100PZ3R8 / U-125PZ3R5 / U-125PZ3R8 / U-140PZ3R5 / U-140PZ3R8

- 1) Mounting hole (4-R6.5), anchor bolt : M10
- 2) Refrigerant tubing (liquid tube),
flared connection (Ø9.52)
- 3) Refrigerant tubing (gas tube),
flared connection (Ø15.88)
- 4) Refrigerant tubing port
- 5) Electrical wiring port (ø13)
- 6) Electrical wiring port (ø22)
- 7) Electrical wiring port (ø27)
- 8) Electrical wiring port (ø35)




U-60PZ3R5 / U-71PZ3R5



Outdoor Unit Dimensions


R32 Model

Dimensions (2.5kW – 2.6kW)
CU-Z25UBRA




unit: mm

Dimensions (4.8kW – 5.7kW)
CU-Z50UBRA / CU-Z60UBRA



unit: mm

Dimensions (3.5kW – 3.7kW)
CU-Z35UBRA



unit: mm


Indoor Unit

High Static Pressure Ducted


High static and large airflow ducted for exceptional installation flexibility.

nanoe™ X
nanoe™ X as a standard*
*nanoe X Generator Mark 2

ECONAVI
ECONAVI ready



S-60PE3R

S-71PE3R
S-100PE3RS-125PE3R
S-140PE3R
S-160PE3RCZ-RTC6BL
CZ-RTC6BLW

CZ-RTC5B



CZ-RTC4



CZ-GAPWFC1



CZ-CENSC1


Note: Product image not to scale.

Technical focus

- Design flexibility thanks to high static pressure and large air volume
- Configurable air temperature control
- Accurate temperature control to reduce cold drafts during operation


Compact Body Size

Hidden in the ceiling, ideal when interior decor is an important consideration such as in residences with many rooms and light commercial buildings.



System Example

An inspection port (450 mm x 450 mm or more) is required at the control-box side of the indoor unit body.



Clean air. Ducts that deliver

Testing has verified that even with three bends and a total length of up to 10m, the effectiveness of nanoe™ X is maintained right through the duct to deliver clean, fresh air where it's needed.




Bend once Bend twice Bend three times

As the experiments demonstrate, even with a total ductwork length of up to 10m, effectiveness of nanoe™ X is maintained.

Note: PF3 and PE3 (16.0kW and below) ranges only.

Cold Drafts Reduced During Heating Operation

- Accurate temperature measurement by E1/E2 sensor to reduce cold drafts during heating operation.



Indoor Unit: High Static Pressure Ducted

High Static Pressure Duct R32 Deluxe model



Capacity			7.1kW	10.0kW	12.5kW	14.0kW	16.0kW		
Model Name	Indoor Unit		S-71PE3R	S-100PE3R	S-125PE3R	S-140PE3R	S-160PE3R		
	Outdoor Unit		U-71PZH3R5	U-100PZH3R5	U-100PZH3R8	U-125PZH3R5	U-140PZH3R8		
Cooling capacity : Heating capacity	kW		7.1 (2.2 - 9.0) 8.0 (2.0 - 9.0)	10.0 (3.1 - 12.5) 11.2 (3.1 - 14.0)	10.0 (3.1 - 12.5) 11.2 (3.1 - 14.0)	12.5 (3.2 - 14.0) 14.0 (3.2 - 16.0)	14.0 (3.3 - 16.0) 16.0 (3.3 - 18.0)	16.0 (5.5 - 18.0) 18.0 (5.5 - 20.0)	
		BTU/h	24,200 (7,500 - 30,700) 27,300 (6,800 - 30,700)	34,100 (10,600 - 42,700) 38,200 (10,600 - 47,800)	34,100 (10,600 - 42,700) 38,200 (10,600 - 47,800)	42,700 (10,900 - 47,800) 47,800 (10,900 - 54,600)	47,800 (11,300 - 54,600) 54,600 (11,300 - 61,400)	54,600 (18,800 - 61,400) 61,400 (18,800 - 68,200)	
EER : COP	W/W		3.48 : 3.88	3.79 : 3.78	3.79 : 3.78	3.57 : 3.80	3.26 : 3.68	3.29 : 3.53	
COP@H2 condition	W/W		2.80	2.77	2.77	2.72	2.65	2.81	
Total power input	Residential	Cooling : Heating	kW	2.04 : 2.06	2.64 : 2.96	2.64 : 2.96	3.50 : 3.68	4.30 : 4.35	4.86 : 5.10
		Hot Climate		4.68 : 4.82	5.04 : 5.10	5.04 : 5.10	4.92 : 5.17	4.29 : 4.69	4.21 : 4.61
		Average Climate		4.11 : 4.22	4.46 : 4.34	4.46 : 4.34	4.49 : 4.40	3.92 : 4.07	3.80 : 3.99
		Cold Climate		4.19 : 3.79	4.54 : 3.93	4.54 : 3.93	4.60 : 3.90	4.03 : 3.62	3.85 : 3.55
		Hot Climate		5.15 : 4.85	5.55 : 5.15	5.55 : 5.15	5.36 : 5.23	4.63 : 4.74	4.53 : 4.63
		Average Climate		5.00 : 4.52	5.47 : 4.73	5.47 : 4.73	5.55 : 4.80	4.60 : 4.39	4.54 : 4.28
Commercial	Hot Climate		5.15 : 4.85	5.55 : 5.15	5.55 : 5.15	5.36 : 5.23	4.63 : 4.74	4.53 : 4.63	
	Average Climate		5.00 : 4.52	5.47 : 4.73	5.47 : 4.73	5.55 : 4.80	4.60 : 4.39	4.54 : 4.28	
Indoor Unit									
Power source	Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	
	V		230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	
Current (rated)	Cooling : Heating		—*1	—*1	—*1	—*1	—*1	2.41 : 2.41 2.38 : 2.38	
Dimension	H x W x D	Indoor	mm	360 X 1,200 X 700	360 X 1,200 X 700	430 X 1,200 X 700	430 X 1,200 X 700	430 X 1,200 X 700	
Net weight		Indoor	kg	36	37	41	50	50	
Air volume (H/M/L)	Cooling : Heating	L/s	501 / 434 / 367 : 501 / 434 / 367	668 / 584 / 484 : 668 / 584 / 484	668 / 584 / 484 : 668 / 584 / 484	835 / 768 / 601 : 835 / 768 / 601	1,002 / 835 / 701 : 1,002 / 835 / 701	1,002 / 835 / 701 : 1,002 / 835 / 701	
External static pressure		Pa	100 (10 - 150)	100 (10 - 150)	100 (10 - 150)	100 (10 - 150)	100 (50 - 150*)	100 (50 - 150*)	
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)	45 / 44 / 43 : 45 / 44 / 43	48 / 46 / 44 : 48 / 46 / 44	48 / 46 / 44 : 48 / 46 / 44	49 / 47 / 45 : 49 / 47 / 45	51 / 49 / 47 : 51 / 49 / 47	51 / 49 / 47 : 51 / 49 / 47	
Sound power level (H/M/L)	Cooling : Heating	dB	62 / 61 / 60 : 62 / 61 / 60	70 / 68 / 66 : 70 / 68 / 66	70 / 68 / 66 : 70 / 68 / 66	71 / 69 / 67 : 71 / 69 / 67	73 / 71 / 69 : 73 / 71 / 69	73 / 71 / 69 : 73 / 71 / 69	
Number of fan speeds			3	3	3	3	3	3	
Drain piping		mm	VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	
Outdoor Unit									
Power source	Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	
	V		230V 240V	230V 240V	400V 415V	230V 240V	400V 415V	230V 240V	
Current (rated)	Cooling : Heating	A	9.85 : 9.95 9.55 : 9.65	12.8 : 14.3 12.2 : 13.7	4.25 : 4.75 4.15 : 4.60	16.7 : 17.6 16.0 : 16.8	5.60 : 5.90 5.40 : 5.70	19.7 : 19.9 18.9 : 19.1	
Dimension	H x W x D	mm	996 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,500 x 980 x 370	
Net weight		kg	66	99	99	99	99	117	
Air volume	Cooling : Heating	L/s	1,018 : 1,002	1,970 : 1,803	1,970 : 1,803	2,087 : 1,870	2,154 : 1,937	2,738 : 2,738	
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)	48 (46) : 50 (48)	52 (50) : 52 (50)	52 (50) : 52 (50)	53 (51) : 53 (51)	54 (52) : 54 (52)	58 (56) : 60 (58)	
Sound power level (Silent mode)	Cooling : Heating	dB	64 (62) : 66 (64)	68 (66) : 68 (66)	68 (66) : 68 (66)	69 (67) : 69 (67)	70 (68) : 70 (68)	76 (74) : 78 (76)	
Piping connections	Liquid / Gas	mm	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø19.05	
Pipe length range	min. - max.	m	5 - 50	5 - 85	5 - 85	5 - 85	5 - 85	5 - 75	
Elevation difference (OU located lower, OU located higher)		m	15, 30	15, 30	15, 30	15, 30	15, 30	30, 30	
Maximum chargeless length		m	30	30	30	30	30	30	
Refrigerant at shipping / Additional gas amount		g	R32 1,950 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,200 / 45 (g/m)	
Operating range	Cooling : Heating	°C	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 46 : -20 to 24	

Specifications of R32 Compact Model



Capacity			6.0kW		7.1kW		10.0kW		12.5kW		14.0kW								
Model Name		Indoor Unit	S-60PE3R		S-71PE3R		S-100PE3R		S-125PE3R		S-125PE3R		S-140PE3R						
		Outdoor Unit	U-60PZ3R5		U-71PZ3R5		U-100PZ3R5		U-125PZ3R5		U-125PZ3R8		U-140PZ3R8						
Cooling capacity : Heating capacity		kW	6.0 (2.0 - 7.1) 6.0 (1.8 - 7.0)		7.1 (2.6 - 7.7) 7.1 (2.1 - 8.1)		10.0 (3.0 - 11.5) 10.0 (3.0 - 14.0)		10.0 (3.0 - 11.5) 10.0 (3.0 - 14.0)		12.5 (3.2 - 13.5) 12.5 (3.3 - 15.0)		12.5 (3.2 - 13.5) 12.5 (3.3 - 15.0)		14.0 (3.3 - 15.0) 14.0 (3.4 - 16.0)		14.0 (3.3 - 15.0) 14.0 (3.4 - 16.0)		
			BTU/h		20,500 (6,800 - 24,200) 20,500 (6,100 - 23,900)		24,200 (8,900 - 26,300) 24,200 (7,200 - 27,600)		34,100 (10,200 - 39,200) 34,100 (10,200 - 47,800)		34,100 (10,200 - 39,200) 34,100 (10,200 - 47,800)		42,700 (10,900 - 46,100) 42,700 (11,300 - 51,200)		42,700 (10,900 - 46,100) 42,700 (11,300 - 51,200)		47,800 (11,300 - 51,200) 47,800 (11,600 - 54,600)		47,800 (11,300 - 51,200) 47,800 (11,600 - 54,600)
EER : COP		W/W	3.26 : 4.08		3.21 : 4.25		3.58 : 4.08		3.58 : 4.08		3.55 : 4.03		3.55 : 4.03		3.25 : 3.76		3.25 : 3.76		
COP@H2 condition		W/W	3.00		3.11		2.88		2.88		2.66		2.66		2.68		2.68		
Total power input		Cooling : Heating	kW	1.84 : 1.47		2.21 : 1.67		2.79 : 2.45		2.79 : 2.45		3.52 : 3.10		3.52 : 3.10		4.31 : 3.72		4.31 : 3.72	
TCSPF : HSPF	Residential	Hot Climate	3.98 : 3.95		3.96 : 4.05		4.64 : 3.95		4.64 : 3.95		4.60 : 3.93		4.60 : 3.93		4.27 : 3.79		4.27 : 3.79		
		Average Climate	3.56 : 3.88		3.59 : 4.00		4.17 : 3.81		4.17 : 3.81		4.16 : 3.79		4.16 : 3.79		3.92 : 3.64		3.92 : 3.64		
		Cold Climate	3.58 : 3.59		3.63 : 3.70		4.23 : 3.55		4.23 : 3.55		4.26 : 3.47		4.26 : 3.47		4.03 : 3.34		4.03 : 3.34		
	Commercial	Hot Climate	4.25 : 3.83		4.22 : 3.91		4.99 : 3.90		4.99 : 3.90		4.96 : 3.84		4.96 : 3.84		4.56 : 3.70		4.56 : 3.70		
		Average Climate	4.16 : 3.74		4.19 : 3.83		4.98 : 3.80		4.98 : 3.80		4.88 : 3.73		4.88 : 3.73		4.53 : 3.58		4.53 : 3.58		
		Cold Climate	4.38 : 3.58		4.41 : 3.67		5.28 : 3.61		5.28 : 3.61		5.20 : 3.52		5.20 : 3.52		4.81 : 3.40		4.81 : 3.40		
Indoor Unit																			
Power source		Phase/Hz	1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		
		V	230V 240V		230V 240V		230V 240V		230V 240V		230V 240V		230V 240V		230V 240V		230V 240V		
Dimensions		H x W x D	Indoor	mm		290 x 1,200 x 700		360 x 1,200 x 700		360 x 1,200 x 700		430 x 1,200 x 700		430 x 1,200 x 700		430 x 1,200 x 700		430 x 1,200 x 700	
Net weight		Indoor / Panel	kg	31		36		37		37		41		41		50		50	
Air volume (H/M/L)		Cooling : Heating	L/s	367 / 334 / 267 : 367 / 334 / 267		501 / 434 / 367 : 501 / 434 / 367		668 / 584 / 484 : 668 / 584 / 484		668 / 584 / 484 : 668 / 584 / 484		835 / 768 / 601 : 835 / 768 / 601		835 / 768 / 601 : 835 / 768 / 601		1,002 / 835 / 701 : 1,002 / 835 / 701		1,002 / 835 / 701 : 1,002 / 835 / 701	
External static pressure			Pa	70 (10 - 150)		100 (10 - 150)		100 (10 - 150)		100 (10 - 150)		100 (10 - 150)		100 (10 - 150)		100 (50 - 150*)		100 (50 - 150*)	
Sound pressure level (H/M/L)		Cooling : Heating	dB(A)	43 / 41 / 40 : 43 / 41 / 40		45 / 44 / 43 : 45 / 44 / 43		48 / 46 / 44 : 48 / 46 / 44		48 / 46 / 44 : 48 / 46 / 44		49 / 47 / 45 : 49 / 47 / 45		49 / 47 / 45 : 49 / 47 / 45		51 / 49 / 47 : 51 / 49 / 47		51 / 49 / 47 : 51 / 49 / 47	
Sound power level (H/M/L)		Cooling : Heating	dB	60 / 58 / 57 : 60 / 58 / 57		62 / 61 / 60 : 62 / 61 / 60		70 / 68 / 66 : 70 / 68 / 66		70 / 68 / 66 : 70 / 68 / 66		71 / 69 / 67 : 71 / 69 / 67		71 / 69 / 67 : 71 / 69 / 67		73 / 71 / 69 : 73 / 71 / 69		73 / 71 / 69 : 73 / 71 / 69	
Number of fan speeds				3		3		3		3		3		3		3		3	
Drain piping			mm	VP-25		VP-25		VP-25		VP-25		VP-25		VP-25		VP-25		VP-25	
Outdoor Unit																			
Power source		Phase/Hz	1 Phase / 50Hz		1 Phase / 50Hz		1 Phase / 50Hz		3 Phase / 50Hz		1 Phase / 50Hz		3 Phase / 50Hz		1 Phase / 50Hz		3 Phase / 50Hz		
		V	230V 240V		230V 240V		230V 240V		400V 415V		230V 240V		400V 415V		230V 240V		400V 415V		
Current (rated)		Cooling : Heating	A	8.50 : 6.85 8.15 : 6.60		10.3 : 8.00 9.90 : 7.65		13.9 : 12.4 13.4 : 11.9		4.45 : 3.90 4.25 : 3.70		17.0 : 15.0 16.3 : 14.4		5.40 : 4.80 5.20 : 4.55		19.7 : 17.0 18.9 : 16.3		6.60 : 5.70 6.40 : 5.50	
Dimensions		H x W x D	mm	695 x 875 x 320		695 x 875 x 320		996 x 980 x 370		996 x 980 x 370		996 x 980 x 370		996 x 980 x 370		996 x 980 x 370		996 x 980 x 370	
Net weight			kg	43		50		83		83		87		87		87		87	
Air volume		Cooling : Heating	L/s	701 : 701		746 : 766		1,219 : 1,219		1,219 : 1,219		1,369 : 1,336		1,369 : 1,336		1,402 : 1,369		1,402 : 1,369	
Sound pressure level (Silent mode)		Cooling : Heating	dB(A)	48 (46) : 49 (47)		49 (47) : 49 (47)		52 (50) : 52 (50)		52 (50) : 52 (50)		55 (53) : 55 (53)		55 (53) : 55 (53)		56 (54) : 56 (54)		56 (54) : 56 (54)	
Sound power level (Silent mode)		Cooling : Heating	dB	66 (64) : 67 (65)		67 (65) : 67 (65)		70 (68) : 70 (68)		70 (68) : 70 (68)		73 (71) : 73 (71)		73 (71) : 73 (71)		74 (72) : 74 (72)		74 (72) : 74 (72)	
Piping connections		Liquid / Gas	mm	Ø6.35 / Ø12.7**		Ø6.35 / Ø15.88**		Ø9.52 / Ø15.88		Ø9.52 / Ø15.88		Ø9.52 / Ø15.88		Ø9.52 / Ø15.88		Ø9.52 / Ø15.88		Ø9.52 / Ø15.88	
Pipe length range		min. - max.	m	3 - 40		3 - 40		5 - 50		5 - 50		5 - 50		5 - 50		5 - 50		5 - 50	
Elevation difference (OU located lower, OU located higher)			m	15, 30		15, 30		15, 30		15, 30		15, 30		15, 30		15, 30		15, 30	
Maximum chargeless length			m	30		30		30		30		30		30		30		30	
Refrigerant at shipping, Additional gas amount			g	R32 1,130 / 15 (g/m)		R32 1,320 / 17 (g/m)		R32 2,400 / 45 (g/m)		R32 2,400 / 45 (g/m)		R32 2,800 / 45 (g/m)		R32 2,800 / 45 (g/m)		R32 2,800 / 45 (g/m)		R32 2,800 / 45 (g/m)	
Operating range		Cooling : Heating	°C	-10 to 46 : -15 to 24		-10 to 46 : -15 to 24		-10 to 46 : -15 to 24		-10 to 46 : -15 to 24		-10 to 46 : -15 to 24		-10 to 46 : -15 to 24		-10 to 46 : -15 to 24		-10 to 46 : -15 to 24	

- Notes:
- In the case of nanoe X OFF
 - In case it is necessary to indicate the air flow volume in (l/s), the value in (m³/min.) shall be multiplied by 16.7 and rounded down the decimal point.
 - AEER and ACOP classification is at 230V(400V) only in accordance with GEMS2019.
 - TCSPF, HSPF and Total Energy consumption indicate the value of average temperature zone.
 - Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions.

*1 Outdoor power supply.
*2 Not adjustable, refer to "Indoor Fan Performance" section of technical data.
*3 For piping connection for 6.0kW unit, connect the gas socket tube (Ø12.7-Ø15.88) to the gas tubing side indoor unit and connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.
*4 For piping connection for 7.1kW unit, connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.

Indoor Unit

High Static Pressure

Splittable Ducted

High static and large airflow ducted for exceptional installation flexibility.



Self-diagnosing Function



Automatic Fan Operation



Dry mode



Automatic Restart Function



DC Motor



S-180PE3R5B
S-200PE3R5B
S-224PE3R5B



CZ-RTC6BL



CZ-RTC5B



CZ-RTC4



CZ-CAPWFC1

Note: Product image not to scale.

Technical focus


- Easy installation with splittable chassis design
 - Max. 200Pa static pressure setting*1
 - Design flexibility thanks to high static pressure and large air volume
 - DC motor equipped
- Low power input
 - Accurate temperature control to reduce cold drafts during operation
 - Configurable air temperature control

*1 In case of S-224PE3R5B


Easy Installation with Light Component

Compared to conventional models, the new Panasonic splittable ducted weighs in at approximately 10%*2 lighter. This notion is further emphasised by the unit's ability to split into three components, the heaviest of which totals at 48kg.

*2 Comparison between S-180PE3R5B and S-180PE2R5B




Dimensions of Each Component




Heat Exchanger

*3 The weight is for the 18.0kW model.
(20.0/22.4kW : 48kg)



Fan

*4 The weight is for the 18.0/20.0kW model.
(22.4kW : 29kg)



Fan Casing

Specifications of R32 Deluxe Model



Capacity			18.0kW	20.0kW	22.4kW
Model Name	Indoor Unit		S-180PE3R5B	S-200PE3R5B	S-224PE3R5B
	Outdoor Unit		U-180PZH2R8	U-200PZH2R8	U-224PZH2R8
Cooling capacity : Heating capacity	kW		18.0 (5.5-20.0) 20.0 (5.5-22.4)	20.0 (5.7-22.4) 22.4 (5.0-25.0)	22.4 (5.7-25.0) 25.0 (4.9-28.0)
		BTU/h	61,400 (18,800-68,200) 68,200 (18,800-76,400)	60,000 (19,400-76,400) 76,400 (17,100-85,300)	76,400 (19,400-85,300) 85,300 (16,700-95,500)
EER : COP	W/W		3.20 : 3.75	3.33 : 3.67	3.09 : 3.52
COP@H2 condition	W/W		2.90	2.70	2.60
Total power input	Cooling : Heating	kW	5.63 : 5.33	6.00 : 6.10	7.24 : 7.10
	Hot Climate		4.35 : 5.00	4.33 : 4.35	3.99 : 4.53
	Average Climate		3.92 : 4.27	3.96 : 3.87	3.67 : 3.86
TCSPF : HSPF	Residential	Cold Climate	4.02 : 3.74	4.03 : 3.43	3.76 : 3.38
		Hot Climate	4.75 : 5.03	4.64 : 4.35	4.27 : 4.65
	Commercial	Average Climate	4.77 : 4.62	4.72 : 4.08	4.30 : 4.27
		Cold Climate	5.11 : 4.12	5.00 : 3.70	4.56 : 3.77
Indoor Unit					
Power source		Phase/Hz	1 Phase / 50Hz	1 Phase/ 50Hz	1 Phase / 50Hz
		V	230V 240V	230V 240V	230V 240V
Current (rated)	Cooling : Heating	A	3.10 : 3.10 3.00 : 3.00	3.30 : 3.30 3.20 : 3.20	4.20 : 4.20 4.10 : 4.10
Dimensions	H x W x D	mm	486 x 1,456 x 916	486 x 1,456 x 916	486 x 1,456 x 916
Heat exchanger	H x W x D	mm	486 x 1,456 x 558	486 x 1,456 x 558	486 x 1,456 x 558
Fan	H x W x D	mm	377 x 1,150 x 427	377 x 1,150 x 427	377 x 1,150 x 427
Case	H x W x D	mm	434 x 1,178 x 360	434 x 1,178 x 360	434 x 1,178 x 360
Net weight		kg	85	86	88
Air volume	Cooling : Heating	L/s	1,200 / 1,050 / 883 1,200 / 1,050 / 883	1,200 / 1,050 / 883 1,200 / 1,050 / 883	1,400 / 1,200 / 983 1,400 / 1,200 / 983
External static pressure		Pa	60 (60 - 150)	75 (75 - 180)	75 (75 - 200)
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)	46 / 44 / 41 : 46 / 44 / 41	46 / 44 / 41 : 46 / 44 / 41	47 / 45 / 42 : 47 / 45 / 42
Sound power level (H/M/L)	Cooling : Heating	dB(A)	78 / 76 / 73 : 78 / 76 / 73	78 / 76 / 73 : 78 / 76 / 73	79 / 77 / 74 : 79 / 77 / 74
Number of fan speeds			3	3	3
Drain pipe size		mm	VP-25	VP-25	VP-25
Outdoor Unit					
Power source		Phase/Hz	3 Phase / 50Hz	3 Phase / 50Hz	3 Phase / 50Hz
		V	400V 415V	400V 415V	400V 415V
Current (rated)	Cooling : Heating	A	8.00 : 7.55 7.70 : 7.25	8.45 : 8.60 8.15 : 8.30	9.95 : 9.75 9.60 : 9.40
Dimensions	H x W x D	mm	1,500 x 980 x 370	1,500 x 980 x 370	1,500 x 980 x 370
Net weight		kg	115	128	128
Air volume	Cooling : Heating	L/s	2,733 : 2,733	2,667 : 2,667	2,667 : 2,667
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)	58 (56) : 60 (58)	58 (56) : 62 (60)	58 (56) : 62 (60)
Sound power level (Silent mode)	Cooling : Heating	dB(A)	76 (74) : 78 (76)	77 (75) : 81 (79)	77 (75) : 81 (79)
Piping connections	Liquid / Gas	mm	Ø9.52 / Ø19.05*5	Ø12.70 / Ø19.05*5	Ø12.70 / Ø19.05*5
Pipe length	min. - max.	m	5 - 75	5 - 60	5 - 60
Elevation difference (OU located lower, OU located higher)		m	30, 30	30, 30	30, 30
Maximum chargeless length		m	30	30	30
Refrigerant at shipping / Additional gas amount		g	R32 3,400 / 45/60*6 (g/m)	R32 5,200 / 80 (g/m)	R32 5,200 / 80 (g/m)
Operation ranges	Cooling : Heating	°C	-15 to 46 : -20 to 24	-15 to 46 : -20 to 24	-15 to 46 : -20 to 24

Notes:

- In the case of nance X OFF
- In case it is necessary to indicate the air flow volume in (l/s), the value in (m³/min.) shall be multiplied by 16.7 and rounded down the decimal point.
- AEER and ACOP classification is at 230V(400V) only in accordance with GEMS2019.
- TCSPF, HSPF and Total Energy consumption indicate the value of average temperature zone.
- Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions

*5 Tubing size is Ø25.40 when the piping length is over 50m for U-180PZH2R8 and 30m for U-200PZH2R8 and U-224PZH2R8.
Also, joint needs to be prepared by the site for U-180PZH2R8 when the piping length is over 50m. Please refer to technical documents for more details.

*6 Additional gas amount is 45g/m when the piping length is under 50m and 60g/m when the piping length is over 50m.

Indoor Unit

High Static Pressure

Adaptive Ducted

Control all aspects of your environment with exceptional performance and quiet operation. Vertical installation flexibility offers the perfect solution when ceiling heights are restricted.

nanoe™ X
nanoe™ X as a standard*
*nanoe X Generator Mark 2

ECONAVI
ECONAVI ready




Technical focus

- Space saving 250mm height
- DC fan motor for variable external static pressure control
- Easy to install and maintain
- Accurate temperature control to reduce cold drafts during operation
- Configurable air temperature control

Variable external static pressure control

Optimal airflow set-up is possible for different ducting design and conditions.



Note: Please refer to technical documents for detail.


Powerful 150Pa external static pressure in an industry-leading vertical installation design

Delivering static pressure up to 150Pa external static pressure, the industry-leading horizontal/vertical design offers the power you need in a compact form factor.



Selectable air inlet position


A removable panel allows air inlet position to be adjusted to enable rear or bottom entry, depending on ductwork installation.

Built-in Drain pump
(DC motor pump)

External electrical equipment box makes maintenance easy

Space saving height of 250mm for all models


250mm standardised height provides easy and uniform installation for models with different capacities, especially when ceiling heights are restricted.



Discharge air temperature control


- Possible to control discharge air temperature for accurate room temperature control.
- Possible to reduce cold drafts during heating operation.

Note: Before spec-in, please consult with an authorised Panasonic dealer.




System example

An inspection port (450 mm x 450 mm or larger) is required at the lower side of the indoor unit body.



More powerful drain pump

Using a high-lift built-in drain pump, drain piping can be elevated up to 701 mm from the base of the unit.



Indoor Unit: High Static Pressure Adaptive Ducted

Specifications of R32 Deluxe Model



Capacity				6.8kW	9.5kW	12.1kW	13.4kW
Model Name	Indoor Unit			S-6071PF3E	S-1014PF3E	S-1014PF3E	S-1014PF3E
	Outdoor Unit			U-71PZH3R5	U-100PZH3R5	U-100PZH3R8	U-125PZH3R5
Cooling capacity : Heating capacity		kW		6.8 (2.2 - 7.8) 7.5 (2.0 - 9.0)	9.5 (3.1 - 11.4) 10.8 (3.1 - 13.5)	9.5 (3.1 - 11.4) 10.8 (3.1 - 13.5)	12.1 (3.2 - 13.6) 13.5 (3.2 - 15.4)
			BTU/h	23,200 (7,500 - 26,600) 25,600 (6,800 - 30,700)	32,400 (10,600 - 38,900) 36,800 (10,600 - 46,100)	32,400 (10,600 - 38,900) 36,800 (10,600 - 46,100)	41,300 (10,900 - 46,400) 46,100 (10,900 - 52,500)
EER : COP		W/W		3.74 : 4.03	4.17 : 3.97	4.17 : 3.97	3.58 : 3.46
COP@H2 condition		W/W		2.96	2.90	2.90	2.60
Total power input		kW		1.82 : 1.86	2.28 : 2.72	2.28 : 2.72	3.38 : 3.90
TCSPF : HSPF	Residential	Cooling : Heating		1.82 : 1.86	2.28 : 2.72	2.28 : 2.72	3.38 : 3.90
		Hot Climate		5.40 : 5.49	5.93 : 5.57	5.93 : 5.57	5.37 : 5.32
		Average Climate		4.75 : 4.67	5.21 : 4.70	5.21 : 4.70	4.86 : 4.32
	Commercial	Cold Climate		4.82 : 4.13	5.29 : 4.21	5.29 : 4.21	5.03 : 3.79
		Hot Climate		6.02 : 5.54	6.59 : 5.61	6.59 : 5.61	5.95 : 5.44
		Average Climate		6.25 : 5.08	6.75 : 5.13	6.75 : 5.13	6.30 : 4.87
Indoor Unit							
Power source		Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz
		V		230V 240V	230V 240V	230V 240V	230V 240V
Dimension	H x W x D	Indoor	mm	250 x 1,000 x 730	250 x 1,400 x 730	250 x 1,400 x 730	250 X 1,400 X 730
Net weight		Indoor	kg	30	39	39	39
Air volume (H/M/L)		Cooling : Heating	L/s	350 / 317 / 250 : 350 / 317 / 250	534 / 434 / 350 : 534 / 434 / 350	534 / 434 / 350 : 534 / 434 / 350	567 / 484 / 384 : 567 / 484 / 384
External static pressure			Pa	30 (10 - 150)	40 (10 - 150)	40 (10 - 150)	50 (10 - 150)
Sound pressure level (H/M/L)		Cooling : Heating	dB(A)	30 / 26 / 23 : 30 / 26 / 23	33 / 29 / 25 : 33 / 29 / 25	33 / 29 / 25 : 33 / 29 / 25	35 / 31 / 27 : 35 / 31 / 27
Sound power level (H/M/L)		Cooling : Heating	dB	53 / 49 / 46 : 53 / 49 / 46	56 / 52 / 48 : 56 / 52 / 48	56 / 52 / 48 : 56 / 52 / 48	58 / 54 / 50 : 58 / 54 / 50
Number of fan speeds				5	5	5	5
Drain piping		mm		VP-20	VP-20	VP-20	VP-20
Outdoor Unit							
Power source		Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz
		V		230V 240V	230V 240V	400V 415V	230V 240V
Current (rated)		Cooling : Heating	A	8.60 : 8.60 8.25 : 8.35	10.8 : 12.7 10.3 : 12.2	3.60 : 4.30 3.50 : 4.15	15.8 : 18.2 15.1 : 17.5
Dimensions	H x W x D	Indoor	mm	996 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340
Net weight		Indoor	kg	66	99	99	99
Air volume		Cooling : Heating	L/s	1,018 : 1,002	1,970 : 1,803	1,970 : 1,803	2,087 : 1,870
Sound pressure level (Silent mode)		Cooling : Heating	dB(A)	48 (46) : 50 (48)	52 (50) : 52 (50)	52 (50) : 52 (50)	53 (51) : 53 (51)
Sound power level (Silent mode)		Cooling : Heating	dB	64 (62) : 66 (64)	68 (66) : 68 (66)	68 (66) : 68 (66)	69 (67) : 69 (67)
Piping connections		Liquid / Gas	mm	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88
Pipe length range	min. - max.	m		5 - 50	5 - 85	5 - 85	5 - 85
Elevation difference (OU located lower, OU located higher)		m		15, 30	15, 30	15, 30	15, 30
Maximum chargeless length		m		30	30	30	30
Refrigerant at shipping / Additional gas amount		g		R32 1,950 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)
Operation ranges		Cooling : Heating	°C	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24

Notes:

- In the case of standard installation (Horizontal installation in the ceiling, rear side air intake)
- In the case of nance X OFF
- In case it is necessary to indicate the air flow volume in (l/s), the value in (m³/min.) shall be multiplied by 16.7 and rounded down the decimal point.
- AEER and ACOP classification is at 230V(400V) only in accordance with GEMS2019.
- TCSPF, HSPF and Total Energy consumption indicate the value of average temperature zone.
- Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions
- H : High at setting 5 stage (Level 5), M : Middle at setting 5 stage (Level 3), L : Low at setting 5 stage (Level 1) Noise of L is indicated by the values at FAN mode.

*1 For piping connection for 6.0kW unit, connect the gas socket tube (Ø12.7-Ø15.88) to the gas tubing side indoor unit and connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.

*2 For piping connection for 7.1kW unit, connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.

Specifications of R32 Compact Model



Capacity				3.4kW	4.6kW	5.7kW	6.8kW	9.5kW	12.1kW	13.4kW
Model Name	Indoor Unit			S-3650PF3E	S-3650PF3E	S-6071PF3E	S-6071PF3E	S-1014PF3E	S-1014PF3E	S-1014PF3E
	Outdoor Unit			U-36PZ3R5	U-50PZ3R5	U-60PZ3R5	U-71PZ3R5	U-100PZ3R5	U-100PZ3R8	U-125PZ3R5
Cooling capacity : Heating capacity		kW		3.4 (1.3 - 4.0) 3.6 (1.3 - 4.6)	4.6 (1.5 - 5.3) 5.0 (1.5 - 5.9)	5.7 (2.0 - 6.3) 5.7 (1.8 - 7.0)	6.8 (2.1 - 7.7) 6.8 (2.1 - 8.1)	9.5 (3.0 - 11.4) 9.5 (3.0 - 13.5)	9.5 (3.0 - 11.4) 9.5 (3.0 - 13.5)	12.1 (3.2 - 13.5) 12.1 (3.3 - 15.0)
			BTU/h	11,600 (4,400 - 13,600) 12,300 (4,400 - 15,700)	15,700 (5,100 - 18,100) 17,100 (5,100 - 20,100)	19,400 (6,800 - 21,500) 23,200 (6,800 - 23,900)	23,200 (8,900 - 26,300) 32,400 (10,200 - 46,100)	32,400 (10,200 - 38,900) 32,400 (10,200 - 46,100)	32,400 (10,200 - 38,900) 32,400 (10,200 - 46,100)	41,300 (10,900 - 46,100) 41,300 (11,300 - 51,200)
EER : COP		W/W		3.78 : 4.29	3.19 : 3.62	3.54 : 4.04	3.18 : 4.00	3.57 : 4.09	3.57 : 4.09	3.40 : 3.56
COP@H2 condition		W/W		3.09	3.33	3.09	2.84	2.88	2.88	2.82
Total power input		kW		0.900 : 0.840	1.44 : 1.38	1.61 : 1.41	2.14 : 1.70	2.66 : 2.32	2.66 : 2.32	3.56 : 3.40
TCSPF : HSPF	Residential	Cooling : Heating		0.900 : 0.840	1.44 : 1.38	1.61 : 1.41	2.14 : 1.70	2.66 : 2.32	2.66 : 2.32	3.56 : 3.40
		Hot Climate		5.11 : 5.05	4.67 : 5.09	5.19 : 5.76	4.57 : 5.26	5.24 : 5.04	5.24 : 5.04	4.90 : 5.01
		Average Climate		4.36 : 4.57	4.23 : 4.31	4.67 : 4.83	4.32 : 4.42	4.52 : 4.52	4.52 : 4.52	4.42 : 4.21
	Commercial	Cold Climate		4.36 : 4.06	4.29 : 3.79	4.82 : 4.13	4.34 : 3.82	4.62 : 4.06	4.62 : 4.06	4.52 : 3.68
		Hot Climate		5.77 : 5.01	5.22 : 5.13	5.69 : 5.77	5.01 : 5.33	5.87 : 4.99	5.87 : 4.99	5.40 : 5.06
		Average Climate		5.84 : 4.72	5.96 : 4.69	6.00 : 5.23	5.53 : 4.86	5.91 : 4.68	5.91 : 4.68	5.81 : 4.60
Indoor Unit										
Power source		Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz
		V		230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V
Dimensions	H x W x D	Indoor	mm	250 x 800 x 730	250 x 800 x 730	250 x 1,000 x 730	250 x 1,000 x 730	250 x 1,400 x 730	250 x 1,400 x 730	250 x 1,400 x 730
Net weight		Indoor	kg	25	25	30	30	39	39	39
Air volume (H/M/L)		Cooling : Heating	L/s	233 / 217 / 167 : 233 / 217 / 167	267 / 250 / 200 : 267 / 250 / 200	350 / 317 / 250 : 350 / 317 / 250	350 / 317 / 250 : 350 / 317 / 250	534 / 434 / 350 : 534 / 434 / 350	534 / 434 / 350 : 534 / 434 / 350	567 / 484 / 384 : 567 / 484 / 384
External static pressure			Pa	30 (10 - 150)	30 (10 - 150)	30 (10 - 150)	30 (10 - 150)	40 (10 - 150)	40 (10 - 150)	50 (10 - 150)
Sound pressure level (H/M/L)		Cooling : Heating	dB(A)	30 / 27 / 22 : 30 / 27 / 22	34 / 30 / 25 : 34 / 30 / 25	30 / 26 / 23 : 30 / 26 / 23	30 / 26 / 23 : 30 / 26 / 23	33 / 29 / 25 : 33 / 29 / 25	33 / 29 / 25 : 33 / 29 / 25	35 / 31 / 27 : 35 / 31 / 27
Sound power level (H/M/L)		Cooling : Heating	dB	53 / 50 / 45 : 53 / 50 / 45	57 / 53 / 48 : 57 / 53 / 48	53 / 49 / 46 : 53 / 49 / 46	53 / 49 / 46 : 53 / 49 / 46	56 / 52 / 48 : 56 / 52 / 48	56 / 52 / 48 : 56 / 52 / 48	58 / 54 / 50 : 58 / 54 / 50
Number of fan speeds				5	5	5	5	5	5	5
Drain piping		mm		VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20
Outdoor Unit										
Power source		Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz
		V		230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	400V 415V	230V 240V
Current (rated)		Cooling : Heating	A	4.00 : 3.80 3.85 : 3.55	6.40 : 6.20 6.10 : 5.95	7.15 : 6.25 6.85 : 6.00	9.50 : 7.55 9.10 : 7.25	12.7 : 11.1 12.2 : 10.6	4.20 : 3.70 4.05 : 3.55	16.5 : 15.7 15.8 : 15.1
Dimensions	H x W x D	Indoor	mm	619 x 824 x 299	619 x 824 x 299	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370
Net weight		Indoor	kg	31	35	43	50	83	83	87
Air volume		Cooling : Heating	L/s	561 : 567	546 : 532	701 : 701	746 : 766	1,219 : 1,219	1,219 : 1,219	1,369 : 1,336
Sound pressure level (Silent mode)		Cooling : Heating	dB(A)	48 (46) : 49 (47)	48 (46) : 49 (47)	48 (46) : 49 (47)	49 (47) : 49 (47)	52 (50) : 52 (50)	52 (50) : 52 (50)	55 (53) : 55 (53)
Sound power level (Silent mode)		Cooling : Heating	dB	66 (64) : 67 (65)	66 (64) : 67 (65)	67 (65) : 67 (65)	67 (65) : 67 (65)	70 (68) : 70 (68)	70 (68) : 70 (68)	73 (71) : 73 (71)
Piping connections		Liquid / Gas	mm	Ø6.35 / Ø12.7	Ø6.35 / Ø12.7	Ø6.35 / Ø12.7 ^{*1}	Ø6.35 / Ø15.88 ^{*2}	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88
Pipe length range	min. - max.	m		3 - 20	3 - 30	3 - 40	3 - 40	5 - 50	5 - 50	5 - 50
Elevation difference (OU located lower, OU located higher)		m		15, 15	15, 15	15, 30	15, 30	15, 30	15, 30	15, 30
Maximum chargeless length		m		7.5	10	30	30	30	30	30
Refrigerant at shipping, Additional gas amount		g		R32 870 / 10 (g/m)	R32 1,140 / 15 (g/m)	R32 1,130 / 15 (g/m)	R32 1,320 / 17 (g/m)	R32 2,400 / 45 (g/m)	R32 2,400 / 45 (g/m)	R32 2,800 / 45 (g/m)
Operating range		Cooling : Heating	°C	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24

Indoor Unit

Ultra Slim Ducted

With a height of only 200 mm, it provides greater flexibility and adaptability for various applications. In addition, high efficiency and extreme low noise level make it highly suitable for apartments and hotels.



Self-diagnosing Function



Automatic Fan Operation



Dry mode



Automatic Restart Function



Built-in Drain Pump



DC Motor



CS-Z25UD3RAW
CS-Z35UD3RAW
CS-Z50UD3RAW
CS-Z60UD3RAW



Wired remote controller included.



CZ-TACG1*1

Note: Product image not to scale.

Technical focus

- Space saving 200mm height
 - Rear or Bottom Return Air Options
 - Built-in Drain Pump
 - DC fan motor greatly reduces power consumption
- Easy maintenance and service by external electrical box
 - 40 Pa static pressure enables ductwork to be fitted.


Ultra-slim profile for all models

200mm height for all models allows installation in very narrow ceilings.



Drain pump with increased power

Using the built-in high-lift drain pump, the drain piping rise height can be increased to 653 mm from the lower surface of the body.



Specifications

Capacity		2.5KW	3.6KW	5.0KW	6.0KW
model Name	Indoor Unit	CS-Z25UD3RAW	CS-Z35UD3RAW	CS-Z50UD3RAW	CS-Z60UD3RAW
	Outdoor Unit	CU-Z25UBRA	CU-Z35UBRA	CU-Z50UBRA	CU-Z60UBRA
Cooling capacity : Heating capacity	kW	2.60 (0.85 - 3.20) 3.30 (0.85 - 4.90)	3.70 (0.85 - 4.00) 4.20 (0.85 - 5.60)	5.00 (0.90 - 5.70) 6.10 (0.90 - 7.20)	5.60 (0.90 - 6.50) 7.00 (0.90 - 8.00)
	BTU/h	8,870 (2,900 - 10,900) 11,300 (2,900 -16,700)	12,600 (2,900 - 13,600) 14,300 (2,900 -19,100)	17,100 (3,070 - 19,400) 20,800 (3,070 - 24,600)	19,100 (3,070 - 22,200) 23,900 (3,070 - 27,300)
EER : COP	W/W	4.48 : 4.23	3.85 : 4.08	3.57 : 3.63	3.29 : 3.24
Power input (min - max)	Cooling : Heating kW	0.58 (0.24 - 0.85) : 0.78 (0.23 - 1.25)	0.96 (0.24 - 1.12) : 1.03 (0.23 - 1.57)	1.40 (0.26 - 1.78) : 1.68 (0.26 - 2.20)	1.70 (0.26 - 2.30) : 2.16 (0.26 - 2.60)
Indoor Unit					
Power source	Phase/Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz
	V	230V 240V	230V 240V	230V 240V	230V 240V
Dimensions	H × W × D	mm 200 x 750 x 640	200 x 750 x 640	200 x 750 x 640	200 x 750 x 640
Net weight	kg	19	19	19	19
Air volume	Cooling : Heating L/s	175 : 175	187 : 187	255 : 255	262 : 262
Sound pressure level (H/M/L)	Cooling : Heating dB(A)	33 / 27 / 24 : 34 / 27 / 24	33 / 26 / 23 : 35 / 27 / 24	39 / 29 / 26 : 39 / 30 / 27	41 / 30 / 27 : 41 / 32 / 29
Sound power level (H/M/L)	Cooling : Heating dB(A)	49 / 43 / 40 : 50 / 43 / 40	49 / 42 / 39 : 51 / 43 / 40	55 / 45 / 42 : 55 / 46 / 43	57 / 46 / 43 : 57 / 48 / 45
Outdoor Unit					
Power source	Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz
	V	230V 240V	230V 240V	230V 240V	230V 240V
Current (rated)	Cooling : Heating A	2.80 : 3.50 2.70 : 3.40	4.30 : 4.70 4.20 : 4.50	6.30 : 7.40 6.10 : 7.20	7.50 : 9.50 7.30 : 9.30
Dimensions	H × W × D	mm 542 x 780 x 289	619 x 824 x 299	695 x 875 x 320	695 x 875 x 320
Net weight	kg	33	35	42	43
Piping connections	Liquid / Gas	mm Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø12.70	Ø6.35 / Ø12.70
Pipe length	min. - max.	m 3 - 20	3 - 20	3 - 30	3 - 30
Elevation difference	m	15	15	20	20
Operation ranges	Cooling : Heating °C	-10 ~ +46 : -15 ~ +24	-10 ~ +46 : -15 ~ +24	-10 ~ +46 : -15 ~ +24	-10 ~ +46 : -15 ~ +24

Notes:
The Rated Capacity, Power Input and Running Current are measured in accordance with AS/NZS 3823

- Cooling: Indoor temperature: 27°C DB/ 19°C WB, Outdoor temperature: 35°C DB/ 24°C WB
- Heating: Indoor temperature: 20°C DB/ 15°C WB, Outdoor temperature: 7°C DB/ 6°C WB
- Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions
- Sound levels are measured in default status which is rear return air, when changing to bottom return air, sounds levels may be higher.
- Ultra Slim Ducted is not supported by PAC Smart Connectivity+.

*1 If you connect WLAN adaptor (CZ-TACG1) to an indoor unit other than wall mounted type and operate from the smartphone with Panasonic Comfort Cloud App, airflow direction may not be operated as it is shown on the display.

Indoor Unit

4-WAY Cassette

Featuring uniform cooling, easy installation, and with a sleek exterior, this unit is the perfect match for all commercial applications.

nanoe™ X
nanoe™ X as a standard*
*nanoe X Generator Mark 1

ECONAVI
ECONAVI ready

- Self-diagnosing Function
- Automatic Fan Operation
- DRY Dry mode
- AUTO Intelligent Auto Swing
- Automatic Restart Function
- Auto Swing (Auto Flap Control)
- DP Built-in Drain Pump
- DC Motor

S-6071PU3E
S-1014PU3E

AIR INTAKE CHAMBER

- Air intake flange (ø100) (field supply).
- Air intake box CZ-ATU2*1 for Air intake plenum.
- Air intake plenum CZ-FDU3

*1 When using Air intake box (CZ-ATU2), Air intake plenum (CZ-FDU3) required.

PANEL (CZ-KPU3H/3A)

Normal Panel : CZ-KPU3H
ECONAVI Panel : CZ-KPU3A

CZ-RTC6BL
CZ-RTC6BLW

CZ-RTC5B

CZ-RTC4

CZ-CAPWFC1

CZ-CENSC1


Note: Product image not to scale.

Technical focus

- Compact design
 - Low sound levels
 - DC fan motor for increased efficiency
 - Powerful drain pump gives 850 mm lift
- Lightweight design
 - Fresh air knockout
 - Branch duct connection
 - Optional air-intake plenum CZ-FDU3

360° Wide & Comfortable Airflow

Our design features wide-angle outlets and flaps that were designed through expert mechanics and prototype tests. Air from the center is sent farther and the air blown out of the larger, side flaps spreads throughout the room. The air comes from all for sides of the unit and expands gently in a circle centered on the indoor unit.




Temperature distribution by thermograph (cooling operation)

Simulation conditions:
P140 4-WAY Ceiling Mounted Cassette type in cooling mode
/ Floor area of 225 m²/ Ceiling height of 3 m


Wide Flap

Adding a sub flap and widening the main flap have reduced turbulence and increased airflow. Also, setting the jetting port at a wider angle allows the airflow to reach the corners of the room more quickly.




3D Turbo Fan

Using a twisted 3D blade made the unit slimmer and more compact, while also increasing the airflow. A 5-Speed mode allows the airflow to be adjusted in 5 steps to suit the situation.



High-Ceiling Installation (Up to 5 m for 10.0kW+ models)

The units can be installed in rooms with high ceilings, where they provide ample floor-level heating in the winter. (See ceiling height guidelines below.)



Ceiling height guidelines

Indoor unit	*3 settings			3-way discharge (optional air-blocking materials)	2-way discharge (optional air-blocking materials) *4
	4-way discharge	Standard (Factory setting)	High ceiling setting 1		
6071PU	3.0	3.3	3.6	3.8	4.2
1014PU	3.6	4.3	5.0	4.7	5.0

*3 When using the unit in a configuration other than the factory settings, it is necessary to make settings on site to increase airflow.
*4 Use air-blocking materials (CZ-CFU3) to completely block two discharge outlets for 2-way airflow.

Indoor Unit: 4-WAY Cassette

Specifications of R32 Deluxe Model



Capacity			7.1kW		10.0kW		12.5kW		14.0kW	
Model Name	Indoor Unit		S-6071PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	
	Outdoor Unit		U-71PZH3R5	U-100PZH3R5	U-100PZH3R8	U-125PZH3R5	U-125PZH3R8	U-140PZH3R5	U-140PZH3R8	
	Panel		Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	
Cooling capacity	kW		7.1 (2.2 - 9.0)	10.0 (3.1 - 12.5)	10.0 (3.1 - 12.5)	12.5 (3.2 - 14.0)	12.5 (3.2 - 14.0)	14.0 (3.3 - 16.0)	14.0 (3.3 - 16.0)	
			8.0 (2.0 - 9.0)	11.2 (3.1 - 14.0)	11.2 (3.1 - 14.0)	14.0 (3.2 - 16.0)	14.0 (3.2 - 16.0)	16.0 (3.3 - 18.0)	16.0 (3.3 - 18.0)	
Heating capacity	BTU/h		24,200 (7,500 - 30,700)	34,100 (10,600 - 42,700)	34,100 (10,600 - 42,700)	42,700 (10,900 - 47,800)	42,700 (10,900 - 47,800)	47,800 (11,300 - 54,600)	47,800 (11,300 - 54,600)	
			27,300 (6,800 - 30,700)	38,200 (10,600 - 47,800)	38,200 (10,600 - 47,800)	47,800 (10,900 - 54,600)	47,800 (10,900 - 54,600)	54,600 (11,300 - 61,400)	54,600 (11,300 - 61,400)	
EER : COP		W/W	4.06 : 4.30	4.41 : 5.00	4.41 : 5.00	3.80 : 4.61	3.80 : 4.61	3.41 : 4.30	3.41 : 4.30	
COP@H2 condition		W/W	2.60	2.90	2.90	2.70	2.70	2.50	2.50	
Total power input	Cooling : Heating	kW	1.75 : 1.86	2.27 : 2.24	2.27 : 2.24	3.29 : 3.04	3.29 : 3.04	4.11 : 3.72	4.11 : 3.72	
			Hot Climate	5.86 : 5.68	6.24 : 5.68	6.24 : 5.68	5.71 : 5.63	5.71 : 5.63	5.35 : 5.60	5.35 : 5.60
TCSPF : HSPF	Residential	Average Climate	5.10 : 4.77	5.53 : 5.15	5.53 : 5.15	5.20 : 4.88	5.20 : 4.88	4.93 : 4.71	4.93 : 4.71	
		Cold Climate	5.16 : 4.11	5.64 : 4.63	5.64 : 4.63	5.39 : 4.28	5.39 : 4.28	5.17 : 4.01	5.17 : 4.01	
		Hot Climate	6.58 : 5.81	6.96 : 5.66	6.96 : 5.66	6.36 : 5.74	6.36 : 5.74	5.96 : 5.76	5.96 : 5.76	
	Commercial	Average Climate	6.83 : 5.30	7.09 : 5.35	7.09 : 5.35	6.72 : 5.32	6.72 : 5.32	6.43 : 5.25	6.43 : 5.25	
		Cold Climate	7.41 : 4.63	7.69 : 4.92	7.69 : 4.92	7.37 : 4.72	7.37 : 4.72	7.10 : 4.53	7.10 : 4.53	
Indoor Unit										
Power source	H x W x D	Phase/Hz	1 Phase / 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	
		V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	
Dimensions	Indoor	mm	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	
		Panel	mm	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	
Net weight	Indoor / Panel	kg	20 / 5	25 / 5	25 / 5	25 / 5	25 / 5	25 / 5	25 / 5	
Air volume (H/M/L)	Cooling : Heating	L/s	367 / 267 / 217 : 367 / 267 / 217	601 / 434 / 300 : 601 / 434 / 300	601 / 434 / 300 : 601 / 434 / 300	617 / 450 / 317 : 617 / 450 / 317	617 / 450 / 317 : 617 / 450 / 317	634 / 484 / 334 : 634 / 484 / 334	634 / 484 / 334 : 634 / 484 / 334	
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)	37 / 31 / 28 : 37 / 31 / 28	45 / 38 / 32 : 45 / 38 / 32	45 / 38 / 32 : 45 / 38 / 32	46 / 39 / 33 : 46 / 39 / 33	46 / 39 / 33 : 46 / 39 / 33	47 / 40 / 34 : 47 / 40 / 34	47 / 40 / 34 : 47 / 40 / 34	
Sound power level (H/M/L)	Cooling : Heating	dB	52 / 46 / 43 : 52 / 46 / 43	60 / 53 / 47 : 60 / 53 / 47	60 / 53 / 47 : 60 / 53 / 47	61 / 54 / 48 : 61 / 54 / 48	61 / 54 / 48 : 61 / 54 / 48	62 / 55 / 49 : 62 / 55 / 49	62 / 55 / 49 : 62 / 55 / 49	
Number of fan speeds			5	5	5	5	5	5	5	
Drain pipe size		mm	VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	
Outdoor Unit										
Power source	H x W x D	Phase/Hz	1 Phase / 50Hz	1 Phase/ 50Hz	3 Phase/ 50Hz	1 Phase/ 50Hz	3 Phase/ 50Hz	1 Phase/ 50Hz	3 Phase/ 50Hz	
		V	230V 240V	230V 240V	400V 415V	230V 240V	400V 415V	230V 240V	400V 415V	
Current (rated)	Cooling : Heating	A	8.25 : 8.70 7.95 : 8.35	10.7 : 10.6 10.3 : 10.1	3.60 : 3.55 3.45 : 3.40	15.4 : 14.2 14.7 : 13.6	5.15 : 4.80 5.00 : 4.65	19.2 : 17.4 18.4 : 16.7	6.45 : 5.90 6.20 : 5.65	
Dimension		mm	996 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	
Net weight		kg	66	99	99	99	99	99	99	
Air volume	Cooling : Heating	m³/min	1,018 : 1,002	1,970 : 1,803	1,970 : 1,803	2,087 : 1,870	2,087 : 1,870	2,154 : 1,937	2,154 : 1,937	
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)	48 (46) : 50 (48)	52 (50) : 52 (50)	52 (50) : 52 (50)	53 (51) : 53 (51)	53 (51) : 53 (51)	54 (52) : 54 (52)	54 (52) : 54 (52)	
Sound power level (Silent mode)	Cooling : Heating	dB	64 (62) : 66 (64)	68 (66) : 68 (66)	68 (66) : 68 (66)	69 (67) : 69 (67)	69 (67) : 69 (67)	70 (68) : 70 (68)	70 (68) : 70 (68)	
Piping connections	Liquid / Gas	mm	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	
Pipe length range	min. - max.	m	5 - 50	5 - 85	5 - 85	5 - 85	5 - 85	5 - 85	5 - 85	
Elevation difference (OU located lower, OU located higher)		m	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	
Maximum chargeless length		m	30	30	30	30	30	30	30	
Refrigerant at shipping, Additional gas amount		g	R32 1,950 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	
Operating range	Cooling : Heating	°C	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	

- Notes:
- In the case of nanoe X OFF
 - In case it is necessary to indicate the air flow volume in (l/s), the value in (m³/min.) shall be multiplied by 16.7 and rounded down the decimal point.
 - AER and ACOP classification is at 230V(400V) only in accordance with GEMS2019.
 - TCSPF, HSPF and Total Energy consumption indicate the value of average temperature zone.
 - Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions
 - H:High at setting 5 stage (Level 5), M:Middle at setting 5 stage (Level 3), L:Low at setting 5 stage (Level 1)

*1 For piping connection for 6.0kW unit, connect the gas socket tube (Ø12.7-Ø15.88) to the gas tubing side indoor unit and connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.
*2 For piping connection for 7.1kW unit, connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.

Specifications of R32 Compact Model



Capacity			6.0kW	7.1kW	10.0kW	12.5kW	14.0kW			
Model Name	Indoor Unit	S-6071PU3E	S-6071PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	S-1014PU3E	
	Outdoor Unit	U-60PZ3R5	U-71PZ3R5	U-100PZ3R5	U-100PZ3R8	U-125PZ3R5	U-125PZ3R8	U-140PZ3R5	U-140PZ3R8	
	Panel	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	Standard type:CZ-KPU3H ECONAVI type:CZ-KPU3A	
Cooling capacity	kW	6.0 (2.0- 7.1)	7.1 (2.6 - 7.7)	10.0 (3.0 - 11.5)	10.0 (3.0-11.5)	12.5 (3.2 - 13.5)	12.5 (3.2 - 13.5)	14.0 (3.3 - 15.0)	14.0 (3.3 - 15.0)	
Heating capacity		6.0 (1.8 - 7.0)	7.1 (2.1 - 8.1)	10.0 (3.0 - 14.0)	10.0 (3.0 - 14.0)	12.5 (3.3 - 15.0)	12.5 (3.3 - 15.0)	14.0 (3.4 - 16.0)	14.0 (3.4 - 16.0)	
	BTU/h	20,500 (6,800 - 24,200)	24,200 (8,900 - 26,300)	34,100 (10,200 - 39,200)	34,100 (10,200-39,200)	42,700 (10,900 - 46,100)	42,700 (10,900 - 46,100)	47,800 (11,300 - 51,200)	47,800 (11,300 - 51,200)	
		20,500 (6,100 - 23,900)	24,200 (7,200 - 27,600)	34,100 (10,200 - 47,800)	34,100 (10,200 - 47,800)	42,700 (11,300 - 51,200)	42,700 (11,300 - 51,200)	47,800 (11,600 - 54,600)	47,800 (11,600 - 54,600)	
EER : COP	W/W	3.82 : 4.48	3.40 : 4.23	3.82 : 4.93	3.82 : 4.93	3.58 : 4.43	3.58 : 4.43	3.23 : 4.18	3.23 : 4.18	
COP@H2 condition	W/W	3.19	3.30	3.27	3.27	2.88	2.88	2.70	2.70	
Total power input	Cooling : Heating	kW	1.57 : 1.34	2.09 : 1.68	2.62 : 2.03	2.62 : 2.03	3.49 : 2.82	3.49 : 2.82	4.34 : 3.35	
TCSPF : HSPF	Residential	Hot Climate	5.65 : 6.69	5.12 : 5.75	5.78 : 5.43	5.78 : 5.43	5.27 : 5.56	5.27 : 5.56	4.94 : 5.52	
		Average Climate	5.04 : 5.44	4.64 : 4.85	5.00 : 5.06	5.00 : 5.06	4.73 : 4.87	4.73 : 4.87	4.54 : 4.72	4.54 : 4.72
		Cold Climate	5.23 : 4.45	4.83 : 4.14	5.10 : 4.62	5.10 : 4.62	4.85 : 4.17	4.85 : 4.17	4.69 : 3.97	4.69 : 3.97
	Commercial	Hot Climate	6.17 : 6.71	5.73 : 5.78	6.60 : 5.34	6.60 : 5.34	5.84 : 5.51	5.84 : 5.51	5.46 : 5.51	5.46 : 5.51
		Average Climate	6.29 : 5.97	6.05 : 5.26	7.05 : 5.11	7.05 : 5.11	6.29 : 5.11	6.29 : 5.11	6.19 : 5.03	6.19 : 5.03
		Cold Climate	6.75 : 5.06	6.79 : 4.61	7.94 : 4.78	7.94 : 4.78	6.95 : 4.53	6.95 : 4.53	6.89 : 4.40	6.89 : 4.40
Indoor Unit										
Power source		Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	
		V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	
Dimensions	H x W x D	Indoor	mm	256 x 840 x 840	256 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	319 x 840 x 840	
		Panel	mm	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	33.5 x 950 x 950	
Net weight	Indoor / Panel	kg	20 / 5	20 / 5	25 / 5	25 / 5	25 / 5	25 / 5	25 / 5	
Air volume (H/M/L)	Cooling : Heating	L/s	350 / 267 / 217 : 350 / 267 / 217	367 / 267 / 217 : 367 / 267 / 217	601 / 434 / 300 : 601 / 434 / 300	601 / 434 / 300 : 601 / 434 / 300	617 / 450 / 317 : 617 / 450 / 317	617 / 450 / 317 : 617 / 450 / 317	634 / 484 / 334 : 634 / 484 / 334	
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)	36 / 31 / 28 : 36 / 31 / 28	37 / 31 / 28 : 37 / 31 / 28	45 / 38 / 32 : 45 / 38 / 32	45 / 38 / 32 : 45 / 38 / 32	46 / 39 / 33 : 46 / 39 / 33	46 / 39 / 33 : 46 / 39 / 33	47 / 40 / 34 : 47 / 40 / 34	
Sound power level (H/M/L)	Cooling : Heating	dB	51 / 46 / 43 : 51 / 46 / 43	52 / 46 / 43 : 52 / 46 / 43	60 / 53 / 47 : 60 / 53 / 47	60 / 53 / 47 : 60 / 53 / 47	61 / 54 / 48 : 61 / 54 / 48	61 / 54 / 48 : 61 / 54 / 48	62 / 55 / 49 : 62 / 55 / 49	
Number of fan speeds			5	5	5	5	5	5	5	
Drain pipe size		mm	VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	VP-25	
Outdoor Unit										
Power source		Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	
		V	230V 240V	230V 240V	230V 240V	400V 415V	230V 240V	400V 415V	230V 240V	
Current (rated)	Cooling : Heating	A	7.20 : 5.95 6.90 : 5.70	9.65 : 7.45 9.25 : 7.15	12.5 : 9.70 12.0 : 9.30	4.15 : 3.20 4.00 : 3.10	16.1 : 13.0 15.4 : 12.5	5.35 : 4.35 5.15 : 4.15	20.0 : 15.5 19.2 : 14.8	
Dimensions	H x W x D	mm	695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	
Net weight		kg	43	50	83	83	87	87	87	
Air volume	Cooling : Heating	m³/min	701 : 701	746 : 766	1,219 : 1,219	1,219 : 1,219	1,369 : 1,336	1,369 : 1,336	1,402 : 1,369	
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)	48 (46) : 49 (47)	49 (47) : 49 (47)	52 (50) : 52 (50)	52 (50) : 52 (50)	55 (53) : 55 (53)	55 (53) : 55 (53)	56 (54) : 56 (54)	
Sound power level (Silent mode)	Cooling : Heating	dB	66 (64) : 67 (65)	67 (65) : 67 (65)	70 (68) : 70 (68)	70 (68) : 70 (68)	73 (71) : 73 (71)	73 (71) : 73 (71)	74 (72) : 74 (72)	
Piping connections	Liquid / Gas	mm	Ø6.35 / Ø12.7*1	Ø6.35 / Ø15.88*2	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	
Pipe length range	min. - max.	m	3 - 40	3 - 40	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	
Elevation difference (OU located lower, OU located higher)		m	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	
Maximum chargeless length		m	30	30	30	30	30	30	30	
Refrigerant at shipping, Additional gas amount		g	R32 1,130 / 15 (g/m)	R32 1,320 / 17 (g/m)	R32 2,400 / 45 (g/m)	R32 2,400 / 45 (g/m)	R32 2,800 / 45 (g/m)	R32 2,800 / 45 (g/m)	R32 2,800 / 45 (g/m)	
Operation ranges	Cooling : Heating	°C	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	

Indoor Unit

4-WAY Mini Cassette

Designed to fit perfectly into a 60 x 60 cm ceiling grid without the need to alter the bar configuration, 4-WAY Mini Cassette is ideal for small commercial and retrofit applications.


Self-diagnosing Function


Automatic Fan Operation


Dry mode


Automatic Restart Function


Auto Swing (Auto Flap Control)


Built-in Drain Pump


DC Motor



CS-Z25UB4RAW
CS-Z35UB4RAW
CS-Z50UB4RAW
CS-Z60UB4RAW



Panel CZ-BT30EW



Wireless remote controller included.



CZ-RD52CP



CZ-TACG1**


Note: Product image not to scale.

Technical focus

- Market Leading Energy Efficiency
 - Compact Design (260mm high)
 - Easy Installation
 - Built-in Drain Pump
 - Mini Cassette fits into a 60 x 60cm ceiling grid
- Powerful drain pump gives 750mm lift
 - DC fan motor with variable speed and a new heat exchanger ensures efficient power consumption
 - Fresh air knock out
 - Multi-directional airflow


Compact design

The panel is a compact (70x70 cm) so it can be installed even in a small room where space is limited.




Lighter and slimmer, easier installation

When only 260mm of indoor body height, it can easily fit in limited spaces and tight spots. (Required 288mm from bottom of panel to top of the unit)



A drain height of up to 750 mm from the ceiling surface

The internal pump allows the drain pipe to be elevated up to 750mm above the base of the unit.



Specifications

Capacity			2.5KW	3.6KW	5.0KW	6.0KW
model Name	Indoor Unit		CS-Z25UB4RAW	CS-Z35UB4RAW	CS-Z50UB4RAW	CS-Z60UB4RAW
	Outdoor Unit		CU-Z25UBRA	CU-Z35UBRA	CU-Z50UBRA	CU-Z60UBRA
Cooling capacity : Heating capacity	kW		2.50 (0.85 - 3.20) 3.20 (0.85 - 4.80)	3.50 (0.85 - 4.00) 4.00 (0.85 - 5.40)	4.80 (0.90 - 5.70) 5.00 (0.90 - 7.10)	5.70 (0.90 - 6.35) 6.00 (0.90 - 8.00)
		BTU/h	8,530 (2,900 - 10,900) 10,900 (2,900 - 16,400)	11,900 (2,900 - 13,600) 13,600 (2,900 - 18,400)	16,400 (3,070 - 19,400) 17,100 (3,070 - 24,200)	19,400 (3,070 - 21,700) 20,500 (3,070 - 27,300)
EER : COP	W/W		4.55 : 4.16	3.89 : 3.92	3.38 : 3.38	3.29 : 3.30
Power input (min - max)	Cooling : Heating	kW	0.55 (0.24 - 0.82) : 0.77 (0.23 - 1.32)	0.90 (0.24 - 1.18) : 1.02 (0.23 - 1.65)	1.42 (0.26 - 1.84) : 1.48 (0.26 - 2.41)	1.73 (0.26 - 2.20) : 1.82 (0.26 - 2.75)
Indoor Unit						
Power source	Phase/Hz		1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz	1 Phase/ 50Hz
	V		230V 240V	230V 240V	230V 240V	230V 240V
Dimensions	H x W x D	mm	260 x 575 x 575	260 x 575 x 575	260 x 575 x 575	260 x 575 x 575
Net weight		kg	18	18	18	18
Air volume	Cooling : Heating	L/s	175 : 180	175 : 195	192 : 197	237 : 253
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)	34 / 25 / 22 : 35 / 28 / 25	34 / 26 / 23 : 37 / 28 / 25	38 / 28 / 25 : 39 / 29 / 26	43 / 32 / 29 : 45 / 32 / 29
Sound power level (H/M/L)	Cooling : Heating	dB(A)	50 / 41 / 38 : 51 / 44 / 41	50 / 42 / 39 : 53 / 44 / 41	54 / 44 / 41 : 55 / 45 / 42	59 / 48 / 45 : 61 / 48 / 45
Outdoor Unit						
Power source	Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz
	V		230V 240V	230V 240V	230V 240V	230V 240V
Current (rated)	Cooling : Heating	A	2.60 : 3.50 2.50 : 3.40	4.05 : 4.55 3.95 : 4.35	6.30 : 6.50 6.10 : 6.30	7.60 : 8.00 7.40 : 7.80
Dimensions	H x W x D	mm	542 x 780 x 289	619 x 824 x 299	695 x 875 x 320	695 x 875 x 320
Net weight		kg	33	35	42	43
Piping connections	Liquid / Gas	mm	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø12.70	Ø6.35 / Ø12.70
Pipe length	min. - max.	m	3 - 20	3 - 20	3 - 30	3 - 30
Elevation difference		m	15	15	20	20
Operation ranges	Cooling : Heating	°C	-10 ~ +46 : -15 ~ +24	-10 ~ +46 : -15 ~ +24	-10 ~ +46 : -15 ~ +24	-10 ~ +46 : -15 ~ +24

Notes:
The Rated Capacity, Power Input and Running Current are measured in accordance with AS/NZS 3823
• Cooling: Indoor temperature: 27°C DB/ 19°C WB, Outdoor temperature: 35°C DB/ 24°C WB
• Heating: Indoor temperature: 20°C DB/ 15°C WB, Outdoor temperature: 7°C DB/ 6°C WB
• Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions
• 4-WAY Mini Cassette is not supported by PAC Smart Connectivity+.

** If you connect WLAN adaptor (CZ-TACG1) to an indoor unit other than wall mounted type and operate from the smartphone with Panasonic Comfort Cloud App, airflow direction may not be operated as it is shown on the display.

Indoor Unit Under Ceiling

Providing outstanding energy-saving performance, comfort and long-distance airflow distribution, these units are perfect for retail stores and schools.

nanoe™X
nanoe™ X as a standard*
*nanoe X Generator Mark 2

ECONAVI
ECONAVI ready

- 
Self-diagnosing Function
- 
Automatic Fan Operation
- 
Automatic Restart Function
- 
DC Motor



S-6071PT3E



S-1014PT3E



CZ-RTC6BL
CZ-RTC6BLW



CZ-RTC5B



CZ-RTC4



CZ-CAPWFC1



CZ-CENSC1

Note: Product image not to scale.

Compact Looking, Stylish, One-Motion Design

With its streamlined, one-motion form, the unit looks thin and compact when installed for a neat appearance in any room.
When not operating, the louver closes to provide an elegant look while also keeping the unit clean.



Energy-Saving Technology Delivering Top-Class Efficiency


Optimisation of the shape of the casing and fan assures bigger air flow and higher efficiency.
Energy-saving performance is top class in the industry.

Top Class Energy Saving

New DC fan motor




Large Diagonal Air Flow Fan



Comfortable, Long-Distance Airflow Distribution

The shape of the outlet has been optimised to provide long-distance air flow distribution.
Even in long rooms, air flow reaches every corner for exceptionally comfortable air conditioning.



High Ceiling Setting*2	Air flow distance		
	100	125	140
4.3m	Up to 12m	Up to 13m	Up to 13m

*2 Dedicated fan speed setting required.



Indoor Unit: Under Ceiling

Specifications of R32 Deluxe Model



Capacity			6.8kW		9.5kW		12.1kW		13.4kW	
Model Name		Indoor Unit	S-6071PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E	S-1014PT3E
		Outdoor Unit	U-71PZH3R5	U-100PZH3R5	U-100PZH3R8	U-125PZH3R5	U-125PZH3R8	U-140PZH3R5	U-140PZH3R8	U-140PZH3R8
Cooling capacity : Heating capacity	kW		6.8 (2.2 - 9.0) 8.0 (2.0 - 9.0)	9.5 (3.1 - 12.5) 11.2 (3.1 - 14.0)	9.5 (3.1 - 12.5) 11.2 (3.1 - 14.0)	12.1 (3.2 - 14.0) 14.0 (3.2 - 16.0)	12.1 (3.2 - 14.0) 14.0 (3.2 - 16.0)	13.4 (3.3 - 16.0) 16.0 (3.3 - 18.0)	13.4 (3.3 - 16.0) 16.0 (3.3 - 18.0)	
		BTU/h	23,200 (7,500 - 30,700) 27,300 (6,800 - 30,700)	32,400 (10,600 - 42,700) 38,200 (10,600 - 47,800)	32,400 (10,600 - 42,700) 38,200 (10,600 - 47,800)	41,300 (10,900 - 47,800) 47,800 (10,900 - 54,600)	41,300 (10,900 - 47,800) 47,800 (10,900 - 54,600)	45,700 (11,300 - 54,600) 54,600 (11,300 - 61,400)	45,700 (11,300 - 54,600) 54,600 (11,300 - 61,400)	
EER : COP	W/W		3.91 : 3.96	4.15 : 4.09	4.15 : 4.09	3.51 : 3.78	3.51 : 3.78	3.21 : 3.48	3.21 : 3.48	
COP@H2 condition	W/W		2.60	2.72	2.72	2.52	2.52	2.37	2.37	
Total power input	Cooling : Heating	kW	1.74 : 2.02	2.29 : 2.74	2.29 : 2.74	3.45 : 3.70	3.45 : 3.70	4.17 : 4.60	4.17 : 4.60	
		Hot Climate	5.96 : 5.61	6.07 : 5.59	6.07 : 5.59	5.42 : 5.37	5.42 : 5.37	5.07 : 5.26	5.07 : 5.26	
		Average Climate	5.13 : 4.63	5.25 : 4.74	5.25 : 4.74	4.85 : 4.44	4.85 : 4.44	4.61 : 4.22	4.61 : 4.22	
	Residential	Cold Climate	5.24 : 4.00	5.33 : 4.21	5.33 : 4.21	5.03 : 3.84	5.03 : 3.84	4.82 : 3.58	4.82 : 3.58	
		Hot Climate	6.74 : 5.74	6.84 : 5.66	6.84 : 5.66	6.07 : 5.50	6.07 : 5.50	5.66 : 5.45	5.66 : 5.45	
		Average Climate	6.92 : 5.18	6.95 : 5.18	6.95 : 5.18	6.41 : 4.97	6.41 : 4.97	6.10 : 4.83	6.10 : 4.83	
		Commercial	Cold Climate	7.55 : 4.53	7.54 : 4.66	7.54 : 4.66	7.03 : 4.35	7.03 : 4.35	6.71 : 4.13	6.71 : 4.13
Indoor Unit										
Power source		Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz
		V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V	230V 240V
Dimension	H x W x D	Indoor	mm	235 X 1,275 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690
Net weight		Indoor	kg	34	40	40	40	40	40	40
Air volume (H/M/L)	Cooling : Heating	L/s		350 / 300 / 258 : 350 / 300 / 258	501 / 417 / 384 : 501 / 417 / 384	501 / 417 / 384 : 501 / 417 / 384	567 / 467 / 400 : 567 / 467 / 400	567 / 467 / 400 : 567 / 467 / 400	584 / 484 / 417 : 584 / 484 / 417	584 / 484 / 417 : 584 / 484 / 417
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)		39 / 35 / 30 : 39 / 35 / 30	42 / 37 / 34 : 42 / 37 / 34	42 / 37 / 34 : 42 / 37 / 34	46 / 40 / 35 : 46 / 40 / 35	46 / 40 / 35 : 46 / 40 / 35	47 / 41 / 36 : 47 / 41 / 36	47 / 41 / 36 : 47 / 41 / 36
Sound power level (H/M/L)	Cooling : Heating	dB		57 / 53 / 48 : 57 / 53 / 48	60 / 55 / 52 : 60 / 55 / 52	60 / 55 / 52 : 60 / 55 / 52	64 / 58 / 53 : 64 / 58 / 53	64 / 58 / 53 : 64 / 58 / 53	65 / 59 / 54 : 65 / 59 / 54	65 / 59 / 54 : 65 / 59 / 54
Number of fan speeds			5	5	5	5	5	5	5	5
Drain piping		mm	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20
Outdoor Unit										
Power source		Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz	3 Phase / 50Hz
		V	230V 240V	230V 240V	400V 415V	230V 240V	400V 415V	230V 240V	400V 415V	400V 415V
Current (rated)	Cooling : Heating	A	8.20 : 9.45 7.90 : 9.05	10.8 : 12.9 10.4 : 12.4	3.65 : 4.35 3.45 : 4.15	16.1 : 17.3 15.5 : 16.6	5.40 : 5.85 5.20 : 5.65	19.5 : 21.5 18.7 : 20.6	6.55 : 7.30 6.30 : 6.95	6.55 : 7.30 6.30 : 6.95
Dimension	H x W x D	mm	996 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340	1,416 x 940 x 340
Net weight		kg	66	99	99	99	99	99	99	99
Air volume	Cooling : Heating	L/s	1,018 : 1,002	1,970 : 1,803	1,970 : 1,803	2,087 : 1,870	2,087 : 1,870	2,154 : 1,937	2,154 : 1,937	2,154 : 1,937
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)	48 (46) : 50 (48)	52 (50) : 52 (50)	52 (50) : 52 (50)	53 (51) : 53 (51)	53 (51) : 53 (51)	54 (52) : 54 (52)	54 (52) : 54 (52)	54 (52) : 54 (52)
Sound power level (Silent mode)	Cooling : Heating	dB	64 (62) : 66 (64)	68 (66) : 68 (66)	68 (66) : 68 (66)	69 (67) : 69 (67)	69 (67) : 69 (67)	70 (68) : 70 (68)	70 (68) : 70 (68)	70 (68) : 70 (68)
Piping connections	Liquid / Gas	mm	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88
Pipe length range	min. - max.	m	5 - 50	5 - 85	5 - 85	5 - 85	5 - 85	5 - 85	5 - 85	5 - 85
Elevation difference (OU located lower, OU located higher)		m	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30
Maximum chargeless length		m	30	30	30	30	30	30	30	30
Refrigerant at shipping / Additional gas amount		g	R32 1,950 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)	R32 3,050 / 45 (g/m)
Operating range	Cooling : Heating	°C	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24

Specifications of R32 Compact Model



Capacity				6.0kW		6.8kW		10.0kW		12.5kW		13.6kW	
Model Name		Indoor Unit	Outdoor Unit	S-6071PT3E	U-60PZ3R5	S-6071PT3E	U-71PZ3R5	S-1014PT3E	U-100PZ3R5	S-1014PT3E	U-125PZ3R5	S-1014PT3E	U-140PZ3R5
Cooling capacity : Heating capacity		kW		6.0 (2.0 - 7.1) 6.0 (1.8 - 7.0)	6.8 (2.6 - 7.7) 6.8 (2.1 - 8.1)	10.0 (3.0 - 11.5) 10.0 (3.0 - 14.0)	10.0 (3.0 - 11.5) 10.0 (3.0 - 14.0)	12.5 (3.2 - 13.5) 12.5 (3.3 - 15.0)	12.5 (3.2 - 13.5) 12.5 (3.3 - 15.0)	13.6 (3.3 - 15.0) 14.0 (3.4 - 16.0)	13.6 (3.3 - 15.0) 14.0 (3.4 - 16.0)		
				BTU/h	20,500 (6,800 - 24,200) 20,500 (6,100 - 23,900)	23,200 (8,900 - 26,300) 23,200 (7,200 - 27,600)	34,100 (10,200 - 39,200) 34,100 (10,200 - 47,800)	34,100 (10,200 - 39,200) 34,100 (10,200 - 47,800)	42,700 (10,900 - 46,100) 42,700 (11,300 - 51,200)	42,700 (10,900 - 46,100) 42,700 (11,300 - 51,200)	46,400 (11,300 - 51,200) 47,800 (11,600 - 54,600)	46,400 (11,300 - 51,200) 47,800 (11,600 - 54,600)	
EER : COP		W/W		3.82 : 4.41	3.33 : 4.22	3.64 : 4.24	3.64 : 4.24	3.32 : 3.89	3.32 : 3.89	3.15 : 3.70	3.15 : 3.70		
COP@H2 condition		W/W		3.19	3.24	2.70	2.70	2.57	2.57	2.53	2.53		
Total power input	Residential	Cooling : Heating	kW	1.57 : 1.36	2.04 : 1.61	2.75 : 2.36	2.75 : 2.36	3.76 : 3.21	3.76 : 3.21	4.32 : 3.78	4.32 : 3.78		
		Hot Climate		5.18 : 5.97	5.02 : 5.60	5.24 : 5.58	5.24 : 5.58	4.98 : 5.36	4.98 : 5.36	4.81 : 5.25	4.81 : 5.25		
		Average Climate		4.54 : 4.88	4.45 : 4.76	4.63 : 4.78	4.63 : 4.78	4.44 : 4.45	4.44 : 4.45	4.33 : 4.25	4.33 : 4.25		
		Cold Climate		4.61 : 4.12	4.60 : 4.09	4.70 : 4.15	4.70 : 4.15	4.57 : 3.76	4.57 : 3.76	4.48 : 3.55	4.48 : 3.55		
		Hot Climate		5.63 : 6.03	5.57 : 5.63	5.84 : 5.60	5.84 : 5.60	5.52 : 5.44	5.52 : 5.44	5.35 : 5.39	5.35 : 5.39		
		Average Climate		5.63 : 5.40	5.69 : 5.14	6.12 : 5.14	6.12 : 5.14	5.76 : 4.91	5.76 : 4.91	5.67 : 4.80	5.67 : 4.80		
	Commercial	Cold Climate		5.98 : 4.66	6.18 : 4.53	6.63 : 4.57	6.63 : 4.57	6.25 : 4.25	6.25 : 4.25	6.20 : 4.09	6.20 : 4.09		
Indoor Unit													
Power source		Phase/Hz	V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	
Dimension	H x W x D	Indoor	mm	235 X 1,275 X 690	235 X 1,275 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	235 X 1,590 X 690	
Net weight		Indoor	kg	34	34	40	40	40	40	40	40		
Air volume (H/M/L)	Cooling : Heating	L/s		334 / 283 / 242 : 334 / 283 / 242	350 / 300 / 258 : 350 / 300 / 258	501 / 417 / 384 : 501 / 417 / 384	501 / 417 / 384 : 501 / 417 / 384	567 / 467 / 400 : 567 / 467 / 400	567 / 467 / 400 : 567 / 467 / 400	584 / 484 / 417 : 584 / 484 / 417	584 / 484 / 417 : 584 / 484 / 417		
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)		38 / 34 / 29 : 38 / 34 / 29	39 / 35 / 30 : 39 / 35 / 30	42 / 37 / 34 : 42 / 37 / 34	42 / 37 / 34 : 42 / 37 / 34	46 / 40 / 35 : 46 / 40 / 35	46 / 40 / 35 : 46 / 40 / 35	47 / 41 / 36 : 47 / 41 / 36	47 / 41 / 36 : 47 / 41 / 36		
Sound power level (H/M/L)	Cooling : Heating	dB		56 / 52 / 47 : 56 / 52 / 47	57 / 53 / 48 : 57 / 53 / 48	60 / 55 / 52 : 60 / 55 / 52	60 / 55 / 52 : 60 / 55 / 52	64 / 58 / 53 : 64 / 58 / 53	64 / 58 / 53 : 64 / 58 / 53	65 / 59 / 54 : 65 / 59 / 54	65 / 59 / 54 : 65 / 59 / 54		
Number of fan speeds				5	5	5	5	5	5	5	5		
Drain piping		mm		VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20	VP-20		
Outdoor Unit													
Power source		Phase/Hz	V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	1 Phase / 50Hz 230V 240V	3 Phase / 50Hz 400V 415V	1 Phase / 50Hz 230V 240V	3 Phase / 50Hz 400V 415V	1 Phase / 50Hz 230V 240V	3 Phase / 50Hz 400V 415V		
Current (rated)	Cooling : Heating	A		7.20 : 6.05 6.90 : 5.80	9.45 : 7.15 9.05 : 6.85	13.1 : 11.3 12.6 : 10.8	4.35 : 3.75 4.20 : 3.60	17.4 : 14.8 16.7 : 14.2	5.75 : 4.95 5.55 : 4.75	20.0 : 17.5 19.1 : 16.8	6.65 : 5.80 6.40 : 5.60		
Dimension	H x W x D	mm		695 x 875 x 320	695 x 875 x 320	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370	996 x 980 x 370		
Net weight		kg		43	50	83	83	87	87	87	87		
Air volume	Cooling : Heating	L/s		701 : 701	746 : 766	1,219 : 1,219	1,219 : 1,219	1,369 : 1,336	1,369 : 1,336	1,402 : 1,369	1,402 : 1,369		
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)		48 (46) : 49 (47)	49 (47) : 49 (47)	52 (50) : 52 (50)	52 (50) : 52 (50)	55 (53) : 55 (53)	55 (53) : 55 (53)	56 (54) : 56 (54)	56 (54) : 56 (54)		
Sound power level (Silent mode)	Cooling : Heating	dB		66 (64) : 67 (65)	67 (65) : 67 (65)	70 (68) : 70 (68)	70 (68) : 70 (68)	73 (71) : 73 (71)	73 (71) : 73 (71)	74 (72) : 74 (72)	74 (72) : 74 (72)		
Piping connections	Liquid / Gas	mm		Ø6.35 / Ø12.7*1	Ø6.35 / Ø15.88*2	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88		
Pipe length range	min. - max.	m		3 - 40	3 - 40	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50	5 - 50		
Elevation difference (OU located lower, OU located higher)		m		15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30	15, 30		
Maximum chargeless length		m		30	30	30	30	30	30	30	30		
Refrigerant at shipping / Additional gas amount		g		R32 1,130 / 15 (g/m)	R32 1,320 / 17 (g/m)	R32 2,400 / 45 (g/m)	R32 2,400 / 45 (g/m)	R32 2,800 / 45 (g/m)	R32 2,800 / 45 (g/m)	R32 2,800 / 45 (g/m)	R32 2,800 / 45 (g/m)		
Operating range	Cooling : Heating	°C		-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24		

Notes:

- In the case of nanoe X OFF
- In case it is necessary to indicate the air flow volume in (l/s), the value in (m³/min.) shall be multiplied by 16.7 and rounded down the decimal point.
- AEER and ACOP classification is at 230V(400V) only in accordance with GEMS2019.
- TCSPF, HSPF and Total Energy consumption indicate the value of average temperature zone.

*1 For piping connection for 6.0kW unit, connect the gas socket tube (Ø12.7-Ø15.88) to the gas tubing side indoor unit and connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.

*2 For piping connection for 7.1kW unit, connect the liquid socket tube (Ø6.35-Ø9.52) to the liquid tubing side indoor unit.

Wall Mounted

Providing small, lightweight and low noise level design, it is ideal for small offices and other commercial applications. It also has a stylish smooth design with a washable front panel.

nanoe™X
nanoe™ X as a standard*
*nanoe X Generator Mark 2



ECONAVI ready



S-100PK3R

- Self-diagnosing Function
- Automatic Fan Operation
- Dry mode
- Intelligent Auto Swing
- Automatic Restart Function
- Auto Swing (Auto Flap Control)
- DC Motor



CZ-RTC6BL CZ-RTC6BLW CZ-RTC5B CZ-RTC4 CZ-CAPWFC1 CZ-CENSC1

Note: Product image not to scale.

Technical focus

- Closed discharge port when not in use
 - Lighter and smaller units make installation easy
 - Quiet operation
 - Smooth and durable design
- Piping outlet in six directions
 - Washable front panel
 - Air distribution is automatically altered depending on the operational mode of the unit

Closed discharge port

When the unit is turned off, the flap closes completely to prevent entry of dust into the unit and to keep the equipment clean.

Quiet operation

Low operating noise level makes these units ideal for hotels and hospital applications.

Piping outlet in six directions

Piping outlet is possible in the six directions of right, right rear, right bottom, left, left rear, left bottom, making installation easier.


Washable front panel

The indoor unit's front panel can be easily cleaned for trouble-free maintenance.



Air distribution is automatically adjusted depending on the operational mode of the unit

Air outlet angle is automatically adjusted for cooling and heating operation.



- Heating: F1 to F5
- Cooling: F1 to F3

Specifications **R32**

Capacity			9.5kW		9.0kW	
Model Name	Indoor Unit		S-100PK3R	S-100PK3R	S-100PK3R	S-100PK3R
	Outdoor Unit		U-100PZH3R5	U-100PZH3R8	U-100PZ3R5	U-100PZ3R8
Cooling capacity : Heating capacity	kW		9.5 (3.1 - 10.5) 9.5 (3.1 - 11.5)	9.5 (3.1 - 10.5) 9.5 (3.1 - 11.5)	9.0 (3.0 - 9.7) 9.0 (3.0 - 10.5)	9.0 (3.0 - 9.7) 9.0 (3.0 - 10.5)
		BTU/h	32,400 (10,600 - 35,800) 32,400 (10,600 - 39,200)	32,400 (10,600 - 35,800) 32,400 (10,600 - 39,200)	30,700 (10,200 - 33,100) 30,700 (10,200 - 35,800)	30,700 (10,200 - 33,100) 30,700 (10,200 - 35,800)
EER : COP	W/W		3.26 : 3.97	3.26 : 3.97	3.47 : 3.93	3.47 : 3.93
COP@H2 condition		W/W	2.50	2.50	2.53	2.53
Total power input	Cooling : Heating	kW	2.91 : 2.39	2.91 : 2.39	2.59 : 2.29	2.59 : 2.29
		Hot Climate	5.07 : 5.70	5.07 : 5.70	4.85 : 5.29	4.85 : 5.29
	Residential	Average Climate	4.52 : 4.74	4.52 : 4.74	4.21 : 4.55	4.21 : 4.55
		Cold Climate	4.72 : 4.10	4.72 : 4.10	4.27 : 3.99	4.27 : 3.99
	Commercial	Hot Climate	5.68 : 5.77	5.68 : 5.77	5.39 : 5.31	5.39 : 5.31
		Average Climate	5.85 : 5.20	5.85 : 5.20	5.42 : 4.87	5.42 : 4.87
TCSPF : HSPF	Cold Climate	6.42 : 4.59	6.42 : 4.59	5.82 : 4.37	5.82 : 4.37	
Indoor Unit						
Power source	Phase/Hz		1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase/ 50Hz
	V		230V 240V	230V 240V	230V 240V	230V 240V
Dimensions	H x W x D	Indoor	mm	302 x 1,120 x 236	302 x 1,120 x 236	302 x 1,120 x 236
Net weight			kg	14	14	14
Air volume (H/M/L)	Cooling : Heating	L/s	367 / 308 / 250 367 / 308 / 250	367 / 308 / 250 367 / 308 / 250	367 / 308 / 250 367 / 308 / 250	367 / 308 / 250 367 / 308 / 250
Sound pressure level (H/M/L)	Cooling : Heating	dB(A)	49 / 45 / 41 : 49 / 45 / 41	49 / 45 / 41 : 49 / 45 / 41	49 / 45 / 41 : 49 / 45 / 41	49 / 45 / 41 : 49 / 45 / 41
Sound power level (H/M/L)	Cooling : Heating	dB	65 / 61 / 57 : 65 / 61 / 57	65 / 61 / 57 : 65 / 61 / 57	65 / 61 / 57 : 65 / 61 / 57	65 / 61 / 57 : 65 / 61 / 57
Number of fan speeds			5	5	5	5
Drain pipe size			mm	VP-16	VP-16	VP-16
Outdoor Unit						
Power source	Phase/Hz		1 Phase / 50Hz	3 Phase / 50Hz	1 Phase / 50Hz	3 Phase / 50Hz
	V		230V 240V	400V 415V	230V 240V	400V 415V
Current (rated)	Cooling : Heating	A	13.8 : 11.3 13.2 : 10.8	4.60 : 3.80 4.40 : 3.60	12.4 : 10.9 11.9 : 10.5	4.10 : 3.65 3.95 : 3.50
Dimensions	H x W x D	mm	1,416 x 940 x 340	1,416 x 940 x 340	996 x 980 x 370	996 x 980 x 370
Net weight			kg	99	83	83
Air volume	Cooling : Heating	m³/min	1,970 : 1,803	1,970 : 1,803	1,219 : 1,219	1,219 : 1,219
Sound pressure level (Silent mode)	Cooling : Heating	dB(A)	52 (50) : 52 (50)	52 (50) : 52 (50)	52 (50) : 52 (50)	52 (50) : 52 (50)
Sound power level (Silent mode)	Cooling : Heating	dB	68 (66) : 68 (66)	68 (66) : 68 (66)	70 (68) : 70 (68)	70 (68) : 70 (68)
Piping connections	Liquid / Gas	mm	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88	Ø9.52 / Ø15.88
Pipe length range	min. - max.	m	5 - 85	5 - 85	5 - 50	5 - 50
Elevation difference (OU located lower, OU located higher)			m	15, 30	15, 30	15, 30
Maximum chargeless length			m	30	30	30
Refrigerant at shipping, Additional gas amount			g	R32 3,050 / 45 (g/m)	R32 2,400 / 45 (g/m)	R32 2,400 / 45 (g/m)
Operating range	Cooling : Heating	°C	-15 to 48 : -20 to 24	-15 to 48 : -20 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24

- Notes:
- In the case of nanoe X OFF
 - In case it is necessary to indicate the air flow volume in (l/s), the value in (m³/min.) shall be multiplied by 16.7 and rounded down the decimal point.
 - AEER and ACOP classification is at 230V(400V) only in accordance with GEMS2019.
 - TCSPF, HSPF and Total Energy consumption indicate the value of average temperature zone.
 - Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions
 - H:High at setting 5 stage (Level 5), M:Middle at setting 5 stage (Level 3), L:Low at setting 5 stage (Level 1)

Floor Console

This floor-type console’s slender profile integrates unobtrusively into any interior, in a position that’s also ideal when you want to warm your feet when it’s cold.

nanoe™X
nanoe™ X as a standard*
*nanoe X Generator Mark 1

- 
Self-diagnosing Function
- 
Automatic Fan Operation
- 
Dry mode
- 
Automatic Restart Function
- 
Auto Swing (Auto Flap Control)
- 
DC Motor



CS-Z25UFRAW
CS-Z35UFRAW
CS-Z50UFRAW



Wireless remote controller included.



CZ-TACG1*1


Note: Product image not to scale.

Technical focus

- A breakthrough design that integrates perfectly with the most modern environments.
- Compact design fits 50mm wall recess


Upper & Lower Vane Blow

Optimum air flow from the top and bottom of the unit assures that even your feet are kept comfortably warm. (Only during heating)



Compact Design

The design features a flat, elegant front panel that provides a neat appearance and the unit can be recessed into a wall up to 50 mm.



Super Quiet

The indoor and outdoor units deliver quiet operation and pressing the Quiet mode button lowers operation noise even further to just 19dB for indoor unit with low fan speed.



19dB*1
Indoor

*1 CS-Z25UFRAW & CS-Z35UFRAW: In the Quiet mode during heating operation with low fan speed.

Specifications of Current Model



Capacity		2.5kW	3.5kW	5.0kW	
Model Name	Indoor Unit	CS-Z25UFRAW	CS-Z35UFRAW	CS-Z50UFRAW	
	Outdoor Unit	CU-Z25UBRA	CU-Z35UBRA	CU-Z50UBRA	
Cooling capacity : Heating capacity	kW	2.50 (0.85~3.40) 3.40 (0.85~5.00)	3.50 (0.85~3.80) 4.30 (0.85~6.00)	5.00 (0.90~5.70) 5.60 (0.90~8.10)	
	BTU/h	8,530 (2,900~11,600) 11,600 (2,900~17,100)	11,900 (2,900~13,000) 14,700 (2,900~20,500)	17,100 (3,070~19,400) 19,100 (3,070~27,600)	
EER : COP	W/W	5.00 : 4.59	5.07 : 4.06	3.65 : 3.81	
Power input (min-max)	Cooling : Heating kW	0.50 (0.24-0.90) 0.74 (0.24-1.35)	0.86 (0.24-1.02) 1.06 (0.24-1.75)	1.37(0.26-1.81) : 1.47 (0.26-2.60)	
TCSPF : HSPF	Residential	Hot Climate	5.70 : 4.12	5.46 : 4.49	5.51 : 4.48
		Average Climate	5.05 : 4.21	5.01 : 4.29	5.20 : 4.18
		Cold Climate	4.97 : 3.94	5.07 : 3.78	5.37 : 3.69
	Commercial	Hot Climate	6.22 : 3.89	6.01 : 4.18	6.16 : 4.20
		Average Climate	6.40 : 3.85	6.60 : 4.00	7.34 : 3.99
		Cold Climate	6.97 : 3.78	7.31 : 3.80	8.46 : 3.76
Indoor Unit					
Power source	Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	
	V	230V 240V	230V 240V	230V 240V	
Dimensions	H x W x D	mm 600 x 750 x 207	600 x 750 x 207	600 x 750 x 207	
Net weight	kg	13	13	13	
Air volume	Cooling : Heating L/s	163 : 173	170 : 182	198 : 227	
Sound pressure level (H/M/L)	Cooling : Heating dB(A)	38 / 25 / 20 : 38 / 25 / 19	39 / 26 / 20 : 39 / 25 / 19	44 / 31 / 27 : 46 / 33 / 29	
Sound power level (H/M/L)	Cooling : Heating dB(A)	54 / 41 / 36 : 54 / 41 / 35	55 / 42 / 36 : 55 / 41 / 35	60 / 47 / 43 : 62 / 49 / 45	
Outdoor Unit					
Power source	Phase/Hz	1 Phase / 50Hz	1 Phase / 50Hz	1 Phase / 50Hz	
	V	230V 240V	230V 240V	230V 240V	
Current (rated)	Cooling : Heating A	2.40 : 3.40 2.30 : 3.25	3.90 : 4.80 3.70 : 4.60	6.20 : 6.60 6.00 : 6.40	
Dimensions	H x W x D	mm 542 x 780 x 289	619 x 824 x 299	695 x 875 x 320	
Net weight	kg	33	35	42	
Piping connections	Liquid / Gas	m Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	Ø6.35 / Ø9.52	
Pipe length	min. - max.	m 3 - 20	3 - 20	3 - 30	
Elevation difference	m	15	15	20	
Piping connections	Cooling : Heating °C	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	-10 to 46 : -15 to 24	

Notes:
The Rated Capacity, Power Input and Running Current are measured in accordance with AS/NZS 3823
• Cooling: Indoor temperature: 27°C DB/ 19°C WB, Outdoor temperature: 35°C DB/ 24°C WB
• Heating: Indoor temperature: 20°C DB/ 15°C WB, Outdoor temperature: 7°C DB/ 6°C WB
• Indoor and outdoor sound levels are determined in an anechoic chamber and may differ once the unit is installed due to ambient conditions.
• Floor console is not supported by PAC Smart Connectivity+.


*1 If you connect WLAN adaptor (CZ-TACG1) to an indoor unit other than wall mounted type and operate from the smartphone with Panasonic Comfort Cloud App, airflow direction may not be operated as it is shown on the display.

Indoor Unit Dimensions

HIGH STATIC PRESSURE DUCTED

Dimensions (6.0kW – 16.0kW)

S-60PE3R / S-71PE3R / S-100PE3R / S-125PE3R / S-140PE3R / S-160PE3R




HIGH STATIC PRESSURE SPLITTABLE DUCTED

Dimensions (18.0kW – 22.4kW)

S-180PE3R5B / S-200PE3R5B / S-224PE3R5B

- 1 Refrigerant liquid tubing (Flare)
Type 180 : $\phi 9.52$
Type 200/224 : $\phi 12.7$
- 2 Refrigerant gas tubing (Brazing)
 $\phi 19.05$
(Type 180 (50 - 75m) :
Connection tubing $\phi 19.05 \rightarrow \phi 25.4$
Type 200/224 (30 - 60m) :
Connection tubing $\phi 19.05 \rightarrow \phi 25.4$)
- 3 Power supply port
- 4 Communication port
- 5 Drain port
- 6 Air intake duct connecting side flange
- 7 Air discharge duct connecting side flange



HIGH STATIC PRESSURE ADAPTIVE DUCTED


Dimensions (3.6kW – 14.0kW)

S-3650PF3E / S-6071PF3E / S-1014PF3E

Detailed dimensions of indoor unit

Type	A	B	C	D	E	F
3650	867	800	450 (Pitch 150 × 3)	71	592	12
6071	1,067	1,000	750 (Pitch 150 × 5)	21	792	16
1014	1,467	1,400	1,050 (Pitch 150 × 7)	71	1,192	20


- a) Refrigerant tubing joint (liquid tube)
- b) Refrigerant tubing joint (gas tube)
- c) Upper drain port VP20 ($\phi 26$ mm)
200 mm flexible hose supplied
- d) Bottom drain port VP20 ($\phi 26$ mm)
- e) Suspension lug (4 – 12 × 30 mm)
- f) Power supply outlet
- g) Fresh air intake port ($\phi 100$ mm)
- h) Flange for flexible air outlet duct
- i) Electrical component box



Indoor Unit Dimensions

Dimensions (2.6kW – 5.6kW)


CS-Z25UD3RAW / CS-Z35UD3RAW / CS-Z50UD3RAW / CS-Z60UD3RAW



unit: mm

Dimensions (6.0kW – 14.0kW)


S-6071PU3E / S-1014PU3E



^{a2} Adjust the suspension bolt length so that the gap from the lower ceiling surface becomes 30 mm or more (18 mm or more from the lower surface of the body) as shown in the figure. When the suspension bolt length is long, it hits the ceiling panel and installation is not possible.

Dimensions (2.5kW – 5.7kW)

CS-Z25UB4RAW / CS-Z35UB4RAW / CS-Z50UB4RAW / CS-Z60UB4RAW




unit: mm

Indoor Unit Dimensions


Dimensions (6.0kW – 14.0kW)

- 1 Drain port VP20 (inside diameter ø26mm, drain hose supplied)
- 2 Left drain position
- 3 Refrigerant liquid tubing (ø9.52mm, flare connection)
- 4 Refrigerant gas tubing (ø15.88mm, flare connection)
- 5 Left side drain hose outlet port (cutout)
- 6 Tubing hole on wall surface (ø100mm)
- 7 Upper side tubing port
- 8 Right side drain hose outlet port (cutout)
- 9 Wireless remote controller receiver installation location




unit: mm

S-1014PT3E



unit: mm


Dimensions (9.5kW)



unit: mm

Dimensions (2.5kW – 5.0kW)

CS-Z25UFRAW / CS-Z35UFRAW / CS-Z50UFRAW



unit: mm

Smart Connectivity and Control Solutions

Panasonic offers a range of smart connectivity and control solutions for residential and commercial applications that allow you to conveniently manage and monitor air conditioning units in single or multiple locations from one mobile device. Add solutions for partners such as contractors and service providers that simplify everything from configuration to repair diagnosis and discover a streamlined, next-generation air conditioning ecosystem.




For Residential

Panasonic Comfort Cloud Home Automation Ready

Personal Control Solutions Panasonic Comfort Cloud

- Remotely manage and monitor multiple air conditioning units in your home**
Easily control and access all features of the air conditioning units with smart centralised control.
- Intuitive voice control**
Control air conditioning units by voice command connecting to smart speaker.



PLUG & PLAY FOR HOME AUTOMATION

Easily connect with integrated controllers to become part of your automated home network.



Note: For further information, please check CLIPSAL® website.

by Schneider Electric

For Light Commercial

Panasonic Comfort Cloud PAC Smart Connectivity+

Cost effective Energy Management Solution

Connectable
up to **200 Units**
with just 1 device

- Multiple location control at your convenience with Comfort Cloud**
Gain control of multiple zones and sites intuitively adjusting temperature by areas with differentiated user rights settings.
- Indoor Air Quality (IAQ) and efficient energy usage with PAC Smart Connectivity+**
 - Ultimate cooling comfort with sensing technology and automatic IAQ control.
 - Simplified Plug & Play installation with BMS connection for better energy consumption.

Wide Range of Smart Control Solutions for All Needs

Whether you're a contractor or service provider looking for solutions to streamline everything from configuration to repair diagnosis, a facility manager overseeing multiple sites or a single office, or you're simply managing a home system, we offer a range of innovative, next-generation smart control solutions to suit your needs.

For end users and facility managers			For contractors/service providers
Panasonic Comfort Cloud Intuitive and scalable air conditioning control solution using a personal mobile device.	PAC Smart Connectivity+ Offers efficient energy management with high indoor air quality (IAQ) control.	Panasonic AC Smart Cloud Monitor and manage energy consumption of multiple location through a cloud computing system.	H&C Diagnosis APP H&C Control APP Connect to APP via Bluetooth for greatly improved convenience during configuration and repair diagnosis.

For Multiple Building Management

Panasonic AC Smart Cloud

Full Control of All Installations From A Single Internet Connection Panasonic AC Smart Cloud


- Manage and monitor energy consumption patterns**
Analyse energy usage, running time and optimise temperatures to reduce energy costs.
- Centralised control solution with zero downtime**
Receive real-time status updates to prevent breakdowns.
- Flexible and scalable solution for expanding businesses and multi sites**
Adaptable solutions that can easily be upgraded for new features, meet user demand and better IT management.

*1 CZ-TACG1 or CZ-CAPWFC1 Network Adaptor required per unit. Requires an Internet connection and the App downloaded from the App Store or GooglePlay Store on your smartphone or tablet with the latest Operating System available. To use Amazon Alexa to control your air conditioner, you will need an Amazon Echo device. To use Google Assistant to control your air conditioner, you will need a Google Assistant device. Google is a trademark of Google LLC. Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates. Google Home and Alexa are compatible with the air conditioning systems shown on pages 4 and 5. Google and Alexa functionality is only available with complete air conditioning systems (including Panasonic controllers).

Panasonic Comfort Cloud

Control air conditioning units from wherever and whenever with your smartphone, by using Panasonic Comfort Cloud and WLAN smart adaptor.

This scalable solution is ideal for one system, one site or multiple locations. Coupling the adapter with the already feature rich systems, makes it an ideal solution for both residential and commercial applications.



For Residential

Remotely manage and monitor air conditioning units from anywhere anytime.

For Light Commercial

Gain control of multiple zones and sites intuitively up to 200 indoor units.

Panasonic Comfort Cloud features

Voice Control

Control air conditioning units by voice command intuitively connecting to smart speaker.*1




From 1 to 200 units

User can control up to 200 indoor units. 10 different sites, with up to 20 units / groups per site.



Easy Scheduling

Complex weekly scheduling made simple. Not only for one units, but across multiple sites and from a smartphone.



Multiple User

The Panasonic Comfort Cloud App allows multiuser access control. Restrict user access to specific units.



Energy Monitor

See the estimated power consumption and compare with other periods to see how energy bill can be reduced even more.*2



Error Codes


Error code notification through the App, provides early notification and allows for faster repair.



Application Examples



Centralised control from reception.



Multiple location control for small business.

System configuration

Network Adaptor

CZ-TACG1 CZ-CAPWFC1




CZ-TACG1: For products for small sized project.
CZ-CAPWFC1: Available for all types of VRF and PAC indoor unit.

Connection Diagram



Indoor Unit



WLAN Smart Adaptor specification

	CZ-TACG1	CZ-CAPWFC1
Input Voltage	DC 12V (Supplied from indoor unit)	
Power Consumption	Maximum 0.66W	Maximum 2.4W
Size [H x W x D]	66 x 36 x 12mm	120 x 70 x 25mm
Weight	Approx. 85g	190g (including communications lines)
Interface	Wireless LAN	
Wireless LAN Standard	IEEE 802.11 b/g/n	
Frequency range	2.4GHz band	
Encryption	WPA2-PSK(TKIP/AES)	
Operation range	0-55°C, 20 - 80RH%	

*1 CZ-TACG1 or CZ-CAPWFC1 Network Adaptor required per unit.
Requires an Internet connection and the App downloaded from the App Store or GooglePlay Store on your smartphone or tablet with the latest Operating System available.
To use Amazon Alexa to control your air conditioner, you will need an Amazon Echo device.
To use Google Assistant to control your air conditioner, you will need a Google Assistant device.
Google is a trademark of Google LLC.
Amazon, Alexa and all related logos are trademarks of Amazon.com, Inc. or its affiliates.
Google Home and Alexa are compatible with the air conditioning systems shown on pages 4 and 5.
Google and Alexa functionality is only available with complete air conditioning systems (including Panasonic controllers).
*2 Function available depending on the model.



Comfort Cloud App



Compatible Device and Browsers

1. IOS 9.0 or above
2. Android 5.0 or above

Plug & Play for Home Automation

Easily connect with integrated controllers to become part of your automated home network. Plug & Play with Clipsal solutions to enjoy simplicity you've been waiting for, empowering you to take control of your home's technology.



Panasonic

Schneider
Electric

Panasonic partnering with Schneider Electric offering home automation solution with CLIPSAL interfaces and devices.

CLIPSAL
by Schneider Electric

Note: For further information please check CLIPSAL® website.

Easy Design / Plug & Play


Clipsal control solution brings you smart home technologies and enables you to control devices at your fingertips from any smart phone or tablet. Panasonic air conditioners are ready for this smart home automation with just plug-and-play connectivity.



Easy Design
Plug & Play



Applies to selected Panasonic Air Conditioning systems only, please consult with Panasonic for more details.



Case study

Panasonic VRF system was selected for the smart apartments, Lilydale Grove, which integrates robust automation technology to simplify your life. While other air conditioner brands need a adaptor to connect to HEMS, Panasonic can seamlessly connect with Schneider's Home automation, one of the market leaders in the HEMS industry.

- Air conditioning system FSV Heat Recovery (20 systems)
FSV Heat Pump (4 systems)
- Cooling Capacity 742kW
- Indoor units 278 units
- Control System SE8000 series 278units

Note: System combination as of July 2020



PAC Smart Connectivity+

Through thorough energy management, Panasonic's PAC Smart Connectivity+*¹ is a completely new, state-of-the-art solution providing energy saving and comfort as well as simple installation, operation and maintenance.



PAC Smart Connectivity+

PAC Smart Connectivity+ offers efficient energy management and a new air conditioning control solution with high IAQ (Indoor Air Quality).

Energy Management System for Rooms

Each room is monitored by high-precision sensors, making it possible to make every room's temperature comfortable without wasting energy.

Management System for the Entire Building

A Building Energy Management System (BMS) can also be connected for Plug & Play centralised control of the building's entire energy consumption.

Advantages



Dramatic Reduction of OpEx with Outstanding IAQ.

- 3 Built-in sensors: Temperature, RH and Occupancy
- ZigBee wireless sensors: CO₂/Temperature/RH%, window/door, ceiling/wall



User-/Owner-friendly.

- Colour touch screen
- Ease and simply of use
- 22 Languages
- Easy-to-understand error description



Ultimate Customisation.

- Background colour customisable
- Custom display/icons, messages
- Programmable logic (also stand alone)
- Various controls and various external connection devices



Easy Design and Plug and Play to Reduce CapEx.

- Simple Plug & Play connection to Building Energy Management System (BMS)
- Stand alone or BMS connected
- Easy Installation of Zigbee Sensors



PAC Smart Connectivity+ ~New SE8000 series~

1. Quality Air Control

Optimum IAQ is realized using the CO₂ & humidity sensors. The interior remains comfortable, while heating and cooling costs are minimized.

The CO₂ sensor controls ventilation systems which contributes to improving the room's air quality.



2. Room Key Card or Key Cardless Solutions for Hotels

Solutions are provided that meet the needs of various regions and hotel grades.

Whilst the previous model's automatic detection function offered optimal air conditioning with or without a hotel room key card, the latest model enables conventional key cards to control air conditioners and other devices coordinately. The increase in the types of devices that can be connected enables customized control of any hotel room.

3. Other Equipment Control

One room controller manages various devices including lighting and the blinds. A ventilation system and other external connection devices can be connected by using HRC*² or SE8350 so that various control is possible with this controller alone, even without BMS.




*¹ Not compatible with Ultra Slim Ducted, 4-Way Mini Cassette and Floor Console systems.

*² Available through a Schneider Electric distribution channel.


Energy Management System for Rooms

By installing a ceiling motion sensor, wall motion temperature sensor, window/door sensor, and CO2 sensor in the room, ideal, waste-free air conditioning is achieved.



Sensing & Control technology

Using sensors from Schneider Electric, high-quality occupancy control and automatic IAQ control were realised. The sensors detect the presence or absence of occupants, and the opening and closing of doors and windows to achieve the most efficient energy management for exceptional air-conditioned comfort. Flexible installation is possible to match different applications and building features such as walls, ceilings and proximity to doors and windows. No wiring means extra installation versatility.



Batteries last for up to five years (10-year battery for CO2 sensor) and are easy to install and replace.

Door/Window Sensor Door and window contact detection sensor to monitor opening and closing.	Wall/Ceiling motion/temperature/humidity Sensor Wall and ceiling sensor to detect the presence or absence of occupants.	CO2 Sensor Monitor indoor air quality, review data on interfacing devices, and control fresh air inside customizable zones.
Water Leakage Sensor Two sensing pads under the body activate when water is present between the two pads. Detecting the water, the sensor reports the event to the controller.	SER8350 Programmable controller for HVAC equipment. Includes local memory to store control sequence.	Hotel Room Controller (HRC)*1 The Hotel Room Controller controls connected guest room devices and aggregates data, making it visible to guest room and property management systems.


*1 Available through a Schneider Electric distribution channel.

Management System for the Entire Building*2

The smarter solution to simplify energy management, optimise building efficiency and drive savings.

Plug and Play BMS connection.

With the SER8150, connection to BMS is extremely easy. Better still, a remote controller is all that's needed to enable use as a stand-alone system. In addition to dramatically reducing the burden on system integrators, this cuts costs.



- A** SER8150 smart controller with direct hub to ZigBee® Pro sensors. Great Occupancy and IAQ control. Ex: Hotel room occupancy check by PIR sensor, IAQ by CO2 sensor, Door / Window contacts.
- B** BACnet MS/TP or Modbus RTU communication are selectable
- C** For Schneider Electric BMS connection, Panasonic VRF widgets enable easy Plug and Play. Better understanding for VRF as a chiller system.

*2 Graphic shows combination of products from Panasonic, Schneider Electric and others. Currently, some products might not available in Australia, please consult authorised dealer for more details.

Smart Management Solutions


1 Hotels
Room Key Card or Key Cardless
Solutions for Hotels

The SER8150 and ZigBee Sensor automatic detection function offer optimal air conditioning regardless of whether there is a hotel room key or not. Sensors detect the presence or absence of occupants and the opening and closing of doors and windows for the optimum air-conditioned environment guests expect. Automatic control ensures the most efficient operation when guests are away or when windows are open. This contributes to an appreciable reduction in operation costs.




1. Remote sensing & IAQ control

In addition to detecting a room's temperature, humidity and CO2 concentration, ZigBee remote sensors detect the opening/closing of windows and doors, and the presence/absence of people in a room. Various IAQ controls and detailed energy savings are possible by using SE8350 based on this detected information.




2. BMS Connectivity

By setting HRC*1 as the guestroom controller, sensing, control and BMS connection can be realized in coordination with SER8150!




3. Key Cardless control

The introduction of SE8350 and HRC enables conventional wired keycards to be connected to the system so that it is possible to meet the specific requirements of various hotel and room types.



4. Other control

The introduction of SE8350 and HRC enables the on/off control of devices having dry contact input, such as ventilation, lighting and blinds.



*1 Available through a Schneider Electric distribution channel.

2 Small and Medium Offices



CO2 sensors (option) and Humidity sensors

CO2 sensors (option) take measurements in units of ppm, and humidity sensors enable fine air quality control. This creates the most comfortable space for occupants while contributing to improved employee satisfaction.

3 Super Markets



Humidity sensors

Humidity sensors enable automatic dehumidification for the optimum IAQ regardless of climatic conditions. This creates an even more comfortable environment for customers, employees, and products themselves.

Innovative and Unrivalled Advantages

Colour and Design to Match Office Interiors

Colour combinations and design can be set to match different facilities.



Customisation in 22 Languages Possible

The display can be customised to match the native languages of guests to enable smooth, stress-free communication for hospitality at its finest.



Easy-to-Understand Error Description

Error description during an emergency is easy to understand, enabling staff to respond quickly.



Programmable Logic


Full customisation of remote control logic possible, and updating to match conditions.



Smart Connectivity Devices



- Features
- Up to 5-year battery life batteries included (CO2 sensor is 10 years)
 - Battery level is a point
 - Sensor points visible when SER8150 is integrated via BACnet MS/TP
 - Sensor status and battery level visible when SER8150 is integrated via ZigBee® Pro




Reference	Description
SER8150R0B1194	Pana Net Con, RH, No PIR, SE Brand, R1R2
SER8150R5B1194	Pana Net Con, RH, PIR, SE Brand, R1R2
VCMB000V5094P	Wireless ZigBee Pro communication card
SE8350	
SE8350U0800	BACnet MS/TP, 24VAC, 7UI/4UO/4DO
HRC*1	
HRCEP14R	Hotel Room Expansion Module 14IO
HRCPBG28R	Hotel Room Controller 28IO
HRCPDG42R	Hotel Room Controller w/Display 42IO

PAC Smart Connectivity+ controller external dimensions

Room Controller for SER8150


Dimensions



Specifications

Dimensions
Height: 12cm/4.72in
Width: 8.6cm/3.39in
Depth: 2.7cm/1.06in
Power Requirements
16 Vdc from Panasonic R-R IDU connectors
50/60 Hz, 4VA, Class 2 Supply
Range from Indoor Unit
Recommended 500ft (150 m)
Operating Conditions
0 °C to 50 °C (32°F to 122°F)
0% to 95% R.H. non-condensing
Storage Conditions
-30°C to 50°C (-22°F to 122°F)
0% to 95% R.H. non-condensing
Temperature Sensor
Local 10 K NTC type 2 thermistor
Temperature Sensor Resolution
± 0.1 °C (± 0.2 °F)
Temperature Sensor Accuracy
± 0.5 °C (± 0.9 °F) @ 21 °C (70 °F) typical calibrated

Humidity Sensor and Calibration
Single point calibrated bulk polymer type sensor
Humidity Sensor Precision
Reading range from 10 to 90 % R.H. non-condensing 10 to 20% precision: 10%
20% to 80% precision: 5%
80% to 90% precision: 10%
Humidity Sensor Stability
Less than 1.0 % yearly (typical drift)
Wiring
Maximum wire length between last indoor unit to SER8150Rx B1194 equals 490ft (150m) with AWG #18 wire (0.82 mm²). Refer to Panasonic VRF guidelines "Wiring System Diagram for Remote Controller" for this limitation.
Approximate Shipping Weight
0.34 kg (0.75 lb)



THIS PRODUCT FOR COMMERCIAL USE ONLY

Water Leakage Sensor

Dimensions



Specifications

Dimensions
70.8mmx66.7mmx19mm
Colour
White
Weight
64g
Communication
ZigBee 3.0 HA
Battery Voltage
3V
Battery Life
Up to 5 years
Rated Power
≥ 90 mW
Maximum Transmitted Power
≤ 5 dBm
Ambient Temperature
-10° - +50°C
Frequency Band
2405-2480 MHz




Check with your local government for instruction on disposal of these products.

Reference	Description
ZigBee Sensors	
SED-CO2-G-5045	Sensor with Room CO2, Temperature and Humidity
SED-TRH-G-5045	Sensor with Room Temperature and Humidity
SED-WDC-G-5045	Door/Window Sensor
SED-MTH-G-5045	Wall/Ceiling motion/temperature/humidity Sensor
SED-WLS-G-5045	Water Leakage Sensor

Wall/Ceiling Wireless Sensor SED-MTH-G-5045

Dimensions



Specifications

Dimensions
70mm diam. x 26.6mm
Colour
White
Weight
59g
Communication
ZigBee 3.0 HA
Detection Range
Ceiling:
Ø4m (installation height 2.5m)
Wall:
R5m (installation height 1.2m)
Battery Voltage
3V
Battery Cell
LR03 AAA (2pcs)
Battery Life
Up to 5 years
Ambient Temperature
-10° - +50°C


Certification



Check with your local government for instruction on disposal of these products.

Door/Window Wireless Sensor SED-WDC-G-5045


Dimensions



Specifications

Dimensions
Master part: 50mmx33mmx16.3mm Slave part: 50mmx9mmx9mm
Colour
White/transp.
Weight
30g
Communication
ZigBee 3.0 HA
Detection Range
Trigger 'close': wood 30mm, metal 18mm
Trigger 'open': wood 32mm, metal 20mm
Battery Voltage
3V
Battery Cell
CR2450
Battery Life
Up to 5 years
Ambient Temperature
-10° - +50°C


Certification



Check with your local government for instruction on disposal of these products.


CO2 Sensor SED-CO2-G-5045

Dimensions



Specifications



Dimensions
3.26in x 2.85in x 0.72in
82.9 mm x 72.4 mm x 18.4 mm
Operating Temperature
0°C to 50°C (32°F to 122°F)
Temperature Accuracy
±0.3°C (0.54 °F) typical within operating range
Humidity Range
0% to 100%
Humidity Accuracy
± 3% RH (typical within 0% to 80% RH)
Measurement Range
0 to 5000 ppm
Measurement/Transmission Intervals
2.5 minutes (day), 10 minutes (evening)
Note: Battery life will be reduced should interval be shortened (i.e. using remote temperature/humidity functions)
±60ppm +3% of reading (400 - 2,000ppm range)
CO2 Accuracy at NTP
Zigbee 3.0 Green Power (encrypted, bi-directional)
Communication
3.6 V
AA Lithium ion
Battery Voltage
10+ years (non-replaceable)
Battery Cell
Note: Battery life can be reduced when sensor is operated at temperatures approaching the operating limits.
-30°C to 70°C



Check with your local government for instruction on disposal of these products.

SE8350*2

Dimensions




Main Specifications

Item	Description
Dimensions	12cm/4.72in (H) x 8.6cm/3.38in (W) x 2.5cm/1in (D)
Power Requirements	Input: 24VAC ±15% recommended, Absolute Max 29.5VAC, 50/60Hz or 24Vdc ±15% Peak device consumption: up to 6VA with CO2 sensor or Wi-Fi module Plus Output Load (max total 94VA) Transformer maximum rating: 100VA, 4.17 A
Output Ratings	Nine Electronic Relays : 24VAC or 24Vdc ±15% same as input power 1.0 Amp, in-rush = 3.0 Amps; Four Analog Outputs : 0 - 10 Vdc, 5mA maximum, (2 kilo-ohm resistance) Configurable Output Analog/Electronic Relay
Operating Conditions	0 °C to 50 °C (32 °F to 122 °F) 0% to 95% R.H. non-condensing
Storage Conditions	-30 °C to 50 °C (-22 °F to 122 °F) 0% to 95% R.H. non-condensing
Temperature Sensor	Local 10 K NTC type 2 thermistor
Temperature Sensor Resolution	± 0.1 °C (± 0.2 °F)
Temperature Control Accuracy	±0.5 °C (± 0.9 °F) @ 21 °C (70 °F) typical
Humidity Sensor Precision	Reading range from 10-90 % R.H. non-condensing 10 to 20% precision: 10% 20% to 70% precision: 5% 70% to 90% precision: 10%
Humidity Sensor Stability	Less than 0.25 % yearly (typical drift)
Dehumidification Setpoint Range	30% to 95% R.H.
Occ, Unocc and Standby Cooling Setpoint Range	12.0 °C to 37.5 °C (54 °F to 100 °F)
Occ, Unocc and Standby Heating Setpoint Range	4.5 °C to 32 °C (40 °F to 90 °F)
Room and Outdoor Air Temperature Display Range	-40 °C to 50 °C (-40 °F to 122 °F)
Proportional Band for Room Temperature Control	Cooling and Heating: Default: 1.8°C (3.2°F)
Analog Inputs	Modulating 0-10 VDC across UI19, UI24 to Common
Binary Inputs	Dry contact across terminals UI16, UI17 to Common
Remote Temperature Sensor	10 K NTC type 2 thermistor UI20, UI22, UI23
Wire Gauge	Power supply: 16 or 18 gauge Communications: 22 gauge typical, 24 gauge minimum
Shipping Weight	0.34 kg (0.75 lb)

*2 SE8350 does not connect directly to the air conditioner itself

Hotel Room Controller HRC*1

Dimensions



Specifications

Dimensions
5.6in x 4.3in x 2.4in
144mm x 110mm x 60.5mm
Digital Inputs
12
High Voltage Relay
10 x 3 A SPST +250 VAC relays
Analog Outputs
12 x configurable analog inputs
DI: voltage free DI, 10 kΩ input impedance
0-20mA: range 0...1000, < 150 Ω impedance
0-10V: range 0...1000 > 10 kΩ impedance
6 x 0-10 V outputs. Load impedance > 700 Ω
Analog Outputs
24 VAC + 10% NOT ISOLATED
Supply Voltage
+20...38 Vdc NOT ISOLATED
Supply Frequency
50/60 Hz
Power Cycle
35 VA / 15 W
Operating Temperature
-20 to 60 °C (-4 to 140 °F) conforming to UL 60730-1
Storage Temperature
-30 to 70 °C (-22 to 158 °F)

Certification



Check with your local government for instruction on disposal of these products.

Panasonic AC Smart Cloud


With Panasonic AC Smart Cloud, have your business under control, and start saving!



Flexible and scalable solution

- Energy saving
- Zero downtime
- Site(s) management

Centralise control of your business premises, from wherever you are, 24/7/365. It doesn't matter how many sites you have, or where they are! The AC Smart Cloud system from Panasonic allows you to have complete control of all your installations, from your tablet or from your computer. In a simple click, all your units from several locations, receive status updates in real-time of all your installations, preventing breakdowns and optimising costs.




*1 Customised to meet user demand / Continuous upgrades: new functions and product introductions / IT smart management.

Panasonic AC Smart Cloud offers continuous improvement always thinking about users

New e-CUT function

E-CUT functions are newly available in Panasonic AC Smart Cloud. 5 energy saving settings reduces automatically its energy consumption.



Key functions and uniqueness

Multi site monitoring

- It doesn't matter how many sites you have, easy to manage, operate, compare sites, locations, rooms.




Schedule setting

- Yearly / weekly / holiday timer setting as you want



Powerful statistics for energy savings

- Power consumption, capacity, efficiency level can be compared with different parameters (Yearly / monthly / weekly / daily bases)




Maintenance notification

- Error notification by email and with floor layout
- Maintenance notification of PAC / VRF outdoor units
- Remote service checker function



User customisation*2

Site administrator can create users as desired and assign customised profiles.



Main functions per user type

Function / Main Tab	Sub-Tab	Basic type (Eg.: Owners, facility managers)	Professional type (Eg.: Installers, maintenance companies)
AC setting	I / U / O / U operation details	✓	✓
	Cloud adapter (CZ-CFUSCC1) details	✓	✓
	AC maintenance	✓	✓
	Map view	✓	✓
Energy saving function	NEW e-CUT	✓	✓
Schedule	Yearly, weekly schedule setting / view	✓	✓
	Power consumption	✓	✓
Powerful statistics	Capacity	✓	✓
	Efficiency ranking	✓	✓

Function / Main Tab	Sub-Tab	Basic type (Eg.: Owners, facility managers)	Professional type (Eg.: Installers, maintenance companies)
Maintenance function	Notification overview / details	✓	✓
	Maintenance settings	✓	✓
	Map view	✓	✓
	Remote service checker	✓	✓
User account *2	New / update user registration	✓	✓
System setting	Distribution group overview / details	✓	✓
	Cut OFF request	✓	✓
	Map editor		✓

*2 Cloud service fee is additionally required. Please contact an authorised Panasonic dealer.

Remote service checker function




Zero down time

- Quick analysis & response
- Time & Cost saving for service maintenance task

Recording service checker parameters from wherever you are!

- Data duration: Maximum 120 minutes
- Data frequency: 10 – 90 seconds
- Mode selection: With test run or Without test run
- Count down schedule setting available



Panasonic AC Smart Cloud parts lists

CZ-CFUSCC1 | AC Smart Cloud communication adaptor. Up to 128 groups. 128 units control

Note: Please contact an authorized Panasonic dealer.

Controllers

A wide variety of control options to meet the requirements of different applications.

Next Generation Control Solutions



WLAN Control



Smart Cloud Control



BMS Plug & Play

Note: Additional accessories or devices are required. Please consult Panasonic for details.

OPERATION SYSTEM	INDIVIDUAL CONTROL SYSTEMS				
Requirements	Simplified high-spec operation	High-spec operation	Normal operation	Operation from anywhere in the room	Normal operation
External appearance					
Type, model name	Simplified high-spec Wired Remote Controller	Deluxe Wired Remote Controller	Timer Remote Controller (Wired)	Wireless Remote Controller	Wired Remote Controller
	CZ-RTC6BL CZ-RTC6BLW	CZ-RTC5B	CZ-RTC4	Controller: CZ-RWS3 Receiver: CZ-RWRU3 CZ-RWRL3 CZ-RWRD3 CZ-RWRT3 CZ-RWRC3	CZ-RD52CP
Built-in thermostat	●	●	●	—	—
nanoe™ X on/off control *not applies to Floor Console	●	●	—	●	—
ECONAVI on/off control	●	●	●	●	—
Number of indoor units which can be controlled	1 group, 8 units	1 group, 8 units	1 group, 8 units	1 group, 8 units	1 unit
Use limitations	● CZ-RTC6BL : Up to 2 controllers can be connected per group(no combination possible with CZ-RTC6BL or CZ-RTC6BLW) ● CZ-RTC6BLW :Up to 1 controller can be connected per group	● Up to 2 controllers can be connected per group (When using ECONAVI sensor, only one remote controller is possible to connect at indoor unit)	● Up to 2 controllers can be connected per group. (When using ECONAVI sensor, only one remote controller is possible to connect at indoor unit)	● Up to 2 controllers can be connected per group.	● Only 1 controller for 1 indoor unit.
Function ON/OFF	●	●	●	●	●
Mode setting	●	●	●	●	●
Fan speed setting	●	●	●	●	●
Temperature setting	●	●	●	●	●
Air flow direction	●	●	●	● ^{*1}	●
Permit/Prohibit switching	—	—	—	—	—
Weekly program	● ^{*2}	●	●	—	—

^{*1} Setting is not possible when a remote controller unit is present (use the remote controller for setting).

^{*2} CZ-RTC6BL with H&C Control App, CZ-RTC6BLW with H&C Control App or Comfort Cloud App.

Note: Product images not to scale.

CENTRALISED CONTROL SYSTEMS				SMART CONTROL SYSTEMS	
Operation with various function from centre station	Only ON/OFF operation from centre station	Simplified load distribution ratio (LDR) for each tenant Touch screen panel	Connection with 3rd Party Controller	Cloud connectivity, operation from anywhere	Schneider Electric room controller
			Seri-Para I/O unit for outdoor unit 		
System Controller	ON/OFF Controller	Intelligent Controller	CZ-CAPDC2 Interface adaptor 	WLAN Smart Adaptor Comfort Cloud App	PAC smart connectivity+
CZ-64ESMC3	CZ-ANC3	CZ-256ESMC3 (CZ-CFUNC2)	CZ-CAPC3 Seri-Para I/O unit for each indoor unit 	CZ-TACG1 / CZ-CAPWFC1	SER8150 (room controller)
—	—	—	—	—	●
—	—	—	—	●	—
●	—	●	—	●	—
64 groups, max. 64 units	16 groups, max. 64 units	64 units x 4 links, max. 256 units	—	1 adaptor : 1 group, 8 units. Multiple adaptors for each indoor units : 200 units(10 location x 20 units)	1 group, 8 units
● Up to 10 controllers, can be connected to one system. ● Main unit/sub unit (1 main unit + 1 sub unit) connection is possible. ● Use without remote controller is possible.	● Up to 8 controllers (4 main units + 4 sub units) can be connected to one system. ● Use without remote controller is impossible.	● A communication adaptor (CZ-CFUNC2) must be installed for three or more links.	CZ-CAPBC2 Communication Adaptor 	● Mobile device, free App and internet router is required separately. ● Wired remote controller (master) required.	● Comparing to RTC5B, up to 1 controller can be connected per IDU. ● Wired to R1/R2. ● VRF and PAC(S-link) model only.
●	●	●	CZ-CFUNC2 LonWorks Interface 	●	●
●	—	●	—	●	●
●	—	●	—	●	●
●	—	●	—	●	●
● ^{*1}	—	● ^{*1}	—	●	●
●	●	●	CZ-CLNC2 	—	—
●	—	●	—	●	—

Simplified high-spec
wired remote controller
(CZ-RTC6BL / CZ-RTC6BLW)



Dimensions
H 86 x W 86 x
D 25mm

C O N E X

Deluxe wired remote controller
(CZ-RTC5B)



Dimensions
H 120 x W 120 x
D 16 mm

	CZ-RTC6BL(W) + H&C CONTROL APP	CZ-RTC5B
Energy Saving		
ECONAVI on/off	●	●
Temperature Auto Return	● ^{*1}	●
Temperature Setting range	● ^{*1}	●
Auto Shutoff	● ^{*1}	●
Schedule peak cut	● ^{*1}	●
Repeat off timer	● ^{*1}	●
Basic Operation		
Individual Louver Control(Lock individual flap for for 4-WAY cassette)	● ^{*1}	●
ON/OFF timer	● ^{*1}	●
Weekly timer	● ^{*1}	●
Filter information	● ^{*1*2}	● ^{*2}
Outing function	●	●
Quiet operation mode	● ^{*1*2}	● ^{*2}
Power consumption monitor	● ^{*1*2}	● ^{*2}
Energy saving	● ^{*1*2}	● ^{*2}
initial settings	—	●
Ventilation	● ^{*1}	●
nanoe™ X	● ^{*1*2}	● ^{*2}
Maintenance Function		
Outdoor unit error data	—	—
Service Contact address	● ^{*1}	—
RC setting mode	●	●
Test run	●	●
Sensor information	● ^{*2}	● ^{*2}
Service check	●	●
Simple/Detailed Settings	●	●
Auto address	● ^{*3}	●
Initial Settings		
Rotation operation	● ^{*1}	●
Backup operation	● ^{*1}	●
Support operation	● ^{*1}	●

^{*1} Only with H&C Control App ^{*2} Subject to the connected model ^{*3} Only with remote controller operation
Note: Product images not to scale.

New service checker interface



The new service checker interface provides easy access to service parameters and service checker data via Bluetooth®.

- A new service checker interface^{*4} for PAC NX Series
- Bluetooth® connection
- Panasonic H&C Diagnosis App

^{*4} Available as a spare part, compatible with new PAC NX Series.

Input voltage	220-240 V ~ 50-60 Hz (supplied from outdoor unit)
Power consumption	Maximum 2.4 W (including outdoor units)
Size (H x W x D)	175 x 125 x 50 mm
Weight	—
Interface	Bluetooth® 4.2 or later
Frequency range	2.4 GHz band
Operation range - Temperature / Humidity	0 ~ 40 °C / 20 ~ 80 % (no condensation)


^{*} Frequency band in which the ratio equipment operates; 2402 - 2480 MHz.

^{*} Maximum radio-frequency power transmitted in the frequency bands in which the ratio equipment operates; +0 dBm.

Individual Control Systems

Control contents	Part name, model No.	Quantity
Standard Control • Control of the various operations of the indoor unit by wired or wireless remote controller. • Cooling or heating mode of the outdoor unit is decided by the first priority of the remote controller.	Wired remotod controller CZ-RTC4 / CZ-RTC5B / CZ-RTC6BL / CZ-RTC6BLW Wireless remote controller + Receiver CZ-RWS3 (Wall Mounted / Mini Cassette) CZ-RWS3 + CZ-RWRU3 (4-WAY Cassette) CZ-RWS3 + CZ-RWRT3 (Under Ceiling) CZ-RWS3 + CZ-RWRC3 (All split type)	1 unit each
(1) Group control • Batch remote control on all indoor units. • Operation of all indoor cells in the same mode. • Up to 8 units can be connected. • The sensor is the body sensor, and thermostat ON/OFF setting in regard to the temperature set by the remote controller is possible for each indoor unit.	Wired remotod controller CZ-RTC4 / CZ-RTC5B / CZ-RTC6BL / CZ-RTC6BLW Wireless remote controller + Receiver CZ-RWS3 (Wall Mounted / Mini Cassette) CZ-RWS3 + CZ-RWRU3 (4-WAY Cassette) CZ-RWS3 + CZ-RWRT3 (Under Ceiling) CZ-RWS3 + CZ-RWRC3 (All split type)	As required
(2) Main/sub remote control • Max 2 remote controllers per indoor unit. (Main remote controller can be connected) • The button pressed last has priority. • Timer setting is possible even with the sub remote controller. When using ECONAVI sensor, only one remote controller is possible to connect at indoor unit.	Main or sub Wired remotod controller CZ-RTC4 / CZ-RTC5B / CZ-RTC6BL Wireless remote controller + Receiver CZ-RWS3 (Wall Mounted / Mini Cassette) CZ-RWS3 + CZ-RWRU3 (4-WAY Cassette) CZ-RWS3 + CZ-RWRT3 (Under Ceiling) CZ-RWS3 + CZ-RWRC3 (All split type)	As required

SYSTEM EXAMPLE



Note: Connectable number of controllers, controller combination, connectable indoor units, remote control maximum wiring length are different between the controller. Please confirm the Installation Instructions of controller or consult with Panasonic service center.

New wired RC & Monitor adaptor & App compatibility ^{*1}

^{*1} End User App Recommendation
CZ-RTC6BL - H&C Control App
CZ-RTC6BLW - Comfort Cloud App

			Wired RC BLUETOOTH  CZ-RTC6BL 	Wired RC BLUETOOTH & WLAN  CZ-RTC6BLW  	WLAN adaptor  CZ-CAPWFC1 	Monitor adaptor for diagnosis  New service checker 
PZH2 / PZ2 series		 & 				
NX series	PZH3 / PZ3 Series ODU × NX series IDU	 & 	 	  		
	PZH2 / PZ2 series ODU × NX series IDU	 & 		 		

Note: Power supply is available only when using NX IDU

Timer remote controller (CZ-RTC4)



Dimensions
H 120 x W 120 x D 20 mm

Basic remote controller ON/OFF

- Operation mode changeover (Cooling, Heating, Dry, Auto, Fan).
- Temperature setting (Cooling / Dry: 18-30 °C Heating: 16-30 °C).
- Fan speed setting H / M / L and Auto.
- Air flow direction adjustment.
- ECONAVI on / off^{*2}

Time Function 24 hours real time clock

- Day of the week indicator.

Weekly Programme Function

- A maximum of 6 settings/day and 42 settings/week can be programmed.

Outing Function

- This function can prevent the room temperature from dropping or rising when the occupants are out for a long time.

Sleeping Function

- This function controls the room temperature for comfortable sleeping.

Maximum 8 indoor units can be controlled from one remote controller

Remote control by main remote controller and sub controller is possible

Maximum 2 remote controllers (main remote controller and sub controller) can be installed for one indoor unit.

^{*2} Depending on the model, some menus cannot be used.

Note: Product images not to scale.

Wireless remote controller



For 4-WAY
Cassette type
CZ-RWS3
+CZ-RWRC3



For all Ducted types
CZ-RWS3
+CZ-RWRC3



For Under Ceiling type
CZ-RWS3
+CZ-RWRT3

Remote control by main remote controller and sub controller is possible

- Maximum 2 remote controllers (main remote controller and sub controller) can be installed for one indoor unit.

When CZ-RWS3+CZ-RWRC3 is used, wireless control becomes possible for all indoor units

- When a separate receiver is set up in a different room, control from that room also becomes possible.
- Automatic operation by means of the emergency operation button is possible even when the remote controller has been lost or the batteries have been exhausted.

In addition, there are other functions such as temperature setting, operation switching, wind direction/fan speed setting, etc

Ventilation independent operation is possible

When commercial ventilation fans or heat-exchange ventilation fans have been installed, they can be operated with this remote control (interlocked operation with the indoor unit or independent ventilation ON/OFF).

Wired remote controller (CZ-RD52CP)



Note: Product images not to scale.


T10 Terminal for External Control (Digital Connection)

Connecting an indoor unit to an external device is easy. The T10 Terminal featured in the electronic circuit board of all indoor units enables digital connection to external devices.




1. T10 Terminal Specification (T10:CN061 at indoor unit PCB)

- Control items: 1. Start/stop input
2. Remote controller prohibit input
3. Start signal output
4. Alarm signal output



NOTE: The wire length from indoor unit to the Relay must be within 2.0m. Pulse signal changeable to static with JP cutting. (Refer to JP001)

Example of wiring



Condition

- 1-2 (Pulse input): Unit ON/OFF condition switching with a pulse signal. (1 pulse signal: shortage status more than 300msec.or more)
- 2-3 (Static input): Open/ Operation with Remote is permitted.(Normal condition) Close/ Remote controller is prohibited.
- 4-5 (Static output): 12V output during the unit ON. / No output at OFF.
- 4-5-6 (Static output): 12V output when some errors occur / No output at normal.


2. Usage Example

Forced OFF control

Condition

1-2 (Static input): Close/ Operation with Remote is permitted. (Normal condition) Open/ Unit is forcibly OFF and Remote controller operation is prohibited.

Example of wiring




Note: The wire length from indoor unit to the Relay must be within 2.0m

Operation ON/OFF signal output

Condition

4-5 (Static output): 12V output during the unit ON / No output at OFF

Example of wiring



Note: The wire length from indoor unit to the Relay must be within 2.0m Pulse signal changeable to static with JP cutting. (Refer to JP001)



Reducing inefficient air conditioning

Providing outstanding energy-saving performance, Panasonic's large capacity air conditioners can be connected to ECONAVI to detect when energy is being wasted. ECONAVI senses the presence or absence of people and the level of activity in each area of a room. When unnecessary heating or cooling is detected, indoor units are individually controlled to match room conditions for energy-saving operation.



ECONAVI Sensor CZ-CENSC1

• please check specific models for compatibility

How 2 sensors work for human detection



Detection of the level of activity enables optimum power saving

Presence or absence of people and the level of activity in the room are detected in real time. Set temperature is automatically adjusted to optimise the power consumption.



Sensors are remotely located to maximise the energy-saving effect

When sensors are built into the indoor unit, pillars, walls, cabinets and other fittings can obstruct the sensors, reducing the area of detection and lowering the energy-saving effect. Panasonic sensors can be located any where in the room which enables the optimum layout for sensors in any location.

Case study at coffee shop




In the morning
Reduced cooling when there are fewer people.

In the afternoon
Thorough cooling when there is a high level of activity.



At night
Automatic Thermo Off depending on conditions at the end of the day.

Wide detection area




A sensor is remotely set to maximise the detection area.


Installation flexibility for indoor unit layout changes.

Remote Controller External Dimensions


SIMPLIFIED HIGH-SPEC
WIRED REMOTE CONTROLLER
(CZ-RTC6BL / CZ-RTC6BLW)




DELUXE WIRED
REMOTE CONTROLLER
(CZ-RTC5B)




TIMER REMOTE
CONTROLLER
(CZ-RTC4)




WIRELESS REMOTE
CONTROLLER
(CZ-RWS3)




SEPARATE RECEIVER FOR
WIRELESS REMOTE CONTROLLER
(CZ-RWRC3)



REMOTE SENSOR
(CZ-CSRC3)




ECONAVI SENSOR
(CZ-CENSC1)




SYSTEM CONTROLLER
(CZ-64ESMC3)

System Controller




Switch Box




Remote Controller External Dimensions


COMMUNICATION ADAPTOR
(CZ-CFUNC2)




INTELLIGENT CONTROLLER
(CZ-256ESMC3)




ON/OFF CONTROLLER
(CZ-ANC3)




Switch box




SERI-PARA I/O UNIT FOR EACH
INDOOR UNIT
(CZ-CAPBC2)




WIRED REMOTE CONTROLLER
FOR RESIDENTIAL MODEL
(CZ-RD52CP)



SERI-PARA I/O UNIT
FOR OUTDOOR UNIT
(CZ-CAPDC2)



WLAN ADAPTOR
(CZ-TACG1)



WLAN ADAPTOR
(CZ-CAPWFC1)

