

FCS-4051 GEMINI PTZ IP Camera, 2-MP, 25x Zoom, H.265, IR 100M

Product Images



Short Description

- Built-in infrared LEDs for night viewing up to 100m
- Built-in Micro SD/SDHC card slot for local storage
- Dual power support: 12V DC/PoE (IEEE 802.3at)
- Video compression: H.265, H.264, MJPEG
- Weatherproof IP66-rated housing
- Supports 25X optical zoom
- Simultaneous Third Streams
- Free surveillance and CMS (Central Management System) software packages with 64-channel license

Description

The LevelOne FCS-4051 is a PTZ IP surveillance camera designed for use outdoors, boasting 2-Megapixel resolution and a 25X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

Additional Information

Code des Harmonisierten Systems (HS)	852589
Zolltariflicher Warencode (TARIC)	8525890000
Farbe	Weiß
EAN	4015867227596
Modellnummer	FCS-4051
Features	Digital Wide Dynamic Range (DWDR), rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser. 3 Stream, SDK Detects up to 5 faces simultaneously. Supports detecting, capturing, grading, selecting of face in motion, and output the best face picture of the face Line crossing, intrusion, region entrance, region exiting Support alarm triggering by specified target types (human and vehicle)
2-way audio	Ja
DI/DO	Ja
IR LED for night vision	Ja
Max. Resolution	2 Megapixels
Resistance	Weatherproof
IP Camera series	GEMINI
Camera Type	Speed Dome
Zoom type	Motorization
PoE Supported	Ja
Zulassungen und Konformität	CE/FCC/UL, /IP66/RoHS UL (UL 62368-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 62368-1:2014+A11:2017); BIS (IS 13252 (Part1):2010+A1:2013+A2:2015); LOA (IEC/EN 60950-1) TVS 6000V lightning protection, surge protection and voltage transient protection

Kompatibilität	Onvif Version 19.12, Profile S, Profile G, Profile T Simultaneous Live View: Up to 20 channels Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.2, TLS 1.3, host authentication (MAC address)
Operating humidity	0% RH ~ 90% RH
Operating temperature	-30°C ~ 65°C
Unterstützte Browser	Edge
Unterstützte Betriebssysteme	Windows 10
Lieferumfang	FCS-4051 Screw Kit Power adapter Quick Installation Guide Resource CD (User Manual, Utility, QIG)
Betrachtungswinkel	Horizontal field of view: 57.6° to 2.5° (wide-tele), Vertical field of view: 34.4° to 1.4° (wide-tele), Diagonal field of view: 64.5° to 2.9° (wide-tele)
Audioformat	G.711/G.722.1/G.726/MP2L2/PCM
Digital-Zoom	16x
Bildsensor	1/2.8" progressive scan CMOS
Indikator	Power
IR Sperrfilter	Ja
Infrarotdistanz in m	Up to 100 meter
Linse	4.8 mm to 120 mm, F1.6
Minimale Beleuchtung (Lux)	Color: 0.005 Lux @ (F1.6, AGC ON); B/W: 0.001 Lux @ (F1.6, AGC ON), 0 Lux with IR
Befestigung	Wall mount
Optischer Zoom	25X
Schwenkbereich	360°, Pan speed: configurable from 0.1° to 80°/s; preset speed: 80°/s
Port Configuration	RJ45/DI/Power
Energieverbrauch	Max. 24 W, including max. 9 W for supplement light

Stromversorgung	VDC 12V /2A
Power supply included	Ja
Auflösung	Main Stream: 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720) Sub-Stream: 50 Hz: 25 fps (704 × 576, 640 × 480, 352 × 288) 60 Hz: 30 fps (704 × 480, 640 × 480, 352 × 240) Third Stream: 50 Hz: 25 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Verschlusszeit	1s to 1/30,000 s
Standards	IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour
Supported storage capacity	256 GB
Neigungsbereich	-15° to 90° (auto flip), Tilt speed: configurable from 0.1° to 80°/s, preset speed 80°/s
Videoformat	H.265/H.264/MJPEG
Wetterfestigkeit	IP66
Dimensions (W x D x H)	295 x 164.5 x 164.5 mm
Produktgewicht (kg)	2

