

USER MANUAL

Table 1: Specifications

Model	Power	Beam Diameter	Beam Distance	Beam Angle	Beam Color	Beam Intensity	Beam Quality	Beam Shape	Beam Size	Beam Weight	Beam Price
TURBO	1300 lumens	4mm	125m	120°	COOL WHITE	CCF: 5700~6700K CRI: 70	125m	120°	125m	120g	125m
HIGH	420 lumens	4mm	135m	120°	NEUTRAL WHITE	CCF: 4000~5000K CRI: 70	135m	120°	135m	120g	135m
MED	180 lumens	4mm	945m	120°			945m	120°	945m	120g	945m
LOW	15 lumens	4mm	55m	120°			55m	120°	55m	120g	55m
MOON	15 lumens	4mm	11 days	120°			11 days	120°	11 days	120g	11 days

Table 2: MCC

Parameter	Value
Cable length	0.5m
Input	USB-A DC 5V 1A
Output	CC&CV 4.2V 1A
Time to fully charge	About 2.5 hours

Table 3: Specifications

Model	Power	Beam Diameter	Beam Distance	Beam Angle	Beam Color	Beam Intensity	Beam Quality	Beam Shape	Beam Size	Beam Weight	Beam Price
TURBO	1300 lumens	4mm	125m	120°	COOL WHITE	CCF: 5700~6700K CRI: 70	125m	120°	125m	120g	125m
HIGH	420 lumens	4mm	135m	120°	NEUTRAL WHITE	CCF: 4000~5000K CRI: 70	135m	120°	135m	120g	135m
MED	180 lumens	4mm	945m	120°			945m	120°	945m	120g	945m
LOW	15 lumens	4mm	55m	120°			55m	120°	55m	120g	55m
MOON	15 lumens	4mm	11 days	120°			11 days	120°	11 days	120g	11 days

Table 4: Specifications

Model	Power	Beam Diameter	Beam Distance	Beam Angle	Beam Color	Beam Intensity	Beam Quality	Beam Shape	Beam Size	Beam Weight	Beam Price
TURBO	1300 lumens	4mm	125m	120°	COOL WHITE	CCF: 5700~6700K CRI: 70	125m	120°	125m	120g	125m
HIGH	420 lumens	4mm	135m	120°	NEUTRAL WHITE	CCF: 4000~5000K CRI: 70	135m	120°	135m	120g	135m
MED	180 lumens	4mm	945m	120°			945m	120°	945m	120g	945m
LOW	15 lumens	4mm	55m	120°			55m	120°	55m	120g	55m
MOON	15 lumens	4mm	11 days	120°			11 days	120°	11 days	120g	11 days

Table 5: Specifications

Model	Power	Beam Diameter	Beam Distance	Beam Angle	Beam Color	Beam Intensity	Beam Quality	Beam Shape	Beam Size	Beam Weight	Beam Price
TURBO	1300 lumens	4mm	125m	120°	COOL WHITE	CCF: 5700~6700K CRI: 70	125m	120°	125m	120g	125m
HIGH	420 lumens	4mm	135m	120°	NEUTRAL WHITE	CCF: 4000~5000K CRI: 70	135m	120°	135m	120g	135m
MED	180 lumens	4mm	945m	120°			945m	120°	945m	120g	945m
LOW	15 lumens	4mm	55m	120°			55m	120°	55m	120g	55m
MOON	15 lumens	4mm	11 days	120°			11 days	120°	11 days	120g	11 days

Table 6: Specifications

Model	Power	Beam Diameter	Beam Distance	Beam Angle	Beam Color	Beam Intensity	Beam Quality	Beam Shape	Beam Size	Beam Weight	Beam Price
TURBO	1300 lumens	4mm	125m	120°	COOL WHITE	CCF: 5700~6700K CRI: 70	125m	120°	125m	120g	125m
HIGH	420 lumens	4mm	135m	120°	NEUTRAL WHITE	CCF: 4000~5000K CRI: 70	135m	120°	135m	120g	135m
MED	180 lumens	4mm	945m	120°			945m	120°	945m	120g	945m
LOW	15 lumens	4mm	55m	120°			55m	120°	55m	120g	55m
MOON	15 lumens	4mm	11 days	120°			11 days	120°	11 days	120g	11 days

Table 7: Specifications

Model	Power	Beam Diameter	Beam Distance	Beam Angle
-------	-------	---------------	---------------	------------

[illegible][illegible]